



Product: [83719](#)

Electronic, 19 C #16 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP

Request Sample

Product Description

High Temperature Electronic, 19 Conductor 16AWG (19x29) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, FEP Outer Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications:

extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

Physical Characteristics (Overall)

Conductor

| Element      | AWG | Stranding | Material           | No. of Conductors |
|--------------|-----|-----------|--------------------|-------------------|
| Conductor(s) | 16  | 19x29     | TC - Tinned Copper | 19                |

Conductor Count:19

Insulation

| Element      | Material                             | Material Trade Name | Nominal Wall Thickness |
|--------------|--------------------------------------|---------------------|------------------------|
| Conductor(s) | FEP - Fluorinated Ethylene Propylene | Teflon®             | 0.007 in               |

Color Chart

| Number | Color        |
|--------|--------------|
| 1      | Black        |
| 2      | White        |
| 3      | Red          |
| 4      | Green        |
| 5      | Orange       |
| 6      | Blue         |
| 7      | White/Black  |
| 8      | Red/Black    |
| 9      | Green/Black  |
| 10     | Orange/Black |
| 11     | Blue/Black   |
| 12     | Black/White  |
| 13     | Red/White    |
| 14     | Green/White  |
| 15     | Blue/White   |
| 16     | Black/Red    |
| 17     | White/Red    |
| 18     | Orange/Red   |
| 19     | Blue/Red     |

Outer Shield Material

| Type | Layer | Material    | Material Trade Name | Coverage [%] |
|------|-------|-------------|---------------------|--------------|
| Tape | 1     | Alum / Poly | Beldfoil®           | 100 %        |

|       |   |                    |  |      |
|-------|---|--------------------|--|------|
| Braid | 2 | TC - Tinned Copper |  | 85 % |
|-------|---|--------------------|--|------|

Outer Jacket Material

| Material                             | Material Trade Name | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------------|---------------------|------------------|------------------------|
| FEP - Fluorinated Ethylene Propylene | Teflon®             | 0.403 in         | 0.014 in               |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 4.43 Ohm/1000ft       | 2.67 Ohm/1000ft          |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 35 pF/ft                                | 63 pF/ft                                                |

Current

| Max. Recommended Current [A]  |
|-------------------------------|
| 3.2 Amps per conductor @ 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS         |

Temperature Range

|                       |                 |
|-----------------------|-----------------|
| Operating Temp Range: | -70°C To +200°C |
|-----------------------|-----------------|

Mechanical Characteristics

|                                  |                |
|----------------------------------|----------------|
| Bulk Cable Weight:               | 218 lbs/1000ft |
| Max Recommended Pulling Tension: | 577 lbs        |
| Min Bend Radius/Minor Axis:      | 4.25 in        |

Standards

|                          |     |
|--------------------------|-----|
| NEC Articles:            | 800 |
| NEC/(UL) Specification:  | CMP |
| CEC/C(UL) Specification: | CMP |
| CPR Euroclass:           | Eca |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| CA Prop 65:                           | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |

Flammability, LS0H, Toxicity Testing

|                       |               |
|-----------------------|---------------|
| UL Flammability:      | NFPA 262      |
| CSA Flammability:     | FT6           |
| ISO/IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating:    | 300 V RMS     |

Plenum/Non-Plenum

|               |     |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Part Number

Variants

| Item #        | Color | Putup Type | Length   | UPC          |
|---------------|-------|------------|----------|--------------|
| 83719 002100  | Red   | Reel       | 100 ft   | 612825205630 |
| 83719 002500  | Red   | Reel       | 500 ft   | 612825205654 |
| 83719 0021000 | Red   | Reel       | 1,000 ft | 612825205647 |

|           |                        |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

Product Notes

|        |                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------|
| Notes: | Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.292 Revision Date: 05-05-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331