


## RS Series Relay Modules

At only 6.2mm thickness the RS series Relay module features a slim Din Rail mountable interface solution. The modules have a plug in construction and are available with or without the relay. The built in LED indicates the relay energizing state. The relay features a SPDT configuration and a maximum switching current of 6A. It is available with several standard coil voltages from 5VAC/DC up to 230V AC/DC.

There is a provision for fitting pluggable jumpers which reduces the wiring time. The modules have screw terminals with finger protection for wire termination and offer an IP 20 protection rating. The relay has an IP67 protection rating. Both the relay and the module are UL recognized.



shown on DIN rail with relays and jumpers


| Part Number | Type number                    | Description                                           | Std. Pk. |
|-------------|--------------------------------|-------------------------------------------------------|----------|
| RSM-12CU    | 41F-1Z-C2-1-555 + HF41F/12-Z-S | 6A@250VAC/30VDC,12VAC/DC Coil, 6.2 mm, LED, SPDT      | 10       |
| RSM-24CU    | 41F-1Z-C2-1-555 + HF41F/24-Z-S | 6A@250VAC/30VDC,24VAC/DC Coil, 6.2 mm, LED, SPDT      | 10       |
| RSM-110CU   | 41F-1Z-C2-3-555 + HF41F/60-Z-S | 6A@250VAC/30VDC,110VAC/DC Coil, 6.2mm, LED, SPDT      | 10       |
| RSM-220CU   | 41F-1Z-C2-4-555 + HF41F/60-Z-S | 6A@250VAC/30VDC,220VAC/DC Coil, 6.2mm, LED, SPDT      | 10       |
| RSJ-RD      | HF41F-AAJ-001-RD               | Jumper for RSM, Red, 36A, 250V, 20 pole               | 10       |
| RSJ-BK      | HF41F-AAJ-001-BK               | Jumper for RSM, Black, 36A, 250V, 20 pole             | 10       |
| RSJ-BL      | HF41F-AAJ-001-BL               | Jumper for RSM, Blue, 36A, 250V, 20 pole              | 10       |
| RSP-1       | HF41F-AAS-001                  | Partition plate for RMS 2.2mm wide                    | 10       |
| RST-1       | HF41F-AAT-001                  | Marking Tag strip for RSM, white, (16 tags per strip) | 4        |

## RS Series Socket

### CHARACTERISTICS

|                            |                                     |
|----------------------------|-------------------------------------|
| Ambient Temperature:       | -40°C to +70°C<br>(-40°F to +158°F) |
| Rated Voltage:             | 250VAC                              |
| Rated Current:             | 6A (per pole)                       |
| Insulation Voltage (Min.): | 5000VAC                             |
| Protection:                | IP20                                |
| Socket Material:           | PA66+GF V0 (UL)                     |
| Contacts Spring Material:  | QSn6.5-0.1                          |
| Terminal Torque:           | 0.6Nm (5.3 lb. in.)                 |
| Wire Strip Length:         | 7mm                                 |
| Applicable Relay Type:     | RSR Series (41F)                    |



| Part Number | Type number     | Description                          |
|-------------|-----------------|--------------------------------------|
| RSS-624U    | 41F-1Z-C2-1-555 | For 6 to 24VAC/DC relays, IP20, LED  |
| RSS-624D    | 41F-1Z-C2-5-555 | For 6 to 24VDC relays, IP20, LED     |
| RSS-4860U   | 41F-1Z-C2-2-555 | For 48 to 60VAC/DC relays, IP20, LED |
| RSS-110U    | 41F-1Z-C2-3-555 | For 110 VAC/DC relays, IP20, LED     |
| RSS-220U    | 41F-1Z-C2-4-555 | For 220 VAC/DC relays, IP20, LED     |



File No.: E253370

#### Notes: Module features/ functions:

- (1) LED indicates the coil energizing state.
- (2) Eliminates negative current of relays.
- (3) Rectifying function (only for VAC/DC types).



## RS Series Subminiature Power Relay

### FEATURES

- Slim size (width 5mm)
- High breakdown voltage 4kV (between coil and contacts)
- Surge voltage up to 6kV (between coil and contacts)
- Clearance/creepage distance: 8mm
- Coil power consumption: 170mW
- Contact configuration: SPDT (Form C)
- Environmental friendly product (RoHS compliant)
- Outline Dimensions: 28.0 x 5.0 x 15.0mm



**cULus**  
File No.:E133481




File No.:40020043

### CONTACT INFORMATION


|                                 |                                                      |           |
|---------------------------------|------------------------------------------------------|-----------|
| Contact arrangement             | SPDT                                                 |           |
| Initial contact Resistance Max. | 100mΩ (at 1A/6VDC)<br>Gold plated: 30mΩ (at 1A/6VDC) |           |
| Contact material                | AgNi                                                 |           |
| Contact rating                  | Resistive Load                                       | 6A/250VAC |
|                                 | Pilot Duty                                           | 6A/30VDC  |
|                                 |                                                      | R300      |
| Max. switching voltage          | 400VAC / 125VDC                                      |           |
| Max. switching current          | 6A                                                   |           |
| Max. switching power            | 1500VA / 180W                                        |           |
| Mechanical life                 | 10 million cycles                                    |           |
| Electrical life                 | 10,000 cycles at 85°C (185°F)                        |           |

| Part Number | Type number      | Description                  |
|-------------|------------------|------------------------------|
| RSR-05DCS   | HF41F/5-Z-S-555  | SPDT, 5 mm, 5VDC Coil, IP67  |
| RSR-06DCS   | HF41F/6-Z-S-555  | SPDT, 5 mm, 6VDC Coil, IP67  |
| RSR-12DCS   | HF41F/12-Z-S-555 | SPDT, 5 mm, 12VDC Coil, IP67 |
| RSR-24DCS   | HF41F/24-Z-S-555 | SPDT, 5 mm, 24VDC Coil, IP67 |
| RSR-48DCS   | HF41F/48-Z-S-555 | SPDT, 5 mm, 48VDC Coil, IP67 |
| RSR-60DCS   | HF41F/60-Z-S-555 | SPDT, 5 mm, 60VDC Coil, IP67 |


Contact Configuration  
1 Form SPDT




Wiring Diagram



PCB Layout



MAXIMUM SWITCHING POWER



### CHARACTERISTICS

|                                   |                                                    |                             |
|-----------------------------------|----------------------------------------------------|-----------------------------|
| Initial insulation resistance     | 1000mΩ (at 500VDC)                                 |                             |
| Dielectric strength               | Between coil & contacts                            | 4000VAC 1 min.              |
|                                   | Between open contacts                              | 1000VAC 1 min.              |
| Operate time (at nominal voltage) | Max. 8ms                                           |                             |
| Release time (at nominal voltage) | Max. 4ms                                           |                             |
| Shock resistance                  | Functional                                         | 50m/s <sup>2</sup> (5g)     |
|                                   | Destructive                                        | 1000m/s <sup>2</sup> (100g) |
| Vibration resistance              | 1mm double amplitude max<br>@ 10 ... 55 Hz, 6G max |                             |
| Humidity                          | 5 to 85% RH                                        |                             |
| Ambient temperature               | -40°C to +85°C (-40°F to +185°F)                   |                             |
| Termination                       | Plug in; PCB mount                                 |                             |
| Unit weight                       | 5.4g (0.2 oz.)                                     |                             |
| Construction                      | Sealed IP67. Flux proof                            |                             |

### COIL


|                         |                                          |
|-------------------------|------------------------------------------|
| Coil power consumption: | 5 to 24VDC: 170mW<br>48VDC, 60VDC: 210mW |
|-------------------------|------------------------------------------|

### COIL DATA


at 20°C

| Nominal Voltage (VDC) | Pick-up Voltage (VDC) | Drop-out Voltage (VDC) | Max. Allowable Voltage (VDC) 85°C | Coil Resistance (Ω) |
|-----------------------|-----------------------|------------------------|-----------------------------------|---------------------|
| 5                     | 3.75                  | 0.25                   | 6.50                              | 147 ± 10%           |
| 6                     | 4.50                  | 0.30                   | 7.80                              | 212 ± 10%           |
| 12                    | 9.00                  | 0.60                   | 15.6                              | 848 ± 10%           |
| 24                    | 18.0                  | 1.20                   | 31.2                              | 3390 ± 15%          |
| 48                    | 36.0                  | 2.40                   | 62.4                              | 10600 ± 15%         |
| 60                    | 45.0                  | 3.00                   | 78.0                              | 16600 ± 15%         |

ENDURANCE CURVE



COIL TEMPERATURE RISE





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331