


FIXED CARBON COMPOSITION RESISTORS

KAMAYA OHM

RC

●Features

- 1. Improved pulse endurance characteristics compared to carbon-film devices.
- 2. Wide resistance range is available, 1 ohm ~ 22M ohm.
- 3. Stability Class : 10%



●Dimensions

Unit : mm

| Style | L                                   | D       | H    | d                                     | *Unit weight/pc. |
|-------|-------------------------------------|---------|------|---------------------------------------|------------------|
| RC1/4 | 6.3 ±0.7                            | 2.4±0.1 | 30±3 | 0.6 ±0.05                             | 222mg            |
| RC1/2 | 9.5 <sup>+0.8</sup> <sub>-0.7</sub> | 3.6±0.2 | 28±3 | 0.7 <sup>+0.07</sup> <sub>-0.05</sub> | 422mg            |

\*Values for reference

●Part Number Description

Example

Style

RC

1/4

Product Type

Rated Dissipation

1/4

0.25W

1/2

0.5W

102

Rated Resistance

E24, 12, 6 Series

e.g. : 2R2=2.2 ohm

102=1k ohm

J

Tolerance on Rated Resistance

J

±5%

K

±10%

M

±20%

B

\*Packaging

B

Bulk (Straight)

H

Horizontal Forming

TB

52 mm Width Tape (Ammo Box)

TD

52 mm Width Tape (Reel)

\*Refer to Tape and Packaging information on pages 66.

## FIXED CARBON COMPOSITION RESISTORS

RC

## ●Ratings

| Style | Rated Dissipation<br>at 70°C<br>W | Limiting Element<br>Voltage<br>V | Rated Resistance<br>Range | Combination of Rated Resistance Range and Temperature Coefficient of Resistance |                          |                                                              | Tolerance on Rated Resistance and<br>Perferred Number Series for Resistors | Isolation<br>Voltage<br>V | Category Temperature<br>Range<br>°C |
|-------|-----------------------------------|----------------------------------|---------------------------|---------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------|----------------------------------------------------------------------------|---------------------------|-------------------------------------|
|       |                                   |                                  |                           | Temperature Coefficient of Resistance %                                         |                          | Rated Resistance<br>Range                                    |                                                                            |                           |                                     |
|       |                                   |                                  |                           | at -55 °C                                                                       | at +125 °C               |                                                              |                                                                            |                           |                                     |
| RC1/4 | 0.25                              | 250                              | 1 ohm~5.6M ohm            | +6.5 ~0<br>+10 ~0                                                               | +1~-5<br>0~-6            | 1 ohm ~ 1k ohm<br>1.1k ohm ~ 10k ohm                         | J ( ± 5%)<br>: E24<br>K ( ± 10%)<br>: E12<br>M( ± 20%)<br>: E6             | 100                       | -55~+125                            |
| RC1/2 | 0.5                               | 350                              | 1 ohm~22M ohm             | +13 ~0<br>+15 ~0<br>+20 ~0                                                      | 0~-7.5<br>0~-10<br>0~-15 | 11k ohm ~100k ohm<br>110k ohm ~ 1M ohm<br>1.1M ohm ~ 22M ohm |                                                                            | 500                       |                                     |

Note1. Rated Voltage =  $\sqrt{(\text{Rated Dissipation}) \times (\text{Rated Resistance})}$ . (d.c. or a.c. r.m.s. Voltage)

Note2. Limiting Element Voltage can only be applied to resistors when the resistance value is equal to or higher than the critical resistance value.

Note3. Critical Resistance Value is the resistance value at which the rated voltage is equal to the limiting element voltage.

## ●Storage

Temperature 20±15°C, Humidity 60%R.H. Max, Recommendation Storing Term 6 months after shipped from factory.

## ●Derating Curve

The derated values of dissipation for temperatures in excess of 70°C shall be indicated by the following Curve.

## ●Climatic Category

55/125/56

|                                              |         |
|----------------------------------------------|---------|
| Lower Category Temperature                   | -55°C   |
| Upper Category Temperature                   | +125°C  |
| Duration of the Damp heat, Steady-State Test | 56 days |



## ●Performance Characteristics JIS C 5201-1 : 1998

| Description                                 | Requirements                                                                                                                      | Test Methods                                                                                                                                              |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage proof                               | No breakdown or flashover                                                                                                         | Clause 4.7 V-block method RC1/4 100Va.c.,60s<br>RC1/2 500Va.c.,60s                                                                                        |
| Variation of resistance with temperature    | See Ratings Table                                                                                                                 | Clause 4.8 Measuring temperature : +20°C/-55°C/<br>+20°C/+125°C/+20°C                                                                                     |
| Overload                                    | $\Delta R \leq \pm(2\%+0.1 \text{ ohm})$<br>No visible damage, legible marking                                                    | Clause 4.13 The applied voltage shall be 2.5 times of the<br>rated voltage or twice of the limiting element voltage,<br>whichever is the less Severe, 5s. |
| Robustness<br>of terminations               | Tensile $\Delta R \leq \pm(2\%+0.1 \text{ ohm})$ No visible damage                                                                | Clause 4.16.2 10N for 5~10s                                                                                                                               |
|                                             | Bending $\Delta R \leq \pm(2\%+0.1 \text{ ohm})$ No visible damage                                                                | Clause 4.16.3 5N twice                                                                                                                                    |
|                                             | Torsion $\Delta R \leq \pm(2\%+0.1 \text{ ohm})$ No visible damage                                                                | Clause 4.16.4 180°C, 2 rotation                                                                                                                           |
| Solderability                               | In accordance with Clause 4.17.4.5                                                                                                | Clause 4.17 235°C, 5s                                                                                                                                     |
| Resistance to soldering heat                | $\Delta R \leq \pm(3\%+0.1 \text{ ohm})$<br>No visible damage, legible marking                                                    | Clause 4.18 After immersion into the flux, the immersion<br>into solder shall be carried out 4mm from the<br>body at 350°C for 3.5s.                      |
| Rapid change of temperature                 | $\Delta R \leq \pm(2\%+0.1 \text{ ohm})$ No visible damage                                                                        | Clause 4.19 5 cycles between -55°C and +125°C.                                                                                                            |
| Climatic sequence                           | $\Delta R \leq \pm(10\%+0.5 \text{ ohm})$ Insulation resistance : $R \geq 100M \text{ ohm}$<br>No visible damage                  | Clause 4.23 Dry/Damp heat(12+12h cycle), first cycle./<br>Cold/Damp heat(12+12h cycle), remaining cycle./<br>D.C.Load.                                    |
| Damp test, steady state                     | $\Delta R \leq \pm(10\%+0.5 \text{ ohm})$ Insulation resistance : $R \geq 100M \text{ ohm}$<br>No visible damage, legible marking | Clause 4.24 40°C, 95%R.H., 56 days, test a) , b) and c) of<br>Clause 4.24.2.1                                                                             |
| Endurance at 70°C                           | $\Delta R \leq \pm(10\%+0.5 \text{ ohm})$ No visible damage<br>Insulation resistance : $R \geq 1G \text{ ohm}$                    | Clause 4.25.1 Rated voltage, 1.5h "ON", 0.5h "OFF",<br>70°C, 1,000h.                                                                                      |
| Endurance at the upper category temperature | $\Delta R \leq \pm(10\%+0.5 \text{ ohm})$ No visible damage<br>Insulation resistance : $R \geq 1G \text{ ohm}$                    | Clause 4.25.3 125°C, no-load, 1,000h.                                                                                                                     |



## FIXED CARBON COMPOSITION RESISTORS

RC


## ●Typical Characteristics

## ●Surge Resistance Characteristics


Charging and discharging a 2,000 pF capacitor for 100 cycles.



## ●Relationship between Load Ratio and Category Temperature




## ●Endurance at 70°C




## ●Variation with Time

Condition : 5~35°C , 45~85% R.H.



## ●Frequency Characteristics



## ●Reliability Test

## Endurance in humidity

Samples : RC1/4J, 100 ohm, 1k ohm, 10k ohm, 100k ohm×150 each. Total 2,400.

Conditions : Direct current voltage equivalent to the following load ratings in cycles on "ON" for 1.5h and "OFF" for 0.5h for a total of 5,000h in an atmosphere of 40°C, 90 to 95%R.H.

"Typical characteristics indicate the mean values of  $\Delta R/R$  etc."

| Criterion (%) | Load Ratio P/Pn (%) | Total Testing Time T(Hrs. ) | Number of Failures r(pcs.) | Failure Ratio   |                      | Average Lifetime (60% reliability level) (Hrs.) |
|---------------|---------------------|-----------------------------|----------------------------|-----------------|----------------------|-------------------------------------------------|
|               |                     |                             |                            | $\hat{\lambda}$ | $\lambda_{CL}(60\%)$ |                                                 |
| $\Delta R/R$  | $\pm 5$             | 0                           | 2.984X10 <sup>6</sup>      | 6               | 0.201                | 4.098×10 <sup>5</sup>                           |
|               |                     | 20                          | 2.990X10 <sup>6</sup>      | 4               | 0.134                | 5.682×10 <sup>5</sup>                           |
|               |                     | 60                          | 2.997X10 <sup>6</sup>      | 2               | 0.067                | 9.615×10 <sup>5</sup>                           |
|               |                     | 100                         | 2.992X10 <sup>6</sup>      | 3               | 0.100                | 7.194×10 <sup>5</sup>                           |
|               |                     | Total                       | 1.196X10 <sup>7</sup>      | 15              | 0.125                | 7.209×10 <sup>5</sup>                           |
|               | $\pm 10$            | Total                       | 1.20X10 <sup>7</sup>       | 0               | 0.0055               | 1.299×10 <sup>7</sup>                           |



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331