

FGAF40S65AQ

Field Stop Trench IGBT

650 V, 40 A

Description

Using novel field stop IGBT technology, ON Semiconductor's new series of field stop 4th generation of RC IGBTs offer the optimum performance for PFC applications and welder where low conduction and switching losses are essential.

Features

- Maximum Junction Temperature: $T_J = 175^\circ\text{C}$
- Positive Temperature Co-efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(\text{sat})} = 1.6 \text{ V (Typ.)} @ I_C = 40 \text{ A}$
- 100% of the Parts Tested for I_{LM} (Note 1)
- High Input Impedance
- Fast Switching
- Tighten Parameter Distribution
- IGBT with Monolithic Reverse Conducting Diode
- This Device is Pb-Free and is RoHS Compliant

Applications



- PFC, Welder



ON Semiconductor®

www.onsemi.com

| V_{CES} | I_C |
|-----------|-------|
| 650 V | 40 A |



TO-3PF
CASE 340AH

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

FGAF40S65AQ

PACKAGE MARKING AND ORDERING INFORMATION

| Part Number | Device Marking | Package | Reel Size | Tape Width | Quantity per Tube |
|-------------|----------------|---------|-----------|------------|-------------------|
| FGAF40S65AQ | FGAF40S65AQ | TO-3PF | - | - | 30 |

Table 1. ABSOLUTE MAXIMUM RATINGS

| Symbol | Description | | FGAF40S65AQ | Unit |
|-------------------|---|-----------------------------|-------------|------------------|
| V_{CES} | Collector to Emitter Voltage | | 650 | V |
| V_{GES} | Gate to Emitter Voltage | | ± 20 | V |
| | Transient Gate to Emitter Voltage | | ± 30 | V |
| I_C | Collector Current | $@ T_C = 25^\circ\text{C}$ | 80 | A |
| | | $@ T_C = 100^\circ\text{C}$ | 40 | |
| I_{LM} (Note 1) | Pulsed Collector Current | $@ T_C = 25^\circ\text{C}$ | 160 | A |
| I_{CM} (Note 2) | Pulsed Collector Current | | 160 | A |
| I_F | Diode Forward Current | $@ T_C = 25^\circ\text{C}$ | 40 | A |
| | | $@ T_C = 100^\circ\text{C}$ | 20 | A |
| I_{FM} (Note 2) | Pulsed Diode Maximum Forward Current | | 160 | A |
| P_D | Maximum Power Dissipation | $@ T_C = 25^\circ\text{C}$ | 94 | W |
| | | $@ T_C = 100^\circ\text{C}$ | 47 | W |
| T_J | Operating Junction Temperature Range | | -55 to +175 | $^\circ\text{C}$ |
| T_{STG} | Storage Temperature Range | | -55 to +175 | $^\circ\text{C}$ |
| T_L | Maximum Lead Temp. for Soldering Purposes, 1/8" from case for 5 sec | | 300 | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. $V_{CC} = 400$ V, $V_{GE} = 15$ V, $I_C = 160$ A, $R_G = 7 \Omega$, Inductive Load.
2. Repetitive rating: Pulse width limited by max. junction temperature.

Table 2. THERMAL CHARACTERISTICS

| Symbol | Parameter | FGAF40S65AQ | Unit |
|------------------------|---|-------------|---------------------------|
| $R_{\theta JC}$ (IGBT) | Thermal Resistance, Junction to Case, Max. | 1.6 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient, Max. | 40 | $^\circ\text{C}/\text{W}$ |

FGAF40S65AQ

Table 3. ELECTRICAL CHARACTERISTICS OF THE IGBT ($T_C = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Unit |
|--|--|--|-----|------|-----------|---------------------------|
| OFF CHARACTERISTICS | | | | | | |
| BV_{CES} | Collector to Emitter Breakdown Voltage | $V_{\text{GE}} = 0 \text{ V}$, $I_C = 1 \text{ mA}$ | 650 | – | – | V |
| $\Delta \text{BV}_{\text{CES}} / \Delta T_J$ | Temperature Coefficient of Breakdown Voltage | $V_{\text{GE}} = 0 \text{ V}$, $I_C = 1 \text{ mA}$ | – | 0.5 | – | $\text{V}/^\circ\text{C}$ |
| I_{CES} | Collector Cut-Off Current | $V_{\text{CE}} = V_{\text{CES}}$, $V_{\text{GE}} = 0 \text{ V}$ | – | – | 250 | μA |
| I_{GES} | G-E Leakage Current | $V_{\text{GE}} = V_{\text{GES}}$, $V_{\text{CE}} = 0 \text{ V}$ | – | – | ± 400 | nA |
| ON CHARACTERISTICS | | | | | | |
| $V_{\text{GE}(\text{th})}$ | G-E Threshold Voltage | $I_C = 40 \text{ mA}$, $V_{\text{CE}} = V_{\text{GE}}$ | 2.6 | 5.3 | 6.6 | V |
| $V_{\text{CE}(\text{sat})}$ | Collector to Emitter Saturation Voltage | $I_C = 40 \text{ A}$, $V_{\text{GE}} = 15 \text{ V}$ | – | 1.6 | 2.1 | V |
| | | $I_C = 40 \text{ A}$, $V_{\text{GE}} = 15 \text{ V}$, $T_C = 175^\circ\text{C}$ | – | 1.9 | – | V |
| DYNAMIC CHARACTERISTICS | | | | | | |
| C_{ies} | Input Capacitance | $V_{\text{CE}} = 30 \text{ V}$, $V_{\text{GE}} = 0 \text{ V}$, $f = 1 \text{ MHz}$ | – | 2590 | – | pF |
| C_{oes} | Output Capacitance | | – | 35 | – | pF |
| C_{res} | Reverse Transfer Capacitance | | – | 10 | – | pF |
| SWITCHING CHARACTERISTICS | | | | | | |
| $T_{\text{d}(\text{on})}$ | Turn-On Delay Time | $V_{\text{CC}} = 400 \text{ V}$, $I_C = 10 \text{ A}$, $R_G = 6 \Omega$, $V_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 25^\circ\text{C}$ | – | 17.8 | – | ns |
| T_r | Rise Time | | – | 6.3 | – | ns |
| $T_{\text{d}(\text{off})}$ | Turn-Off Delay Time | | – | 81.6 | – | ns |
| T_f | Fall Time | | – | 9.3 | – | ns |
| E_{on} | Turn-On Switching Loss | | – | 132 | – | μJ |
| E_{off} | Turn-Off Switching Loss | | – | 62 | – | μJ |
| E_{ts} | Total Switching Loss | | – | 194 | – | μJ |
| $T_{\text{d}(\text{on})}$ | Turn-On Delay Time | $V_{\text{CC}} = 400 \text{ V}$, $I_C = 20 \text{ A}$, $R_G = 6 \Omega$, $V_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 25^\circ\text{C}$ | – | 19.5 | – | ns |
| T_r | Rise Time | | – | 9.6 | – | ns |
| $T_{\text{d}(\text{off})}$ | Turn-Off Delay Time | | – | 76.8 | – | ns |
| T_f | Fall Time | | – | 7.4 | – | ns |
| E_{on} | Turn-On Switching Loss | | – | 296 | – | μJ |
| E_{off} | Turn-Off Switching Loss | | – | 111 | – | μJ |
| E_{ts} | Total Switching Loss | | – | 407 | – | μJ |
| $T_{\text{d}(\text{on})}$ | Turn-On Delay Time | $V_{\text{CC}} = 400 \text{ V}$, $I_C = 10 \text{ A}$, $R_G = 6 \Omega$, $V_{\text{GE}} = 15 \text{ V}$, Inductive Load, $T_C = 175^\circ\text{C}$ | – | 17.5 | – | ns |
| T_r | Rise Time | | – | 6.8 | – | ns |
| $T_{\text{d}(\text{off})}$ | Turn-Off Delay Time | | – | 88 | – | ns |
| T_f | Fall Time | | – | 9.7 | – | ns |
| E_{on} | Turn-On Switching Loss | | – | 285 | – | μJ |
| E_{off} | Turn-Off Switching Loss | | – | 106 | – | μJ |
| E_{ts} | Total Switching Loss | | – | 391 | – | μJ |

FGAF40S65AQ

Table 3. ELECTRICAL CHARACTERISTICS OF THE IGBT ($T_C = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Unit |
|----------------------------------|--------------------------|---|-----|------|-----|---------------|
| SWITCHING CHARACTERISTICS | | | | | | |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 400 \text{ V}, I_C = 20 \text{ A}, R_G = 6 \Omega, V_{GE} = 15 \text{ V},$ Inductive Load, $T_C = 175^\circ\text{C}$ | - | 19.1 | - | ns |
| T_r | Rise Time | | - | 11.2 | - | ns |
| $T_{d(off)}$ | Turn-Off Delay Time | | - | 81.6 | - | ns |
| T_f | Fall Time | | - | 9.2 | - | ns |
| E_{on} | Turn-On Switching Loss | | - | 552 | - | μJ |
| E_{off} | Turn-Off Switching Loss | | - | 186 | - | μJ |
| E_{ts} | Total Switching Loss | | - | 738 | - | μJ |
| Q_g | Total Gate Charge | $V_{CE} = 400 \text{ V}, I_C = 40 \text{ A},$ $V_{GE} = 15 \text{ V}$ | - | 75 | - | nC |
| Q_{ge} | Gate to Emitter Charge | | - | 15 | - | nC |
| Q_{gc} | Gate to Collector Charge | | - | 18 | - | nC |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Table 4. ELECTRICAL CHARACTERISTICS OF THE DIODE ($T_C = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Test Conditions | | Min | Typ | Max | Unit | |
|-----------|-------------------------------|--|---------------------------|-----|------|-----|---------------|--|
| V_{FM} | Diode Forward Voltage | $I_F = 20 \text{ A}$ | $T_C = 25^\circ\text{C}$ | - | 1.2 | 1.6 | V | |
| | | | $T_C = 175^\circ\text{C}$ | - | 1.16 | - | | |
| E_{rec} | Reverse Recovery Energy | $I_F = 20 \text{ A},$ $dI_F/dt = 200 \text{ A}/\mu\text{s}$ | $T_C = 175^\circ\text{C}$ | - | 325 | - | μJ | |
| T_{rr} | Diode Reverse Recovery Time | | $T_C = 25^\circ\text{C}$ | - | 274 | - | ns | |
| | | | $T_C = 175^\circ\text{C}$ | - | 362 | - | | |
| Q_{rr} | Diode Reverse Recovery Charge | | $T_C = 25^\circ\text{C}$ | - | 1596 | - | nC | |
| | | | $T_C = 175^\circ\text{C}$ | - | 2651 | - | | |

TYPICAL CHARACTERISTICS




Figure 1. Typical Output Characteristics




Figure 2. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 5. Saturation Voltage vs. V_{GE}




Figure 6. Saturation Voltage vs. V_{GE}

TYPICAL CHARACTERISTICS (Continued)




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Turn-on Characteristics vs. Gate Resistance




Figure 10. Turn-off Characteristics vs. Gate Resistance




Figure 11. Switching Loss vs. Gate Resistance










Figure 12. Turn-on Characteristics vs. Collector Current

TYPICAL CHARACTERISTICS (Continued)



FGAF40S65AQ

TYPICAL CHARACTERISTICS (Continued)




Figure 19. Reverse Recovery Time




Figure 20. Stored Charge





Figure 21. Transient Thermal Impedance of IGBT

FGAF40S65AQ

PACKAGE DIMENSIONS



TO-3PF-3L
CASE 340AH
ISSUE A

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR UNCONTROLLED IN THIS AREA (6 PLACES).
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR GATE PROTRUSIONS. MOLD FLASH AND GATE PROTRUSIONS NOT TO EXCEED 0.13 PER SIDE. THESE DIMENSIONS ARE TO BE MEASURED AT THE OUTERMOST EXTREME OF THE PLASTIC BODY.
5. DIMENSION b2 DOES NOT INCLUDE DAMBAR PROTRUSION. LEAD WIDTH INCLUDING PROTRUSION SHALL NOT EXCEED 2.20.

| | MILLIMETERS | |
|-----|-------------|-------|
| DIM | MIN | MAX |
| A | 5.30 | 5.70 |
| A1 | 2.80 | 3.20 |
| A2 | 3.10 | 3.50 |
| A3 | 1.80 | 2.20 |
| b | 0.65 | 0.95 |
| b2 | 1.90 | 2.15 |
| b3 | 3.80 | 4.20 |
| c | 0.80 | 1.10 |
| D | 24.30 | 24.70 |
| D2 | 24.70 | 25.30 |
| D3 | 3.30 | 3.70 |
| E | 15.30 | 15.70 |
| e | 5.35 | 5.55 |
| H1 | 9.80 | 10.20 |
| L | 19.10 | 19.50 |
| L1 | 4.80 | 5.20 |
| L2 | 1.90 | 2.20 |
| P | 3.40 | 3.80 |
| Q | 4.30 | 4.70 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada

Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литер Н,
помещение 100-Н Офис 331