



ES Rectangle . RS

10.4~49.4W

LED Module maximum operating temperature(Tc) <105°C

BXRA-xxx0800/0950/1100 (10.4W)
BXRA-xxx1200/1350/1600 (14.8W)
BXRA-xxx2000/1350/2600 (25.9W)
BXRA-xxx3500/4000/4500-F-00 (31.8W)
BXRA-xxx4000/4500/5300-H-00 (49.4W)

CL-L340

47.3W

LED Module maximum operating temperature(Tc) <100°C

CL-L340-MC41N1-C1 (47.3W)
CL-L340-MC41W1-C (47.3W)
CL-L340-MC41WW1-C (47.3W)
CL-L340-MC41L1-C (47.3W)
CL-L340-MC41L2-C (47.3W)
CL-L340-C41N-C (47.3W)

PrevaLED

11.5~51.6W

LED Module maximum operating temperature(Tc) <85°C

PL-CORE-Z3-1000 (11.5W)
PL-CORE-Z3-2000 (21.4W)
PL-CORE-Z3-3000 (32.5W)
PL-CORE-Z3-5000 (51.6W)

Fortimo SLM

23~45W

LED Module maximum operating temperature(Tc) <75°C

2000lm G3 (23W)
3000lm G3 (33W)
4000lm G3 (45W)
4500lm G3 (45W)

TALEXX

21.5~41.0W

LED Module maximum operating temperature(Tc) <90°C

STARK-SLE-G3-19-2000-SEL (21.5 W)
STARK-SLE-G3-19-3000-SEL (32.5 W)
STARK-SLE-G3-23-3000-SEL (30.0 W)
STARK-SLE-G3-19-2000-SEL (40.9 W)
STARK-SLE-G3-23-4000-SEL (41.0 W)

LUGA Shop

28.8~54.4W

LED Module maximum operating temperature(Tc) <85°C

WU-M-461 (28.8W)
WU-M-462 (42.0W)
WU-M-464 (54.4W)

Size : Ø86 x 30.4mm		Size : Ø86 x 45.4mm		Size : Ø86 x 52.4mm	
LA001-018A81DY (aluminum colour 5V)		LA004-024A83DY (aluminum colour 5V)		LA006-006A83DY (aluminum colour 5V)	
LA001-018B81DY (black 5V)		LA004-024B83DY (black 12V)		LA006-006B83DY (black 5V)	
LA001-019A81DY (aluminum colour 12V)		LA004-025A83DY (aluminum colour 12V)		LA006-007A83DY (aluminum colour 12V)	
LA001-019B81DY (black 12V)		LA004-025B83DY (black 12V)		LA006-007B83DY (black 12V)	
Weight (g)	112	Weight (g)	194	Weight (g)	234
Fan Speed (RPM)	2200	Fan Speed (RPM)	2200	Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	17.0	Noise @ 1M , (dB(A))	17.0	Noise @ 1M , (dB(A))	17.0
Zhaga Zhaga hole : Book3		Zhaga Zhaga hole : Book3		Zhaga Zhaga hole : Book3	



ES Rectangle RS

85.4W

LED Module maximum operating temperature (Tc) <105°C

BXRA-XXX7000/7500/9000-J-00 (85.4W)

Size : 121 x 92.3 x 66.0 mm	
LM310-003A99DN	
Weight (g)	352
Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	17.8



COB

10.9~42.9W

LED Module maximum operating temperature (Tc) <100°C

CLL032-1205A5 (10.9W) CLL032-1208A5 (17.4W)
CLL032-1205A5 (26.8W) CLL032-1208A5 (42.9W)
CLL032-1206A5 (13.0W) CLL032-1212A5 (26.1W)
CLL032-1206A5 (32.2W) CLL042-1218A5 (39.1W)

Size : Ø86 x 40.4mm	
LA003-014A82DN (aluminum colour 12V)	
LA003-014B82DN (black 12V)	
Weight (g)	163
Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	16.5



Partner GE Lighting

Infusion

13.5~40W

LED Module maximum operating temperature (Tp) <65°C

Gen3 M1000 Series (13.5W)
Gen3 M1500 Series (20W)
Gen3 M2000 Series (27W)
Gen3 M3000 Series (40W)

Size : Ø86x40.4mm	
LA003-013A82DY (Aluminum colour 5V)	
LA003-013B82DY (Black 5V)	
LA003-012A82DY (Aluminum colour 12V)	
LA003-012B82DY (Black 12V)	
Weight (g)	163
Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	16.5



Fortimo SLM

23~33W

LED Module maximum operating temperature (Tc) <75°C

2000lm Gen3 (23W)
3000lm Gen3 (33W)

Size : Ø99 x 110mm	
SM203-13002	
Weight (g)	211
Heat Sink Material	AL1050
	C1100
*1 TDP (W)	23.8
*2 Thermal Resistance (°C/W)	1.38
ΔT (°C)	32.9
Zhaga Zhaga hole : Book3	



XSM

5.7~28.8W

LED Module maximum operating temperature (Tc) <90°C

XSM80XX-400-C (5.7W) XSM80XX-1300-C (17.8W)
XSM80XX-700-C (9.7W) XSM80XX-2000-C (28.8W)
XSM80XX-1000-C (13W)

Size : Ø52 x 20mm	
LA002-012A9BDN (M2 screw)	
LA002-014A9BDN (M3 screw)	
Weight (g)	48
Fan Speed (RPM)	3800
Noise @ 1M , (dB(A))	16.8



COB

58.8~171W

LED Module maximum operating temperature (Tc) <100°C

CLL042-1818A5 (58.8W)
CLL042-1218A5 (96.61W)
CLL042-1818A5 (144.9W)
CLL052-1825B1 (79.1W)
CLL052-1825B1 (171W)

Size : 121 x 92.3 x 66.0 mm	
LM310-001A99DN	
Weight (g)	352
Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	17.8

Size : Ø86x57.4mm	
LA004-017A83DY (Aluminum colour 12V)	
LA004-017B83DY (Black 12V)	
Weight (g)	268
Fan Speed (RPM)	2200
Noise @ 1M , (dB(A))	15.9

*1 TDP (Thermal Design Power) is for reference only. Actual thermal performance may vary by different applications. Please test it again by using on different applications.

*2 Thermal resistance is measured from the bottom middle of heat sink in free air without airflow obstructions, with PHILIPS(Fortimo LED SLM 3000 33W/930 L19 G3) LED chip.



www.sunon.com
sunon@email.sunon.com.tw
2014/7/16 (197-E)

※ The cooling modules pass LED light engine manufacturers' operating temperature requirement and it tests at at 35°C ambient temperature.
※ If you need special specification. Please contact Sunon sales.
※ Specifications are subject to change without notice. Specifications in this catalog are for reference. More Sunon products information please visit SUNON web site at www.sunon.com.

■ LED Lighting Active Cooling Module & Cooling Fan

Application : MR16



Specifications		
Model No.	EF30080S2-E00U-A99	HA30101V3-E00U-A99
Module Dimension (mm)	φ 30 x 8	φ 39.8 x 10.4
Weight (g)	4.3	7.3
Rated Voltage (V)	3.3/5	12
Power Consumption (W)	0.20 / 0.40	0.30
Fan Speed (RPM)	4300 / 7000	4400
Air Flow (CFM)	1.8 / 3.0	1.9
Static Pressure (Inch-H ₂ O)	0.03 / 0.08	0.04
Noise @ 1M (dB(A))	3.1 / 17.0	10.5
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE

Application : A19



Specifications		Specifications	
Model No.	TA001-09012	Model No.	HA40101V3-E00U-A99
Module Dimension (mm)	φ 59 x 20.53	Module Dimension (mm)	φ 48.9 x 10.6
Weight (g)	48.0	Weight (g)	11.8
Noise @ 1M (dB(A))	16.8	Rated Voltage (V)	12
Rated Voltage (V)	5	Power Consumption (W)	0.32
Power Consumption (W)	0.21	Fan Speed (RPM)	3900
Fan Speed (RPM)	3800	Air Flow (CFM)	4.5
Heat Sink Material	ADC12	Static Pressure (Inch-H ₂ O)	0.05
Zhaga Holes	- -	Noise @ 1M (dB(A))	13.1
Safety	UL / CUR / TUV / CE	Safety	UL / CUR / TUV / CE

■ Cooling Fan

Application : Spotlight / Downlight



Specifications				
Model No.	HA60150V3-E03U-A99	HA60151V3-E00U-A99	HA60150V3-E02U-A99	HA60151V3-E01U-A99
Fan Dimension (mm)	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 15.4
Weight (g)	29.1	29.1	27.3	27.3
Rated Voltage (V)	5	12	5	12
Power Consumption (W)	0.26	0.28	0.40	0.34
Fan Speed (RPM)	2300	2300	2300	2300
Air Flow (CFM)	9.7	9.7	13.2	13.2
Static Pressure (Inch-H ₂ O)	0.03	0.03	0.03	0.03
Noise @1M (dB(A))	15.4	15.4	16.1	16.1
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE

* model with PWM control function



Specifications				
Model No.	HA60150V3-E00U-H99 *	HA60151V3-E05U-H99 *	HA60200V3-E00U-A99	HA60201V3-E00U-A99
Fan Dimension (mm)	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 20.4	φ 84.9 x 20.4
Weight (g)	28.8	28.8	30.5	30.5
Rated Voltage (V)	5	12	5	12
Power Consumption (W)	0.33	0.42	0.31	0.34
Rated Speed (RPM)	2300	2300	2300	2300
Air Flow (CFM)	13.2	13.2	13	13
Static Pressure (Inch-H ₂ O)	0.03	0.03	0.03	0.03
Noise @1M (dB(A))	16.1	16.1	17.5	17.5
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE

■ LED Lighting Passive Cooling Module



Specifications		
Model No.	SM203-13002	
Module Dimension (mm)	φ 99 x 110	
Weight (g)	211	
Heat Sink Material	AL1050 + ADC10 + C1100	
* ₁ TDP (W)	23.8	
* ₂ Thermal Resistance (°C/W)	1.38	
ΔT (°C)	32.9	

*₁ TDP (Thermal Design Power) is for reference only. Actual thermal performance may vary by different applications. Please test it again by using on different applications.

*₂ Thermal resistance is measured from the bottom middle of heat sink in free air without airflow obstructions, with PHILIPS(Fortimo LED SLM 3000 33W/930 L19 G3) heat source.





**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331