



### Main

|                           |                  |
|---------------------------|------------------|
| Range of product          | 9007             |
| Series name               | Miniature potted |
| Product or component type | Limit switch     |
| Device short name         | 9007MS/ML        |
| Sensor design             | Miniature        |
| Body type                 | Fixed            |
| Head type                 | Rotary head      |
| Material                  | Metal            |
| Body material             | Cast zinc        |
| Number of poles           | 1                |

### Complementary

|                                              |                                                                                                               |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Fixing mode                                  | By the body                                                                                                   |
| Movement of operating head                   | Rotary                                                                                                        |
| Type of operator                             | Spring return without operating lever (-)                                                                     |
| Type of approach                             | Lateral approach 2 directions                                                                                 |
| Switch actuation                             | From left and right<br>CW and CCW                                                                             |
| Contacts type and composition                | NC-NO                                                                                                         |
| Switch function                              | SPDT                                                                                                          |
| Contact form                                 | Form C                                                                                                        |
| Contacts material                            | Gold flashed contacts                                                                                         |
| Contact operation                            | Snap action                                                                                                   |
| Positive opening                             | Without                                                                                                       |
| Electrical connection                        | Pre-wired cable bottom                                                                                        |
| Type of cable                                | SJTO cable (AWG 18), 9 ft, yellow                                                                             |
| Terminals description ISO n°1                | (green-yellow)gnd<br>(black)com<br>(white)NO<br>(red)NC                                                       |
| Wire insulation material                     | PVC                                                                                                           |
| Minimum torque for tripping                  | 48 ozf.in                                                                                                     |
| Maximum actuation speed                      | 90 ft/min with 45° cam angle, levers only<br>130 ft/min with 30° cam angle, levers only                       |
| Tripping angle                               | 35 °                                                                                                          |
| Maximum displacement angle                   | 70 °                                                                                                          |
| [Ie] rated operational current               | 100 mAat 125 V AC<br>30 mAat 28 V DC                                                                          |
| [Ithe] conventional enclosed thermal current | 10 A                                                                                                          |
| [Ui] rated insulation voltage                | 300 V degree of pollution 3 conforming to UL 508<br>300 V degree of pollution 3 conforming to CSA C22.2 No 14 |
| Electrical durability                        | 100000 cycles                                                                                                 |
| Mechanical durability                        | 10000000 cycles                                                                                               |
| Marking                                      | CE<br>CSA<br>UL                                                                                               |
| Sale per indivisible quantity                | 1                                                                                                             |
| Height                                       | 2.49 in                                                                                                       |
| Width                                        | 1.56 in                                                                                                       |
| Depth                                        | 0.62 in                                                                                                       |
| Product weight                               | 1.2 lb(US)                                                                                                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |                                                                                                                                                                                             |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| shock resistance                      | 35 gn (duration = 9 ms) conforming to IEC 60068-2-27                                                                                                                                        |
| vibration resistance                  | 10 gn (f = 75...1200 Hz) conforming to IEC 60068-2-6                                                                                                                                        |
| NEMA degree of protection             | NEMA 1 conforming to Nema type 250<br>NEMA 2 conforming to Nema type 250<br>NEMA 4 conforming to Nema type 250<br>NEMA 6 conforming to Nema type 250<br>NEMA 6P conforming to Nema type 250 |
| IP degree of protection               | IP67 conforming to IEC 60529                                                                                                                                                                |
| ambient air temperature for operation | -40...220 °F                                                                                                                                                                                |
| ambient air temperature for storage   | -40...220 °F                                                                                                                                                                                |
| protective treatment                  | Epoxy powder coat                                                                                                                                                                           |
| product certifications                | CE<br>CSA<br>UL                                                                                                                                                                             |
| standards                             | LR 25490 Class 32 11 03<br>E78403                                                                                                                                                           |

## Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                  | Not Green Premium product                                                                                                  |
| Will not be Compliant                                                                                                      | Will not be Compliant                                                                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Available                                                                                                                  | Available                                                                                                                  |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331