


1 Watt IA Series



- Dual Output
- SIP or DIP Package
- Industry Standard Pinout
- 1000 VDC Isolation
- -40 °C to +85 °C Operation
- MTBF >1.1 Mhrs
- 3 Year Warranty

Specification

Input

- | | |
|----------------------------------|--|
| Input Voltage Range | • Nominal $\pm 10\%$ ⁽⁵⁾ |
| Input Reflected Ripple Current | • 20 mA pk-pk (through 12 μ H inductor 5 Hz to 20 MHz) |
| Input Reverse Voltage Protection | • None |

Output

- | | |
|-------------------------|--|
| Output Voltage | • See table |
| Minimum Load | • None ⁽⁶⁾ |
| Line Regulation | • 1.2%/1% Δ Vin |
| Load Regulation | • 10% 20-100% load change (3.3 V models $\pm 20\%$) |
| Setpoint Accuracy | • $\pm 3\%$ |
| Ripple & Noise | • 75 mV pk-pk max, 20 MHz bandwidth |
| Temperature Coefficient | • 0.02%/°C |
| Maximum Capacitive Load | • $\pm 100 \mu$ F |

General

- | | |
|-----------------------|--|
| Efficiency | • See table |
| Isolation Voltage | • 1000 VDC minimum |
| Isolation Resistance | • $10^9 \Omega$ |
| Isolation Capacitance | • 60 pF typical |
| Switching Frequency | • Variable, 80 KHz typical |
| MTBF | • >1.12 Mhrs to MIL-HDBK-217F at 25 °C, GB |

Environmental

- | | |
|-----------------------|---------------------|
| Operating Temperature | • -40 °C to +85 °C |
| Storage Temperature | • -40 °C to +125 °C |
| Case Temperature | • 100 °C max |
| Cooling | • Convection-cooled |

Notes


1. Replace 'S' in model number with 'D' for DIP package.
2. SIP 48 Vin models, dimension is 0.28 (7.20) max.
3. DIP 48 Vin models, dimension is 0.27 (6.88) max.
4. Outputs power-trade.
5. For 48 V models a 10 μ F capacitor is required between +Vin and -Vin pins.
6. Operation at no load will not damage unit but it may not meet all specifications.
7. All dimensions in inches (mm).
8. Pin pitch tolerance: ± 0.014 (± 0.35)
9. Case tolerance ± 0.02 (± 0.5)
10. Weight: SIP 0.006 lbs (2.6 g), DIP 0.005 lbs (2.3 g)

Input Voltage	Output Voltage	Output Current ⁽⁴⁾	Efficiency	Model Number ⁽¹⁾
3.3 VDC	± 5.0 V	± 100 mA	66%	IA0305S
5 VDC	± 3.3 V	± 151 mA	65%	IA0503S [^]
	± 5.0 V	± 100 mA	74%	IA0505S ^{†^}
	± 9.0 V	± 55 mA	78%	IA0509S ^{†^}
	± 12.0 V	± 42 mA	78%	IA0512S ^{†^}
	± 15.0 V	± 33 mA	80%	IA0515S ^{†^}
	± 24.0 V	± 21 mA	80%	IA0524S [^]
12 VDC	± 3.3 V	± 151 mA	66%	IA1203S [^]
	± 5.0 V	± 100 mA	75%	IA1205S ^{†^}
	± 9.0 V	± 55 mA	76%	IA1209S ^{†^}
	± 12.0 V	± 42 mA	78%	IA1212S ^{†^}
	± 15.0 V	± 33 mA	80%	IA1215S ^{†^}
	± 24.0 V	± 21 mA	76%	IA1224S [^]
24 VDC	± 3.3 V	± 151 mA	68%	IA2403S [^]
	± 5.0 V	± 100 mA	74%	IA2405S ^{†^}
	± 9.0 V	± 55 mA	76%	IA2409S [^]
	± 12.0 V	± 42 mA	78%	IA2412S ^{†^}
	± 15.0 V	± 33 mA	78%	IA2415S ^{†^}
	± 24.0 V	± 21 mA	78%	IA2424S [^]
48 VDC ⁽⁵⁾	± 3.3 V	± 151 mA	60%	IA4803S
	± 5.0 V	± 100 mA	70%	IA4805S [†]
	± 9.0 V	± 55 mA	72%	IA4809S
	± 12.0 V	± 42 mA	74%	IA4812S [†]
	± 15.0 V	± 33 mA	74%	IA4815S
	± 24.0 V	± 21 mA	70%	IA4824S

[†] Available from Farnell & element14. See pages 284-290.

[^] Available from Newark. See pages 291-296.

Mechanical Details





**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331