

Switch Mode Power Supply S8VS

15/30-W Models

Compact, Thin Power Supplies That Mount Just About Anywhere to Contribute to Control Panel Downsizing

- Compact, thin size: 22.5 × 85 × 96.5 mm (W × H × D).
- Three mounting directions (standard, horizontal, facing horizontal).
- Mounting directly onto the panel is possible.
- Safety standards:
UL508/60950-1/1604, CSA C22.2 No. 14/60950-1/213,
EN50178 (= VDE0160), EN60950-1 (= VDE0805).



60/90/120/180/240-W Models

New Models with Total Run Time Monitor in Addition to Models with Maintenance Forecast Monitor

- Compact size: 40 × 95 mm (W × H) (60-W Models).
- Status displayed on 3-digit, 7-segment display.
- Safety standards:
UL508/60950, CSA C22.2 No. 14/60950,
EN50178 (= VDE0160), EN60950 (= VDE0805).



Features Common to All Models

- Mount to DIN-rail.
- Lead-free solder.

Model Number Structure

■ Model Number Legend

S8VS-

1 2 3

1. Power Ratings

015: 15 W
030: 30 W
060: 60 W
090: 90 W
120: 120 W
180: 180 W
240: 240 W

2. Output voltage

05: 5 V
12: 12 V
24: 24 V

3. Configuration

15-W, 30-W Models

None: Standard

60-W Models

None: Standard

A: With maintenance forecast monitor
B: With total run time monitor

90-W, 120-W, 180-W, 240-W Models

None: Standard

A: With maintenance forecast monitor and undervoltage alarm (transistor (sinking))
B: With total run time monitor and undervoltage alarm (transistor (sinking))
AP: With maintenance forecast monitor and undervoltage alarm (transistor (sourcing))
BP: With total run time monitor and undervoltage alarm (transistor (sourcing))

Ordering Information

Power ratings	Input Voltage	Output voltage	Output current	Alarm output	Model number	
15 W	100 to 240 VAC	5 V	2.0 A	---	S8VS-01505 (See note 1.)	
		12 V	1.2 A		S8VS-01512	
		24 V	0.65 A		S8VS-01524	
30 W		5 V	4.0 A	---	S8VS-03005 (See note 2.)	
		12 V	2.5 A		S8VS-03012	
		24 V	1.3 A		S8VS-03024	
60 W		24 V	2.5 A	---	S8VS-06024	
					S8VS-06024A	
					S8VS-06024B	
90 W			3.75 A		---	S8VS-09024
					Sinking	S8VS-09024A
					Sourcing	S8VS-09024AP
					Sinking	S8VS-09024B
					Sourcing	S8VS-09024BP
120 W			5 A		---	S8VS-12024
					Sinking	S8VS-12024A
					Sourcing	S8VS-12024AP
					Sinking	S8VS-12024B
					Sourcing	S8VS-12024BP
180 W			7.5 A		---	S8VS-18024
					Sinking	S8VS-18024A
					Sourcing	S8VS-18024AP
					Sinking	S8VS-18024B
					Sourcing	S8VS-18024BP
240 W			10 A		---	S8VS-24024
					Sinking	S8VS-24024A
					Sourcing	S8VS-24024AP
					Sinking	S8VS-24024B
					Sourcing	S8VS-24024BP

Note: 1. The output capacity of the S8VS-01505 is 10 W.

2. The output capacity of the S8VS-03005 is 20 W.

Specifications

■ Ratings/Characteristics

Power ratings		15 W	30 W
Type		Standard	Standard
Item			
Efficiency (typical)	5-V models	72% min. (76% typ.)	70% min. (76% typ.)
	12-V models	74% min. (79% typ.)	76% min. (83% typ.)
	24-V models	77% min. (81% typ.)	80% min. (85% typ.)
Input	Voltage	100 to 240 VAC (85 to 264 VAC)	
	Frequency	50/60 Hz (47 to 450 Hz)	
	Current	100 V input	0.45 A max.
		200 V input	0.25 A max.
		230 V input	5 V: (0.14 A typ.), 12 V/24 V (0.19 A typ.)
	Power factor	---	
	Harmonic current emissions	Conforms to EN61000-3-2	
	Leakage current	100 V input	0.5 mA max.
		200 V input	1.0 mA max.
		230 V input	5 V/12 V/24 V: (0.30 mA typ.)
Inrush current (See note 1.)	100 V input	25 A max. (20 A typ.) (for a cold start at 25°C)	
	200 V input	50 A max. (40 A typ.) (for a cold start at 25°C)	
	230 V input	5 V/12 V/24 V: (29 A typ.) (See note 6.)	
		5 V/12 V/24 V: (40 A typ.) (See note 6.)	
Output	Voltage adjustment range (See note 2.)	-10% to 15% (with V.ADJ) (guaranteed)	
	Ripple	2.0% (p-p) max. (at rated input/output voltage)	
		f=20MHz measuring	5 V: (0.70%(p-p) typ.), 12 V:(0.48%(p-p) typ.), 24 V:(0.25%(p-p) typ.)
	f=100MHz measuring	5 V: (0.86%(p-p) typ.), 12 V:(0.56%(p-p) typ.), 24 V:(0.32%(p-p) typ.)	5 V: (0.70%(p-p) typ.), 12 V:(0.52%(p-p) typ.), 24 V:(0.19%(p-p) typ.)
		5 V: (0.80%(p-p) typ.), 12 V:(0.58%(p-p) typ.), 24 V:(0.21%(p-p) typ.)	
	Input variation influence	0.5% max. (at 85 to 264 VAC input, 100% load)	
	Load variation influence (rated input voltage)	2.0% max. (5 V), 1.5% max. (12 V, 24 V), (with rated input, 0 to 100% load)	
	Temperature variation influence	0.05%/°C max.	
	Start up time (See note 1 and 7.)	100 ms max. (at rated input/output voltage)	
		5 V: (6 ms typ.), 12 V: (12 ms typ.), 24 V: (18 ms typ.)	1,000 ms max. (at rated input/output voltage)
	Hold time (See note 1.)	20 ms min. (at rated input/output voltage)	
		5 V: (328 ms typ.), 12V: (251 ms typ.), 24 V: (243 ms typ.)	5 V/12 V/24 V: (240 ms typ.)
	at 100% load	5 V: (299 ms typ.), 12 V: (217 ms typ.), 24 V: (210 ms typ.)	
Additional functions	Overload protection (See note 1.)	105% to 160% of rated load current, voltage drop, automatic reset	
	Overvoltage protection (See note 1.)	Yes (a zener diode clamp) (See note 3.)	
	Output voltage indication	No	
	Output current indication	No	
	Peak-hold current indication	No	
	Maintenance forecast monitor indication	No	
	Maintenance forecast monitor output	No	
	Total run time monitor indication	No	
	Total run time monitor output	No	
	Undervoltage alarm indication	Yes (color: red)	
	Undervoltage alarm output	No	
	Parallel operation	No	
	Series operation	Models with 24-V output: Possible for up to 2 Power Supplies (with external diode) Models with 5- or 12-V output: Not possible	
Other	Operating ambient temperature	Refer to the derating curve in <i>Engineering Data</i> . (with no icing or condensation)	
	Storage temperature	-25 to 65°C	
	Operating ambient humidity	25% to 85% (Storage humidity: 25% to 90%)	
	Dielectric strength	3.0 kVAC for 1 min. (between all inputs and outputs; detection current: 20 mA)	
		2.0 kVAC for 1 min. (between all inputs and PE terminals; detection current: 20 mA)	
		1.0 kVAC for 1 min. (between all outputs and PE terminals; detection current: 20 mA)	
	Insulation resistance	100 MΩ min. (between all outputs and all inputs/ PE terminals) at 500 VDC	
	Vibration resistance	10 to 55 Hz, 0.375-mm single amplitude for 2 h each in X, Y, and Z directions	
	Shock resistance	10 to 150 Hz, 0.35-mm single amplitude (5 G max.) for 80 min. each in X, Y, and Z directions	
	Shock resistance	150 m/s ² , 3 times each in ±X, ±Y, and ±Z directions	
	Output indicator	Yes (color: green)	
	EMI	Conducted Emissions	Conforms to EN61204-3 EN55011 Class B and based on FCC Class A
		Radiated Emissions	Conforms to EN61204-3 EN55011 Class B
	EMS	Conforms to EN61204-3 high severity levels	
	Approved standards	UL: UL508 (Listing, Class 2: Per UL1310), UL60950-1, UL1604 (Class I/Division2) cUL: CSA C22.2 No.14 (Class 2), No.60950-1, No.213 (Class I/Division2) EN/VDE: EN50178 (=VDE0160), EN60950-1 (=VDE0805) SELV (EN60950/EN50178/UL60950-1) According to VDE0106/P100, IP20	
	Weight	160 g max.	180 g max.

- Note:**
1. Refer to the *Engineering Data* section on page B-21 for details.
 2. If the V.ADJ adjuster is turned, the voltage will increase by more than +15% of the voltage adjustment range. When adjusting the output voltage, confirm the actual output voltage from the Power Supply and be sure that the load is not damaged.
 3. The overvoltage protection of the S8VS-015 uses a zener diode clamp. If the internal feedback circuit is destroyed by any chance, the load may be destroyed by the clamped output voltage (approx. 140% to 190% of the rated output voltage).
 4. To reset the protection, turn OFF the power supply for three minutes or longer and then turn the power supply back ON.
 5. The typical values indicate the values for an input condition of 230 VAC. All items are measured at a frequency of 50 Hz.
 6. The inrush current circuits do not differ for voltage specifications. Therefore, the typical values are the data values for 24-V models.
 7. The circuit forms are different, so the start up time is shorter only when using a 15-W power rating.

Specifications

■ Ratings/Characteristics

Power ratings Type			60 W			90 W		
			Standard	Maintenance forecast monitor	Total run time monitor	Standard	Maintenance forecast monitor	Total run time monitor
Efficiency (typical)			78% min. (86% typ.)			80% min. (87% typ.)		
Input	Voltage		100 to 240 VAC (85 to 264 VAC)					
	Frequency		50/60 Hz (47 to 450 Hz)					
	Current	100 V input	1.7 A max.			2.3 A max.		
		200 V input	1.0 A max.			1.4 A max.		
		230 V input	(0.7 A typ.)			(0.9 A typ.)		
	Power factor		---					
	Harmonic current emissions		Conforms to EN61000-3-2					
	Leakage current	100 V input	0.5 mA max.					
		200 V input	1.0 mA max.					
		230 V input	(0.40 mA typ.)			(0.35 mA typ.)		
Inrush current (See note 1.)	100 V input	25 A max. (for a cold start at 25°C)						
	200 V input	50 A max. (for a cold start at 25°C)						
	230 V input	(47 A typ.)			(38 A typ.)			
Output	Voltage adjustment range (See note 2.)		-10% to 15% (with V.ADJ.) (guaranteed)					
	Ripple		2.0% (p-p) max. (at rated input/output voltage)					
		f=20MHz measuring	(0.29% (p-p) typ.)			(0.38% (p-p) typ.)		
		f=100MHz measuring	(0.32% (p-p) typ.)			(0.42% (p-p) typ.)		
	Input variation influence		0.5% max. (at 85 to 264 VAC input, 100% load)					
	Load variation influence (rated input voltage)		1.5% max. (with rated input, 0 to 100% load)					
	Temperature variation influence		0.05%/°C max.					
	Start up time (See note 1.)	1,000 ms max. (at rated input/output voltage)						
		(270 ms typ.)			(260 ms typ.)			
	Hold time (See note 1.)	20 ms min. (at rated input/output voltage)						
at 100% load		(220 ms typ.)			(190 ms typ.)			
Additional functions	Overload protection (See note 1.)		105% to 160% of rated load current, voltage drop, intermittent, automatic reset					
	Overvoltage protection (See notes 1 and 3.)		Yes					
	Output voltage indication (See note 4.)		No	Yes (selectable) (See note 5.)		No	Yes (selectable) (See note 5.)	
	Output current indication (See note 4.)		No	Yes (selectable) (See note 6.)		No	Yes (selectable) (See note 6.)	
	Peak-hold current indication (See note 4.)		No	Yes (selectable) (See note 7.)		No	Yes (selectable) (See note 7.)	
	Maintenance forecast monitor indication (See note 4.)		No	Yes (selectable)		No	Yes (selectable)	
	Maintenance forecast monitor output		No			Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	No	
	Total run time monitor indication (See note 4.)		No	Yes (selectable)		No	Yes (selectable)	
	Total run time monitor output		No				Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	
	Undervoltage alarm indication (See note 4.)		No	Yes (selectable)		No	Yes (selectable)	
	Undervoltage alarm output terminals		No				Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	
	Parallel operation		No					
	Series operation		Yes for up to 2 Power Supplies (with external diode)					
Other	Operating ambient temperature		Refer to the derating curve in <i>Engineering Data</i> . (with no icing or condensation)					
	Storage temperature		-25 to 65°C					
	Operating ambient humidity		25% to 85% (Storage humidity: 25% to 90%)					
	Dielectric strength		3.0 kVAC for 1 min. (between all inputs and outputs/ alarm outputs; detection current: 20 mA) 2.0 kVAC for 1 min. (between all inputs and PE terminals; detection current: 20 mA) 1.0 kVAC for 1 min. (between all outputs/ alarm outputs and PE terminals; detection current: 20 mA) 500 VAC for 1 min. (between all outputs and alarm outputs; detection current: 20 mA)					
	Insulation resistance		100 MΩ min. (between all outputs/ alarm outputs and all inputs/ PE terminals) at 500 VDC					
	Vibration resistance		10 to 55 Hz, 0.375-mm single amplitude for 2 h each in X, Y, and Z directions 10 to 150Hz, 0.35-mm single amplitude (5 G max.) for 80 min each in-X, Y, and Z directions					
	Shock resistance		150 m/s², 3 times each in ±X, ±Y, and ±Z directions					
	Output indicator		Yes (color: green)					
	EMI	Conducted Emissions	Conforms to EN61204-3 EN55011 Class A and based on FCC Class A Conforms to EN61204-3 EN55011 Class B (See note 9.)					
		Radiated Emissions	Conforms to EN61204-3 EN55011 Class A Conforms to EN61204-3 EN55011 Class B (See note 9.)					
	EMS		Conforms to EN61204-3 high severity levels					
	Approved standards		UL: UL508 (Listing, Class 2: Per UL1310), UL60950 cUL: CSA C22.2 No.14 (Class 2), No.60950 EN/VDE: EN50178 (=VDE0160), EN60950 (=VDE0805) SELV (EN60950/EN50178/UL60950-1) According to VDE0106/P100, IP20			UL: UL508 (Listing), UL60950 cUL: CSA C22.2 No.14, No.60950 EN/VDE: EN50178 (=VDE0160), EN60950 (=VDE0805) SELV (EN60950/EN50178/UL60950-1) According to VDE0106/P100, IP20		
	Weight		330 g max.			490 g max.		

- Note:**
1. Refer to the *Engineering Data* section on page B-21 for details.
 2. If the V.ADJ adjuster is turned, the voltage will increase by more than +15% of the voltage adjustment range (by more than +10% for 240-W models). When adjusting the output voltage, confirm the actual output voltage from the Power Supply and be sure that the load is not damaged.
 3. To reset the protection, turn OFF the power supply for three minutes or longer and then turn the power supply back ON.
 4. Displayed on 7-segment LED. (character height: 8 mm)
 5. Resolution of output voltage indication: 0.1 V; Precision of output voltage indication: ±2% (percentage of output voltage value, ±1 digit)
 6. Resolution of output current indication: 0.1 A; Precision of output current indication: ±5% F.S. ±1 digit max. (specified by rated output voltage)
 7. Resolution of peak-hold current indication: 0.1 A; Precision of peak-hold current indication: ±5% F.S. ±1 digit max. (specified by rated output voltage);
Signal width required for peak-hold current: 20 ms
 8. A Type and B Type: Sinking, AP Type and P Type: Sourcing
 9. To ensure the emission rating, a ferrite ring core should be used in all cabling (TDK HF60T, HF70RH or equivalent model).
 10. The typical values indicate the values for an input condition of 230 VAC. All items are measured at a frequency of 50 Hz.

Item	Power ratings		120 W			180 W			240 W				
	Type		Standard	Maintenanc e forecast monitor	Total run time monitor	Standard	Maintenanc e forecast monitor	Total run time monitor	Standard	Maintenanc e forecast monitor	Total run time monitor		
Efficiency (typical)			80% min. (87% typ.)			80% min. (88% typ.)			80% min. (86% typ.)				
Input	Voltage		100 to 240 VAC (85 to 264 VAC)										
	Frequency		50/60 Hz (47 to 63 Hz)										
	Current	100 V input	1.9 A max.			2.9 A max.			3.8 A max.				
		200 V input	1.1 A max.			1.6 A max.			2.0 A max.				
		230 V input	(0.6 A typ.)			(0.9 A typ.)			(1.2 A typ.)				
	Power factor		0.95 min.										
	Harmonic current emissions		Conforms to EN61000-3-2										
	Leakage current	100 V input	0.5 mA max.										
		200 V input	1.0 mA max.										
		230 V input	(0.43 mA typ.)			(0.45 mA typ.)			(0.45 mA typ.)				
Inrush current (See note 1.)	100 V input	25 A max. (for a cold start at 25°C)											
	200 V input	50 A max. (for a cold start at 25°C)											
	230 V input	(41 mA typ.)			(34 mA typ.)			(39 mA typ.)					
Output	Voltage adjustment range (See note 2.)		−10% to 15% (with V.ADJ.) (guaranteed)						±10% (with V.ADJ.) (guaranteed)				
	Ripple		2.0% (p-p) max. (at rated input/output voltage)										
			f=20MHz measuring		(0.66%(p-p) typ.)			(0.45%(p-p) typ.)			(0.13%(p-p) typ.)		
			f=100MHz measuring		(0.67%(p-p) typ.)			(0.52%(p-p) typ.)			(0.21%(p-p) typ.)		
	Input variation influence		0.5% max. (at 85 to 264 VAC input, 100% load)										
	Load variation influence (rated input voltage)		1.5% max. (with rated input, 0 to 100% load)										
	Temperature variation influence		0.05%/°C max.										
	Start up time (See note 1.)		1,000 ms max. (at rated input/output voltage)										
	Hold time (See note 1.)		(380 ms typ.)			(530 ms typ.)			(780 ms typ.)				
			20 ms min. (at rated input/output voltage)										
at 100% load		(60 ms typ.)			(60 ms typ.)			(30 ms typ.)					
Additional func- tions	Overload protection (See note 1.)		105% to 160% of rated load current, voltage drop, intermittent, automatic reset							105% to 160% of rated load current, voltage drop, automatic reset			
	Overvoltage protection (See notes 1 and 3.)		Yes										
	Output voltage indication (See note 4.)		No	Yes (selectable) (See note 5.)		No	Yes (selectable) (See note 5.)		No	Yes (selectable) (See note 5.)			
	Output current indication (See note 4.)		No	Yes (selectable) (See note 6.)		No	Yes (selectable) (See note 6.)		No	Yes (selectable) (See note 6.)			
	Peak-hold current indication (See note 4.)		No	Yes (selectable) (See note 7.)		No	Yes (selectable) (See note 7.)		No	Yes (selectable) (See note 7.)			
	Maintenance forecast monitor indication (See note 4.)		No	Yes (selectable)	No	No	Yes (selectable)	No	No	Yes (selectable)	No		
	Maintenance forecast monitor output		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	No	No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	No	No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)	No		
	Total run time monitor indication (See note 4.)		No	Yes (selectable)		No	Yes (selectable)		No	Yes (selectable)			
	Total run time monitor output		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)			
	Undervoltage alarm indication (See note 4.)		No	Yes (selectable)		No	Yes (selectable)		No	Yes (selectable)			
	Undervoltage alarm output terminals		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)		No	Yes (open collector output), 30 VDC max., 50 mA max. (See note 8.)			
	Parallel operation		No										
	Series operation		Yes for up to 2 Power Supplies (with external diode)										
Other	Operating ambient temperature		Refer to the derating curve in <i>Engineering Data</i> . (with no icing or condensation)										
	Storage temperature		−25 to 65°C										
	Operating ambient humidity		25% to 85% (Storage humidity: 25% to 90%)										
	Dielectric strength		3.0 kVAC for 1 min. (between all inputs and outputs/ alarm outputs; detection current: 20 mA) 2.0 kVAC for 1 min. (between all inputs and PE terminals; detection current: 20 mA) 1.0 kVAC for 1 min. (between all outputs/ alarm outputs and PE terminals; detection current: 20 mA) 500 VAC for 1 min. (between all outputs and alarm outputs; detection current: 20 mA)										
	Insulation resistance		100 MΩ min. (between all outputs/ alarm outputs and all inputs/ PE terminals) at 500 VDC										
	Vibration resistance		10 to 55 Hz, 0.375-mm single amplitude for 2 h each in X, Y, and Z directions 10 to 150Hz, 0.35-mm single amplitude (5 G max.) for 80 min each in-X, Y, and Z directions										
	Shock resistance		150 m/s², 3 times each in ±X, ±Y, and ±Z directions										
	Output indicator		Yes (color: green)										
	EMI	Conducted Emissions	Conforms to EN61204-3 EN55011 Class A and based on FCC Class A Conforms to EN61204-3 EN55011 Class B (See note 9.)										
		Radiated Emissions	Conforms to EN61204-3 EN55011 Class A Conforms to EN61204-3 EN55011 Class B (See note 9.)										
	EMS		Conforms to EN61204-3 high severity levels										
	Approved standards		UL: UL508 (Listing), UL60950 cUL: CSA C22.2 No.14, No.60950 EN/VDE: EN50178 (=VDE0160), EN60950 (=VDE0805) SELV (EN60950/UL50178/UL60950-1) According to VDE0106/P100, IP20										
	Weight		550 g max.			850 g max.			1,150 g max.				



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331