

## Product Facts

- Designed to be the smallest, lightest weight, lowest cost sealed contactor in the industry with its current rating (500+A carry, 2000A interrupt at 320VDC).
- Built-in coil economizer – only 1.7W hold power @ 12VDC and it limits back EMF to 0V. Models requiring external economizer also available.
- Optional auxiliary contact for easy monitoring of power contact position.
- Hermetically sealed – intrinsically safe, operates in explosive/harsh environments with no oxidation or contamination of coils or contacts, including long periods of non-operation.
- Versatile coil/power connections.
- CE marked for EC applications.
- AIAG QS9000 designed, built and approved



EV200 Series Contactor  
(CZONKA® Relay, Type III)

Typical EV200 applications include battery switching and back-up, DC voltage power control, circuit protection and safety.

For factory-direct application assistance, dial 800-253-4560, ext. 2055, or 805-220-2055.

## Performance Data

| Parameter                                            | Units   | Value for EV200 Series                                                                                        |
|------------------------------------------------------|---------|---------------------------------------------------------------------------------------------------------------|
| Contact Arrangement, power contacts                  |         | 1 Form X (SPST-NO-DM)                                                                                         |
| Rated Operating Voltage                              | VDC     | 12 - 900                                                                                                      |
| Continuous (Carry) Current, Typical                  | A       | 500 @ 85°C, 400 mcm conductors<br><i>Consult Factory for required conductors for higher (500+ A) currents</i> |
| Make/Break Current at Various Voltages <sup>1/</sup> | A       | See next page                                                                                                 |
| Break Current at 320VDC <sup>1/</sup>                | A       | 2,000, 1 cycle <sup>3/</sup>                                                                                  |
| Contact Resistance, Typ. (@200A)                     | mohms   | 0.2                                                                                                           |
| Load Life                                            | Cycles  | See next page                                                                                                 |
| Mechanical Life                                      | Cycles  | 1 million                                                                                                     |
| Contact Arrangement, auxiliary contacts              |         | 1 Form A (SPST-NO)                                                                                            |
| Aux. Contact Current, Max.                           | A       | 2A @ 30VDC / 3A @ 125VAC                                                                                      |
| Aux. Contact Current, Min.                           | mA      | 100mA @ 8V                                                                                                    |
| Aux. Contact Resistance, Max.                        | ohms    | 0.417 @ 30VDC / .150 @ 125VAC                                                                                 |
| Operate Time @ 25°C                                  |         |                                                                                                               |
| Close (includes bounce), Typ.                        | ms      | 15                                                                                                            |
| Bounce (after close only), Max.                      | ms      | 7                                                                                                             |
| Release (includes arcing), Max @ 2000A               | ms      | 12                                                                                                            |
| Dielectric Withstanding Voltage                      | Vrms    | 2,200 @ sea level (leakage <1mA)                                                                              |
| Insulation Resistance @ 500VDC                       | megohms | 100 <sup>2/</sup>                                                                                             |
| Shock, 11ms 1/2 sine, peak, operating                | G       | 20                                                                                                            |
| Vibration, sine, 80-2000Hz., peak                    | G       | 20                                                                                                            |
| Operating Ambient Temperature                        | °C      | -40 to +85                                                                                                    |
| Weight, Nominal                                      | lb.(kg) | .95 (.43)                                                                                                     |

<sup>1/</sup> Main power contacts

<sup>2/</sup> 50 at end of life

<sup>3/</sup> Does not meet dielectric & IR after test, 1700 amp for unit with Aux. Contacts

## Coil Operating Voltage (valid over temperature range)

| Voltage (will operate)        | 9-36VDC              | 32-95VDC  | 48-95VDC  |
|-------------------------------|----------------------|-----------|-----------|
| Voltage (Max.)                | 36VDC                | 95VDC     | 95VDC     |
| Pickup (close) Voltage Max.   | 9VDC                 | 32VDC     | 48VDC     |
| Hold Voltage (Min.)           | 7.5VDC               | 22VDC     | 34VDC     |
| Dropout (open) Voltage (Min.) | 6VDC                 | 18VDC     | 27VDC     |
| Inrush Current (Max.)         | 3.8A                 | 1.3A      | 0.7A      |
| Holding Current (Avg.)        | 0.13A@12V, 0.07A@24V | 0.03A@48V | 0.02A@72V |
| Inrush Time (Max.)            | 130ms                | 130ms     | 130ms     |

## Part Numbering System

### Typical Part Number

EV200 A A A N A

### Series:

EV200 = 500+ Amp, 12-900VDC Contactor

### Contact Form:

A = Normally Open H = Normally Open with Aux. Contacts

### Coil Voltage:

A = 9-36VDC (1 = requires external coil economizer)  
D = 32-95VDC (2 = requires external coil economizer)  
J = 48-95VDC (3 = requires external coil economizer)  
R = 28VDC with Mechanical Economizer

### Coil Wire Length:

A = 15.3 in (390 mm) B = 6.0 in (152 mm)

### Coil Terminal Connector:

N = None

B = Yazaki 7282-5558-10 male, 7114-4102-02, 7158-3030-50  
+red is pin 2 (B length only)

C = Molex Mini-fit Jr, 2 Ckt, Female 18-24, P/N 39-01-2020 &  
39-00-0060 +red is pin 1 (A length only)

### Mounting & Power Terminals:

A = Bottom Mount & Male 10mm x M8 Terminals


© 2004 & 2007 by Tyco Electronics Corporation. All Rights Reserved.

KILOVAC, CZONKA, TE mark and TYCO ELECTRONICS are trademarks.


Other products and company names mentioned herein may be trademarks of their respective owners.

## KILOVAC EV200 Series (CZONKA® Relay, Type III) (Continued)

### Outline Dimensions



### Estimated Make & Break Power Switching Ratings



#### NOTES:

- 1) For resistive loads with 300H maximum inductance. Consult factory for inductive loads.
- 2) Estimates based on extrapolated data. User is encouraged to confirm performance in application.
- 3) End of life when dielectric strength between terminals falls below 50 megohms @ 500VDC.
- 4) The maximum make current is 650A to avoid contact welding.

### Electrical Load Life Ratings for Typical EV Applications


| Make/Break Life Capacitive & Resistive Loads at 320VDC (1) (2) |               |                  |
|----------------------------------------------------------------|---------------|------------------|
| @90% capacitive pre-charge (make only) see chart below         | Cycles        | 50,000           |
| @80% capacitive pre-charge (make only) see chart below         | Cycles        | 50               |
| @200A make/break (2 consecutive, reverse polarity) (1)         | Cycles        | 12               |
| 2,000A (break only) (1)                                        | Cycles        | 1*               |
| <b>Mechanical Life</b>                                         | <b>Cycles</b> | <b>1 million</b> |

(1) Resistive load includes inductance L = 25μH. Load @ 2500A tested @ 200μH.

(2) Life based on projected Weibull Life with 95% reliability.

\* Does not meet dielectric and IR after test.

#### EV200 Capacitive Make Test Curves for Pre-Charged Motor Controller





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331