



Micro Commercial Components



Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

**BC846AW/BW**  
**BC847AW/BW/CW**  
**BC848AW/BW/CW**

**Features**

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Low current (max. 100mA)
- Low voltage (max. 65V)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

**Maximum Ratings**

- Operating temperature : -65°C to +150°C
- Storage temperature : -65°C to +150°C
- Thermal resistance from junction to ambient\*: 625K/W
- Marking: BC846AW---1A ; BC846BW---1B  
 BC847AW---1E ; BC847BW---1F ; BC847CW---1G  
 BC848AW---1JS/1J ; BC848BW---1KS/1K ; BC848CW---1LS/1L

**Electrical Characteristics @ 25°C Unless Otherwise Specified**

Symbol	Parameter	Min	Max	Units
--------	-----------	-----	-----	-------


**OFF CHARACTERISTICS**

$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ( $I_C=10\mu A_{dc}$ , $I_E=0$ )			Vdc
	BC846AW/BW	---	80	
	BC847AW/BW/CW	---	50	
	BC848AW/BW/CW	---	30	
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ( $I_C=10mAdc$ , $I_B=0$ )			Vdc
	BC846AW/BW	---	65	
	BC847AW/BW/CW	---	45	
	BC848AW/BW/CW	---	30	
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ( $I_E=1\mu A_{dc}$ , $I_C=0$ )			Vdc
	BC846AW/BW, BC847AW/BW/CW	---	6	
	BC848AW/BW/CW	---	5	
$I_C$	Collector Current (DC)	---	100	mAdc
$I_{CM}$	Peak Collector Current	---	200	mAdc
$I_{BM}$	Peak Base Current	---	200	mAdc

\* Transistor mounted on an FR4 printed-circuit board


**NPN**  
**General Purpose**  
**Transistors**

**SOT-323**



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.079	.087	2.00	2.20	
D	.026 Nominal		0.65 Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.012	.016	.30	.40	

**Suggested Solder Pad Layout**



**ON CHARACTERISTICS**

Symbol	Parameter	Min	Typ	Max	Units
$I_{CBO}$	Collector-base Cut-off Current ( $I_{CE}=0, V_{CB}=30Vdc$ ) ( $I_{CE}=0, V_{CB}=30Vdc, T_J=150^{\circ}C$ )	---	---	15	nA
		---	---	5	$\mu A$
$I_{CEO}$	Emitter-base Cut-off Current ( $I_C=0, V_{EB}=5Vdc$ )	---	---	100	nA
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ( $I_C=10mAdc, I_B=0.5mAdc$ ) ( $I_C=100mAdc, I_B=5mAdc^*$ )	---	90	250	mVdc
		---	200	600	mVdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ( $I_C=10mAdc, I_B=0.5mAdc$ ) ( $I_C=100mAdc, I_B=5mAdc^*$ )	---	700	---	mVdc
		---	900	---	mVdc
$h_{FE}$	DC Current Gain ( $I_C=10\mu A; V_{CE}=5V$ )	---	90	---	
	BC846AW; BC847AW; BC848AW	---	150	---	
	BC846BW; BC847BW; BC848BW	---	270	---	
	BC847CW; BC848CW	---		---	
	DC Current Gain ( $I_C=2mA; V_{CE}=5V$ )				
	BC846AW; BC847AW; BC848AW	110	180	220	
	BC846BW; BC847BW; BC848BW	200	290	450	
	BC847CW; BC848CW	420	520	800	
$V_{BE}$	Base-emitter Voltage ( $I_C=2mAdc, V_{CE}=5V$ ) ( $I_C=10mAdc, V_{CE}=5V$ )	580	660	700	mVdc
		---	---	770	mVdc
$C_C$	Collector Capacitance ( $V_{CB}=10V; I_E=I_C=0; f=1MHz$ )	---	---	4.5	pF
$f_T$	Transition Frequency ( $V_{CE}=5V; I_C=10mA; f=100MHz$ )	100	---	---	MHz
F	Noise Figure ( $V_{CE}=5V; I_C=200\mu A; f=1KHz; B=200Hz; R_S=2K\Omega$ )	---	---	10	dB

\* Pulse test:  $t_p \leq 300\mu s; \delta \leq 0.02$

**Typical Characteristics**

846AW, BW; BC847AW, BW, CW; BC848AW, BW, CW




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Collector Saturation Region




Figure 4. Base-Emitter Temperature Coefficient




Figure 5. Capacitances




Figure 6. Current-Gain - Bandwidth Product




Figure 7. DC Current Gain




Figure 8. "On" Voltage




Figure 9. Collector Saturation Region




Figure 10. Base-Emitter Temperature Coefficient




Figure 11. Capacitance




Figure 12. Current-Gain - Bandwidth Product



Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 3Kpcs/Reel

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331