







This document is the property of and embodies
CONFIDENTIAL and PROPRIETARY information of FCI.
No part of the information shown on this
document may be used in any way or disclosed
to others without the written consent of FCI.
Copyright FCI.

PRODUCT NUMBER	PLATING PERFORMANCE LEVEL	PRESS FIT TAIL PLATING
55004-102ZZZ	TELCORDIA CO	STANDARD
55004-102ZZZLF		LEAD FREE
55004-502ZZZ	TELCORDIA UE	STANDARD
55004-502ZZZLF		LEAD FREE



***ROW C AND F INFORMATION**
ODD NUMBER COLUMNS WITHIN ROW C & F ARE COMMONED
TO GROUND INTERNALLY WITHIN THE HOUSING. THE
EVEN NUMBER COLUMNS WITHIN ROW C & F ARE NOT.
FOR MAXIMUM PERFORMANCE IT IS RECOMMENDED THESE
EVEN COLUMNS BE GROUND COMMONED WITHIN PCB.
SEE NOTE 12




mat'l code SEE NOTE 3				tolerances unless otherwise specified		CUSTOMER		FCI www.fciconnect.com	
ltr	ecn no.	dr	date	linear	0.X ± 0.3	projection	COPY	title	VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD STD.
H	V07-0686	HTB	2007-11-19		0.XX ± 0.13				
J	V08-0039	HTB	2008-01-25		.XXX ± .051				
-	-	-	-	angles	0° ± 2°	MM scale 2:1	product family METRAL 4000 size A	code 55004 sheet 1 of 5	cage code 22526
D	V05-0771	VS	2005-09-06	dr	E. KROPER.	2001-10-24			
E	V06-0492	DCH	2006-05-23	enrg	J. VOLSTORF	2001-10-24			
F	V06-0868	DCH	2006-08-29	chr	J. VOLSTORF	2001-10-24	sheet 1 of 5	cage code 22526	4
G	V07-0176	DCH	2007-04-17	appd	J. VOLSTORF	2001-10-24			
sheet index	revision sheet	J	J	J	J	J			
		1	2	3	4	5			



PRODUCT NUMBER
SEE SHEET 1

PRESS-FIT HOLES	OPTION 1	OPTION 2
HOLE DIAMETER AFTER PLATING	0.45-0.55	0.48-0.57
DRILLED HOLE	0.60±0.02	0.60±0.02
COPPER PLATING	0.025 MIN-0.050 MAX.	0.025 MIN-0.050 MAX.
SnPb PLATING	0.005-0.015	---



RECOMMENDED PCB HOLE PATTERN
(COMPONENT SIDE)
SEE NOTE 11

mat'l code SEE NOTE 3				tolerances unless otherwise specified		CUSTOMER		FCI www.fciconnect.com	
ltr	ecn no.	dr	date	linear	0.X ±0.3	projection	COPY	title	VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD STD.
J					0.XX ±0.13				
					.XXX ±.051				
				angles	0° ±2°	MM scale 2:1	product family METRAL 4000 size A	code 213 sheet 2	55004
				dr	E. KROPER. 2001-10-24				
				enr	J. VOLSTORF 2001-10-24				
				chr	J. VOLSTORF 2001-10-24	cage code	22526	3	4
				appd	J. VOLSTORF 2001-10-24				
sheet index	revision sheet								


PRODUCT NUMBER

SEE SHEET 1

NOTES:

1. SEE APPLICATION SPECIFICATION GS-20-014 FOR INFORMATION ON AVAILABLE TOOLING, CIRCUIT BOARD DESIGN CONSIDERATIONS, REPAIR PROCEDURE AND PRODUCT OFFERINGS. SEE PRODUCT SPECIFICATION GS-12-185.
2. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME Y14.5, 1994
3. HOUSING MATERIAL: LIQUID CRYSTAL POLYMER, 30% GLASS FILLED, FLAME RETARDANT PER UL 94-V0.
PIN MATERIAL: PHOSPHOR BRONZE
GROUND SPRING MATERIAL: PHOSPHOR BRONZE
STRIPLINE SHIELD MATERIAL: PHOSPHOR BRONZE
4. PLATING INFORMATION: PLATING ON CONTACT AREA MEETS THE PERFORMANCE LEVELS SHOWN IN TABLE ON SHEET 1. PLATING ON "LF" TAILS IS Sn. PLATING ON ALL OTHER TAILS IS SnPb.
5. DIMENSIONAL RESTRICTIONS OF PINS IN HEADERS.
FOR USE WITH METRAL 4000 RECEPTACLES.
DIM A : 5.00mm MIN, 6.50mm MAX FOR ROWS A,B,D,E,G,H
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS C-F
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROWS GND
FOR USE WITH METRAL 1000 RECEPTACLES
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS A,B,C,D,E,F,G,H
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND
6. THE MIN PCB THICKNESS FOR FRONT PLUG-UP APPLICATIONS IS 1.6mm.
7. THE 'CONNECTOR OUTLINE' IS THE MIN OUTLINE REQUIRED. TO DETERMINE THE OUTLINE NECESSARY TO PERMIT THE VARIOUS TYPES OF REPAIR OPERATIONS, SEE APPLICATION SPECIFICATION GS-20-010.
8. CURRENT RATING : 1 AMP PER PIN
9. TEMPERATURE RANGE : -55°C TO +105°C

10. P/N 55004-X02ZZZLF




LEAD FREE (OPTIONAL)
SPECIAL LOAD PATTERN
NUMBER MODULES
PLATING CODE

11. AVOID TRACES ON TOP OF BOARD DUE TO EXPOSED GROUND SHIELDS.
12. FOR FRONT PLUG-UP APPLICATIONS, THE EVEN NUMBERED PINS IN ROW "C" AND "F" CAN BE USED FOR POWER AS WELL AS FOR GROUND. IF THE SURROUNDING PINS ARE NOT USED FOR POWER, THEN EACH PIN CAN CARRY 3 AMPS. IF THE SURROUNDING PINS ARE USED FOR POWER, THEN EACH PIN CAN CARRY 1 AMP. WHEN THE SURROUNDING PINS ARE USED ONLY FOR LOW SPEED SIGNALS, THEN THE EVEN NUMBERED "C" AND "F" ROW PINS CAN ALSO BE USED FOR LOW SPEED SIGNALS.
13. AFTER INSERTION INTO CIRCUIT BOARD WITH QUALIFIED TOOL.
14. THE PRODUCTS WHERE THE PART NUMBER ENDS IN 'LF' MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY AS DESCRIBED IN GS-22-008. ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
15. FOR LEAD FREE PART NUMBERS, ADD AN 'LF' SUFFIX. EXAMPLE: 55004-X02002LF.
16. EQUIVALENT PRECIOUS METAL PLATING MAY BE SUBSTITUTED.



mat'l code SEE NOTE 3				tolerances unless otherwise specified		CUSTOMER		 www.fciconnect.com				
ltr	ecr no.	dr	date	linear	0.X ±0.3		COPY		title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD STD.			
J					0.XX ±0.13		projection					
					.XXX ±.051							
				angles	0° ±2°		 MM scale 2:1		product family METRAL 4000		code	
				dr	E. KROPER.	2001-10-24			size	dwg no	213	
				enrg	J. VOLSTORF	2001-10-24			A	55004	sheet 3	
				chr	J. VOLSTORF	2001-10-24						
				appd	J. VOLSTORF	2001-10-24						
sheet index	revision sheet											

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

PRODUCT NUMBER
SEE SHEET 1



RECOMMENDED TRACK AND ANTIPAD DIMENSIONS
SCALE 4:1

mat'l code SEE NOTE 3				tolerances unless otherwise specified			CUSTOMER		 www.fciconnect.com				
ltr	ecr no.	dr	date	linear	0. X ±0.3			COPY			title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD STD.		
J					0. XX ±0.13			projection					
					.XXX ±.051								
				angles	0° ±2°								
		dr			E. KROPER.	2001-10-24	 MM scale 2:1	product family		code	A	55004	213 sheet 4
		enrg			J. VOLSTORF	2001-10-24		METRAL 4000					
		chr			J. VOLSTORF	2001-10-24		size					
		appd			J. VOLSTORF	2001-10-24		dwg no					
sheet index		revision sheet											



www.fciconnect.com

title
VERTICAL SIGNAL HDR 8 ROW
P.F. 96 POS. SPECIAL LOAD STD.

product family METRAL 4000 code

size dwg no 55004 sheet

4

cage code 22526

4

This document is the property of and embodies
CONFIDENTIAL and PROPRIETARY information of FCI.
No part of the information shown on this
document may be used in any way or disclosed
to others without the written consent of FCI.
Copyright FCI.


This document is the property of and embodies
CONFIDENTIAL and PROPRIETARY information of FCI.
No part of the information shown on this
document may be used in any way or disclosed
to others without the written consent of FCI.
Copyright FCI.



PRODUCT #	SPECIAL LOAD PATTERN	
	ROW	PIN CODES
55004-X02002 SEE NOTE 15 LEAD FREE OPTION	H	03
	G	
	F	
	E	
	D	
	C	
	B	
	A	
	GND	02

DIM A	PIN CODES
5.00	01
5.75	02
6.50	03
7.25	04
8.00	*19

* CURRENTLY NOT AVAILABLE

mat'l code SEE NOTE 3				tolerances unless otherwise specified			CUSTOMER		 www.fciconnect.com				
ltr	ecr no.	dr	date	linear	0.X ±0.3			projection 	title VERTICAL SIGNAL HDR 8 ROW P.F. 96 POS. SPECIAL LOAD STD				
J					0.XX ±0.13								
					.XXX ±.051								
				angles	0° ±2°			 scale 1:1	product family				code
				dr	E. KROPER.	2001-10-24	size		dwg no		213 sheet 5		
				enrg	J. VOLSTORF	2001-10-24							
				chr	J. VOLSTORF	2001-10-24							
				appd	J. VOLSTORF	2001-10-24							
sheet index		revision sheet											

cage code 22526

Pro/E

3

4

PDM: Rev:J

STATUS: Released Printed: May 13, 2011



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331