




ON Semiconductor®

## FDG6301N-F085

### Dual N-Channel, Digital FET

#### Features

- 25 V, 0.22 A continuous, 0.65 A peak.
- $R_{DS(ON)} = 4 \Omega @ V_{GS} = 4.5 V$ ,
- $R_{DS(ON)} = 5 \Omega @ V_{GS} = 2.7 V$ .
- Very low level gate drive requirements allowing direct operation in 3 V circuits ( $V_{GS(th)} < 1.5 V$ ).
- Gate-Source Zener for ESD ruggedness (>6kV Human Body Model).
- Compact industry standard SC70-6 surface mount package.
- Qualified to AEC Q101
- RoHS Compliant



#### Applications

- Low voltage applications as a replacement for bipolar digital transistors and small signal MOSFETs

#### MOSFET Maximum Ratings $T_A = 25^\circ C$ unless otherwise noted

Symbol	Parameter	Ratings	Units
$V_{DSS}$	Drain to Source Voltage	25	V
$V_{GS}$	Gate to Source Voltage	8	V
$I_D$	Drain Current Continuous	0.22	A
	Pulsed	0.65	
$P_D$	Power Dissipation	0.3	W
$T_J, T_{STG}$	Operating and Storage Temperature	-55 to +150	$^\circ C$
ESD	Electrostatic Discharge Rating MIL-STD-883D Human Body Model(100 pF / 1500 W)	6.0	kV
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	415	$^\circ C/W$

#### Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDG6301N	FDG6301N-F085	SC70-6	7"	8mm	3000 units

#### Notes:

- 1:  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design, while  $R_{\theta JA}$  is determined by the board design.  $R_{\theta JA} = 415 \text{ }^\circ C/W$  on minimum pad mounting on FR-4 board in still air
- 2: A suffix as "...F085P" has been temporarily introduced in order to manage a double source strategy as ON Semiconductor has officially announced in Aug 2014.
- 3: Pulse Test: Pulse Width < 300 $\mu s$ , Duty Cycle < 2.0%.

FDG6301N-F085 Dual N-Channel Digital FET

**Electrical Characteristics**  $T_A = 25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

**Off Characteristics**

$B_{VDSS}$	Drain to Source Breakdown Voltage	$I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$	25	-	-	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 20\text{V},$ $V_{GS} = 0\text{V}$	-	-	1	$\mu\text{A}$
		$T_J = 55^\circ\text{C}$	-	-	10	
$I_{GSS}$	Gate to Source Leakage Current	$V_{GS} = \pm 8\text{V}$	-	-	$\pm 100$	nA

**On Characteristics**

$V_{GS(th)}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}, I_D = 250\mu\text{A}$	0.65	0.85	1.5	V
$r_{DS(on)}$	Drain to Source On Resistance	$I_D = 0.22\text{A}, V_{GS} = 4.5\text{V}$	-	2.6	4	$\Omega$
		$I_D = 0.19\text{A}, V_{GS} = 2.7\text{V}$	-	3.7	5	
		$I_D = 0.22\text{A}, V_{GS} = 4.5\text{V}$ $T_J = 125^\circ\text{C}$	-	5.3	7	
$I_{D(on)}$	On-State Drain Current	$V_{GS} = 4.5\text{V}, V_{DS} = 5\text{V}$	0.22	-	-	
$g_{FS}$	Forward Transconductance	$I_D = 0.22\text{A}, V_{DS} = 5\text{V}$	-	0.2	-	S

**Dynamic Characteristics**

$C_{iss}$	Input Capacitance	$V_{DS} = 10\text{V}, V_{GS} = 0\text{V},$ $f = 1\text{MHz}$	-	9.5	-	pF
$C_{oss}$	Output Capacitance		-	6	-	pF
$C_{rss}$	Reverse Transfer Capacitance		-	1.3	-	pF
$Q_{g(TOT)}$	Total Gate Charge at -4.5V	$V_{GS} = 0$ to 4.5V	-	0.29	0.4	nC
$Q_{gs}$	Gate to Source Gate Charge	$V_{DD} = 5\text{V}$ $I_D = 0.22\text{A}$	-	0.12	-	nC
$Q_{gd}$	Gate to Drain "Miller" Charge		-	0.03	-	nC

**Switching Characteristics**

$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = 5\text{V}, I_D = 0.5\text{A}$ $V_{GS} = 4.5\text{V}, R_{GEN} = 50\Omega$	-	5	10	ns
$t_r$	Rise Time		-	4.5	10	ns
$t_{d(off)}$	Turn-Off Delay Time		-	4	8	ns
$t_f$	Fall Time		-	3.2	7	ns

**Drain-Source Diode Characteristics**

$I_S$	Maximum Continuous Source Current	-	-	0.25	A	
$V_{SD}$	Source to Drain Diode Voltage	$I_{SD} = 0.25\text{A}, V_{GS} = 0\text{V}$	-	0.8	1.2	V

## Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

## Typical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331