



## RF Power LDMOS Transistor

### N-Channel Enhancement-Mode Lateral MOSFET

This 28 W asymmetrical Doherty RF power LDMOS transistor is designed for cellular base station applications requiring very wide instantaneous bandwidth capability covering the frequency range of 1880 to 2025 MHz.

#### 1880–2025 MHz

- Typical Doherty single-carrier W-CDMA performance:  $V_{DD} = 28$  Vdc,  $I_{DQA} = 400$  mA,  $V_{GSB} = 0.2$  Vdc,  $P_{out} = 28$  W Avg., input signal PAR = 9.9 dB @ 0.01% probability on CCDF.

| Frequency | $G_{ps}$ (dB) | $\eta_D$ (%) | Output PAR (dB) | ACPR (dBc) |
|-----------|---------------|--------------|-----------------|------------|
| 1880 MHz  | 16.8          | 45.8         | 8.3             | -32.5      |
| 1960 MHz  | 17.0          | 47.7         | 8.2             | -33.5      |
| 2025 MHz  | 16.5          | 47.9         | 8.0             | -34.3      |

#### Features


- Advanced high performance in-package Doherty
- Designed for wide instantaneous bandwidth applications
- Greater negative gate-source voltage range for improved Class C operation
- Able to withstand extremely high output VSWR and broadband operating conditions
- Designed for digital predistortion error correction systems

**A2T20H160W04NR3**

**1880–2025 MHz, 28 W AVG., 28 V  
AIRFAST RF POWER LDMOS  
TRANSISTOR**



OM-780-4L  
PLASTIC



Note: Exposed backside of the package is the source terminal for the transistor.

**Figure 1. Pin Connections**

1. Pin connections 1 and 2 are DC coupled and RF independent.

**Table 1. Maximum Ratings**

| Rating                                     | Symbol           | Value       | Unit |
|--------------------------------------------|------------------|-------------|------|
| Drain-Source Voltage                       | V <sub>DSS</sub> | -0.5, +65   | Vdc  |
| Gate-Source Voltage                        | V <sub>GS</sub>  | -6.0, +10   | Vdc  |
| Operating Voltage                          | V <sub>DD</sub>  | 32, +0      | Vdc  |
| Storage Temperature Range                  | T <sub>stg</sub> | -65 to +150 | °C   |
| Case Operating Temperature Range           | T <sub>C</sub>   | -40 to +125 | °C   |
| Operating Junction Temperature Range (1,2) | T <sub>J</sub>   | -40 to +225 | °C   |

**Table 2. Thermal Characteristics**

| Characteristic                                                                                                                                                   | Symbol           | Value (2,3) | Unit |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-------------|------|
| Thermal Resistance, Junction to Case<br>Case Temperature 75°C, 28 W Avg., W-CDMA, 28 Vdc, I <sub>DQA</sub> = 400 mA,<br>V <sub>GSB</sub> = 0.2 Vdc, f = 1960 MHz | R <sub>θJC</sub> | 0.45        | °C/W |

**Table 3. ESD Protection Characteristics**

| Test Methodology                      | Class |
|---------------------------------------|-------|
| Human Body Model (per JESD22-A114)    | 2     |
| Machine Model (per EIA/JESD22-A115)   | B     |
| Charge Device Model (per JESD22-C101) | IV    |

**Table 4. Moisture Sensitivity Level**

| Test Methodology                     | Rating | Package Peak Temperature | Unit |
|--------------------------------------|--------|--------------------------|------|
| Per JESD22-A113, IPC/JEDEC J-STD-020 | 3      | 260                      | °C   |

**Table 5. Electrical Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)**

| Characteristic                                                                                 | Symbol           | Min | Typ | Max | Unit |
|------------------------------------------------------------------------------------------------|------------------|-----|-----|-----|------|
| <b>Off Characteristics (4)</b>                                                                 |                  |     |     |     |      |
| Zero Gate Voltage Drain Leakage Current<br>(V <sub>DS</sub> = 65 Vdc, V <sub>GS</sub> = 0 Vdc) | I <sub>DSS</sub> | —   | —   | 10  | µAdc |
| Zero Gate Voltage Drain Leakage Current<br>(V <sub>DS</sub> = 32 Vdc, V <sub>GS</sub> = 0 Vdc) | I <sub>DSS</sub> | —   | —   | 5   | µAdc |
| Gate-Source Leakage Current<br>(V <sub>GS</sub> = 5 Vdc, V <sub>DS</sub> = 0 Vdc)              | I <sub>GSS</sub> | —   | —   | 1   | µAdc |

**On Characteristics - Side A, Carrier**

|                                                                                                             |                     |     |      |     |     |
|-------------------------------------------------------------------------------------------------------------|---------------------|-----|------|-----|-----|
| Gate Threshold Voltage<br>(V <sub>DS</sub> = 10 Vdc, I <sub>D</sub> = 80 µAdc)                              | V <sub>GS(th)</sub> | 1.4 | 1.8  | 2.2 | Vdc |
| Gate Quiescent Voltage<br>(V <sub>DD</sub> = 28 Vdc, I <sub>DA</sub> = 400 mA, Measured in Functional Test) | V <sub>GSA(Q)</sub> | 2.2 | 2.6  | 3.0 | Vdc |
| Drain-Source On-Voltage<br>(V <sub>GS</sub> = 10 Vdc, I <sub>D</sub> = 0.8 Adc)                             | V <sub>DS(on)</sub> | 0.1 | 0.15 | 0.3 | Vdc |

**On Characteristics - Side B, Peaking**

|                                                                                 |                     |     |      |     |     |
|---------------------------------------------------------------------------------|---------------------|-----|------|-----|-----|
| Gate Threshold Voltage<br>(V <sub>DS</sub> = 10 Vdc, I <sub>D</sub> = 110 µAdc) | V <sub>GS(th)</sub> | 0.8 | 1.2  | 1.6 | Vdc |
| Drain-Source On-Voltage<br>(V <sub>GS</sub> = 10 Vdc, I <sub>D</sub> = 1.1 Adc) | V <sub>DS(on)</sub> | 0.1 | 0.15 | 0.3 | Vdc |

1. Continuous use at maximum temperature will affect MTTF.
2. MTTF calculator available at <http://www.nxp.com/RF/calculators>.
3. Refer to AN1955, *Thermal Measurement Methodology of RF Power Amplifiers*. Go to <http://www.nxp.com/RF> and search for AN1955.
4. Side A and Side B are tied together for these measurements.

(continued)

**Table 5. Electrical Characteristics** ( $T_A = 25^\circ\text{C}$  unless otherwise noted) (continued)

| Characteristic                                                                                                                                                                                                                                                                                                                                                                                              | Symbol      | Min  | Typ   | Max   | Unit |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|------|-------|-------|------|
| <b>Functional Tests</b> (1,2,3) (In NXP Doherty Test Fixture, 50 ohm system) $V_{DD} = 28 \text{ Vdc}$ , $I_{DQA} = 400 \text{ mA}$ , $V_{GSB} = 0.2 \text{ Vdc}$ , $P_{out} = 28 \text{ W Avg.}$ , $f = 1960 \text{ MHz}$ , Single-Carrier W-CDMA, IQ Magnitude Clipping, Input Signal PAR = 9.9 dB @ 0.01% Probability on CCDF. ACPR measured in 3.84 MHz Channel Bandwidth @ $\pm 5 \text{ MHz}$ Offset. |             |      |       |       |      |
| Power Gain                                                                                                                                                                                                                                                                                                                                                                                                  | $G_{ps}$    | 16.0 | 17.0  | 19.0  | dB   |
| Drain Efficiency                                                                                                                                                                                                                                                                                                                                                                                            | $\eta_{ID}$ | 45.0 | 47.7  | —     | %    |
| Output Peak-to-Average Ratio @ 0.01% Probability on CCDF                                                                                                                                                                                                                                                                                                                                                    | PAR         | 7.75 | 8.2   | —     | dB   |
| Adjacent Channel Power Ratio                                                                                                                                                                                                                                                                                                                                                                                | ACPR        | —    | -33.5 | -28.0 | dBc  |

**Load Mismatch** (3) (In NXP Doherty Test Fixture, 50 ohm system)  $I_{DQA} = 400 \text{ mA}$ ,  $V_{GSB} = 0.2 \text{ Vdc}$ ,  $f = 1960 \text{ MHz}$ 

|                                                                                               |                       |
|-----------------------------------------------------------------------------------------------|-----------------------|
| VSWR 10:1 at 32 Vdc, 158 W CW Output Power<br>(3 dB Input Overdrive from 90 W CW Rated Power) | No Device Degradation |
|-----------------------------------------------------------------------------------------------|-----------------------|


**Typical Performance** (3) (In NXP Doherty Test Fixture, 50 ohm system)  $V_{DD} = 28 \text{ Vdc}$ ,  $I_{DQA} = 400 \text{ mA}$ ,  $V_{GSB} = 0.2 \text{ Vdc}$ , 1880–2025 MHz Bandwidth

|                                                                                                    |                    |   |       |   |       |
|----------------------------------------------------------------------------------------------------|--------------------|---|-------|---|-------|
| $P_{out}$ @ 1 dB Compression Point, CW                                                             | P1dB               | — | 90    | — | W     |
| $P_{out}$ @ 3 dB Compression Point (4)                                                             | P3dB               | — | 200   | — | W     |
| AM/PM<br>(Maximum value measured at the P3dB compression point across the 1880–2025 MHz bandwidth) | $\Phi$             | — | -9.1  | — | °     |
| VBW Resonance Point<br>(IMD Third Order Intermodulation Inflection Point)                          | VBW <sub>res</sub> | — | 140   | — | MHz   |
| Gain Flatness in 145 MHz Bandwidth @ $P_{out} = 28 \text{ W Avg.}$                                 | $G_F$              | — | 0.5   | — | dB    |
| Gain Variation over Temperature<br>(-30°C to +85°C)                                                | $\Delta G$         | — | 0.002 | — | dB/°C |
| Output Power Variation over Temperature<br>(-30°C to +85°C)                                        | $\Delta P_{1dB}$   | — | 0.003 | — | dB/°C |

**Table 6. Ordering Information**

| Device          | Tape and Reel Information                             | Package   |
|-----------------|-------------------------------------------------------|-----------|
| A2T20H160W04NR3 | R3 Suffix = 250 Units, 32 mm Tape Width, 13-inch Reel | OM-780-4L |

1.  $V_{DDA}$  and  $V_{DDB}$  must be tied together and powered by a single DC power supply.
2. Part internally matched both on input and output.
3. Measurement made with device in an asymmetrical Doherty configuration.
4.  $P_{3dB} = P_{avg} + 7.0 \text{ dB}$  where  $P_{avg}$  is the average output power measured using an unclipped W-CDMA single-carrier input signal where output PAR is compressed to 7.0 dB @ 0.01% probability on CCDF.



\*C2 and C3 are mounted vertically.


Note: V<sub>DDA</sub> and V<sub>DDB</sub> must be tied together and powered by a single DC power supply.

**Figure 2. A2T20H160W04NR3 Test Circuit Component Layout**


**Table 7. A2T20H160W04NR3 Test Circuit Component Designations and Values**

| Part                                        | Description                                       | Part Number        | Manufacturer |
|---------------------------------------------|---------------------------------------------------|--------------------|--------------|
| C1                                          | 6.8 pF Chip Capacitor                             | ATC600F6R8BT250XT  | ATC          |
| C2, C3                                      | 12 pF Chip Capacitors                             | ATC100B120JT500XT  | ATC          |
| C4                                          | 1.2 pF Chip Capacitor                             | ATC600F1R2BT250XT  | ATC          |
| C5                                          | 0.6 pF Chip Capacitor                             | ATC600F0R6BT250XT  | ATC          |
| C6, C7, C8, C9, C10                         | 12 pF Chip Capacitors                             | ATC600F120JT250XT  | ATC          |
| C11                                         | 0.4 pF Chip Capacitor                             | ATC600F0R4BT250XT  | ATC          |
| C12, C13                                    | 0.5 pF Chip Capacitors                            | ATC600F0R5BT250XT  | ATC          |
| C14, C15, C16, C17, C18, C19, C20, C21, C22 | 10 $\mu$ F Chip Capacitors                        | GRM32ER61H106KA12L | Murata       |
| R1, R2                                      | 3.3 $\Omega$ , 1/2 W Chip Resistors               | ERJ-14YJ3R3U       | Panasonic    |
| R3                                          | 50 $\Omega$ , 4 W Chip Resistor                   | CW12010T0050GBK    | ATC          |
| Z1                                          | 1800–2200 MHz Band, 90°, 2 dB Directional Coupler | X3C20F1-02S        | Anaren       |
| PCB                                         | Rogers RO4350B, 0.020", $\epsilon_r = 3.66$       | D75413             | MTL          |


## TYPICAL CHARACTERISTICS — 1880–2025 MHz



**Figure 3. Single-Carrier Output Peak-to-Average Ratio Compression (PARC) Broadband Performance @  $P_{out} = 28$  Watts Avg.**




**Figure 4. Intermodulation Distortion Products versus Two-Tone Spacing**




**Figure 5. Output Peak-to-Average Ratio Compression (PARC) versus Output Power**

## TYPICAL CHARACTERISTICS — 1880–2025 MHz





**Figure 6. Single-Carrier W-CDMA Power Gain, Drain Efficiency and ACPR versus Output Power**




**Figure 7. Broadband Frequency Response**

## PACKAGE DIMENSIONS



| © NXP SEMICONDUCTORS N.V.<br>ALL RIGHTS RESERVED |                          | MECHANICAL OUTLINE | PRINT VERSION NOT TO SCALE |             |
|--------------------------------------------------|--------------------------|--------------------|----------------------------|-------------|
| TITLE:                                           | OM780-4<br>STRAIGHT LEAD |                    | DOCUMENT NO: 98ASA10833D   | REV: B      |
|                                                  |                          |                    | STANDARD: NON-JEDEC        |             |
|                                                  |                          |                    | SOT1818-4                  | 16 MAR 2016 |

**A2T20H160W04NR3**



BOTTOM VIEW  
VIEW G-G

|                                                  |                          |                            |
|--------------------------------------------------|--------------------------|----------------------------|
| © NXP SEMICONDUCTORS N.V.<br>ALL RIGHTS RESERVED | MECHANICAL OUTLINE       | PRINT VERSION NOT TO SCALE |
| TITLE:<br><br>OM780-4<br>STRAIGHT LEAD           | DOCUMENT NO: 98ASA10833D | REV: B                     |
|                                                  | STANDARD: NON-JEDEC      |                            |
|                                                  | SOT1818-4                | 16 MAR 2016                |

NOTES:

1. CONTROLLING DIMENSION: INCH
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994.
3. DATUM PLANE -H- IS LOCATED AT TOP OF LEAD AND IS COINCIDENT WITH THE LEAD WHERE THE LEAD EXITS THE PLASTIC BODY AT THE TOP OF THE PARTING LINE.
4. DIMENSIONS "D" AND "E1" DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE PROTRUSION IS .006 PER SIDE. DIMENSIONS "D" AND "E1" DO INCLUDE MOLD MISMATCH AND ARE DETERMINED AT DATUM PLANE -H-.
5. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE .005 TOTAL IN EXCESS OF THE b DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. DATUMS -A- AND -B- TO BE DETERMINED AT DATUM PLANE -H-.
7. DIMENSION A1 APPLIES WITHIN ZONE "J" ONLY.
8. HATCHING REPRESENTS THE EXPOSED AREA OF THE HEAT SLUG. THE DIMENSIONS D1 AND E2 REPRESENT THE VALUES BETWEEN THE TWO OPPOSITE POINTS ALONG THE EDGES OF EXPOSED AREA OF HEAT SLUG.
9. DIMPLED HOLE REPRESENTS INPUT SIDE.

| DIM | INCH     |      | MILLIMETER |       | DIM | INCH |      | MILLIMETER |       |
|-----|----------|------|------------|-------|-----|------|------|------------|-------|
|     | MIN      | MAX  | MIN        | MAX   |     | MIN  | MAX  | MIN        | MAX   |
| A   | 0.148    | .152 | 3.76       | 3.86  | b   | .147 | .153 | 3.73       | 3.89  |
| A1  | .059     | .065 | 1.50       | 1.65  | c1  | .007 | .011 | 0.18       | 0.28  |
| D   | .808     | .812 | 20.52      | 20.62 | e   | .350 | BSC  | 8.89       | BSC   |
| D1  | .720     | ---- | 18.29      | ----  | e1  | .721 | .729 | 18.31      | 18.52 |
| E   | .762     | .770 | 19.36      | 19.56 | aaa | .004 |      | 0.10       |       |
| E1  | .390     | .394 | 9.91       | 10.01 |     |      |      |            |       |
| E2  | .306     | ---- | 7.77       | ----  |     |      |      |            |       |
| E3  | .383     | .387 | 9.72       | 9.83  |     |      |      |            |       |
| F   | .025 BSC |      | 0.635 BSC  |       |     |      |      |            |       |

|                                                  |                                      |                            |
|--------------------------------------------------|--------------------------------------|----------------------------|
| © NXP SEMICONDUCTORS N.V.<br>ALL RIGHTS RESERVED | MECHANICAL OUTLINE                   | PRINT VERSION NOT TO SCALE |
| TITLE:<br><br>OM780-4<br>STRAIGHT LEAD           | DOCUMENT NO: 98ASA10833D      REV: B |                            |
|                                                  | STANDARD: NON-JEDEC                  |                            |
|                                                  | SOT1818-4      16 MAR 2016           |                            |

A2T20H160W04NR3

## PRODUCT DOCUMENTATION, SOFTWARE AND TOOLS

Refer to the following resources to aid your design process.

### Application Notes

- AN1907: Solder Reflow Attach Method for High Power RF Devices in Over-Molded Plastic Packages
- AN1955: Thermal Measurement Methodology of RF Power Amplifiers

### Engineering Bulletins

- EB212: Using Data Sheet Impedances for RF LDMOS Devices

### Software

- Electromigration MTTF Calculator
- .s2p File

### Development Tools

- Printed Circuit Boards

### To Download Resources Specific to a Given Part Number:

1. Go to <http://www.nxp.com/RF>
2. Search by part number
3. Click part number link
4. Choose the desired resource from the drop down menu

## REVISION HISTORY

The following table summarizes revisions to this document.

| Revision | Date      | Description                     |
|----------|-----------|---------------------------------|
| 0        | Aug. 2016 | • Initial release of data sheet |

**How to Reach Us:**

**Home Page:**  
[nxp.com](http://nxp.com)

**Web Support:**  
[nxp.com/support](http://nxp.com/support)

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: [nxp.com/SalesTermsandConditions](http://nxp.com/SalesTermsandConditions).

NXP, the NXP logo, Freescale, the Freescale logo, and Airfast are trademarks of NXP B.V. All other product or service names are the property of their respective owners.  
© 2016 NXP B.V.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литер Н,  
помещение 100-Н Офис 331