



Power Architecture® 32-bit Microcontroller Fact Sheet

## Qorivva MPC5510 Family

Dual-core 32-bit MCUs for body and gateway applications

Product Map									
Device	MPC5517G	MPC5517E	MPC5517S	MPC5516G	MPC5516E	MPC5516S	MPC5515S	MPC5514G	MPC5514E
Core Platform	Power Architecture® e200z1 + e200z0	Power Architecture e200z1 + e200z0	Power Architecture e200z1	Power Architecture e200z1 + e200z0	Power Architecture e200z1 + e200z0	Power Architecture e200z1	Power Architecture e200z1	Power Architecture e200z1 + e200z0	Power Architecture e200z1 + e200z0
Program Flash	1.5 MB	1.5 MB	1.5 MB	1 MB	1 MB	1 MB	768 KB	512K	512K
SRAM	80 KB	80 KB	64 KB	64 KB	64 KB	48 KB	48 KB	64 KB	32 KB
DMA	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
EEPROM	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash	Emulated in Program Flash
eSCI	6	6, 8	6	8	6	6	6	8	6
DSPI	4	4	4	4	4	3	3	3	4
FlexCAN	6	5	4, 5	6	5	4, 5	4, 5	6	5
ƒC	1	1	1	1	1	1	1	1	1
FlexRay™	√	-	-	√	-	-	-	√	√
MediaLB for MOST	Emulated via z0	Emulated via z0	-	Emulated via z0	Emulated via z0	-	-	Emulated via z0	Emulated via z0
External Bus	√	√	√	√	√	-	-	√	√
Nexus2+	√	√	√	√	√	√	√	√	√
eMIOS Timer Module	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit	24-ch., 16-bit
PIT Timer	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit	8-ch., 32-bit
ADC	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit	40-ch., 12-bit
Voltage	5V	5V	5V	5V	5V	5V	5V	5V	5V
Temp. Range	C, V, M	C, V, M	C, V, M	C, V, M	C, V, M	C, V, M	C, V, M	C, V, M	C, V, M
Frequency Range	48–80 MHz	48–80 MHz	48–66 MHz	48–80 MHz	48–66 MHz	48–66 MHz	48–66 MHz	48–80 MHz	48–80 MHz
Package Options	208 MAPBGA	144 LQFP, 208 MAPBGA, 176 LQFP	144 LQFP, 208 MAPBGA, 176 LQFP	144 LQFP, 208 MAPBGA	144 LQFP, 208 MAPBGA, 176 LQFP	144 LQFP, 176 LQFP	144 LQFP, 176 LQFP	144 LQFP	144 LQFP
Additional Information	MPU, 32 kHz RTC	MPU, 32 kHz RTC	MPU	MPU, 32 kHz RTC	MPU, 32 kHz RTC	MPU	MPU	MPU, 32 kHz RTC	MPU, 32 kHz RTC

## Overview

The Qorivva MPC5510 family is the first automotive 32-bit microcontroller, built on Power Architecture® technology, featuring flexible low-power modes. This high-performance MCU inherits the single cycle access flash memory and advanced peripherals from the existing Qorivva MPC5500 product families and reuses the same proven 130 nm automotive flash technology. The Qorivva MPC5510 family is supported by outstanding development tools and software support built around Power Architecture technology in automotive applications.

## Applications

- Central body controller
- Gateway
- Center stack display
- Smart junction box







## Product Benefits

- Enables centralized architectures which reduce the number of distributed electronic control units (ECU) and complexity of vehicle architectures
- Connects FlexRay™ nodes to the body electronics domain
- Exceeds 100 Dhrystone MIPS (DMIPS) performance
- Minimizes ECU leakages below 200 µA, depending on functionality
- Provides extensive communication capabilities, including FlexRay communications protocol, multiple CAN and LIN support
- Offers room to grow with scalable family ranging from 512 KB up to 1.5 MB of embedded flash
- Leverages Power Architecture network for third-party tools and software

## Prototype Ordering Information

Part Number	Package
PPC5517GMLQ66	144 LQFP
PPC5517GMLU66	176 LQFP
PPC5517GMMG66	208MAPBGA

## Development Tools Support

	Compilers	Debuggers	Simulators	Evaluation Boards	Initialization Tools
	✓			✓	
	✓	✓	✓		
<b>WIND RIVER</b>	✓	✓	✓		
<b>LAUTERBACH</b> 		✓	✓		
		✓		✓	
		✓		✓	
					✓

### Freescale Tools for Qorivva MPC5510

#### CWS-MPC-5500B-CX

CodeWarrior MPC55xx compiler (Build Only Edition)



144 LQFP  
20 mm x 20 mm

#### RAppID

Rapid Application Initialization and Documentation

#### MPC5510KIT144

Qorivva MPC5510 evaluation kit with 144LQFP daughter card, comes with code size limited free CodeWarrior compiler and P&E debugger



176 LQFP  
24 mm x 24 mm

#### MPC5510KIT208

Qorivva MPC5510 evaluation kit with 208MAPBGA daughter card, comes with code size limited free CodeWarrior compiler and P&E debugger



208 MAPBGA  
17 mm x 17 mm

#### MPC5510DEMO

Entry-level evaluation board with embedded JTAG interface from P&E, comes with code size limited free CodeWarrior compiler and P&E debugger

### Learn More:

For more information about our Power Architecture-based products, please visit [freescale.com/Qorivva](http://freescale.com/Qorivva).



Freescale, the Freescale logo and CodeWarrior are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. Qorivva is a trademark of Freescale Semiconductor, Inc. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. All other product or service names are the property of their respective owners.  
© 2008, 2010 Freescale Semiconductor, Inc.

Document Number: MPC5510FAMFS / REV 3





## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331