
42M048C





42M048C DIMENSIONS: MILLIMETERS / INCHES


Technical Specifications

Part Number		Unipolar		Bipolar	
		42M048C1U	42M048C2U	42M048C1B	42M048C2B
Rated voltage	(vdc)	5	12	5	12
Resistance per phase ± 10%	(ohms)	9.10	52.40	9.10	52.40
Inductance per phase, Typ	(mH)	8.10	51.70	16.70	85.70
Rated current per phase *	(amps)	0.55	0.23	0.55	0.23
Holding torque, min *	(oz-in / mNm)	9.4 / 66.2		11.9 / 84	
Step angle *	(degrees)	7.5 ± 0.5°			
Steps per revolution *		48			
Detent torque, max	(oz-in / mNm)	1.8 / 12.7			
Thermal resistance	(ºC / watt)	N.A.			
Rotor moment of inertia	(oz-in-s^2 / g-cm^2)	0.068 / 12.5			
Ambient temperature range					
Operating	(ºC)	-20 ~ +70			
Storage	(ºC)	-40 ~ +85			
Bearing type		Sintered Bronze Sleeve			
Insulation resistance at 500vdc	(MΩ)	100			
Dielectric withstanding voltage	(vac)	650 for 2 seconds			
Weight	(lbs / g)	0.31875 / 145			
Shaft load ratings, max at 1500 rpm					
Radial	(lbs / kg)	1.124 / 0.509			
Axial	(lbs / kg)	0.337 / 0.153			
Leadwires		AWG 26, UL 1430			
Temperature class, max	(ºC)	B(130ºC)			
RoHS		Compliant			

All motor data values at 25ºC unless otherwise specified
* Energise at rated current, 2 phase on


42M048C1U
Torque vs Speed
5 vdc, full step, unipolar voltage
oz-in
mNm
0
1
2
3
4
5
6
0.00
5.00
10.00
15.00
20.00
25.00
30.00
35.00
40.00
50.0
100.0
150.0
200.0
250.0
300.0
pps
62.5
125.0
187.5
250.0
312.5
375.0
rpm
42M048C1U Pull-Out Torque
42M048C1U Pull-in Torque


42M048C1B
Torque vs Speed
5 vdc, full step, bipolar voltage drive
oz-in
mNm
0
1
2
3
4
5
6
7
8
0.00
10.00
20.00
30.00
40.00
50.00
50.0
100.0
150.0
200.0
250.0
300.0
pps
62.5
125.0
187.5
250.0
312.5
375.0
rpm
42M048C1B Pull-Out Torque
42M048C1B Pull-in Torque


42L048D1U
Torque vs Speed
5 vdc, full step, unipolar voltage
oz-in
mNm
0
1
2
3
4
5
6
7
8
9
0.00
10.00
20.00
30.00
40.00
50.00
60.00
100
200
300
pps
125
250
375
rpm
42L048D1U Pull-Out Torque
42L048D1U Pull-in Torque

42M SERIES SYNCHRONOUS MOTOR

Technical Specifications

Part Number			42M250C3A	42M250C5A	42M250C7A
Ac operating voltage		(vac)	24.0	120.0	230.0
Frequency		(Hz)	50.0	50.0	50.0
Speed		(rpm)	250.0	250.0	250.0
Direction of rotation		-	Reversible	Reversible	Reversible
Synchronous torque		(oz-in / mNm)	5.05 / 35.66	5.78 / 40.82	5.47 / 38.63
Capacitance		(µF)	6.8	0.33	0.100
Rotor moment of inertia		($oz\text{-}in\text{-}s^2$ / $g\text{-}cm^2$)	0.068 / 12.5		
Weight		(lbs / g)	0.31875 / 145		
Leadwires			AWG 24, UL 1015		
Ambient temperature range	Operating	(ºC)	-20 ~ +70		
	Storage	(ºC)	-40 ~ +85		
Bearing type			Sintered Bronze Sleeve		
Insulation resistance at 500vdc		(Mohms)	100		
Dielectric withstanding voltage		(vac)	1250 ± 50 VRMS, 2 seconds		
Temperature class, max		(ºC)	B(130ºC)		
RoHS			Compliant		

All motor data values at 25ºC unless otherwise specified


42M SERIES SYNCHRONOUS MOTOR

Technical Specifications

Part Number			42M300C3A	42M300C5A	42M300C7A
Ac operating voltage		(vac)	24.0	120.0	230.0
Frequency		(Hz)	60.0	60.0	60.0
Speed		(rpm)	300.0	300.0	300.0
Direction of rotation		-	Reversible	Reversible	Reversible
Synchronous torque		(oz-in / mNm)	5.05 / 35.66	5.78 / 40.82	5.47 / 38.63
Capacitance		(µF)	6.8	0.33	0.082
Rotor moment of inertia		($oz\text{-}in\text{-}s^2$ / $g\text{-}cm^2$)	0.068 / 12.5		
Weight		(lbs / g)	0.31875 / 145		
Leadwires			AWG 24, UL 1015		
Ambient temperature range	Operating	(ºC)	-20 ~ +70		
	Storage	(ºC)	-40 ~ +85		
Bearing type			Sintered Bronze Sleeve		
Insulation resistance at 500vdc		(Mohms)	100		
Dielectric withstanding voltage		(vac)	1250 ± 50 VRMS, 2 seconds		
Temperature class, max		(ºC)	B(130ºC)		
RoHS			Compliant		


All motor data values at 25ºC unless otherwise specified

42M-R



DIMENSIONS: MILLIMETERS / INCHES

42M-Z



DIMENSIONS: MILLIMETERS / INCHES

Gear Ratios Available for Can Stack

26M-V GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 100 PPS*	Running torque @ 100 PPS* oz-in / mN-m
- V 11	2 : 1	90.0%	3.75°	62.50	1.16 / 8.9
- V 16	5 : 1	81.0%	1.5°	25.00	2.41 / 17.01
- V 19	7.5 : 1	73.0%	1.00°	16.66	3.00 / 21.08
- V 21	10 : 1	73.0%	0.75°	12.50	4.00 / 28.24
- V 24	15 : 1	66.0%	0.5°	8.33	5.00 / 35.3
- V 27	20 : 1	66.0%	0.375°	6.25	6.64 / 46.88
- V 31	30 : 1	66.0%	0.25°	4.17	10.00 / 70.6
- V 37	60 : 1	59.0%	0.125°	2.09	16.00 / 112.96

35M-X GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 240 PPS*	Running torque @ 240 PPS* oz-in / mN-m
- X 24	15 : 1	80.0%	0.500°	20.00	5.0 / 35.30 MAX
- X 27	20 : 1	80.0%	0.375°	15.00	5.0 / 35.30 MAX
- X 31	30 : 1	80.0%	0.250°	10.00	5.0 / 35.30 MAX
- X 37	60 : 1	80.0%	0.125°	5.00	5.0 / 35.30 MAX
- X 39	75 : 1	80.0%	0.100°	4.00	5.0 / 35.30 MAX
- X 45	150 : 1	70.0%	0.050°	2.00	5.0 / 35.30 MAX
- X 52	300 : 1	70.0%	0.025°	1.00	5.0 / 35.30 MAX
- X 64	1350 : 1	65.0%	0.0055°	0.22	5.0 / 35.30 MAX

* Energise at rated current, 2 phase on

42M-R GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 240 PPS*	Running torque @ 240 PPS* oz-in / mN-m
- R 12	2.5 : 1	90.0%	3.0°	120.00	8.3 / 58
- R 16	5 : 1	80.0%	1.5°	60.00	16.6 / 117
- R 21	10 : 1	80.0%	0.75°	30.00	29.9 / 211
- R 24	15 : 1	70.0%	0.5°	20.00	44.9 / 317
- R 27	20 : 1	70.0%	0.375°	15.00	59.9 / 423
- R 31	30 : 1	70.0%	0.25°	10.00	89.9 / 634
- R 36	50 : 1	65.0%	0.15°	6.00	100 / 706 MAX
- R 39	75 : 1	65.0%	0.10°	4.00	100 / 706 MAX

42M-Z GEAR RATIOS

Part suffix	Gear ratio	Efficiency %	Output step angle	Output speed rpm @ 240 PPS*	Running torque @ 240 PPS* oz-in / mN-m
- Z 16	5 : 1	80.0%	1.5°	60.00	15 / 106
- Z 21	10 : 1	80.0%	0.75°	30.00	29.9 / 211
- Z 24	15 : 1	80.0%	0.5°	20.00	44.9 / 317
- Z 27	20 : 1	80.0%	0.375°	15.00	59.9 / 423
- Z 31	30 : 1	70.0%	0.25°	10.00	80.8 / 570
- Z 36	50 : 1	65.0%	0.15°	6.00	121 / 854

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331