

Subminiature Fuse, 2.3 x 8 mm, Quick-Acting F, 125 VAC, 125 VDC



UL 248-14 · 125 VAC · 125 VDC · Quick-Acting F

See below:

[Approvals and Compliances](#)**Description**

- High breaking capacity

**References**[Packaging Details](#)**Weblinks**[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#)**Technical Data**

|                              |                               |
|------------------------------|-------------------------------|
| Rated Voltage                | 32 - 125VAC, 32 - 125VDC      |
| Rated current                | 0.063 - 15 A                  |
| Breaking Capacity            | 50A - 300A                    |
| Characteristic               | Quick-Acting F                |
| Admissible Ambient Air Temp. | -55 °C to 85 °C               |
| Climatic Category            | 55/085/56 acc. to IEC 60068-1 |
| Material: Tube               | Ceramics                      |
| Material: Axial Leads        | Tin-Plated Copper             |
| Unit Weight                  | 0.46 g                        |
| Storage Conditions           | 0 °C to 60 °C, max. 70% r.h.  |
| Product Marking              | Rated current                 |

|                              |  |
|------------------------------|--|
| Soldering Methods            | Wave<br><a href="#">Soldering Profile</a>                    |
| Solderability                | 235 °C / 2 sec acc. to IEC 60068-2-20,<br>Test Ta, method 1  |
| Resistance to Soldering Heat | 260 °C / 5 sec acc. to IEC 60068-2-20,<br>Test Tb, method 1A |



**Approvals and Compliances**Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

**Approvals**



The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: 172322

| Approval Logo  | Certificates                  | Certification Body | Description                     |
|--|-------------------------------|--------------------|---------------------------------|
|               | <a href="#">UL Approvals</a>  | UL                 | UL File Number: E42088          |
| <br>GAM<br>T1 | <a href="#">CSA Approvals</a> | CSA                | CSA Certification Record: 34549 |


**Product standards**

Product standards that are referenced

| Organization  | Design                | Standard           | Description                                     |
|---|-----------------------|--------------------|---|
|  | Designed according to | UL 248-14          | Low voltage fuses - Part 14: Additional fuses   |
|  | Designed according to | CSA22.2 No. 248.14 | Low-Voltage Fuses - Part 14: Supplemental Fuses |

### Application standards

Application standards where the product can be used

| Organization   | Design                         | Standard       | Description  |
|--|--------------------------------|----------------|--|
|  | Designed for applications acc. | IEC/UL 62368-1 | IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment. |

### Compliances

The product complies with following Guide Lines

| Identification   | Details                                      | Initiator   | Description   |
|--|--|-------------|---|
|  | <a href="#">CE declaration of conformity</a> | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | RoHS   | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863  |
|  | China RoHS                                   | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.  |
|  | REACH  | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.                               |

### Dimension [mm]

8 mm



In ≤ 10 A: ØA = 0.62 mm  
 In > 10 A: ØA = 0.82 mm

### Pre-Arcing Time

| Rated Current In | 1.0 x In min. | 1.5 x In max. | 2.0 x In max. | 2.75 x In max. | 4.0 x In max. | 10.0 x In max. |
|------------------|---------------|---------------|---------------|----------------|---------------|----------------|
| 0.063 A - 10 A   | 4 h           | 10 min        | 5 s           | 300 ms         | 30 ms         | 4 ms           |
| 12 A - 15 A      | 4 h           | 10 min        | 10 s          | -              | 60 ms         | -              |

Time-Current-Curves



All Variants

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I <sub>n</sub> typ. [mV] | Power Dissipation 1.0 I <sub>n</sub> typ. [mW] | Melting I <sup>2</sup> t 10.0 I <sub>n</sub> typ. [A <sup>2</sup> s] |   GAM T1 | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|---|--------------|
| 0.063             | 125                 | 125                 | 1)                | 1050                                      | 66   | 0.0008   | ● ●   | 7010.7010.13 |
| 0.063             | 125                 | 125                 | 1)                | 1050                                      | 66   | 0.0008   | ● ●   | 7010.7010.37 |
| 0.063             | 125                 | 125                 | 1)                | 1050                                      | 66   | 0.0008   | ● ●   | 7010.7010.39 |
| 0.063             | 125                 | 125                 | 1)                | 1050                                      | 66   | 0.0008   | ● ●   | 7010.7010.47 |
| 0.063             | 125                 | 125                 | 1)                | 1050                                      | 66   | 0.0008   | ● ●   | 7010.7010.49 |
| 0.125             | 125                 | 125                 | 1)                | 900                                       | 115  | 0.0036   | ● ● ●   | 7010.7020.13 |
| 0.125             | 125                 | 125                 | 1)                | 900                                       | 115  | 0.0036   | ● ● ●   | 7010.7020.37 |
| 0.125             | 125                 | 125                 | 1)                | 900                                       | 115  | 0.0036   | ● ● ●   | 7010.7020.39 |
| 0.125             | 125                 | 125                 | 1)                | 900                                       | 115  | 0.0036   | ● ● ●   | 7010.7020.47 |
| 0.125             | 125                 | 125                 | 1)                | 900                                       | 115  | 0.0036   | ● ● ●   | 7010.7020.49 |
| 0.25              | 125                 | -                   | 2)                | 325                                       | 82   | 0.0094   | ● ● ●   | 7010.7030.13 |
| 0.25              | 125                 | -                   | 2)                | 325                                       | 82   | 0.0094   | ● ● ●   | 7010.7030.37 |
| 0.25              | 125                 | -                   | 2)                | 325                                       | 82   | 0.0094   | ● ● ●   | 7010.7030.39 |
| 0.25              | 125                 | -                   | 2)                | 325                                       | 82   | 0.0094   | ● ● ●   | 7010.7030.47 |
| 0.25              | 125                 | -                   | 2)                | 325                                       | 82   | 0.0094   | ● ● ●   | 7010.7030.49 |
| 0.375             | 125                 | -                   | 2)                | 245                                       | 92   | 0.019  | ● ● ●   | 7010.7040.13 |
| 0.375             | 125                 | -                   | 2)                | 245                                       | 92   | 0.019  | ● ● ●   | 7010.7040.37 |
| 0.375             | 125                 | -                   | 2)                | 245                                       | 92   | 0.019  | ● ● ●   | 7010.7040.39 |
| 0.375             | 125                 | -                   | 2)                | 245                                       | 92   | 0.019  | ● ● ●   | 7010.7040.47 |
| 0.375             | 125                 | -                   | 2)                | 245                                       | 92   | 0.019  | ● ● ●   | 7010.7040.49 |
| 0.5               | 125                 | -                   | 2)                | 260                                       | 130  | 0.07   | ● ● ●   | 7010.7050.13 |
| 0.5               | 125                 | -                   | 2)                | 260                                       | 130  | 0.07   | ● ● ●   | 7010.7050.37 |
| 0.5               | 125                 | -                   | 2)                | 260                                       | 130  | 0.07   | ● ● ●   | 7010.7050.39 |
| 0.5               | 125                 | -                   | 2)                | 260                                       | 130  | 0.07   | ● ● ●   | 7010.7050.47 |
| 0.5               | 125                 | -                   | 2)                | 260                                       | 130  | 0.07   | ● ● ●   | 7010.7050.49 |
| 0.75              | 125                 | -                   | 2)                | 245                                       | 185  | 0.18   | ● ● ●   | 7010.7060.13 |
| 0.75              | 125                 | -                   | 2)                | 245                                       | 185  | 0.18   | ● ● ●   | 7010.7060.37 |
| 0.75              | 125                 | -                   | 2)                | 245                                       | 185  | 0.18   | ● ● ●   | 7010.7060.39 |

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I <sub>n</sub> typ. [mV] | Power Dissipation 1.0 I <sub>n</sub> typ. [mW] | Melting I <sup>2</sup> t 10.0 I <sub>n</sub> typ. [A <sup>2</sup> s] |    |   |   | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|--|---|---|--------------|
| 0.75              | 125                 | -                   | 2)                | 245                                       | 185  | 0.18   | ●  | ● | ● | 7010.7060.47 |
| 0.75              | 125                 | -                   | 2)                | 245                                       | 185  | 0.18   | ●  | ● | ● | 7010.7060.49 |
| 1                 | 125                 | -                   | 2)                | 210                                       | 210  | 0.3  | ●  | ● | ● | 7010.7070.13 |
| 1                 | 125                 | -                   | 2)                | 210                                       | 210  | 0.3  | ●  | ● | ● | 7010.7070.37 |
| 1                 | 125                 | -                   | 2)                | 210                                       | 210  | 0.3  | ●  | ● | ● | 7010.7070.39 |
| 1                 | 125                 | -                   | 2)                | 210                                       | 210  | 0.3  | ●  | ● | ● | 7010.7070.47 |
| 1                 | 125                 | -                   | 2)                | 210                                       | 210  | 0.3  | ●  | ● | ● | 7010.7070.49 |
| 1.5               | 125                 | -                   | 2)                | 230                                       | 345  | 0.38   | ●  | ● | ● | 7010.7080.13 |
| 1.5               | 125                 | -                   | 2)                | 230                                       | 345  | 0.38   | ●  | ● | ● | 7010.7080.37 |
| 1.5               | 125                 | -                   | 2)                | 230                                       | 345  | 0.38   | ●  | ● | ● | 7010.7080.39 |
| 1.5               | 125                 | -                   | 2)                | 230                                       | 345  | 0.38   | ●  | ● | ● | 7010.7080.47 |
| 1.5               | 125                 | -                   | 2)                | 230                                       | 345  | 0.38   | ●  | ● | ● | 7010.7080.49 |
| 2                 | 125                 | -                   | 2)                | 190                                       | 380  | 1.1  | ●  | ● | ● | 7010.7090.13 |
| 2                 | 125                 | -                   | 2)                | 190                                       | 380  | 1.1  | ●  | ● | ● | 7010.7090.37 |
| 2                 | 125                 | -                   | 2)                | 190                                       | 380  | 1.1  | ●  | ● | ● | 7010.7090.39 |
| 2                 | 125                 | -                   | 2)                | 190                                       | 380  | 1.1  | ●  | ● | ● | 7010.7090.47 |
| 2                 | 125                 | -                   | 2)                | 190                                       | 380  | 1.1  | ●  | ● | ● | 7010.7090.49 |
| 2.5               | 125                 | -                   | 2)                | 175                                       | 440  | 1.4  | ●  | ● | ● | 7010.7100.13 |
| 2.5               | 125                 | -                   | 2)                | 175                                       | 440  | 1.4  | ●  | ● | ● | 7010.7100.39 |
| 2.5               | 125                 | -                   | 2)                | 175                                       | 440  | 1.4  | ●  | ● | ● | 7010.7100.47 |
| 2.5               | 125                 | -                   | 2)                | 175                                       | 440  | 1.4  | ●  | ● | ● | 7010.7100.49 |
| 3                 | 125                 | -                   | 2)                | 170                                       | 510  | 2  | ●  | ● | ● | 7010.7110.13 |
| 3                 | 125                 | -                   | 2)                | 170                                       | 510  | 2  | ●  | ● | ● | 7010.7110.39 |
| 3                 | 125                 | -                   | 2)                | 170                                       | 510  | 2  | ●  | ● | ● | 7010.7110.47 |
| 3                 | 125                 | -                   | 2)                | 170                                       | 510  | 2  | ●  | ● | ● | 7010.7110.49 |
| 3.5               | 125                 | -                   | 2)                | 160                                       | 560  | 2.6  | ●  | ● | ● | 7010.7180.13 |
| 3.5               | 125                 | -                   | 2)                | 160                                       | 560  | 2.6  | ●  | ● | ● | 7010.7180.37 |
| 3.5               | 125                 | -                   | 2)                | 160                                       | 560  | 2.6  | ●  | ● | ● | 7010.7180.39 |
| 3.5               | 125                 | -                   | 2)                | 160                                       | 560  | 2.6  | ●  | ● | ● | 7010.7180.47 |
| 3.5               | 125                 | -                   | 2)                | 160                                       | 560  | 2.6  | ●  | ● | ● | 7010.7180.49 |
| 4                 | 125                 | -                   | 2)                | 180                                       | 720  | 4  | ●  | ● | ● | 7010.7120.13 |
| 4                 | 125                 | -                   | 2)                | 180                                       | 720  | 4  | ●  | ● | ● | 7010.7120.37 |
| 4                 | 125                 | -                   | 2)                | 180                                       | 720  | 4  | ●  | ● | ● | 7010.7120.39 |
| 4                 | 125                 | -                   | 2)                | 180                                       | 720  | 4  | ●  | ● | ● | 7010.7120.47 |
| 4                 | 125                 | -                   | 2)                | 180                                       | 720  | 4  | ●  | ● | ● | 7010.7120.49 |
| 5                 | 125                 | 125                 | 1)                | 170                                       | 850  | 6.2  | ●  | ● | ● | 7010.7130.13 |
| 5                 | 125                 | 125                 | 1)                | 170                                       | 850  | 6.2  | ●  | ● | ● | 7010.7130.37 |
| 5                 | 125                 | 125                 | 1)                | 170                                       | 850  | 6.2  | ●  | ● | ● | 7010.7130.39 |
| 5                 | 125                 | 125                 | 1)                | 170                                       | 850  | 6.2  | ●  | ● | ● | 7010.7130.47 |
| 5                 | 125                 | 125                 | 1)                | 170                                       | 850  | 6.2  | ●  | ● | ● | 7010.7130.49 |
| 7                 | 125                 | 125                 | 1)                | 135                                       | 945  | 13   | ●  | ● | ● | 7010.7140.13 |
| 7                 | 125                 | 125                 | 1)                | 135                                       | 945  | 13   | ●  | ● | ● | 7010.7140.37 |
| 7                 | 125                 | 125                 | 1)                | 135                                       | 945  | 13   | ●  | ● | ● | 7010.7140.39 |
| 7                 | 125                 | 125                 | 1)                | 135                                       | 945  | 13   | ●  | ● | ● | 7010.7140.47 |
| 7                 | 125                 | 125                 | 1)                | 135                                       | 945  | 13   | ●  | ● | ● | 7010.7140.49 |
| 10                | 125                 | 125                 | 1)                | 130                                       | 1300   | 39   | ●  | ● | ● | 7010.7150.13 |
| 10                | 125                 | 125                 | 1)                | 130                                       | 1300   | 39   | ●  | ● | ● | 7010.7150.37 |
| 10                | 125                 | 125                 | 1)                | 130                                       | 1300   | 39   | ●  | ● | ● | 7010.7150.39 |
| 10                | 125                 | 125                 | 1)                | 130                                       | 1300   | 39   | ●  | ● | ● | 7010.7150.47 |
| 10                | 125                 | 125                 | 1)                | 130                                       | 1300   | 39   | ●  | ● | ● | 7010.7150.49 |
| 12                | 32                  | 32                  | 3)                | 130                                       | 1450   | 57   | ●  | ● | ● | 7010.7160.13 |
| 12                | 32                  | 32                  | 3)                | 130                                       | 1450   | 57   | ●  | ● | ● | 7010.7160.37 |
| 12                | 32                  | 32                  | 3)                | 130                                       | 1450   | 57   | ●  | ● | ● | 7010.7160.39 |
| 12                | 32                  | 32                  | 3)                | 130                                       | 1450   | 57   | ●  | ● | ● | 7010.7160.47 |

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I <sub>n</sub> typ. [mV] | Power Dissipation 1.0 I <sub>n</sub> typ. [mW] | Melting I <sup>2</sup> t 10.0 I <sub>n</sub> typ. [A <sup>2</sup> s] |  | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|--|--------------|
| 12                | 32                  | 32                  | 3)                | 130                                       | 1450   | 57   | ● ● ●  | 7010.7160.49 |
| 15                | 32                  | 32                  | 3)                | 120                                       | 1800   | 90   | ● ● ●  | 7010.7170.13 |
| 15                | 32                  | 32                  | 3)                | 120                                       | 1800   | 90   | ● ● ●  | 7010.7170.37 |
| 15                | 32                  | 32                  | 3)                | 120                                       | 1800   | 90   | ● ● ●  | 7010.7170.47 |
| 15                | 32                  | 32                  | 3)                | 120                                       | 1800   | 90   | ● ● ●  | 7010.7170.49 |

Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

1) UL: 50 A @ 125 VAC, p.f. ≥ 0.95 / 300 A @ 125 VDC

1) CSA: 300 A @ 125 VAC/DC

2) UL: 50 A @ 125 VAC, p.f. ≥ 0.95

2) CSA: 300 A @ 125 VAC

3) UL: 50 A @ 32 VAC, p.f. ≥ 0.95 / 300 A @ 32 VDC

3) CSA: 300 A @ 32 VAC/DC

**Packaging Unit**

|           |   |
|-----------|---|
| .xx = .13 | Plastic Bag, Fuse Length 86 mm (100 pcs.)       |
| .xx = .37 | Taped 19 cm Reel, Fuse Length 65 mm (1500 pcs.) |
| .xx = .39 | Taped 19 cm Reel, Fuse Length 65 mm (5000 pcs.) |
| .xx = .47 | Taped 19 cm Reel, Fuse Length 86 mm (1500 pcs.) |
| .xx = .49 | Taped 19 cm Reel, Fuse Length 85 mm (5000 pcs.) |



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331