

For more Information
please call

1-800-Belden1



Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	16	26x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.762

Overall Insulation

Overall Cabling

Overall Nominal Diameter: 3.124 mm

Mechanical Characteristics (Overall)

Bulk Cable Weight: 20.463 Kg/Km

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	600 V, 105°C
UL Type:	MTW or AWM 1015/1230
CSA Rating:	600 V, 105°C
CSA Type:	AWM I A/B or TEW
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	VW-1
CSA Flame Test:	FT1

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Related Documents:

No related documents are available for this product

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8917 001100	30 MT	0.953 KG	BROWN		16 STR PVC BRN
8917 0011000	305 MT	6.804 KG	BROWN	P	16 STR PVC BRN
8917 002100	30 MT	0.953 KG	RED		16 STR PVC RED
8917 0021000	305 MT	6.804 KG	RED	C P	16 STR PVC RED
8917 002500	152 MT	3.402 KG	RED		16 STR PVC RED
8917 0025000	1,524 MT	31.752 KG	RED	C	#16 STR PVC RED
8917 003100	30 MT	0.953 KG	ORANGE		16 STR PVC ORG
8917 0031000	305 MT	6.804 KG	ORANGE	P	16 STR PVC ORG
8917 004100	30 MT	0.953 KG	YELLOW		16 STR PVC YEL
8917 0041000	305 MT	6.804 KG	YELLOW	C P	16 STR PVC YEL
8917 005100	30 MT	0.953 KG	GREEN, DARK		16 STR PVC DGRN
8917 0051000	305 MT	6.804 KG	GREEN, DARK	P	16 STR PVC DGRN
8917 005500	152 MT	3.402 KG	GREEN, DARK		16 STR PVC DGRN
8917 0071000	305 MT	6.804 KG	VIOLET	P	#16 STR PVC VIO
8917 0081000	305 MT	6.804 KG	GRAY	C P	#16 STR PVC GRY
8917 009100	30 MT	0.953 KG	WHITE		16 STR PVC WHT
8917 0091000	305 MT	6.804 KG	WHITE	P	16 STR PVC WHT
8917 009500	152 MT	3.402 KG	WHITE		16 STR PVC WHT
8917 0095000	1,524 MT	31.752 KG	WHITE	C	#16 STR PVC WHT
8917 010100	30 MT	0.953 KG	BLACK		16 STR PVC BLK
8917 0101000	305 MT	6.804 KG	BLACK	P	16 STR PVC BLK
8917 010500	152 MT	3.402 KG	BLACK		16 STR PVC BLK
8917 0105000	1,524 MT	31.752 KG	BLACK	C P	#16 STR PVC BLK
8917 013100	30 MT	0.953 KG	BLUE, DARK		16 STR PVC DBLU
8917 0131000	305 MT	6.804 KG	BLUE, DARK	P	16 STR PVC DBLU
8917 013500	152 MT	3.402 KG	BLUE, DARK		16 STR PVC DBLU
8917 0135000	1,524 MT	31.752 KG	BLUE, DARK	C	#16 STR PVC DBLU
8917 189100	30 MT	0.953 KG	GREEN/YELLOW	A	16 STR PVC GRN/YEL
8917 1891000	305 MT	5.897 KG	GREEN/YELLOW	C A	16 STR PVC GRN/YEL

Notes:

A = STOCKED STRIPE COLORS.

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 2 Revision Date: 08-26-2008

© 2011 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331