RoHS

defining a degree of excellence

Surface Mount PTC


0ZCJ Series

1206 Chip

RoHS6 Compliant & Halogen-Free

0ZCJ Oct2013D

0ZCJ Series Fuse



Maximum Voltage

6-60V (per table)

Temperature Range

-40℃ to 85℃

Agency Approval

TUV (Std. EN60738-1-1 , Cert. R50102117)
UL Component (Std. UL1434, File E305051)
UL Conditions of Acceptability:

1.These devices have been investigated for use in safety circuits and are suitable as a limiting device.
2.These devices have been calibrated to limit the current to 8 amps within 5 seconds , per ANSI/NFPA 70, "National Electrical Code"

Application

All high-density boards

Product Features

1206 Chip Size , Fast Trip Time, Low DCR Resistance

Operating (Hold Current) Range

50mA - 2A

HALOGEN FREE = HF

LEAD FREE = Pb

Electrical Characteristics (23℃)

	Part Number	Hold Current	Trip Current	Max Time to Trip		Maximum Current	Rated Voltage	Typical Power	Resistance Tolerance		Agency Approvals	
				Current	Time				Rmin	R1max		
		IH, A	IT, A	A	Sec	Imax, A	Vmax, Vdc	Pd, W	Ohms	Ohms		
A	0ZCJ0005FF2E	0.05	0.15	0.25	1.50	10	60	0.4	3.600	50.00	Y	Y
B	0ZCJ0010FF2E	0.10	0.25	0.50	1.00	10	60	0.4	1.600	15.000	Y	Y
C	0ZCJ0012FF2E	0.12	0.39	1.00	0.20	10	48	0.6	1.400	6.500	Y	Y
D	0ZCJ0016FF2E	0.16	0.45	1.00	0.30	10	48	0.6	1.100	5.000	Y	Y
E	0ZCJ0020FF2E	0.20	0.40	8.00	0.10	10	30	0.4	0.600	2.500	Y	Y
F	0ZCJ0025FF2E	0.25	0.50	8.00	0.08	100	16	0.6	0.550	2.300	Y	Y
	0ZCJ0025AF2E	0.25	0.50	8.00	0.08	40	24	0.6	0.550	2.300	Y	Y
G	0ZCJ0035FF2G	0.35	0.75	8.00	0.10	40	16	0.4	0.300	1.200	Y	Y
	0ZCJ0035AF2E	0.35	0.75	8.00	0.10	40	30	0.6	0.300	1.200	Y	Y
H	0ZCJ0050FF2G	0.50	1.00	8.00	0.10	100	8	0.4	0.150	0.700	Y	Y
	0ZCJ0050AF2E	0.50	1.00	8.00	0.10	100	24	0.6	0.150	0.750	Y	Y
I	0ZCJ0075FF2E	0.75	1.50	8.00	0.20	100	6	0.6	0.090	0.290	Y	Y
	0ZCJ0075AF2E	0.75	1.50	8.00	0.20	100	16	0.6	0.090	0.290	Y	Y
J	0ZCJ0100FF2E	1.00	1.80	8.00	0.30	100	6	0.6	0.055	0.210	Y	Y
K	0ZCJ0110FF2E	1.10	2.20	8.00	0.30	100	6	0.8	0.040	0.180	Y	Y
L	0ZCJ0150FF2C	1.50	3.00	8.00	1.00	100	6	0.8	0.040	0.120	Y	Y
M	0ZCJ0200FF2C	2.00	3.50	8.00	1.50	100	6	0.8	0.018	0.080	Y	Y

I_H	Hold Current-maximum current at which the device will not trip in still air at 23℃.
I_T	Trip current-minimum current at which the device will always trip in still air at 23℃.
Imax	Maximum fault current device can withstand without damage at rated voltage (Vmax).
Vmax	Maximum voltage device can withstand without damage at its rated current.
Pd	Typical power dissipated by device when in tripped state in 23℃ still air environment.
Rmin	Minimum device resistance at 23℃.
R1max	Maximum device resistance at 23℃, 1 hour after initial device trip, or after being soldered to PCB in end application.

Specifications subject to change without notice

Bel Fuse Inc. 206 Van Vorst Street, Jersey City, NJ 07302 • Tel: 201-432-0463 • Fax: 201-432-9542 • E-Mail: belfuse@belf.com
Website: www.belfuse.com

PTC's – Basic Theory of Operation / "Tripped" Resistance Explanation


Fundamentally, a Bel PTC consists of a block of polymeric material containing conductive filler and bonded between two conductive, planar terminations.
At currents below the device IHOLD rating, AND at temperatures below 100C, the PTC maintains a resistance value below its R1 MAX rating.

As the device's temperature approaches 130C, either due to an increase in ambient temperature or a current exceeding its I TRIP rating, volumetric expansion of the filled polymer breaks apart the majority of conductive pathways across the terminals created by chain contact of adjacent filler particles and device resistance increases sharply by several orders of magnitude.

At the much higher "Tripped" resistance, there is just enough leakage current to allow internal heating to "hold" the device in its tripped state (around 125C) until power is interrupted. Once power is removed, the PTC's core cools and contracts allowing conductive chains to reform and return the device to its low resistance state.

The catalog data for each device specifies a "**Typical Power**" value. This is the power required to exactly match the heat lost by the tripped device to its ambient surroundings at 23C. By Ohm's Law, power can be stated as: W = E^2/R. Thus the approximate resistance of a "Tripped" PTC can be determined by:
R = E^2/W, where "E" is the voltage appearing across the PTC (usually the supply's open circuit voltage), and "W" is the **Typical Power** value for the particular PTC.
Since the PPTC acts to maintain a constant internal temperature, its apparent resistance will change based upon applied voltage and, to a lesser degree, ambient conditions. Consider the following example....
A PTC with a **Typical Power** of 1 watt protecting a circuit using a 60V supply will demonstrate an apparent, tripped resistance "R" of:
R = 60^2/1 = 3,600 ohms
This same tripped device when used to protect a 12V circuit would now present an apparent resistance of:
R = 12^2/1 = 144 ohms
The value for Typical Power is "typical" because any physical factors that affect heat loss (such as ambient temperature or air convection) will somewhat alter the level of power that the PTC needs to maintain its internal temperature. In short, PTCs do not exhibit a constant, quantifiable tripped resistance value.

Typical Time - To - Trip at 23°C



RoHS


bel

0ZCJ Oct2013D

Surface Mount PTC
0ZCJ Series

1206 Chip
RoHS6 Compliant & Halogen-Free


Thermal Derating Curve



Cautionary Notes

1. Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.
2. These Polymer PTC (PPTC) devices are intended for protection against occasional overcurrent/ overtemperature fault conditions and may not be suitable for use in applications where repeated and/ or prolonged fault conditions are anticipated.
3. Avoid contact of PTC device with chemical solvent. Prolonged contact may adversely impact the PTC performance.
4. These PTC devices may not be suitable for use in circuits with a large inductance, as the PTC trip can generate circuit voltage spikes above the PTC rated voltage.
5. These devices are intended for use in DC voltage applications only. Use in AC voltage applications should be first discussed with Bel Fuse engineering
6. Not recommended for use on potted or conformal coated PCB's. Restriction of free air flow could affect electrical performance and/or result in device failure Consult Bel Fuse engineering.
7. In the "Indeterminate Performance / grey zone", tripping may occur but cannot be relied upon. For special circumstances considering use within this region, consult Bel Fuse Engineering.
8. MSL : 2a (According to IPC J-Std-020).

Mechanical Dimensions



All dimensions in mm.

Part Number	C		D	
	Min	Max	Min	Max
0ZCJ0005FF2E	0.45	0.85	0.10	0.75
0ZCJ0010FF2E	0.45	0.85	0.10	0.75
0ZCJ0012FF2E	0.45	0.85	0.10	0.75
0ZCJ0016FF2E	0.45	0.75	0.10	0.75
0ZCJ0020FF2E	0.45	0.75	0.10	0.75
0ZCJ0025FF2E	0.45	0.75	0.10	0.75
0ZCJ0025AF2E	0.45	0.75	0.10	0.75
0ZCJ0035FF2G	0.45	0.75	0.10	0.75
0ZCJ0035AF2E	0.90	1.30	0.25	0.75
0ZCJ0050FF2G	0.25	0.55	0.10	0.75
0ZCJ0050AF2E	0.90	1.30	0.25	0.75
0ZCJ0075FF2E	0.45	1.25	0.25	0.75
0ZCJ0075AF2E	0.45	1.25	0.25	0.75
0ZCJ0100FF2E	0.45	1.00	0.25	0.75
0ZCJ0110FF2E	0.45	1.00	0.25	0.75
0ZCJ0150FF2C	0.80	1.40	0.25	0.75
0ZCJ0200FF2C	0.85	1.60	0.25	0.75

PTC Marking




"b" , IH code.

Part Number	IH Code
0ZCJ0005FF2E	C
0ZCJ0010FF2E	D
0ZCJ0012FF2E	Y
0ZCJ0016FF2E	Z
0ZCJ0020FF2E	F
0ZCJ0025FF2E	G
0ZCJ0025AF2E	g
0ZCJ0035FF2G	J
0ZCJ0035AF2E	j
0ZCJ0050FF2G	M
0ZCJ0050AF2E	m
0ZCJ0075FF2E	P
0ZCJ0075AF2E	p
0ZCJ0100FF2E	1
0ZCJ0110FF2E	R
0ZCJ0150FF2C	S
0ZCJ0200FF2C	2

Pad Layout

The dimensions in the table below provide the recommended pad layout.



P		S		W	
Nominal		Nominal		Nominal	
mm	Inch	mm	Inch	mm	Inch
2.00	0.787	1.00	0.394	1.90	0.748

Termination Pad Materials

Matte Tin - Plated Copper

Specifications subject to change without notice

Bel Fuse Inc. 206 Van Vorst Street, Jersey City, NJ 07302 • Tel: 201-432-0463 • Fax: 201-432-9542 • E-Mail: belfuse@belf.com


Website: www.belfuse.com

Surface Mount PTC
0ZCJ Series

1206 Chip
RoHS6 Compliant & Halogen-Free

Solder Reflow and Rework Recommendations

Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (Tsmax to Tp)	3 ℃/second max.
Preheat : Temperature Min (Tsmin) Temperature Max (Tsmax) Time (tsmin to tsmax)	 150 ℃ 200 ℃ 60-180 seconds
Time maintained above: Temperature(T_L) Time (t_L)	 217 ℃ 60-150 seconds
Peak/Classification Temperature(Tp) :	260 ℃
Time within 5℃ of actual Peak : Temperature (tp)	 20-40 seconds
Ramp-Down Rate :	6 ℃/second max.
Time 25 ℃ to Peak Temperature :	8 minutes max.



Solder Reflow

Due to " lead free / RoHS6 " construction of these PTC devices , the required Temperature and Dwell Time in the " Soldering "zone of the reflow profile are greater than those used for non-RoHS devices.

1.Recommended reflow methods ; IR , vapor phase oven , hot air oven.
2. Not Recommended For Wave Solder / Direct Immersion.
3. Recommended maximum ; paste thickness is 0.25mm.
4. Devices are compatible with standard industry cleaning solvents and methods.

Caution

If reflow temperature / dwell times exceed the recommended profile, the electrical performance of the PTC may be affected.

Rework : MIL-STD-202G Method 210F. Test Condition A.

Standard Packaging

Part Number	Tape/Reel Qty
0ZCJ0005FF2E Thru 0ZCJ0025AF2E	3,000
0ZCJ0035FF2G	4,000
0ZCJ0035AF2E	3,000
0ZCJ0050FF2G	4,000
0ZCJ0050AF2E Thru 0ZCJ0110FF2E	3,000
0ZCJ0150FF2C Thru	2,000
0ZCJ0200FF2C	

4000,3000 or 2000 fuses in 7 inches dia. Reel, 8mm wide tape, 4mm pitch, per EIA-481 (equivalent IEC-286 part 3).

P/N Explanation and Ordering Information

0ZCJ 0XXX X X XX

PTC series
0ZCJ, 1206 Size

I HOLD Rating
Refer to Part Number and IH Rating in Electrical Characteristics Table on P.1.

Elctrical Characteristics
F = Standard Design
A to Z (except F) = Special, customer spec, DCR sort, etc.

Mechanical Features
F = Standard Design
A to Z (except F) = Special, customer spec, lead forming, etc.

Tape & Reel Qty
See standard packaging

Specifications subject to change without notice

CORPORATE OFFICE
Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
E-Mail: belfuse@belf.com
Website: www. belfuse.com

FAR EAST OFFICE
Bel Fuse Ltd.
8/F Luk Hop Industrial Building
8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706

EUROPE OFFICE
Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite F15
Preston, Lancashire, PR1 8UQ
United Kingdom
Tel 44-1772-556601
Fax 44-1772-561008

EUROPE
Bel Stewart GmbH
Industriestrasse 20
61381 Friedrichsdorf
Germany
Tel 49-6172-9552-0
Fax 49-6172-9552-40

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331