




227-1221-X		REVISIONS			
DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ.		OFFICIAL ENG. RELEASE TO MFG.	5/31/73	19829	
	AA	REDRAWN WAS 'C' SIZE; ADD DASH -63 & NOTE 11	8/4/95	40734	CPM/DR
	AB	ADD DASH -100	10/25/96	41606	CPM/JJD
	AC	DASH 100, DIM 'A' WAS .263		43282	CPM/

AMPHENOL PART No.	DANIELS PART No.	DIMENSIONS				CABLE TYPE: RG-()/U	CONNECTOR SERIES
		±.003 'A'	±.003 'B'	±.010 'C'	±.010 'D'		
227-1221-09	Y204P	.178	.068	.400	.093	122, 180, 195, 21-597, 174, 179, 187, 188	BNC, TNC-CAV. A&B, SMA-CAV. A
-11	Y205P	.213	.068	.400	.093	55, 58, 141, 142, 223, 303, 400	BNC, TNC-CAV. A&B, UHF&SMA-CAV. A
-13	Y206P	.255	.068	.400	.093	59, 62, 140, 210	BNC, TNC-CAV. A&B, UHF-CAV. A
-15	Y207P	.263	.068	.400	.093	71	BNC, TNC-CAV. A & B
-25	Y110	.429	.100	.400	.120	8, 9, 11, 87A, 149, 165, 213, 214, 216, 225, 393	N-CAV. A&B
-29	Y109P	.324	.100	.400	.120	5, 6, 21, 143, 212, 222, 304	N-CAV. A&B
-23	Y145	.384		.400		8, 9, 11, 149, 213	UHF
-57	Y209P	.213	.100	.400	.120	55, 58, 141, 142, 223, 303, 400	N-CAV. A&B
-59	Y208P	.255	.100	.400	.120	59, 62, 140, 210	N-CAV. A&B
-03	Y196	.128	.105	.325		174, 179B, 186A, 187A, 316	SMA
-90		.312 ^{+.003} _{-.002}		.400		3/16 DIA CABLE	SMA, TNC, N
-35	Y137	.324	.128	.400	.120	SPECIAL NORTHROP NA1-1253	TNC, N
-27	Y151	.532		.400		SPECIAL NORTHROP NA1-1253	TNC, N
-37	Y138	.314	.151	.400		GALILEO 3000-(X)S FIBER OPTIC	905 & 906 SERIES
-45	Y143	.231	.218	.400		VARIOUS FIBER OPTIC CABLE	905 & 906 SERIES
-39	Y139	.309	.160	.400		VARIOUS FIBER OPTIC CABLE	905 & 906 SERIES
-31	Y150	.501		.400		F/O STRAIN RELIEF	801 MULTICHANNEL
-32		.324	.068	.400	.093	SPECIAL	
-34		.263	.100	.400	.120	COMM-SCOPE F59SSV & 71	N
-61		.429	.116	.400	.093	BELDEN 9913	REVERSE POLARITY TNC
-62		.151	.068	.400	.093	SIMILAR TO RG178	REVERSE POLARITY TNC
-63		.429	.116 ^{+.000} _{-.003}	.400	.120	BELDEN 9913, 9914	N
-572		.300		.400		FOR 95-572-0500X SERIES ANTENNAS	
227-1221-2522	SEE NOTE 5						
227-1221-1122	SEE NOTE 6 (EAR 70853-0)						
227-1221-100		.275	.068	.400	.093	59 QUAD SHEILD & HEADEND	BNC

NOTES:

- DIES TO BE PACKAGED IN PLASTIC CONTAINERS SUPPLIED BY DANIELS MFG CORP. AMPHENOL PART No. MUST APPEAR ON TOP SIDE OF CONTAINER. SIZE: 1-1/4" L x 1-1/4" W x 1-1/4" H.
- MATERIAL: CRIMPING DIES - TOOL STEEL. HEAT TREAT TO ROCKWELL C52-60.
- FINISH: ON CRIMPING SURFACES 32 MICROINCHES MAX. BLACK OXIDE COATING PER MIL-C-13924.
- DIES SHALL BE SUPPLIED WITH APPROPRIATE ROLL PINS.
- SAME AS -25 EXCEPT PACKAGE PER AMPHENOL SPEC 349-50371, SHEET 2, WANG PART No. 723-0350.
- (SAME AS -11) PACKAGE DIE WITH PLASTIC CONTAINER IN UNPRINTED BAG 999-256. BAG SHALL BE STAMPED WITH DATE CODE AND WANG PART No. "723-0391-1022". FOR PACKAGING & SHIPPING PROCEDURE SEE SPEC 349-50371.
- MANUFACTURED BY DANIELS MFG CORP., BLOOMFIELD, MICHIGAN.
- USED IN CONJUNCT WITH AMPHENOL TOOL FRAME PART No. 227-944. (DANIELS MFG CORP. TOOL FRAME HX4).
- DIMENSIONS SHOWN ARE AT FULLY BUTTED CONDITIONS.
- BASIC DIE DIMENSIONS MUST BE PER MIL-C-22520/5C.
- DO NOT SCALE THIS DRAWING.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL
MATERIAL SEE NOTE 2.
QQ-B-628, CLASS B
FINISH SEE NOTE 3.

REFERENCE

DRAWN T. ALBERA	DATE 9/20/89
ENGINEER D. ROYCE	DATE 9/29/89
APPROVED D. ROYCE	DATE 9/29/89
CAD FILE F:\DEPT611\TOOLS\227\1221	

TITLE
HEX CRIMP
DIE

Amphenol

Amphenol Corporation
RF/Microwave Operations
Danbury, Conn. U.S.A. 06810

SCALE: 1:1 SHEET OF

CODE ID 74868	DWG SIZE B	DRAWING NO. 227-1221-X	REV AC
------------------	---------------	---------------------------	-----------



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331