



Main

Range	TeSys
Product name	TeSys LK
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	100 A conforming to CSA 100 A conforming to UL 100 A (AC-22A) at 400 V AC conforming to IEC 100 A (AC-23A) at 400 V AC conforming to IEC 100 A (AC-22A) at 690 V AC conforming to IEC 100 A (AC-23A) at 690 V AC conforming to IEC
System Voltage	600 V AC 50/60 Hz
[Ui] rated insulation voltage	750 V
Control type	Rotary handle
Type of operating handle	External frontal External right side
Mounting support	Plate
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC
Rated power in W	51 kW at 400 V 63 kW at 500 V 90 kW at 690 V
Rated power in hp	30 hp at 240 V 53 A AC 75 hp at 480 V 64 A AC 100 hp at 600 V 51 A AC 10 hp at 125 V 77 A DC 15 hp at 250 V 54 A DC
[Icw] rated short-time withstand current	17.6 kA
Mechanical durability	8000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 cable(s) 4 mm ²
Height	6.3 in (160 mm)
Width	7.09 in (180 mm)
Depth	3.74 in (95 mm)

Environment

standards	IEC 60947-3 CSA C22.2 No 4 UL98
product certifications	CE CSA UL

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1240 - Schneider Electric declaration of conformity	Compliant - since 1240 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: Cancer - www.P65Warnings.ca.gov	WARNING: Cancer - www.P65Warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331