

# G3VM-21PR11

MOS FET Relays

## Smallest Class in market, USOP High-power, 0.9A Switching in a 20V Load Voltage Model

- Dielectric strength of 500Vrms between I/O.



**NEW**

**Note:** The actual product is marked differently from the image shown here.



**RoHS Compliant**

Refer to "Common Precautions".

### ■ Application Examples

- Semiconductor test equipment
- Communication equipment
- Test & measurement equipment
- Data loggers

### ■ Terminal Arrangement/Internal Connections



**Note:** The actual product is marked differently from the image shown here.

### ■ List of Models

Package type	Contact form	Terminals	Load voltage (peak value) (See note.)	Model	Minimum package quantity
					Number per tape & reel
USOP4	1a (SPST-NO)	Surface-mounting terminals	20V	G3VM-21PR11	—
				G3VM-21PR11 (TR05)	500
				G3VM-21PR11 (TR)	1,500

**Note 1.** Ask your OMRON representative for orders under 1,500 pcs or 500 pcs.

2. Tape-cut USOPs are packaged without humidity resistance. Use manual soldering to mount them. Refer to common precautions.

3. The AC peak and DC value is given for the load voltages.

### ■ Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )


Item	Symbol	Rating	Unit	Measurement conditions
LED forward current	I <sub>F</sub>	50	mA	
LED forward current reduction rate	$\Delta I_F/\text{°C}$	-0.5	mA/°C	$T_a \geq 25^\circ\text{C}$
LED reverse voltage	V <sub>R</sub>	5	V	
Connection temperature	T <sub>J</sub>	125	°C	
Load voltage (AC peak/DC)	V <sub>OFF</sub>	20	V	
Continuous load current (AC peak/DC)	I <sub>O</sub>	900	mA	
ON current reduction rate	$\Delta I_O/\text{°C}$	-12	mA/°C	$T_a \geq 50^\circ\text{C}$
Pulse ON current	I <sub>OP</sub>	2700	mA	t=100ms, Duty=1/10
Connection temperature	T <sub>J</sub>	125	°C	
Dielectric strength between I/O (See note 1.)	V <sub>I-O</sub>	500	Vrms	AC for 1 min
Ambient operating temperature	T <sub>a</sub>	-40~+85	°C	With no icing or condensation
Ambient storage temperature	T <sub>STG</sub>	-40~+125	°C	With no icing or condensation
Soldering temperature	—	260	°C	10s

**Note: 1.** The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

### ■ Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
LED forward voltage	V <sub>F</sub>	1.0	1.15	1.3	V	I <sub>F</sub> =10mA
Reverse current	I <sub>R</sub>	—	—	10	μA	V <sub>R</sub> =5V
Capacity between terminals	C <sub>T</sub>	—	15	—	pF	V=0, f=1MHz
Trigger LED forward current	I <sub>FT</sub>	—	0.6	3	mA	I <sub>O</sub> =100mA
Maximum resistance with output ON	R <sub>ON</sub>	—	0.18	0.22	Ω	I <sub>F</sub> =5mA, I <sub>O</sub> =900mA, t<1s
Current leakage when the relay is open	I <sub>LEAK</sub>	—	—	1	nA	V <sub>OFF</sub> =20V, T <sub>a</sub> =25°C
Capacity between terminals	C <sub>OFF</sub>	—	40	—	pF	V=0, f=100MHz, t<1s
Capacity between I/O terminals	C <sub>I-O</sub>	—	0.4	—	pF	f=1MHz, V <sub>s</sub> =0V
Insulation resistance between I/O terminals	R <sub>I-O</sub>	1000	—	—	MΩ	V <sub>I-O</sub> =500VDC, RoH≤60%
Turn-ON time	t <sub>ON</sub>	—	0.5	2	ms	I <sub>F</sub> =5mA, R <sub>L</sub> =200Ω, V <sub>DD</sub> =10V (See note 2.)
Turn-OFF time	t <sub>OFF</sub>	—	0.1	1	ms	V <sub>DD</sub> =10V (See note 2.)

**Note: 2.** Turn-ON and Turn-OFF Times




### ■Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.


Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	VDD	—	—	16	V
Operating LED forward current	IF	5	7.5	20	mA
Continuous load current (AC peak/DC)	Io	—	—	900	mA
Ambient operating temperature	Ta	-20	—	65	°C

### ■Engineering Data


**LED forward current vs.  
Ambient temperature**




**Continuous load current vs.  
On-state voltage**




**Turn ON, Turn OFF time vs.  
LED forward current**




**Output terminal capacitance  
COFF/COFF(ov) vs. Load voltage**




**Continuous load current vs.  
Ambient temperature**




**On-state resistance vs.  
Ambient temperature**




**Turn ON, Turn OFF time vs.  
Ambient temperature**




**LED forward current vs.  
LED forward voltage**



**Trigger LED forward current vs.  
Ambient temperature**



**Current leakage vs.  
Load voltage**




### ■Safety Precautions

- Refer to "Common Precautions" for all G3VM models.

## ■Appearance

USOP (Ultra Small Outline Package)

USOP4



Note: The actual product is marked differently from the image shown here.


## ■Dimensions

(Unit: mm)

### Surface-mounting Terminals




Weight: 0.03g



Note: The actual product is marked differently from the image shown here.

### Actual Mounting Pad Dimensions

(Recommended Value, Top View)



- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

**OMRON Corporation**

ELECTRONIC AND MECHANICAL COMPONENTS COMPANY

Contact: [www.omron.com/ecb](http://www.omron.com/ecb)

Cat. No. K196-E1-02

1112(0912)(O)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литер Н,  
помещение 100-Н Офис 331