


# HIGH SPEED PNP SILICON BIPOLAR TRANSISTOR

## 2N2894AC1

- Hermetic Ceramic Surface Mount Package (SOT23 Compatible)
- Silicon Planar Epitaxial PNP Transistor
- High Speed low Saturation Switching
- Space Level and High-Reliability Screening Options Available



### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25°C unless otherwise stated)

V <sub>CBO</sub>	Collector – Base Voltage	-12V
V <sub>CEO</sub>	Collector – Emitter Voltage	-12V
V <sub>EBO</sub>	Emitter – Base Voltage	-4.5V
I <sub>C</sub>	Continuous Collector Current	-200mA
P <sub>D</sub>	Total Power Dissipation at T <sub>A</sub> = 25°C	360mW
	Derate Above 25°C	2.88mW/°C
T <sub>J</sub>	Junction Temperature Range	-65 to +150°C
T <sub>stg</sub>	Storage Temperature Range	-65 to +150°C

### THERMAL PROPERTIES

Symbol	Parameter	Max	Units
R <sub>θJA</sub>	Thermal Resistance Junction to Ambient	347	°C/W

Semelab Limited reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing an order.

# HIGH SPEED PNP SILICON BIPOLAR TRANSISTOR 2N2894AC1

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise stated)

Symbols	Parameters	Test Conditions	Min	Typ	Max	Units
$V_{(BR)CBO}^{(1)}$	Collector-Base Breakdown Voltage	$I_C = -10\mu\text{A}$ $I_E = 0$	-12			V
$V_{(BR)CEO}^{(1)}$	Collector-Emitter Breakdown Voltage	$I_C = -10\text{mA}$ $I_B = 0$	-12			
$V_{(BR)EBO}^{(1)}$	Emitter-Base Breakdown Voltage	$I_E = -100\mu\text{A}$ $I_C = 0$	-4.5			
$I_{CBO}$	Collector Cut-Off Current	$V_{CB} = -10\text{V}$ $I_E = 0$			-100	nA
		$T_A = 125^\circ\text{C}$			-10	$\mu\text{A}$
$h_{FE}^{(1)}$	Forward-current transfer ratio	$I_C = -10\text{mA}$ $V_{CE} = -0.3\text{V}$	30			
		$I_C = -30\text{mA}$ $V_{CE} = -0.5\text{V}$	40		120	
		$T_A = -55^\circ\text{C}$	20			
$V_{CE(sat)}^{(1)}$	Collector-Emitter Saturation Voltage	$I_C = -10\text{mA}$ $I_B = -1.0\text{mA}$			-0.15	V
		$I_C = -30\text{mA}$ $I_B = -3.0\text{mA}$			-0.19	
		$I_C = -100\text{mA}$ $I_B = -10\text{mA}$			-0.45	
$V_{BE(sat)}^{(1)}$	Base-Emitter Saturation Voltage	$I_C = -10\text{mA}$ $I_B = -1.0\text{mA}$			-0.98	V
		$I_C = -30\text{mA}$ $I_B = -3.0\text{mA}$			-1.15	
		$I_C = -100\text{mA}$ $I_B = -10\text{mA}$			-1.50	

## DYNAMIC CHARACTERISTICS

$f_T$	Current Gain-Bandwidth Product	$I_C = -30\text{mA}$ $V_{CE} = -10\text{V}$ $f = 100\text{MHz}$	650			MHz
$C_{OBO}$	Output Capacitance	$V_{CB} = -5\text{V}$ , $I_E = 0$ , 1.0MHz			4.5	pF
$C_{IBO}$	Input Capacitance	$V_{EB} = -0.5\text{V}$ , $I_C = 0$ , 1.0MHz			6.0	
$t_{on}$	Turn-On Time	$V_{CC} = -2\text{V}$ $I_C = -30\text{mA}$			60	ns
$t_{off}$	Turn-Off Time	$I_{B1} = 1.5\text{mA}$ $I_{B2} = -1.5\text{mA}$			60	


### Notes

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle <2%

# HIGH SPEED PNP SILICON BIPOLAR TRANSISTOR 2N2894AC1

## MECHANICAL DATA

Dimensions in mm (Inches)



**C1**  
**Underside View**

## PACKAGE VARIANT TABLE

Variant	Pad 1	Pad 2	Pad 3	Pad 4
C1A	Base	Emitter	Collector	No Pad (3-Pins Only)
C1B	Base	Emitter	Collector	Lid Contact *

\* The additional contact provides a connection to the lid in the application. Connecting the metal lid to a known electrical potential stops deep dielectric discharge in space applications; see the Space Weather link [www.semelab.co.uk/mil/lcc1\\_4](http://www.semelab.co.uk/mil/lcc1_4) on the Semelab web site. Package variant to be specified at order.

# HIGH SPEED PNP SILICON BIPOLAR TRANSISTOR 2N2894AC1

## SCREENING OPTIONS

Space Level (JQRS/ESA) and High Reliability options are available in accordance with the [High Reliability and Screening Options Handbook](#) available for download from the from the TT electronics Semelab web site.

ESA Quality Level Products are based on the testing procedures specified in the generic ESCC 5000 and in the corresponding part detail specifications.

Semelabs QR216 and QR217 processing specifications (JQRS), in conjunction with the companies ISO 9001:2000 approval present a viable alternative to the American MIL-PRF-19500 space level processing.

QR217 (Space Level Quality Conformance) is based on the quality conformance inspection requirements of MIL-PRF-19500 groups A (table V), B (table VIa), C (table VII) and also ESA / ESCC 5000 (chart F4) lot validation tests.

QR216 (Space Level Screening) is based on the screening requirements of MIL-PRF-19500 (table IV) and also ESA / ESCC 5000 (chart F3).

JQRS parts are processed to the device data sheet and screened to QR216 with conformance testing to Q217 groups A and B in accordance with MIL-STD-750 methods and procedures.

Additional conformance options are available, for example Pre-Cap Visual Inspection, Buy-Off Visit or Data Packs. These are chargeable and must be specified at the order stage (See Ordering Information). Minimum order quantities may apply.

Alternative or additional customer specific conformance or screening requirements would be considered. Contact Semelab sales with enquiries.

## MARKING DETAILS

Parts can be marked with approximately 8 characters on two lines and can include the cathode identification. Typical marking would include part or specification number, week of seal or serial number subject to available space and legibility.

Customer specific marking requirements can be arranged at the time of order.

Example Marking:



## ORDERING INFORMATION

Part numbers are built up from Type, Package Variant, and screening level. The part numbers are extended to include the additional options as shown below.

Type – See Electrical Stability Characteristics Table

Package Variant – See Mechanical Data

Screening Level – See Screening Options (ESA / JQRS)

Additional Options:

Customer Pre-Cap Visual Inspection	CVP
Customer Buy-Off visit	CVB
Data Pack	DA
Solderability Samples	SS
Scanning Electron Microscopy	SEM
Radiography (X-ray)	.XRAY
Total Dose Radiation Test	.RAD
MIL-PRF-19500 (QR217)	
Group B charge	.GRPB
Group B destructive mechanical samples	.GBDM (12 pieces)
Group C charge	.GRPC
Group C destructive electrical samples	.GCDE (12 pieces)
Group C destructive mechanical samples	.GCDM (6 pieces)
ESA/ESCC	
Lot Validation Testing (subgroup 1) charge	.LVT1
LVT1 destructive samples (environmental)	.L1DE (15 pieces)
LVT1 destructive samples (mechanical)	.L1DM (15 pieces)
Lot Validation Testing (subgroup 2) charge	.LVT2
LVT2 endurance samples (electrical)	.L2D (15 pieces)
Lot Validation Testing (subgroup 3) charge	.LVT3
LVT3 destructive samples (mechanical)	.L3D (5 pieces)

Additional Option Notes:

- 1) All 'Additional Options' are chargeable and must be specified at order stage.
- 2) When Group B,C or LVT is required, additional electrical and mechanical destructive samples must be ordered
- 3) All destructive samples are marked the same as other production parts unless otherwise requested.

Example ordering information:

The following example is for the 2N2894AC1 part with package variant B, JQRS screening, additional Group C conformance testing and a Data pack.

Part Numbers:

- 2N2894AC1B-JQRS (Include quantity for flight parts)
- 2N2894AC1B.GRPC (chargeable conformance option)
- 2N2894AC1B.GCDE (charge for destructive parts)
- 2N2894AC1B.GCDM (charge for destructive parts)
- 2N2894AC1B.DA (charge for Data pack)

Customers with any specific requirements (e.g. marking or screening) may be supplied with a similar alternative part number (there is maximum 20 character limit to part numbers). Contact Semelab sales with enquiries.

High Reliability and Screening Options Handbook link: [http://www.semelab.co.uk/pdf/misc/documents/hirel\\_and\\_screening\\_options.pdf](http://www.semelab.co.uk/pdf/misc/documents/hirel_and_screening_options.pdf)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331