


Spectra-Bond® parallel conductors — 111 series and Spectra-Bond® twisted pairs — 114 series



description

Bonded planar cable was originally developed, patented and introduced by Spectra-Strip. Bonded flat ribbon cables reduce both cost and packaging volume because they can be contour-formed, are self-supporting with minimum clamping, and can dissipate heat faster than round multi-conductor cable. They are used today in a great variety of interconnective systems using point-to-point wiring applications. These flat cables are fully compatible with standard termination techniques such as soldering, crimping and wire wrapping.

Spectra-Strip standard bonded cable consists of stranded or solid round conductors insulated with color-coded PVC and bonded together by a patented process to form a flat ribbon.


special bonded cables

Spectra-Strip has a highly versatile design and manufacturing capability for planar bonded PVC cables. A wide range of specially designed and produced constructions can be obtained by consulting the factory with specific requirements and cable descriptions.

Bonded constructions may be designed so that a single cable can contain several different wires or cables to provide a complete range of circuit functions including power, control, transmission and signalling.

A special cross-linked PVC insulation offering improved performance in resistance to heat and abrasion plus outstanding flame retardancy is also available. It is produced by exposure to a high-energy electron beam which cross-links the molecular structure of the PVC.

dimensions



30 AWG	=	.032"	(0.81 mm)
28 AWG	=	.035"	(0.89 mm)
26 AWG	=	.039"	(1.00 mm)
24 AWG	=	.044"	(1.12 mm)
22 AWG	=	.051"	(1.30 mm)

$$\text{WIDTH} = (\text{Number of Conductors}) \times (\text{O.D.})$$

benefits

- Low cost point-to-point wiring
- Insulation easily separated for circuit routing
- Color coded
- Standard termination techniques
- Versatile applications
- UL recognized style 

characteristics

Physical

— 111 series — parallel

Conductors: 22-30 AWG, 7 and 19 strand, tinned copper

Insulation: .010" nom. wall, flame retardant PVC

Number of conductors: 2 to 100

Color code: brown, red, orange, yellow, green, blue, violet, gray, white, black (repeat)

— 114 series — twisted pairs

Conductors: 22-30 AWG, 7 strand, tinned copper

Insulation: .010" nom. wall, flame retardant PVC, .016" nom. wall, flame retardant PVC available

Number of conductors: 2 to 100

Electrical

Voltage rating: 300 V per UL

Insulation resistance:
10¹⁰ ohms — 10 ft., min.

UL style number: Cable style 2697, cable style 2693

Temperature rating: 2697 (80°C, 300V), 2693 (105°C, 300V)

CSA: Available upon request

Spectra-Bond® parallel conductors and Spectra-Bond® twisted pairs

order information

— 111 series

Part No.	AWG	No. Cond.	STR	Nom. Width 'W' in. (mm)	Approx. Wt./Roll lbs. (kg)
843-111-3003-010	30	10	7/38	.32 (8,13)	.74 (0,34)
843-111-3003-015	30	15	7/38	.48 (12,19)	1.11 (0,50)
843-111-3003-020	30	20	7/38	.64 (16,26)	1.48 (0,67)
843-111-3003-030	30	30	7/38	.96 (24,38)	2.22 (1,01)
843-111-2803-010	28	10	7/36	.35 (8,89)	1.00 (0,45)
843-111-2803-015	28	15	7/36	.53 (13,34)	1.50 (0,68)
843-111-2803-020	28	20	7/36	.70 (17,78)	2.00 (0,91)
843-111-2803-030	28	30	7/36	1.05 (26,67)	3.00 (1,36)
843-111-2609-010	26	10	7/34	.39 (9,91)	1.42 (0,64)
843-111-2609-014	26	14	7/34	.55 (13,88)	1.99 (0,90)
843-111-2609-015	26	15	7/34	.59 (14,86)	2.13 (0,97)
843-111-2609-016	26	16	7/34	.63 (15,88)	3.18 (1,44)
843-111-2609-020	26	20	7/34	.78 (19,81)	2.84 (1,29)
843-111-2609-030	26	30	7/34	1.17 (29,72)	4.26 (1,93)
843-111-2413-010	24	10	7/32	.44 (11,18)	2.05 (0,93)
843-111-2414-010	24	10	19/36	.45 (11,43)	2.22 (1,01)
843-111-2413-015	24	15	7/32	.66 (16,76)	3.08 (1,40)
843-111-2414-015	24	15	19/36	.68 (17,15)	3.33 (1,51)
843-111-2413-020	24	20	7/32	.88 (22,35)	4.10 (1,86)
843-111-2414-020	24	20	19/36	.90 (22,86)	4.44 (2,01)
843-111-2413-030	24	30	7/32	1.32 (33,53)	6.15 (2,79)
843-111-2414-030	24	30	19/36	1.35 (34,29)	6.66 (3,02)
843-111-2213-010	22	10	7/30	.51 (12,94)	2.97 (1,35)
843-111-2214-010	22	10	19/34	.51 (12,94)	3.22 (1,46)
843-111-2213-015	22	15	7/30	.77 (19,43)	4.46 (2,02)
843-111-2214-015	22	15	19/34	.77 (19,43)	4.83 (2,19)
843-111-2213-020	22	20	7/30	1.02 (25,91)	5.94 (2,69)
843-111-2214-020	22	20	19/34	1.02 (25,91)	6.44 (2,92)
843-111-2213-030	22	30	7/30	1.53 (38,86)	8.91 (4,04)
843-111-2214-030	22	30	19/34	1.53 (38,86)	9.66 (4,38)

Standard sizes are stocked and packaged in 100 foot put-ups.

order information

— 114 series

Please consult factory for full information.

80°C, 300V cable may be certified under Canadian Standards Association (CSA) Appliances Wiring Material Program, (specify UL Style or CSA at time of order). For different wire gauges, number of conductors, color striping, materials and other special requirements, please consult the factory.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331