

NLAS4051

Analog Multiplexer/ Demultiplexer

TTL Compatible, Single-Pole, 8-Position Plus Common Off

The NLAS4051 is an improved version of the MC14051 and MC74HC4051 fabricated in sub-micron Silicon Gate CMOS technology for lower $R_{DS(on)}$ resistance and improved linearity with low current. This device may be operated either with a single supply or dual supply up to ± 3.0 V to pass a 6.0 V_{PP} signal without coupling capacitors.

When operating in single supply mode, it is only necessary to tie V_{EE}, pin 7 to ground. For dual supply operation, V_{EE} is tied to a negative voltage, not to exceed maximum ratings.

Features

- Improved $R_{DS(on)}$ Specifications
- Pin for Pin Replacement for MAX4051 and MAX4051A
 - ◆ One Half the Resistance Operating at 5.0 V
- Single or Dual Supply Operation
 - ◆ Single 2.5–5.0 V Operation, or Dual ± 3.0 V Operation
 - ◆ With V_{CC} of 3.0 to 3.3 V, Device Can Interface with 1.8 V Logic, No Translators Needed
 - ◆ Address and Inhibit Logic are Over-Voltage Tolerant and May Be Driven Up +6.0 V Regardless of V_{CC}
- Improved Linearity Over Standard HC4051 Devices
- Popular SOIC, and Space Saving TSSOP, and QSOP 16 Pin Packages
- Pb-Free Packages are Available*




Figure 1. Pin Connection
(Top View)




ON Semiconductor®

<http://onsemi.com>



MARKING DIAGRAMS




SOIC-16
D SUFFIX
CASE 751B



TSSOP-16
DT SUFFIX
CASE 948F



QSOP-16
QS SUFFIX
CASE 492



A = Assembly Location
WL, L = Wafer Lot
Y = Year
WW, W = Work Week
G or ■ = Pb-Free Package

ORDERING INFORMATION

| Device | Package | Shipping† |
|---------------|-----------------------|------------------|
| NLAS4051DR2 | SOIC-16 | 2500/Tape & Reel |
| NLAS4051DR2G | SOIC-16 (Pb-Free) | 2500/Tape & Reel |
| NLAS4051DTR2 | TSSOP-16 | 2500/Tape & Reel |
| NLAS4051DTR2G | TSSOP-16 (Pb-Free) | 2500/Tape & Reel |
| NLAS4051QSR | QSOP-16 | 2500/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NLAS4051

TRUTH TABLE

| Inhibit | Address | | | ON SWITCHES* |
|---------|-----------------|-----------------|-----------------|---------------------|
| | C | B | A | |
| 1 | X don't care | X don't care | X don't care | All switches open |
| 0 | 0 | 0 | 0 | COM-NO ₀ |
| 0 | 0 | 0 | 1 | COM-NO ₁ |
| 0 | 0 | 1 | 0 | COM-NO ₂ |
| 0 | 0 | 1 | 1 | COM-NO ₃ |
| 0 | 1 | 0 | 0 | COM-NO ₄ |
| 0 | 1 | 0 | 1 | COM-NO ₅ |
| 0 | 1 | 1 | 0 | COM-NO ₆ |
| 0 | 1 | 1 | 1 | COM-NO ₇ |

*NO and COM pins are identical and interchangeable. Either may be considered an input or output; signals pass equally well in either direction.




Figure 2. Logic Diagram

MAXIMUM RATINGS

| Parameter | Symbol | Value | Unit |
|---|---------------|---|------|
| Negative DC Supply Voltage (Referenced to GND) | V_{EE} | -7.0 to +0.5 | V |
| Positive DC Supply Voltage (Note 1) (Referenced to GND) (Referenced to V_{EE}) | V_{CC} | -0.5 to +7.0 -0.5 to +7.0 | V |
| Analog Input Voltage | V_{IS} | $V_{EE} - 0.5$ to $V_{CC} + 0.5$ | V |
| Digital Input Voltage (Referenced to GND) | V_{IN} | -0.5 to 7.0 | V |
| DC Current, Into or Out of Any Pin | I | ± 50 | mA |
| Storage Temperature Range | T_{STG} | -65 to +150 | °C |
| Lead Temperature, 1 mm from Case for 10 Seconds | T_L | 260 | °C |
| Junction Temperature under Bias | T_J | +150 | °C |
| Thermal Resistance | θ_{JA} | SOIC 143 TSSOP 164 QSOP 164 | °C/W |
| Power Dissipation in Still Air, | P_D | SOIC 500 TSSOP 450 QSOP 450 | mW |
| Moisture Sensitivity | MSL | Level 1 | |
| Flammability Rating | F_R | Oxygen Index: 30% – 35% UL 94 V-0 @ 0.125 in | |
| ESD Withstand Voltage | V_{ESD} | Human Body Model (Note 2) > 2000 Machine Model (Note 3) > 200 Charged Device Model (Note 4) > 1000 | V |
| Latchup Performance | $I_{LATCHUP}$ | Above V_{CC} and Below GND at 125°C (Note 5) ± 300 | mA |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. The absolute value of $V_{CC} \pm |V_{EE}| \leq 7.0$.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.
5. Tested to EIA/JESD78.

NLAS4051

RECOMMENDED OPERATING CONDITIONS

| Parameter | Symbol | Min | Max | Unit |
|--|------------|--|------------|------|
| Negative DC Supply Voltage (Referenced to GND) | V_{EE} | -5.5 | GND | V |
| Positive DC Supply Voltage (Referenced to GND) (Referenced to V_{EE}) | V_{CC} | 2.5 2.5 | 5.5 6.6 | V |
| Analog Input Voltage | V_{IS} | V_{EE} | V_{CC} | V |
| Digital Input Voltage (Note 6) (Referenced to GND) | V_{IN} | 0 | 5.5 | V |
| Operating Temperature Range, All Package Types | T_A | -55 | 125 | °C |
| Input Rise/Fall Time (Channel Select or Enable Inputs) | t_r, t_f | 0 0 | 100 20 | ns/V |
| | | $V_{CC} = 3.0 \text{ V} \pm 0.3 \text{ V}$ $V_{CC} = 5.0 \text{ V} \pm 0.5 \text{ V}$ | | |

6. Unused digital inputs may not be left open. All digital inputs must be tied to a high-logic voltage level or a low-logic input voltage level.

DC CHARACTERISTICS – Digital Section (Voltages Referenced to GND)

| Parameter | Condition | Symbol | V_{CC} V | Guaranteed Limit | | | Unit |
|---|--|----------|---------------|------------------|--------|---------|------|
| | | | | -55 to 25°C | ≤ 85°C | ≤ 125°C | |
| Minimum High-Level Input Voltage, Address and Inhibit Inputs | | V_{IH} | 2.5 | 1.75 | 1.75 | 1.75 | V |
| | | | 3.0 | 2.1 | 2.1 | | |
| | | | 4.5 | 3.15 | 3.15 | | |
| | | | 5.5 | 3.85 | 3.85 | | |
| Maximum Low-Level Input Voltage, Address and Inhibit Inputs | | V_{IL} | 2.5 | .45 | .45 | .45 | V |
| | | | 3.0 | 0.9 | 0.9 | | |
| | | | 4.5 | 1.35 | 1.35 | | |
| | | | 5.5 | 1.65 | 1.65 | | |
| Maximum Input Leakage Current, Address or Inhibit Inputs | $V_{IN} = 6.0$ or GND | I_{IN} | 0 V to 6.0 V | ± 0.1 | ± 1.0 | ± 1.0 | µA |
| Maximum Quiescent Supply Current (per Package) | Address, Inhibit and $V_{IS} = V_{CC}$ or GND | I_{CC} | 6.0 | 4.0 | 40 | 80 | µA |

DC ELECTRICAL CHARACTERISTICS – Analog Section

| Parameter | Test Conditions | Symbol | V_{CC} V | V_{EE} V | Guaranteed Limit | | | Unit |
|--|--|-----------------|---------------|---------------|------------------|--------|---------|------|
| | | | | | -55 to 25°C | ≤ 85°C | ≤ 125°C | |
| Maximum "ON" Resistance (Note 7) | $V_{IN} = V_{IL}$ or V_{IH} $V_{IS} = (V_{EE} \text{ to } V_{CC})$ $ I_S = 10 \text{ mA}$ (Figures 4 thru 9) | R_{ON} | 3.0 | 0 | 86 | 108 | 120 | Ω |
| | | | 4.5 | 0 | 37 | 46 | 55 | |
| | | | 3.0 | -3.0 | 26 | 33 | 37 | |
| Maximum Difference in "ON" Resistance Between Any Two Channels in the Same Package | $V_{IN} = V_{IL}$ or V_{IH} , $V_{IS} = 2.0 \text{ V}$ $V_{IS} = \frac{1}{2}(V_{CC} - V_{EE})$, $V_{IS} = 3.0 \text{ V}$ $ I_S = 10 \text{ mA}$, $V_{IS} = 2.0 \text{ V}$ | ΔR_{ON} | 3.0 | 0 | 15 | 20 | 20 | Ω |
| | | | 4.5 | 0 | 13 | 18 | 18 | |
| | | | 3.0 | -3.0 | 10 | 15 | 15 | |
| ON Resistance Flatness | $ I_S = 10 \text{ mA}$ $V_{COM} = 1, 2, 3.5 \text{ V}$ $V_{COM} = 2, 0, 2 \text{ V}$ | $R_{flat(ON)}$ | 4.5 3.0 | 3.0 | 4 2 | 4 2 | 5 3 | Ω |
| Maximum Off-Channel Leakage Current | Switch Off $V_{IN} = V_{IL}$ or V_{IH} $V_{IO} = V_{CC} - 1.0 \text{ V}$ or $V_{EE} + 1.0 \text{ V}$ (Figure 17) | $I_{NC(OFF)}$ | 6.0 | 0 | 0.1 | 5.0 | 100 | nA |
| | | $I_{NO(OFF)}$ | 3.0 | -3.0 | 0.1 | 5.0 | 100 | |
| Maximum On-Channel Leakage Current, Channel- to-Channel | Switch On $V_{IO} = V_{CC} - 1.0 \text{ V}$ or $V_{EE} + 1.0 \text{ V}$ (Figure 17) | $I_{COM(ON)}$ | 6.0 | 0 | 0.1 | 5.0 | 100 | nA |
| | | | 3.0 | -3.0 | 0.1 | 5.0 | 100 | |

7. At supply voltage (V_{CC}) approaching 2.5 V the analog switch on-resistance becomes extremely non-linear. Therefore, for low voltage operation it is recommended that these devices only be used to control digital signals.

NLAS4051

AC CHARACTERISTICS (Input $t_r = t_f = 3$ ns)

| Parameter | Test Conditions | Symbol | V_{CC} V | V_{EE} V | Guaranteed Limit | | | | Unit |
|--------------------------------|---|-----------|-------------------|--------------------|-------------------|-------------------|-------------|-------------|------|
| | | | | | -55 to 25°C | | ≤ 85°C | ≤ 125°C | |
| | | | | | Min | Typ* | | | |
| Minimum Break-Before-Make Time | $V_{IN} = V_{IL}$ or V_{IH} $V_{IS} = V_{CC}$ $R_L = 300 \Omega$, $C_L = 35$ pF (Figure 19) | t_{BBM} | 3.0 4.5 3.0 | 0.0 0.0 -3.0 | 1.0 1.0 1.0 | 6.5 5.0 3.5 | - - - | - - - | ns |

*Typical Characteristics are at 25°C.

AC CHARACTERISTICS ($C_L = 35$ pF, Input $t_r = t_f = 3$ ns)

| Parameter | Symbol | V_{CC} V | V_{EE} V | Guaranteed Limit | | | | | | Unit | |
|--|----------------------|--------------------------|---------------------|------------------|----------------------|----------------------|--------|----------------------|---------|----------------------|-----|
| | | | | -55 to 25°C | | | ≤ 85°C | | ≤ 125°C | | |
| | | | | Min | Typ | Max | Min | Max | Min | | Max |
| Transition Time (Address Selection Time) (Figure 18) | t_{TRANS} | 2.5 3.0 4.5 3.0 | 0 0 0 -3.0 | | 22 20 16 16 | 40 28 23 23 | | 45 30 25 25 | | 50 35 30 28 | ns |
| Turn-on Time (Figures 14, 15, 20, and 21) Inhibit to N_O or N_C | t_{ON} | 2.5 3.0 4.5 3.0 | 0 0 0 -3.0 | | 22 18 16 16 | 40 28 23 23 | | 45 30 25 25 | | 50 35 30 28 | ns |
| Turn-off Time (Figures 14, 15, 20, and 21) Inhibit to N_O or N_C | t_{OFF} | 2.5 3.0 4.5 3.0 | 0 0 0 -3.0 | | 22 18 16 16 | 40 28 23 23 | | 45 30 25 25 | | 50 35 30 28 | ns |
| Typical @ 25°C, $V_{CC} = 5.0$ V | | | | | | | | | | | |
| Maximum Input Capacitance, Select Inputs | C_{IN} | | | | | | | 8 | | | pF |
| Analog I/O | C_{NO} or C_{NC} | | | | | | | 10 | | | |
| Common I/O | C_{COM} | | | | | | | 10 | | | |
| Feedthrough | $C_{(ON)}$ | | | | | | | 1.0 | | | |

ADDITIONAL APPLICATION CHARACTERISTICS (GND = 0 V)

| Parameter | Condition | Symbol | V_{CC} V | V_{EE} V | Typ | Unit |
|--|--|-----------|--------------------------|---------------------------|--------------------------|------|
| | | | | | 25°C | |
| Maximum On-Channel Bandwidth or Minimum Frequency Response | $V_{IS} = \frac{1}{2}(V_{CC} - V_{EE})$ Source Amplitude = 0 dBm (Figures 10 and 22) | BW | 3.0 4.5 6.0 3.0 | 0.0 0.0 0.0 -3.0 | 80 90 95 95 | MHz |
| Off-Channel Feedthrough Isolation | $f = 100$ kHz; $V_{IS} = \frac{1}{2}(V_{CC} - V_{EE})$ Source = 0 dBm (Figures 12 and 22) | V_{ISO} | 3.0 4.5 6.0 3.0 | 0.0 0.0 0.0 -3.0 | -93 -93 -93 -93 | dB |
| Maximum Feedthrough On Loss | $V_{IS} = \frac{1}{2}(V_{CC} - V_{EE})$ Source = 0 dBm (Figures 10 and 22) | V_{ONL} | 3.0 4.5 6.0 3.0 | 0.0 0.0 0.0 -3.0 | -2 -2 -2 -2 | dB |
| Charge Injection | $V_{IN} = V_{CC}$ to V_{EE} , $f_{IS} = 1$ kHz, $t_r = t_f = 3$ ns $R_{IS} = 0 \Omega$, $C_L = 1000$ pF, $Q = C_L * \Delta V_{OUT}$ (Figures 16 and 23) | Q | 5.0 3.0 | 0.0 -3.0 | 9.0 12 | pC |
| Total Harmonic Distortion THD + Noise | $f_{IS} = 1$ MHz, $R_L = 10$ K Ω , $C_L = 50$ pF, $V_{IS} = 5.0$ V _{PP} sine wave $V_{IS} = 6.0$ V _{PP} sine wave (Figure 13) | THD | 6.0 3.0 | 0.0 -3.0 | 0.10 0.05 | % |

NLAS4051




Figure 3. I_{CC} versus Temp, $V_{CC} = 3\text{ V}$ and 5 V




Figure 4. R_{ON} versus V_{CC} , Temp = 25°C




Figure 5. Typical On Resistance
 $V_{CC} = 2.0\text{ V}$, $V_{EE} = 0\text{ V}$




Figure 6. Typical On Resistance
 $V_{CC} = 3.0\text{ V}$, $V_{EE} = 0\text{ V}$




Figure 7. Typical On Resistance
 $V_{CC} = 4.5\text{ V}$, $V_{EE} = 0\text{ V}$




Figure 8. Typical On Resistance
 $V_{CC} = 5.5\text{ V}$, $V_{EE} = 0\text{ V}$

NLAS4051




Figure 9. Typical On Resistance
 $V_{CC} = 3.3\text{ V}$, $V_{EE} = -3.3\text{ V}$




Figure 10. Bandwidth, $V_{CC} = 5.0\text{ V}$




Figure 11. Phase Shift, $V_{CC} = 5.0\text{ V}$




Figure 12. Off Isolation, $V_{CC} = 5.0\text{ V}$




Figure 13. Total Harmonic Distortion

NLAS4051




Figure 14. t_{ON} and t_{OFF} versus V_{CC}




Figure 15. t_{ON} and t_{OFF} versus Temp




Figure 16. Charge Injection versus COM Voltage




Figure 17. Switch Leakage versus Temperature





Figure 18. Channel Selection Propagation Delay

NLAS4051





Figure 19. t_{BMM} (Time Break-Before-Make)





Figure 20. t_{ON}/t_{OFF}






Figure 21. t_{ON}/t_{OFF}

NLAS4051



Channel switch Address and Inhibit/s test socket is normalized. Off isolation is measured across an off channel. On loss is the bandwidth of an On switch. V_{ISO} , Bandwidth and V_{ONL} are independent of the input signal direction.

$$V_{ISO} = \text{Off Channel Isolation} = 20 \text{ Log} \left(\frac{V_{OUT}}{V_{IN}} \right) \text{ for } V_{IN} \text{ at } 100 \text{ kHz}$$

$$V_{ONL} = \text{On Channel Loss} = 20 \text{ Log} \left(\frac{V_{OUT}}{V_{IN}} \right) \text{ for } V_{IN} \text{ at } 100 \text{ kHz to } 50 \text{ MHz}$$

Bandwidth (BW) = the frequency 3 dB below V_{ONL}

Figure 22. Off Channel Isolation/On Channel Loss (BW)/Crosstalk (On Channel to Off Channel)/ V_{ONL}




Figure 23. Charge Injection: (Q)

TYPICAL OPERATION




Figure 24. 5.0 Volts Single Supply
 $V_{CC} = 5.0 \text{ V}, V_{EE} = 0$





Figure 25. Dual Supply
 $V_{CC} = 3.0 \text{ V}, V_{EE} = -3.0 \text{ V}$

NLAS4051

PACKAGE DIMENSIONS

SOIC-16 D SUFFIX CASE 751B-05 ISSUE J




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 9.80 | 10.00 | 0.386 | 0.393 |
| B | 3.80 | 4.00 | 0.150 | 0.157 |
| C | 1.35 | 1.75 | 0.054 | 0.068 |
| D | 0.35 | 0.49 | 0.014 | 0.019 |
| F | 0.40 | 1.25 | 0.016 | 0.049 |
| G | 1.27 BSC | | 0.050 BSC | |
| J | 0.19 | 0.25 | 0.008 | 0.009 |
| K | 0.10 | 0.25 | 0.004 | 0.009 |
| M | 0° | 7° | 0° | 7° |
| P | 5.80 | 6.20 | 0.229 | 0.244 |
| R | 0.25 | 0.50 | 0.010 | 0.019 |

TSSOP-16 CASE 948F-01 ISSUE A



NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.90 | 5.10 | 0.193 | 0.200 |
| B | 4.30 | 4.50 | 0.169 | 0.177 |
| C | --- | 1.20 | --- | 0.047 |
| D | 0.05 | 0.15 | 0.002 | 0.006 |
| F | 0.50 | 0.75 | 0.020 | 0.030 |
| G | 0.65 BSC | | 0.026 BSC | |
| H | 0.18 | 0.28 | 0.007 | 0.011 |
| J | 0.09 | 0.20 | 0.004 | 0.008 |
| J1 | 0.09 | 0.16 | 0.004 | 0.006 |
| K | 0.19 | 0.30 | 0.007 | 0.012 |
| K1 | 0.19 | 0.25 | 0.007 | 0.010 |
| L | 6.40 BSC | | 0.252 BSC | |
| M | 0° | 8° | 0° | 8° |

NLAS4051

PACKAGE DIMENSIONS

QSOP-16
QS SUFFIX
CASE 492-01
ISSUE O



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. THE BOTTOM PACKAGE SHALL BE BIGGER THAN THE TOP PACKAGE BY 4 MILS (NOTE: LEAD SIDE ONLY). BOTTOM PACKAGE DIMENSION SHALL FOLLOW THE DIMENSION STATED IN THIS DRAWING.
4. PLASTIC DIMENSIONS DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 6 MILS PER SIDE.
5. BOTTOM EJECTOR PIN WILL INCLUDE THE COUNTRY OF ORIGIN (COO) AND MOLD CAVITY I.D.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|--------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.189 | 0.196 | 4.80 | 4.98 |
| B | 0.150 | 0.157 | 3.81 | 3.99 |
| C | 0.061 | 0.068 | 1.55 | 1.73 |
| D | 0.008 | 0.012 | 0.20 | 0.31 |
| F | 0.016 | 0.035 | 0.41 | 0.89 |
| G | 0.025 BSC | | 0.64 BSC | |
| H | 0.008 | 0.018 | 0.20 | 0.46 |
| J | 0.0098 | 0.0075 | 0.249 | 0.191 |
| K | 0.004 | 0.010 | 0.10 | 0.25 |
| L | 0.230 | 0.244 | 5.84 | 6.20 |
| M | 0° | 8° | 0° | 8° |
| N | 0° | 7° | 0° | 7° |
| P | 0.007 | 0.011 | 0.18 | 0.28 |
| Q | 0.020 DIA | | 0.51 DIA | |
| R | 0.025 | 0.035 | 0.64 | 0.89 |
| U | 0.025 | 0.035 | 0.64 | 0.89 |
| V | 0° | 8° | 0° | 8° |

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331