# PDTA143Z series

## PNP resistor-equipped transistors; R1 = 4.7 kΩ, R2 = 47 kΩ

Rev. 7 — 5 December 2011 Product data sheet

## 1. Product profile

### 1.1 General description

PNP Resistor-Equipped Transistor (RET) family in Surface-Mounted Device (SMD) plastic packages.

**Table 1. Product overview**

| Type number | Package | | | NPN complement | Package configuration |
|---|---|---|---|---|---|
| | Nexperia | JEITA | JEDEC | | |
| PDTA143ZE | SOT416 | SC-75 | - | PDTC143ZE | ultra small |
| PDTA143ZM | SOT883 | SC-101 | - | PDTC143ZM | leadless ultra small |
| PDTA143ZT | SOT23 | - | TO-236AB | PDTC143ZT | small |
| PDTA143ZU | SOT323 | SC-70 | - | PDTC143ZU | very small |

### 1.2 Features and benefits

- 100 mA output current capability
- Built-in bias resistors
- Simplifies circuit design
- Reduces component count
- Reduces pick and place costs
- AEC-Q101 qualified

### 1.3 Applications

- Digital applications in automotive and industrial segments
- Control of IC inputs
- Cost-saving alternative for BC847/857 series in digital applications
- Switching loads

### 1.4 Quick reference data

**Table 2. Quick reference data**

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $V_{CEO}$ | collector-emitter voltage | open base | - | - | –50 | V |
| $I_O$ | output current | | - | - | –100 | mA |
| R1 | bias resistor 1 (input) | | 3.3 | 4.7 | 6.1 | kΩ |
| R2/R1 | bias resistor ratio | | 8 | 10 | 12 | |

## 2. Pinning information

**Table 3. Pinning**

| Pin | Description | Simplified outline | Graphic symbol |
|---|---|---|---|
| **SOT23; SOT323; SOT416** | | | |
| 1 | input (base) |   006aaa144 |   sym003 |
| 2 | GND (emitter) | | |
| 3 | output (collector) | | |
| **SOT883** | | | |
| 1 | input (base) |   Transparent top view |   sym003 |
| 2 | GND (emitter) | | |
| 3 | output (collector) | | |

## 3. Ordering information

**Table 4. Ordering information**

| Type number | Package | | |
|---|---|---|---|
| | Name | Description | Version |
| PDTA143ZE | SC-75 | plastic surface-mounted package; 3 leads | SOT416 |
| PDTA143ZM | SC-101 | leadless ultra small plastic package; 3 solder lands; body 1.0 × 0.6 × 0.5 mm | SOT883 |
| PDTA143ZT | - | plastic surface-mounted package; 3 leads | SOT23 |
| PDTA143ZU | SC-70 | plastic surface-mounted package; 3 leads | SOT323 |

## 4. Marking

**Table 5. Marking codes**

| Type number | Marking code[1] |
|---|---|
| PDTA143ZE | 37 |
| PDTA143ZM | DP |
| PDTA143ZT | *19 |
| PDTA143ZU | *47 |

[1] * = placeholder for manufacturing site code


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 5. Limiting values

**Table 6. Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134).*

| Symbol | Parameter | Conditions | | Min | Max | Unit |
|---|---|---|---|---|---|---|
| $V_{CBO}$ | collector-base voltage | open emitter | | - | –50 | V |
| $V_{CEO}$ | collector-emitter voltage | open base | | - | –50 | V |
| $V_{EBO}$ | emitter-base voltage | open collector | | - | –5 | V |
| $V_I$ | input voltage | | | | | |
| | positive | | | - | +5 | V |
| | negative | | | - | –30 | V |
| $I_O$ | output current | | | - | –100 | mA |
| $I_{CM}$ | peak collector current | single pulse; $t_p \leq 1$ ms | | - | –100 | mA |
| $P_{tot}$ | total power dissipation | $T_{amb} \leq 25$ °C | | | | |
| | PDTA143ZE (SOT416) | | [1][2] | - | 150 | mW |
| | PDTA143ZM (SOT883) | | [2][3] | - | 250 | mW |
| | PDTA143ZT (SOT23) | | [1] | - | 250 | mW |
| | PDTA143ZU (SOT323) | | [1] | - | 200 | mW |
| $T_j$ | junction temperature | | | - | 150 | °C |
| $T_{amb}$ | ambient temperature | | | –65 | +150 | °C |
| $T_{stg}$ | storage temperature | | | –65 | +150 | °C |

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

[2] Reflow soldering is the only recommended soldering method.

[3] Device mounted on an FR4 PCB with 70 μm copper strip line, standard footprint.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




(1) SOT23; FR4 PCB, standard footprint
SOT883; FR4 PCB with 70 μm copper strip line, standard footprint

(2) SOT323; FR4 PCB, standard footprint

(3) SOT416; FR4 PCB, standard footprint

**Fig 1. Power derating curves**

## 6. Thermal characteristics

**Table 7. Thermal characteristics**

| Symbol | Parameter | Conditions | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|---|
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | in free air | | | | | |
| | PDTA143ZE (SOT416) | | [1][2] | - | - | 830 | K/W |
| | PDTA143ZM (SOT883) | | [2][3] | - | - | 500 | K/W |
| | PDTA143ZT (SOT23) | | [1] | - | - | 500 | K/W |
| | PDTA143ZU (SOT323) | | [1] | - | - | 625 | K/W |

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Reflow soldering is the only recommended soldering method.

[3] Device mounted on an FR4 PCB with 70 μm copper strip line, standard footprint.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




FR4 PCB, standard footprint

**Fig 2. Transient thermal impedance from junction to ambient as a function of pulse duration for PDTA143ZE (SOT416); typical values**




FR4 PCB, 70 μm copper strip line

**Fig 3. Transient thermal impedance from junction to ambient as a function of pulse duration for PDTA143ZM (SOT883); typical values**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




FR4 PCB, standard footprint

**Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration for PDTA143ZT (SOT23); typical values**




FR4 PCB, standard footprint

**Fig 5. Transient thermal impedance from junction to ambient as a function of pulse duration for PDTA143ZU (SOT323); typical values**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 7. Characteristics

**Table 8. Characteristics**

*$T_{amb}$ = 25 °C unless otherwise specified.*

| Symbol | Parameter | Conditions | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|---|
| $I_{CBO}$ | collector-base cut-off current | $V_{CB}$ = –50 V; $I_E$ = 0 A | | - | - | –100 | nA |
| $I_{CEO}$ | collector-emitter cut-off current | $V_{CE}$ = –30 V; $I_B$ = 0 A | | - | - | –1 | μA |
| | | $V_{CE}$ = –30 V; $I_B$ = 0 A; $T_j$ = 150 °C | | - | - | –5 | μA |
| $I_{EBO}$ | emitter-base cut-off current | $V_{EB}$ = –5 V; $I_C$ = 0 A | | - | - | –170 | μA |
| $h_{FE}$ | DC current gain | $V_{CE}$ = –5 V; $I_C$ = –10 mA | | 100 | - | - | |
| $V_{CEsat}$ | collector-emitter saturation voltage | $I_C$ = –5 mA; $I_B$ = –0.25 mA | | - | - | –100 | mV |
| $V_{I(off)}$ | off-state input voltage | $V_{CE}$ = –5 V; $I_C$ = –100 μA | | - | –0.6 | –0.5 | V |
| $V_{I(on)}$ | on-state input voltage | $V_{CE}$ = –0.3 V; $I_C$ = –5 mA | | –1.3 | –0.9 | - | V |
| R1 | bias resistor 1 (input) | | | 3.3 | 4.7 | 6.1 | kΩ |
| R2/R1 | bias resistor ratio | | | 8 | 10 | 12 | |
| $C_c$ | collector capacitance | $V_{CB}$ = –10 V; $I_E$ = $i_e$ = 0 A; f = 1 MHz | | - | - | 3 | pF |
| $f_T$ | transition frequency | $V_{CE}$ = –5 V; $I_C$ = –10 mA; f = 100 MHz | [1] | - | 180 | - | MHz |

[1] Characteristics of built-in transistor


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




$V_{CE}$ = −5 V

(1) $T_{amb}$ = 100 °C

(2) $T_{amb}$ = 25 °C

(3) $T_{amb}$ = −40 °C

**Fig 6. DC current gain as a function of collector current; typical values**




$I_C/I_B$ = 20

(1) $T_{amb}$ = 100 °C

(2) $T_{amb}$ = 25 °C

(3) $T_{amb}$ = −40 °C

**Fig 7. Collector-emitter saturation voltage as a function of collector current; typical values**




$V_{CE}$ = −0.3 V

(1) $T_{amb}$ = −40 °C

(2) $T_{amb}$ = 25 °C

(3) $T_{amb}$ = 100 °C

**Fig 8. On-state input voltage as a function of collector current; typical values**




$V_{CE}$ = −5 V

(1) $T_{amb}$ = −40 °C

(2) $T_{amb}$ = 25 °C

(3) $T_{amb}$ = 100 °C

**Fig 9. Off-state input voltage as a function of collector current; typical values**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




f = 1 MHz; $T_{amb}$ = 25 °C

**Fig 10. Collector capacitance as a function of collector-base voltage; typical values**




$V_{CE}$ = −5 V; $T_{amb}$ = 25 °C

**Fig 11. Transition frequency as a function of collector current; typical values of built-in transistor**

# 8. Test information

## 8.1 Quality information

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard *Q101 - Stress test qualification for discrete semiconductors*, and is suitable for use in automotive applications.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 9. Package outline




Fig 12. Package outline PDTA143ZE (SOT416/SC-75)




Fig 13. Package outline PDTA143ZM (SOT883/SC-101)




Fig 14. Package outline PDTA143ZT (SOT23)




Fig 15. Package outline PDTA143ZU (SOT323/SC-70)

## 10. Packing information

**Table 9. Packing methods**

*The indicated -xxx are the last three digits of the 12NC ordering code.*[1]

| Type number | Package | Description | Packing quantity | | |
|---|---|---|---|---|---|
| | | | 3000 | 5000 | 10000 |
| PDTA143ZE | SOT416 | 4 mm pitch, 8 mm tape and reel | -115 | - | -135 |
| PDTA143ZM | SOT883 | 2 mm pitch, 8 mm tape and reel | - | - | -315 |
| PDTA143ZT | SOT23 | 4 mm pitch, 8 mm tape and reel | -215 | - | -235 |
| PDTA143ZU | SOT323 | 4 mm pitch, 8 mm tape and reel | -115 | - | -135 |

[1] For further information and the availability of packing methods, see Section 14.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 11. Soldering




Reflow soldering is the only recommended soldering method.

**Fig 16. Reflow soldering footprint PDTA143ZE (SOT416/SC-75)**




Reflow soldering is the only recommended soldering method.

**Fig 17. Reflow soldering footprint PDTA143ZM (SOT883/SC-101)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




**Fig 18. Reflow soldering footprint PDTA143ZT (SOT23)**




**Fig 19. Wave soldering footprint PDTA143ZT (SOT23)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved




**Fig 20. Reflow soldering footprint PDTA143ZU (SOT323/SC-70)**




**Fig 21. Wave soldering footprint PDTA143ZU (SOT323/SC-70)**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 12. Revision history

**Table 10. Revision history**

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|---|---|---|---|---|
| PDTA143Z_SER v.7 | 20111205 | Product data sheet | - | PDTA143Z_SERIES v.6 |
| Modifications: | • The format of this document has been redesigned to comply with the new identity guidelines of NXP Semiconductors.<br>• Legal texts have been adapted to the new company name where appropriate.<br>• Type numbers PDTA143ZEF, PDTA143ZK and PDTA143ZS removed.<br>• Section 1 “Product profile”: updated<br>• Section 3 “Ordering information”: added<br>• Section 4 “Marking”: updated<br>• Figure 1 to 11: added<br>• Section 6 “Thermal characteristics”: updated<br>• Table 8 “Characteristics”: $V_{i(on)}$ redefined to $V_{I(on)}$ on-state input voltage, $V_{i(off)}$ redefined to $V_{I(off)}$ off-state input voltage, $I_{CEO}$ updated, $f_T$ added<br>• Section 8 “Test information”: added<br>• Section 9 “Package outline”: superseded by minimized package outline drawings<br>• Section 10 “Packing information”: added<br>• Section 11 “Soldering”: added<br>• Section 13 “Legal information”: updated | | | |
| PDTA143Z_SERIES v.6 | 20040805 | Product data sheet | - | PDTA143Z_SERIES v.5 |
| PDTA143Z_SERIES v.5 | 20030908 | Product specification | - | PDTA143Z_SERIES v.4 |
| PDTA143Z_SERIES v.4 | 20030410 | Product specification | - | - |


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

# 13. Legal information

## 13.1 Data sheet status

| Document status[1][2] | Product status[3] | Definition |
|---|---|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

## 13.2 Definitions

**Draft —** The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet —** A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification —** The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

## 13.3 Disclaimers

**Limited warranty and liability —** Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes —** Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use —** Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications —** Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values —** Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale —** Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license —** Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

**Export control —** This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Quick reference data —** The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

### 13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 14. Contact information

For more information, please visit: **http://www.nexperia.com**

For sales office addresses, please send an email to: **salesaddresses@nexperia.com**


All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2017. All rights reserved

## 15. Contents


**1 Product profile . . . . . 1**
1.1 General description . . . . . 1
1.2 Features and benefits . . . . . 1
1.3 Applications . . . . . 1
1.4 Quick reference data . . . . . 1
**2 Pinning information . . . . . 2**
**3 Ordering information . . . . . 2**
**4 Marking . . . . . 2**
**5 Limiting values . . . . . 3**
**6 Thermal characteristics . . . . . 4**
**7 Characteristics . . . . . 7**
**8 Test information . . . . . 9**
8.1 Quality information . . . . . 9
**9 Package outline . . . . . 10**
**10 Packing information . . . . . 10**
**11 Soldering . . . . . 11**
**12 Revision history . . . . . 14**
**13 Legal information . . . . . 15**
13.1 Data sheet status . . . . . 15
13.2 Definitions . . . . . 15
13.3 Disclaimers . . . . . 15
13.4 Trademarks . . . . . 16
**14 Contact information . . . . . 16**
**15 Contents . . . . . 17**


© **Nexperia B.V. 2017. All rights reserved**

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
**Date of release: 05 December 2011**

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331