
PowerStor®

Supercapacitors

B Series - High Capacitance

Description

Cooper Bussmann PowerStor® supercapacitors are unique, ultra-high capacitance devices utilizing electrochemical double layer capacitor (EDLC) construction combined with new, high performance materials. This combination of advanced technologies allows Cooper Bussmann to offer a wide variety of capacitor solutions tailored to specific applications that range from a few micro-amps for several days to several amps for milliseconds.



Cylindrical Device

Features & Benefits

- High specific capacitance
- Very low ESR
- Low leakage currents
- Long cycle life

Applications

- Main power
- Hybrid battery packs
- Hold-up power
- Pulse power

Specifications	
Working Voltage	2.5V
Surge Voltage	3.0V
Capacitance	3.3F to 100F
Capacitance Tolerance	-20% to +80% (20°C)
Operating Temperature Range	3.3-22F = -25°C to 70°C, 33-100F = -25°C to 60°C

Standard Product

Nominal Capacitance (F)	Part Number	Nominal ESR (Ω) (Equivalent Series Resistance) Measured @ 1kHz	Nominal Dimensions (mm)		Typical Mass (grams/piece)
			Diameter	Length	
3.3	B1020-2R5335-R	0.150	10	20.5	2.8
4.7	B0830-2R5475-R	0.150	8	30	2.6
6.8	B1030-2R5685-R	0.100	10	30	3.9
10	B1325-2R5106-R	0.060	13	26	5.6
22	B1635-2R5226-R	0.040	16	35	11.0
33	B1835-2R5336-R	0.030	18	35	13.5
50	B1840-2R5506-R	0.025	18	40	14.7
100	B1860-2R5107-R	0.020	18	60	22.0


Not For New Designs
See HB Series Data Sheet # 4375

Performance

Parameter	Capacitance Change (% of initial measured value)	ESR (% of initial specified value)
Life (3.3F - 22F = 1000 hrs @ 70°C @ 2.5Vdc) (33F - 100F = 1000 hrs @ 60°C @ 2.5Vdc)	≤ 30 %	≤ 300 %
Storage Low and High Temperature (3.3F - 22F = 1000 hrs @ -25°C and 70°C) (33F - 100F = 1000 hrs @ -25°C and 60°C)	≤ 30 %	≤ 300 %

Dimensions (mm)								
Part Number	D	D'	L	L'	F	d'	C	C'
B1020-2R5335-R	10.0	10.5	21.8	22.3	5.0	0.60	20.0	5.0
B0830-2R5475-R	8.0	8.5	30.5	31.0	3.5	0.50	20.0	5.0
B1030-2R5685-R	10.0	10.5	31.0	31.5	5.0	0.60	20.0	5.0
B1325-2R5106-R	13.0	13.5	27.9	28.4	5.0	0.60	20.0	5.0
B1635-2R5226-R	16.0	16.5	37.5	38.0	7.5	0.80	20.0	5.0
B1835-2R5336-R	18.0	18.5	37.5	38.0	7.5	0.80	20.0	5.0
B1840-2R5506-R	18.0	18.5	41.5	42.0	7.5	0.80	20.0	5.0
B1860-2R5107-R	18.0	18.5	59.5	60.5	7.5	0.80	20.0	5.0
Tolerances	Maximum				± 0.5	± 0.02	Minimum	

Note: Longer lead is positive.



Part Numbering System											
B	□	□	□	□	–	2	R	5	□	□	□
Series Code	Dimensions (mm)				Voltage (V) R is Decimal				Capacitance (µF) Value		Multiplier
B Series	Diameter		Length		2R5 = 2.5V				Example: 475 = 47 x 10^5µF or 4.7F		

Not For New Designs
See HB Series Data Sheet # 4375

Packaging Information

Packaging:
- Standard packaging: Bulk, 100 units per bag.
- Larger bulk packages available on request.

Part Marking

Manufacturer
Capacitance (F)
Max Operating Voltage (V)
Series Code (or part number)
Polarity

North America
Cooper Bussmann
1225 Broken Sound Parkway NW
Suite F
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-636-527-1607

Europe
Cooper Bussmann
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Cooper Bussmann
Avda. Santa Eulalia, 290
08223
Terrassa, (Barcelona), Spain
Tel: +34 937 362 812
+34 937 362 813
Fax: +34 937 362 719

Asia Pacific
Cooper Bussmann
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

© 2010 Cooper Bussmann
www.cooperbussmann.com

COILTRONICS® COOPER Bussmann® PowerStor®

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331