

Vectron International**Filter specification****TFS 433AH****1/5****Measurement condition**

Ambient temperature T_A :	23	°C
Input power level:	0	dBm
Terminating impedance:		
Input:	190 Ω	-3.4 pF
Output:	190 Ω	-3.4 pF

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 433AH is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_C is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 433.92 MHz without any tolerance. The given values for the relative attenuation a_{rel} have to be achieved at the frequencies given below even if the centre frequency f_C is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_C .

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)		a_e	2.6 dB	max.	3.5	dB
Nominal frequency		f_N	-		433.92	MHz
Centre frequency		f_C	433.92 MHz		-	
Bandwidth		BW				
2	dB		700 kHz	min.	400	kHz
3	dB		800 kHz	min.	440	kHz
6	dB		955 kHz	min.	560	kHz
Relative attenuation		a_{rel}				
f_N	... $f_N \pm 200.00$ kHz	-	dB	max.	2.0	dB
$f_N \pm 200.00$ kHz	... $f_N \pm 220.00$ kHz	-	dB	max.	3.0	dB
$f_N \pm 220.00$ kHz	... $f_N \pm 280.00$ kHz	-	dB	max.	6.0	dB
$f_N - 1.0$ MHz	... $f_N - 5.92$ MHz	17	dB	min.	15	dB
$f_N - 5.92$ MHz	... $f_N - 19.92$ MHz	42	dB	min.	40	dB
$f_N - 19.92$ MHz	... $f_N - 423.92$ MHz	55	dB	min.	45	dB
$f_N + 1.00$ MHz	... $f_N + 8.00$ MHz	14	dB	min.	10	dB
$f_N + 116.08$ MHz	... $f_N + 566.00$ MHz	60	dB	min.	45	dB
Input power level		-		max.	0	dBm
Operating temperature range		OTR	-		-25 ... +80	°C
Storage temperature range		-			-55 ... +125	°C
Frequency inversion temperature		10	°C		-	
Temperature coefficient of frequency		TC_f *)	-0.04 ppm/K ²		-	



*) $\Delta f = TC_f(T - T_0)^2 f_N$

Generated:**Checked / Approved:**

Vectron International GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@vectron.com


Vectron International GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Filter characteristic



Construction and pin connection

(All dimensions in mm)



1	Ground
2	Input
3	Ground
4	Ground
5	Output
6	Ground
7	Ground
8	Ground

Date code: Year + week


J 2017

K 2018

L 2019

...

50 Ω Test circuit



Vectron International GmbH
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@vectron.com

Vectron International GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:

1. Shock: 500 g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 60068 T2 - 27
2. Vibration: 10 Hz to 2000 Hz, 0.35 mm or 5 g respectively, 1 octave per min, 10 cycles per plane, 3 planes; DIN IEC 60068 T2 - 6
3. Change of temperature: -55 °C to 125 °C / 15 min. each / 100 cycles
DIN IEC 60068 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;
5. SAW devices are Electrostatic Discharge (ESD) sensitive devices.

This filter is RoHS compliant (2011/65/EU)

Packing

Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


reel of empty components at start: min. 300 mm
reel of empty components at start including leader: min. 500 mm
trailer: min. 300 mm

Tape (all dimensions in mm)

W	: 12.00 ±0.3
Po	: 4.00 ±0.1
Do	: 1.50 +0.1/-0
E	: 1.75 ±0.1
F	: 5.50 ±0.05
G(min)	: 0.75
P2	: 2.00 ±0.05
P1	: 8.00 ±0.1
D1(min)	: 1.50
Ao	: 4.30 ±0.1
Bo	: 4.30 ±0.1
Ct	: 9.2 ±0.1
Ko	: 1.80 ±0.1
t	: 0.30 ±0.05

Reel (all dimensions in mm)

A	: 330 or 180
W1	: 12.4 +2/-0
W2(max)	: 18.40
N(min)	: 50.00
C	: 13.0 +0.5/-0.2




The minimum bending radius is 45 mm.

Vectron International GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@vectron.com

Vectron International GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30 °C to 217 °C)	less than 3 °C / second
> 100 °C	between 300 and 600 seconds
> 150 °C	between 240 and 500 seconds
> 217 °C	between 30 and 150 seconds
Peak temperature	max. 260 °C
Time within 5 °C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50 °C)	less than 6 °C / second
Time from 30 °C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile

Vectron International**Filter specification****TFS 433AH****5/5****History**

Version	Reason of Changes	Name	Date
1.0	Generation of filter specification.	Abutaimah	08.03.2017
1.1	update typos update storage temperature range update tape & reel	Schönbein	26.07.2017



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331