



## Metal Film Resistors, Industrial Power, Precision, Flameproof



## FEATURES

- High power rating, small size
- Flameproof, high temperature coating
- Special filming and coating processes
- Excellent high frequency characteristics
- Low noise
- Low voltage coefficient
- Material categorization:

For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



RoHS\*  
COMPLIANT

## Note

\* Lead (Pb)-containing terminations are not RoHS-compliant. Exemptions may apply.

## STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL | HISTORICAL MODEL | POWER RATING<br>$P_{70^{\circ}\text{C}}$<br>W | MAXIMUM WORKING VOLTAGE <sup>(1)</sup><br>V | RESISTANCE RANGE $\Omega$             |                                       |                                        |                                        |                                        |                                        |
|--------------|------------------|-----------------------------------------------|---------------------------------------------|---------------------------------------|---------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------|
|              |                  |                                               |                                             | 0.1 % to 1 %                          | 0.1 % to 5 %                          | 0.5 % to 5 %                           | 1 % to 5 %                             | 1 %                                    | 2 % to 5 %                             |
|              |                  |                                               |                                             | $\pm 25 \text{ ppm}/^{\circ}\text{C}$ | $\pm 50 \text{ ppm}/^{\circ}\text{C}$ | $\pm 100 \text{ ppm}/^{\circ}\text{C}$ | $\pm 150 \text{ ppm}/^{\circ}\text{C}$ | $\pm 200 \text{ ppm}/^{\circ}\text{C}$ | $\pm 200 \text{ ppm}/^{\circ}\text{C}$ |
| CPF1         | CPF-1            | 1                                             | 250                                         | 5 to 150K                             | 5 to 150K                             | 1 to 150K                              | 0.5 to 150K                            | 0.5 to 150K                            | 0.1 to 150K                            |
| CPF2         | CPF-2            | 2                                             | 350                                         | 5 to 150K                             | 5 to 150K                             | 1 to 150K                              | 0.5 to 150K                            | 0.5 to 150K                            | 0.1 to 150K                            |
| CPF3         | CPF-3            | 3                                             | 500                                         | 8 to 150K                             | 8 to 150K                             | 1 to 150K                              | 1 to 150K                              | 1 to 150K                              | 0.1 to 150K                            |

## Note

<sup>(1)</sup> Continuous working voltage shall be  $\sqrt{P \times R}$  or maximum working voltage, whichever is less.

## TEMPERATURE COEFFICIENT CODES

| GLOBAL TC CODE | HISTORICAL TC CODE | TEMPERATURE COEFFICIENT     |
|----------------|--------------------|-----------------------------|
| E              | T-9                | 25 ppm/ $^{\circ}\text{C}$  |
| H              | T-2                | 50 ppm/ $^{\circ}\text{C}$  |
| K              | T-1                | 100 ppm/ $^{\circ}\text{C}$ |
| L              | T-0                | 150 ppm/ $^{\circ}\text{C}$ |
| N              | T-00               | 200 ppm/ $^{\circ}\text{C}$ |

## TECHNICAL SPECIFICATIONS

| PARAMETER                                  | UNIT               | CPF1                                          | CPF2 | CPF3 |
|--------------------------------------------|--------------------|-----------------------------------------------|------|------|
| Rated Dissipation at 70 $^{\circ}\text{C}$ | W                  | 1                                             | 2    | 3    |
| Limiting Element Voltage <sup>(2)</sup>    | V $\cong$          | 250                                           | 350  | 500  |
| Insulation Voltage                         | V <sub>eff</sub>   | 900                                           | 900  | 900  |
| Thermal Resistance                         | K/W                | 85                                            | 60   | 50   |
| Insulation Resistance                      | $\Omega$           | 10 <sup>10</sup>                              |      |      |
| Category Temperature Range                 | $^{\circ}\text{C}$ | - 65 $^{\circ}\text{C}/+ 230^{\circ}\text{C}$ |      |      |

## Note

<sup>(2)</sup> Rated voltage  $\sqrt{P \times R}$

## GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: CPF1562R00FKR36 (preferred part numbering format)

|                      |   |   |                                                                                                            |   |   |                                                                                                           |   |   |                                                                       |   |   |                                                                                                                                                                                                     |   |   |                                                                             |  |  |
|----------------------|---|---|------------------------------------------------------------------------------------------------------------|---|---|-----------------------------------------------------------------------------------------------------------|---|---|-----------------------------------------------------------------------|---|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|-----------------------------------------------------------------------------|--|--|
| C                    | P | F | 1                                                                                                          | 5 | 6 | 2                                                                                                         | R | 0 | 0                                                                     | F | K | R                                                                                                                                                                                                   | 3 | 6 |                                                                             |  |  |
| GLOBAL MODEL         |   |   | RESISTANCE VALUE                                                                                           |   |   | TOLERANCE CODE                                                                                            |   |   | TEMPERATURE COEFFICIENT                                               |   |   | PACKAGING                                                                                                                                                                                           |   |   | SPECIAL                                                                     |  |  |
| CPF1<br>CPF2<br>CPF3 |   |   | R = $\Omega$<br>K = k $\Omega$<br>R10000 = 0.1 $\Omega$<br>10R000 = 10 $\Omega$<br>150K00 = 150 k $\Omega$ |   |   | B = $\pm 0.1\%$<br>C = $\pm 0.25\%$<br>D = $\pm 0.5\%$<br>F = $\pm 1\%$<br>G = $\pm 2\%$<br>J = $\pm 5\%$ |   |   | E = 25 ppm<br>H = 50 ppm<br>K = 100 ppm<br>L = 150 ppm<br>N = 200 ppm |   |   | E14 = Lead (Pb)-free, bulk<br>E36 = Lead(Pb)-free, T/R (full)<br>EE6 = Lead (Pb)-free, T/R (1000 pieces)<br>B14 = Tin/lead, bulk<br>R36 = Tin/lead, T/R (full)<br>RE6 = Tin/lead, T/R (1000 pieces) |   |   | Blank = Standard (Dash Number) (Up to 3 digits) From 1 to 999 as applicable |  |  |


Historical Part Number example: CPF-15620FT-1 R36 (will continue to be accepted)

|                  |                  |                |                   |           |
|------------------|------------------|----------------|-------------------|-----------|
| CPF-1            | 5620             | F              | T-1               | R36       |
| HISTORICAL MODEL | RESISTANCE VALUE | TOLERANCE CODE | TEMP. COEFFICIENT | PACKAGING |

## Note

- For additional information on packaging, refer to the Through-Hole Resistor Packaging document ([www.vishay.com/doc?31544](http://www.vishay.com/doc?31544)).

## DIMENSIONS



### Notes

- (1) Lead length for product in bulk pack. For product supplied in tape and reel, the actual lead length would be based on the body size, tape spacing and lead trim.
- Surface temperatures were taken with an infrared pyrometer in + 25 °C still air. Resistors were supported by their leads in test clips at a point 0.500" (12.70 mm) out from the resistor body ends.



## THERMAL RESISTANCE

| MATERIAL SPECIFICATIONS |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Element                 | Proprietary nickel-chrome alloy                                                                |
| Core                    | Cleaned high purity ceramic                                                                    |
| Coating                 | Special high temperature conformal coat                                                        |
| Termination             | Standard lead material is solder-coated<br>Solderable and weldable per<br>MIL-STD-1276, Type C |

| GLOBAL MODEL | DIMENSIONS in inches (millimeters) |                                 |                     |                                |
|--------------|------------------------------------|---------------------------------|---------------------|--------------------------------|
|              | L                                  | D                               | L <sub>1</sub> max. | d                              |
| CPF1         | 0.240 ± 0.020<br>(6.10 ± 0.51)     | 0.090 ± 0.008<br>(2.29 ± 0.20)  | 0.310<br>(7.87)     | 0.025 ± 0.002<br>(0.64 ± 0.05) |
| CPF2         | 0.344 ± 0.031<br>(8.74 ± 0.79)     | 0.145 ± 0.015<br>(3.68 ± 0.38)  | 0.425<br>(10.80)    | 0.032 ± 0.002<br>(0.81 ± 0.05) |
| CPF3         | 0.555 ± 0.041<br>(14.10 ± 1.04)    | 0.180 ± 0.015<br>(4.57 ± 0.381) | 0.650<br>(16.51)    | 0.032 ± 0.002<br>(0.81 ± 0.05) |



## DERATING

| MECHANICAL SPECIFICATIONS |                                                                                               |
|---------------------------|-----------------------------------------------------------------------------------------------|
| Terminal strength         | 2 pound pull test                                                                             |
| Solderability             | Continuous satisfactory coverage<br>when tested in accordance with<br>MIL-STD-202, Method 208 |

## MARKING

Temperature Coefficient: T00 = 200 ppm, T0 = 150 ppm, T1 = 100 ppm, T2 = 50 ppm, T9 = 25 ppm

CPF1, CPF2, CPF3: (5 lines)

|         |                     |
|---------|---------------------|
| DALE    | Manufacturer's name |
| CPF-1   | Style and size      |
| 49.9 kΩ | Value               |
| 1 % T2  | Tolerance and TC    |
| 1208    | 4-digit date code   |

## PERFORMANCE

| TEST                            | MAX. ΔR (TYPICAL TEST LOTS) |
|---------------------------------|-----------------------------|
| Thermal Shock                   | ± 1.0 %                     |
| Short Time Overload             | ± 0.5 %                     |
| Low Temperature Operation       | ± 0.5 %                     |
| Moisture Resistance             | ± 1.5 %                     |
| Resistance To Soldering Heat    | ± 0.5 %                     |
| Shock                           | ± 0.5 %                     |
| Vibration                       | ± 0.5 %                     |
| Terminal Strength               | ± 0.5 %                     |
| Dielectric Withstanding Voltage | ± 0.5 %                     |
| Life                            | ± 2.0 %                     |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331