

JD

Screw Terminal Type, High Energy Density Type

series

Upgrade


- High energy density.
- Suitable for electric power storage.
- Compliant to the RoHS directive (2002/95/EC).



■ Specifications

Item	Performance Characteristics		
Category Temperature Range	− 25 to + 60°C		
Rated Voltage Range	2.5V		
Rated Capacitance Range	600 to 6000F See Note		
Capacitance Tolerance	±20% (20°C)		
Leakage Current	0.5C (mA) [C : Rated Capacitance (F)] (After 30 minutes' application of rated voltage. 2.5V)		
Stability at Temperature	Capacitance (− 25°C) /Capacitance (+20°C) ×100 ≧ 70% DCR(−25°C) / DCR (+20°C) ≦ 7		
DCR*	Refer to the list below. (20°C) *DC internal resistance		
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 60°C.	Capacitance change	Within ±30% of the initial capacitance value
		DCR	300% or less than the initial value
		Leakage current	Less than or equal to the initial specified value
Shelf Life	The specifications listed at right shall be met when the capacitors are restored to 20°C after storing the capacitors under no load for 2000 hours at 60°C.	Capacitance change	Within ±30% of the initial capacitance value
		DCR	300% or less than the initial value
		Leakage current	Less than or equal to the initial specified value
Marking	Printed with white color letter on black sleeve.		

■ Drawing



Type numbering system (Example : 2.5V 600F)

1	2	3	4	5	6	7	8	9	10	11	12	13	14
J	J	D	0	E	6	0	7	M	S	E	C		

Case dia. code (φ35) (φ35, φ40)

Configuration ※

φD	Code
35	C
40	D
51	F
63.5	G
76.2	H

Code less 2-leg brackets

Code	2-leg brackets
BN	No brackets

Code less 3-leg brackets

Code	3-leg brackets
BB	2-leg brackets
BN	No bracket

※ Configuration

Cr (III) Plating (RoHS compliant)
SE

■ Dimensions

Rated Voltage (Code)	Cap. (F)	Cap. code	DCR ※ Typical (mΩ)	Case size		Ref. Weight (g)
				φ (mm)	L (mm)	
2.5V (0E)	600	607	13.5	35	85	130
	800	807	10.0		105	160
	950	957	8.5		135	210
	1000	108	8.0	40	105	210
	1300	138	6.0		135	250
	2300	238	4.0	51	135	450
	2500	258	3.5		150	500
	4000	408	2.2	63.5	150	800
	6000	608	2.2	76.2	165	1300

※ The listed DCR value is typical and therefore not a guaranteed value.

● Dimensions of terminal pitch (W) and length (ℓ) and Normal dia. of bolt (mm)

φ D	W	ℓ	α	Nominal of bolt
35	12.7	6	3	M5
40	18.8	9	3	M6
51	26.0	10	3	M6
63.5	28.6	10	3	M6
76.2	31.8	6	3	M6

● Dimensions of mounting bracket (mm)

Symbol	3-Legs				2-Legs			
	51	63.5	76.2	35	40	51	63.5	76.2
P	32.5	38.1	44.5	24	27	33.2	40.5	46.5
A	38.5	43	49.2	29	32	40	46.5	53
B	—	—	—	45	48	—	—	—
T	7.5	8.0	7.0	7.0	7.0	6.0	7.0	6.0
S	5.0	5.0	5.0	3.5	3.5	4.5	4.5	4.5
U	12	14	14	10	10	14	14	14
θ°	60	60	60	30	45	30	30	30
H	20	25	30	15	17	25	35	35
h	15	20	24	10	12	15	20	20

Note :

The capacitance calculated from discharge time (ΔT) with constant current (i) after 30minute charge with rated voltage (2.5V).
 The discharge current (i) is 0.01 × rated capacitance (F).
 The discharge time (ΔT) measured between 2V and 1V with constant current.

The capacitance calculated below.

$$\text{Capacitance (F)} = i \times \Delta T$$

CAT.8100A



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331