

120-960W, 24V Output DIN Rail Mount Power Supplies

Features

- ◆ Very Compact Size
- ◆ High Efficiency (Up to 95%)
- ◆ 150% Peak Power Capability for 4s
- ◆ ErP Compliant Design
- ◆ Low Standby Power Draw
- ◆ Remote On/Off
- ◆ Remote Voltage Adjustment
- ◆ Hazardous Location Option (/HL)



Key Market Segments & Applications



Specifications					
Model		DRF120	DRF240	DRF480	DRF960
Input Voltage Range ⁽¹⁾	V	85 - 264VAC, 125 - 370VDC*			180 - 264VAC
Input Frequency	Hz	47 - 63Hz			
Inrush Current (typ) (Cold Start)	A	20			
Power Factor (115/230VAC) (Meets EN61000-3-2)	-	0.98 / 0.95	0.98 / 0.95	0.98 / 0.92	- / 0.98
Input Current (115/230VAC)	A	1.2 / 0.6	2.4 / 1.2	4.7 / 2.5	- / 4.5
Line Regulation	mV	<96mV			
Load Regulation	mV	<240mV			
Ripple & Noise ⁽²⁾	mV	<240mV			
Overcurrent Protection	-	>101% of peak current rating. Shutdown after 4 seconds			
Overvoltage Protection	-	30 - 35.5V, (31.5 - 34V for DRF960). Cycle input voltage or remote on/off to reset			
Hold Up Time (230VAC input)	ms	> 20ms			>10ms
Efficiency (115 / 230VAC)	%	89 / 91	92.5 / 94	92.5 / 94	- / 95
Standby Power Draw	W	<0.5W	<0.5W	<0.75W	<1W
LED Indicators	-	Green LED = DC is OK (>80% Nom). Red LED = Peak Load Operation			
DC OK relay	-	Relay contact 30V/1A			
Remote On / Off	-	When signal is low, the output is On			
Remote Voltage Adjust	-	5 - 6V voltage programs output from 24 - 28V			
Operating Temperature	°C	-25 to +70°C. Start up at -40°C. Derate linearly to 75% load above 60°C (50°C for DRF960)			
Storage Temperature	°C	-40 to +85°C			
Operating Humidity (non condensing)	%RH	5 - 95%RH			
Parallel Operation	-	Droop Mode - Refer to Installation Manual			
Series Operation	-	Possible			
Cooling	-	Convection			
Withstand Voltage (For 1 minute)	VAC	Input to Output 3kVAC, Input to GND 1.5kVAC, Output to GND 500VDC (960W : 500VAC)			
Isolation Resistance	MΩ	>100MΩ at 25°C, 70%RH & 500VDC			
Vibration (Non operating)	-	10-55Hz (sweep for 1 min); 19.6m/s ² (2G) Constant; X,Y,Z each 1 hour			
Shock	-	<196m/s ²			
Safety Agency Certifications ⁽³⁾	-	UL508 Listed, IEC/UL/EN60950-1†, CE Mark ATEX, IEC Ex, & GL. Class 1 Div 2, Group A, B, C, D (DRF120-480 only)			
Conducted & Radiated EMI	-	EN55032-B Radiated & Conducted			
Immunity	-	EN61000-4-2 (contact lvl 2, air lvl 3), -3 (lvl 3), -4 (lvl 3) -5 (norm mode lvl 3, com mode lvl 4), -6 (lvl 3), -8 (lvl 4), -11			
Line Dips	-	SEMI-F47 (200VAC input, 120-480W only)			
Weight (Typ)	g	600	900	1300	1735
Size (WxHxD)	in	1.44 x 4.86 x 4.53	1.93 x 4.86 x 4.53	3.23 x 4.86 x 4.53	4.33 x 4.86 x 5.47
Mounts on TS-35/7.5 or -35/15 rail	mm	36.5 x 123.4 x 115	49 x 123.4 x 115	82 x 123.4 x 115	110 x 123.4 x 139
Case material	-	Metal			
Warranty	yrs	Five years			

(1) Withstands 300VAC for 5s (2) See installation manual (3) See options table

*Safety certified for AC input only

(4) Operating period at peak output current is 4 sec, max duty cycle <35% & < rated output power

† Certification to the IEC62368-1 standard in progress (2019)

Model	Output Voltage	Adjust Range	Max Current	Max Power	Peak Output Current ⁽⁴⁾	Peak Output Power ⁽⁴⁾
DRF120-24-1	24V	24 - 28V	5A	120W	7.5A	180W
DRF240-24-1	24V	24 - 28V	10A	240W	15A	360W
DRF480-24-1	24V	24 - 28V	20A	480W	30A	720W
DRF960-24-1	24V	24 - 28V	40A	960W	60A	1440W

Figure 6: Dimensions of DRF120-24-1

The figure illustrates the mechanical specifications of the DRF120-24-1 device through four orthographic views:

- Top View:** Shows the overall footprint with a width of 175±0.1 mm and a height of 115±0.1 mm. It details the location of the DIN rail connector, output terminals, and mounting holes.
- Front View:** Displays the depth of the unit as 86±0.1 mm, along with the position of the name plate and mounting holes.
- Side View:** Provides another perspective of the 86±0.1 mm depth, highlighting the DIN rail bracket and mounting features.
- Rear View:** Focuses on the terminal block, showing the output voltage adjustment potentiometer, DC OK indicator (green LED), PF OK indicator (red LED), and the front seal.

Technical drawings of the TDN240-24-1 LED driver, showing front, top, and side views with dimensions and labels.

Front View:

- Overall width: 77.0
- Overall height: 115.6 ± 0.3
- Top edge features a **SERIAL CONNECTOR** with dimensions 19.35 and 16.35.
- Bottom edge features a **NAME PLATE** with dimensions 13.60 and 11.45.
- Left side features a **DISSIPABLE BRACKET** with a height of 6.35.

Top View:

- Overall width: 77.0
- Overall height: 115.6 ± 0.3
- Left side features a **DISSIPABLE BRACKET** with a height of 6.35.
- Right side features a **FRONT SEAL** with a height of 11.45.

Side View:

- Overall width: 77.0
- Overall height: 115.6 ± 0.3
- Top edge features a **DISSIPABLE BRACKET** with a height of 6.35.
- Bottom edge features a **FRONT SEAL** with a height of 11.45.

Front View Details:

- Output voltage adjustment potentiometer (green LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (red LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (green LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (red LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (green LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (red LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (green LED) with dimensions 7.62, 6.35, and 12.7.
- Output voltage adjustment potentiometer (red LED) with dimensions 7.62, 6.35, and 12.7.

Figure 1: Dimensions of the DRF480-24-1. The figure consists of four views: front, top, side, and rear. The front view shows a rectangular unit with a perforated metal front panel and a nameplate. The top view shows the top surface with a nameplate and a terminal block. The side view shows the side profile with a nameplate and a terminal block. The rear view shows the back panel with a nameplate and a terminal block. Dimensions are provided in inches and millimeters.

FIGURE 1

Model 2000-04-1

Dimensions:

- Overall Width: 19.8 (503)
- Overall Height: 17.1 (433)
- Signal Connector: 1.5 (38.1)
- Name Plate: SEE NOTE A
- Output Voltage Adjustment: 1.5 (38.1)
- DC OK Indicator (Green LED): 1.5 (38.1)
- Peak Indicator (Red LED): 1.5 (38.1)
- Front Seal: 1.5 (38.1)
- Mounting Bracket: 1.5 (38.1)
- Mounting Feet: 1.5 (38.1)

Suffix	Description
/HL (DRF120-480 only)	ATEX, IEC EX, GL Certification (Incl pcb coating)





**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331