


### Surface Mount Type

Series: **FC** Type: **V**

FC High temperature Lead-Free reflow(suffix:A\*)

Low impedance



### ■ Features

- Endurance : 105 °C 1000 h
- Low impedance (1/2 for HA series)
- Vibration-proof product is available upon request. (ø8 mm and larger)
- RoHS directive compliant

### ■ Specifications


|                                    |                                                                                                                                                                                            |                                    |    |    |    |    |                             |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|----|----|----|----|-----------------------------|
| Category Temp. Range               | -40 °C to +105 °C                                                                                                                                                                          |                                    |    |    |    |    |                             |
| Rated W.V. Range                   | 6.3 V.DC to 35 V.DC                                                                                                                                                                        |                                    |    |    |    |    |                             |
| Nominal Cap. Range                 | 1 µF to 1500 µF                                                                                                                                                                            |                                    |    |    |    |    |                             |
| Capacitance Tolerance              | ±20 % (120 Hz/+20 °C)                                                                                                                                                                      |                                    |    |    |    |    |                             |
| DC Leakage Current                 | I ≤ 0.01 CV or 3 (µA) After 2 minutes (Whichever is greater)                                                                                                                               |                                    |    |    |    |    |                             |
| tan δ                              | Please see the attached High temperature lead-free reflow products list.                                                                                                                   |                                    |    |    |    |    |                             |
| Characteristics at Low Temperature | W.V. (V)                                                                                                                                                                                   | 6.3                                | 10 | 16 | 25 | 35 | (Impedance ratio at 120 Hz) |
|                                    | Z(-25 °C) / Z(+20 °C)                                                                                                                                                                      | 2                                  | 2  | 2  | 2  | 2  |                             |
|                                    | Z(-40 °C) / Z(+20 °C)                                                                                                                                                                      | 3                                  | 3  | 3  | 3  | 3  |                             |
| Endurance                          | After applying rated working voltage for 1000 hours at +105 °C±2 °C and then being stabilized at +20 °C, Capacitors shall meet the following limits.                                       |                                    |    |    |    |    |                             |
|                                    | Capacitance change                                                                                                                                                                         | ±20 % of initial measured value    |    |    |    |    |                             |
|                                    | tan δ                                                                                                                                                                                      | ≤ 200 % of initial specified value |    |    |    |    |                             |
|                                    | DC leakage current                                                                                                                                                                         | ≤ initial specified value          |    |    |    |    |                             |
| Shelf Life                         | After storage for 1000 hours at +105 °C±2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance.(With voltage treatment) |                                    |    |    |    |    |                             |
| Resistance to Soldering Heat       | After reflow soldering and then being stabilized at +20 °C, capacitors shall meet the following limits.                                                                                    |                                    |    |    |    |    |                             |
|                                    | Capacitance change                                                                                                                                                                         | ±10 % of initial measured value    |    |    |    |    |                             |
|                                    | tan δ                                                                                                                                                                                      | ≤ initial specified value          |    |    |    |    |                             |
|                                    | DC leakage current                                                                                                                                                                         | ≤ initial specified value          |    |    |    |    |                             |

### ■ Frequency correction factor for ripple current

|                   | Frequency (Hz) |      |      |      |          |
|-------------------|----------------|------|------|------|----------|
|                   | 50, 60         | 120  | 1 k  | 10 k | 100 k to |
| Correction factor | 0.70           | 0.75 | 0.90 | 0.95 | 1.00     |

### ■ Marking

Example: 6.3 V 22 µF  
Marking color : BLACK




#### Rated Voltage Mark

|   |       |   |      |
|---|-------|---|------|
| j | 6.3 V | E | 25 V |
| A | 10 V  | V | 35 V |
| C | 16 V  |   |      |

### ■ Dimensions in mm (not to scale)

(Unit : mm)



| Size code | D    | L                                   | A, B | H         | I   | W        | P   | K                                      |
|-----------|------|-------------------------------------|------|-----------|-----|----------|-----|----------------------------------------|
| B         | 4.0  | 5.4 <sup>+0.1</sup> <sub>-0.2</sub> | 4.3  | 5.5 max.  | 1.8 | 0.65±0.1 | 1.0 | 0.35 <sup>+0.15</sup> <sub>-0.20</sub> |
| C         | 5.0  | 5.4 <sup>+0.1</sup> <sub>-0.2</sub> | 5.3  | 6.5 max.  | 2.2 | 0.65±0.1 | 1.5 | 0.35 <sup>+0.15</sup> <sub>-0.20</sub> |
| D         | 6.3  | 5.4 <sup>+0.1</sup> <sub>-0.2</sub> | 6.6  | 7.8 max.  | 2.6 | 0.65±0.1 | 1.8 | 0.35 <sup>+0.15</sup> <sub>-0.20</sub> |
| E         | 8.0  | 6.2±0.3                             | 8.3  | 9.5 max.  | 3.4 | 0.65±0.1 | 2.2 | 0.35 <sup>+0.15</sup> <sub>-0.20</sub> |
| F         | 8.0  | 10.2±0.3                            | 8.3  | 10.0 max. | 3.4 | 0.90±0.2 | 3.1 | 0.70±0.2                               |
| G         | 10.0 | 10.2±0.3                            | 10.3 | 12.0 max. | 3.5 | 0.90±0.2 | 4.6 | 0.70±0.2                               |

## ■ High temperature Lead-Free reflow Products

Endurance : 105 °C 1000 h

| W.V. | Cap.<br>(±20 %) | Case size |        |              | Specification                                             |                                       |                                           | Part No.<br>(RoHS:compliant) | Reflow | Min.<br>Packaging Q'ty |
|------|-----------------|-----------|--------|--------------|-----------------------------------------------------------|---------------------------------------|-------------------------------------------|------------------------------|--------|------------------------|
|      |                 | Dia.      | Length | Size<br>Code | Ripple<br>Current<br>(100 kHz)<br>(+105°C)<br>(mA r.m.s.) | $\tan \delta$<br>(120 Hz)<br>(+20 °C) | Impedance<br>(100 kHz)<br>(+20 °C)<br>(Ω) |                              |        | Taping                 |
| (V)  | (μF)            | (mm)      | (mm)   |              |                                                           |                                       |                                           |                              |        | (pcs)                  |
| 6.3  | 22              | 4         | 5.4    | B            | 60                                                        | 0.26                                  | 3.00                                      | EEFC0J220AR                  | (5)    | 2000                   |
|      | 47              | 5         | 5.4    | C            | 95                                                        | 0.26                                  | 1.80                                      | EEFC0J470AR                  | (5)    | 1000                   |
|      | 68              | 6.3       | 5.4    | D            | 140                                                       | 0.26                                  | 1.00                                      | EEFC0J680AP                  | (5)    | 1000                   |
|      | 100             | 6.3       | 5.4    | D            | 140                                                       | 0.26                                  | 1.00                                      | EEFC0J101AP                  | (5)    | 1000                   |
|      | 220             | 8         | 6.2    | E            | 230                                                       | 0.26                                  | 0.40                                      | EEFC0J221AP                  | (6)    | 1000                   |
|      | 330             | 8         | 10.2   | F            | 450                                                       | 0.26                                  | 0.30                                      | EEFC0J331AP                  | (6)    | 500                    |
|      | 1000            | 10        | 10.2   | G            | 670                                                       | 0.26                                  | 0.15                                      | EEFC0J102AP                  | (6)    | 500                    |
|      | 1500            | 10        | 10.2   | G            | 670                                                       | 0.26                                  | 0.15                                      | EEFC0J152AP                  | (6)    | 500                    |
| 10   | 33              | 5         | 5.4    | C            | 95                                                        | 0.19                                  | 1.80                                      | EEFC1A330AR                  | (5)    | 1000                   |
|      | 100             | 8         | 6.2    | E            | 230                                                       | 0.19                                  | 0.40                                      | EEFC1A101AP                  | (6)    | 1000                   |
|      | 150             | 8         | 6.2    | E            | 230                                                       | 0.19                                  | 0.40                                      | EEFC1A151AP                  | (6)    | 1000                   |
|      | 220             | 8         | 10.2   | F            | 450                                                       | 0.19                                  | 0.30                                      | EEFC1A221AP                  | (6)    | 500                    |
|      | 470             | 10        | 10.2   | G            | 670                                                       | 0.19                                  | 0.15                                      | EEFC1A471AP                  | (6)    | 500                    |
|      | 1000            | 10        | 10.2   | G            | 670                                                       | 0.19                                  | 0.15                                      | EEFC1A102AP                  | (6)    | 500                    |
| 16   | 10              | 4         | 5.4    | B            | 60                                                        | 0.16                                  | 3.00                                      | EEFC1C100AR                  | (5)    | 2000                   |
|      | 22              | 5         | 5.4    | C            | 95                                                        | 0.16                                  | 1.80                                      | EEFC1C220AR                  | (5)    | 1000                   |
|      | 47              | 6.3       | 5.4    | D            | 140                                                       | 0.16                                  | 1.00                                      | EEFC1C470AP                  | (5)    | 1000                   |
|      | 68              | 8         | 6.2    | E            | 230                                                       | 0.16                                  | 0.40                                      | EEFC1C680AP                  | (6)    | 1000                   |
|      | 100             | 8         | 6.2    | E            | 230                                                       | 0.16                                  | 0.40                                      | EEFC1C101AP                  | (6)    | 1000                   |
|      | 220             | 10        | 10.2   | G            | 670                                                       | 0.16                                  | 0.15                                      | EEFC1C221AP                  | (6)    | 500                    |
|      | 330             | 10        | 10.2   | G            | 670                                                       | 0.16                                  | 0.15                                      | EEFC1C331AP                  | (6)    | 500                    |
|      | 470             | 10        | 10.2   | G            | 670                                                       | 0.16                                  | 0.15                                      | EEFC1C471AP                  | (6)    | 500                    |
|      | 680             | 10        | 10.2   | G            | 670                                                       | 0.16                                  | 0.15                                      | EEFC1C681AP                  | (6)    | 500                    |
| 25   | 6.8             | 4         | 5.4    | B            | 60                                                        | 0.14                                  | 3.00                                      | EEFC1E6R8AR                  | (5)    | 2000                   |
|      | 22              | 6.3       | 5.4    | D            | 140                                                       | 0.14                                  | 1.00                                      | EEFC1E220AP                  | (5)    | 1000                   |
|      | 33              | 6.3       | 5.4    | D            | 140                                                       | 0.14                                  | 1.00                                      | EEFC1E330AP                  | (5)    | 1000                   |
|      | 47              | 8         | 6.2    | E            | 230                                                       | 0.14                                  | 0.40                                      | EEFC1E470AP                  | (6)    | 1000                   |
|      | 68              | 8         | 10.2   | F            | 450                                                       | 0.14                                  | 0.30                                      | EEFC1E680AP                  | (6)    | 500                    |
|      | 100             | 8         | 10.2   | F            | 450                                                       | 0.14                                  | 0.30                                      | EEFC1E101AP                  | (6)    | 500                    |
|      | 220             | 10        | 10.2   | G            | 670                                                       | 0.14                                  | 0.15                                      | EEFC1E221AP                  | (6)    | 500                    |
|      | 330             | 10        | 10.2   | G            | 670                                                       | 0.14                                  | 0.15                                      | EEFC1E331AP                  | (6)    | 500                    |
|      | 470             | 10        | 10.2   | G            | 670                                                       | 0.14                                  | 0.15                                      | EEFC1E471AP                  | (6)    | 500                    |
| 35   | 1               | 4         | 5.4    | B            | 60                                                        | 0.12                                  | 3.00                                      | EEFC1V1R0AR                  | (5)    | 2000                   |
|      | 2.2             | 4         | 5.4    | B            | 60                                                        | 0.12                                  | 3.00                                      | EEFC1V2R2AR                  | (5)    | 2000                   |
|      | 3.3             | 4         | 5.4    | B            | 60                                                        | 0.12                                  | 3.00                                      | EEFC1V3R3AR                  | (5)    | 2000                   |
|      | 4.7             | 4         | 5.4    | B            | 60                                                        | 0.12                                  | 3.00                                      | EEFC1V4R7AR                  | (5)    | 2000                   |
|      | 6.8             | 5         | 5.4    | C            | 95                                                        | 0.12                                  | 1.80                                      | EEFC1V6R8AR                  | (5)    | 1000                   |
|      | 10              | 5         | 5.4    | C            | 95                                                        | 0.12                                  | 1.80                                      | EEFC1V100AR                  | (5)    | 1000                   |
|      | 22              | 6.3       | 5.4    | D            | 140                                                       | 0.12                                  | 1.00                                      | EEFC1V220AP                  | (5)    | 1000                   |
|      | 33              | 8         | 6.2    | E            | 230                                                       | 0.12                                  | 0.40                                      | EEFC1V330AP                  | (6)    | 1000                   |
|      | 47              | 8         | 6.2    | E            | 230                                                       | 0.12                                  | 0.40                                      | EEFC1V470AP                  | (6)    | 1000                   |
|      | 100             | 10        | 10.2   | G            | 670                                                       | 0.12                                  | 0.15                                      | EEFC1V101AP                  | (6)    | 500                    |
|      | 220             | 10        | 10.2   | G            | 670                                                       | 0.12                                  | 0.15                                      | EEFC1V221AP                  | (6)    | 500                    |
|      | 330             | 10        | 10.2   | G            | 670                                                       | 0.12                                  | 0.15                                      | EEFC1V331AP                  | (6)    | 500                    |

- Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
- When requesting vibration-proof product, please put the last "V" instead to "P"



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331