ATmega809/1609/3209/4809 – 48-pin

48-pin Data Sheet – megaAVR® 0-series

Introduction

The ATmega809/1609/3209/4809 microcontrollers of the megaAVR® 0-series are using the AVR® processor with hardware multiplier, running at up to 20 MHz, with a wide range of Flash sizes up to 48 KB, up to 6 KB of SRAM, and 256 bytes of EEPROM in 28-, 32-, 40-, or 48-pin package. The series uses the latest technologies from Microchip with a flexible and low-power architecture including Event System and SleepWalking, accurate analog features and advanced peripherals.

The devices described here offer Flash sizes from 8 KB to 48 KB in a 48-pin package.

Features

- AVR® CPU
  - Single-cycle I/O access
  - Two-level interrupt controller
  - Two-cycle hardware multiplier
- Memories
  - Up to 48 KB In-system self-programmable Flash memory
  - 256B EEPROM
  - Up to 6 KB SRAM
  - Write/Erase endurance:
    - Flash 10,000 cycles
    - EEPROM 100,000 cycles
  - Data retention: 40 Years at 55°C
- System
  - Power-on Reset (POR) circuit
  - Brown-out Detector (BOD)
  - Clock options:
    - 16/20 MHz low-power internal oscillator
    - 32.768 kHz Ultra Low-Power (ULP) internal oscillator
    - 32.768 kHz external crystal oscillator
    - External clock input
  - Single pin Unified Program Debug Interface (UPDI)
  - Three sleep modes:
    - Idle with all peripherals running for immediate wake-up
    - Standby
      - Configurable operation of selected peripherals

© 2019 Microchip Technology Inc.

        - SleepWalking peripherals
    - Power-Down with limited wake-up functionality
- Peripherals
  - One 16-bit Timer/Counter type A (TCA) with a dedicated period register and three compare channels
  - Four 16-bit Timer/Counter type B with input capture (TCB)
  - One 16-bit Real-Time Counter (RTC) running from an external crystal or an internal RC oscillator
  - Four USART with fractional baud rate generator, auto-baud, and start-of-frame detection
  - Master/slave Serial Peripheral Interface (SPI)
  - Dual mode Master/Slave TWI with dual address match
    - Standard mode (Sm, 100 kHz)
    - Fast mode (Fm, 400 kHz)
    - Fast mode plus (Fm+, 1 MHz)
  - Event System for CPU independent and predictable inter-peripheral signaling
  - Configurable Custom Logic (CCL) with up to four programmable Look-up Tables (LUT)
  - One Analog Comparator (AC) with a scalable reference input
  - One 10-bit 150 ksps Analog to Digital Converter (ADC)
  - Five selectable internal voltage references: 0.55V, 1.1V, 1.5V, 2.5V, and 4.3V
  - CRC code memory scan hardware
    - Optional automatic scan before code execution is allowed
  - Watchdog Timer (WDT) with Window mode, with separate on-chip oscillator
  - External interrupt on all general purpose pins
- I/O and Packages:
  - 41 programmable I/O lines
  - 48-pin UQFN 6x6 and TQFP 7x7
- Temperature Range: -40°C to 125°C
- Speed Grades -40°C to 105°C:
  - 0-5 MHz @ 1.8V – 5.5V
  - 0-10 MHz @ 2.7V – 5.5V
  - 0-20 MHz @ 4.5V – 5.5V
- Speed Grades -40°C to 125°C:
  - 0-8 MHz @ 2.7V - 5.5V
  - 0-16 MHz @ 4.5V - 5.5V

© 2019 Microchip Technology Inc.

Table of Contents

Introduction....1

Features....1

1. Block Diagram....5

2. Pinout....6
   2.1. 48-pin UQFN/TQFP....6

3. I/O Multiplexing and Considerations....7
   3.1. Multiplexed Signals....7

4. Electrical Characteristics....9
   4.1. Disclaimer....9
   4.2. Absolute Maximum Ratings....9
   4.3. General Operating Ratings....9
   4.4. Power Considerations....11
   4.5. Power Consumption....11
   4.6. Peripherals Power Consumption....13
   4.7. BOD and POR Characteristics....14
   4.8. External Reset Characteristics....15
   4.9. Oscillators and Clocks....15
   4.10. I/O Pin Characteristics....17
   4.11. USART....19
   4.12. SPI....20
   4.13. TWI....21
   4.14. VREF....23
   4.15. ADC....25
   4.16. AC....28
   4.17. UPDI Timing....29
   4.18. Programming Time....30

5. Typical Characteristics....31
   5.1. Power Consumption....31
   5.2. GPIO....39
   5.3. VREF Characteristics....46
   5.4. BOD Characteristics....48
   5.5. ADC Characteristics....51
   5.6. AC Characteristics....61
   5.7. OSC20M Characteristics....63
   5.8. OSCULP32K Characteristics....65

6. Ordering Information....67

7. Online Package Drawings....68

8. Package Drawings....69
8.1. 48-Pin TQFP....69
8.2. 48-Pin UQFN....73
9. Conventions....77
9.1. Memory Size and Type....77
9.2. Frequency and Time....77
10. Data Sheet Revision History....78
10.1. Rev.B - 03/2019....78
10.2. Rev. A - 02/2018....78
The Microchip Web Site....79
Customer Change Notification Service....79
Customer Support....79
Product Identification System....80
Microchip Devices Code Protection Feature....80
Legal Notice....80
Trademarks....81
Quality Management System Certified by DNV....81
Worldwide Sales and Service....82

1. Block Diagram



2. Pinout

2.1 48-pin UQFN/TQFP



Power

- Input supply
- Ground
- GPIO on VDD power domain
- GPIO on AVDD power domain

Functionality

- Programming, debug
- Clock, crystal
- TWI
- Digital functions only
- Analog functions

3. I/O Multiplexing and Considerations

3.1 Multiplexed Signals

UQFN48/ TQFP48	Pin name (1,2)	Special	ADC0	AC0	USARTn	SPI0	TWI0	TCA0	TCBn	EVSYS	CCL-LUTn
44	PA0	EXTCLK			0,TxD			0-WO0			0-IN0
45	PA1				0,RxD			0-WO1			0-IN1
46	PA2	TWI			0,XCK		SDA(MS)	0-WO2	0-WO	EVOUTA	0-IN2
47	PA3	TWI			0,XDIR		SCL(MS)	0-WO3	1-WO		0-OUT
48	PA4				0,TxD(3)	MOSI		0-WO4			
1	PA5				0,RxD(3)	MISO		0-WO5			
2	PA6				0,XCK(3)	SCK					0-OUT(3)
3	PA7	CLKOUT		OUT	0,XDIR(3)	SS				EVOUTA(3)	
4	PB0				3,TxD			0-WO0(3)			
5	PB1				3,RxD			0-WO1(3)			
6	PB2				3,XCK			0-WO2(3)		EVOUTB	
7	PB3				3,XDIR			0-WO3(3)			
8	PB4				3,TxD(3)			0-WO4(3)	2-WO(3)		
9	PB5				3,RxD(3)			0-WO5(3)	3-WO		
10	PC0				1,TxD	MOSI(3)		0-WO0(3)	2-WO		1-IN0
11	PC1				1,RxD	MISO(3)		0-WO1(3)	3-WO(3)		1-IN1
12	PC2	TWI			1,XCK	SCK(3)	SDA(MS)(3)	0-WO2(3)		EVOUTC	1-IN2
13	PC3	TWI			1,XDIR	SS(3)	SCL(MS)(3)	0-WO3(3)			1-OUT
14	VDD										
15	GND										
16	PC4				1,TxD(3)			0-WO4(3)			
17	PC5				1,RxD(3)			0-WO5(3)			
18	PC6				1,XCK(3)						1-OUT(3)
19	PC7				1,XDIR(3)					EVOUTC(3)	
20	PD0		AIN0					0-WO0(3)			2-IN0
21	PD1		AIN1	P3				0-WO1(3)			2-IN1
22	PD2		AIN2	P0				0-WO2(3)		EVOUTD	2-IN2
23	PD3		AIN3	N0				0-WO3(3)			2-OUT
24	PD4		AIN4	P1				0-WO4(3)			
25	PD5		AIN5	N1				0-WO5(3)			
26	PD6		AIN6	P2							2-OUT(3)
27	PD7	VREFA	AIN7	N2						EVOUTD(3)	
28	AVDD										
29	GND										
30	PE0		AIN8			MOSI(3)		0-WO0(3)			
31	PE1		AIN9			MISO(3)		0-WO1(3)			
32	PE2		AIN10			SCK(3)		0-WO2(3)		EVOUTE	
33	PE3		AIN11			SS(3)		0-WO3(3)			
34	PF0	TOSC1			2,TxD			0-WO0(3)			3-IN0
35	PF1	TOSC2			2,RxD			0-WO1(3)			3-IN1
36	PF2	TWI	AIN12		2,XCK		SDA(S)(3)	0-WO2(3)		EVOUTF	3-IN2
37	PF3	TWI	AIN13		2,XDIR		SCL(S)(3)	0-WO3(3)			3-OUT

.....continued

UQFN48/ TQFP48	Pin name (1,2)	Special	ADC0	AC0	USARTn	SPI0	TWI0	TCA0	TCBn	EVSYS	CCL-LUTn
38	PF4		AIN14		2,TxD(3)			0-WO4(3)	0-WO(3)		
39	PF5		AIN15		2,RxD(3)			0-WO5(3)	1-WO(3)		
40	PF6	RESET			2,XCK(3)						3-OUT(3)
41	UPDI										
42	VDD										
43	GND										

Note:

1. Pin names are of type P*xn*, with *x* being the PORT instance (A,B,C, ...) and *n* the pin number. Notation for signals is PORT*x*_PIN*n*. All pins can be used as event input.
2. All pins can be used for external interrupt, where pins P*x*2 and P*x*6 of each port have full asynchronous detection.
3. Alternate pin positions. For selecting the alternate positions, refer to the PORTMUX documentation.

4. Electrical Characteristics

4.1 Disclaimer

All typical values are measured at T = 25°C and V_{DD} = 3V unless otherwise specified. All minimum and maximum values are valid across operating temperature and voltage unless otherwise specified.

Typical values given should be considered for design guidance only, and actual part variation around these values is expected.

4.2 Absolute Maximum Ratings

Stresses beyond those listed in this section may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Table 4-1. Absolute Maximum Ratings

Symbol	Description	Conditions	Min.	Max.	Unit
V_{DD}	Power Supply Voltage		-0.5	6	V
I_{VDD}	Current into a V_{DD} pin	T_A=[-40, 85]°C	-	200	mA
		T_A=[85, 125]°C	-	100	mA
I_{GND}	Current out of a GND pin	T_A=[-40, 85]°C	-	200	mA
		T_A=[85, 125]°C	-	100	mA
V_{PIN}	Pin voltage with respect to GND		-0.5	V_{DD}+0.5	V
I_{PIN}	I/O pin sink/source current		-40	40	mA
I_{c1}(1)	I/O pin injection current except for the RESET pin	V_{pin}<GND-0.6V or 5.5V<V_{pin}≤6.1V 4.9V<V_{DD}≤5.5V	-1	1	mA
I_{c2}(1)	I/O pin injection current except for the RESET pin	V_{pin}<GND-0.6V or V_{pin}≤5.5V V_{DD}≤4.9V	-15	15	mA
$T_{storage}$	Storage temperature		-65	150	°C

Note:

1. – If V_{PIN} is lower than GND-0.6V, then a current limiting resistor is required. The negative DC injection current limiting resistor is calculated as R = (GND-0.6V – V_{pin})/I_{Cn}.
   – If V_{PIN} is greater than V_{DD}+0.6V, then a current limiting resistor is required. The positive DC injection current limiting resistor is calculated as R = (V_{pin}-(V_{DD}+0.6))/I_{Cn}.

4.3 General Operating Ratings

The device must operate within the ratings listed in this section in order for all other electrical characteristics and typical characteristics of the device to be valid.

Table 4-2. General Operating Conditions

Symbol	Description	Condition	Min.	Max.	Unit
V_{DD}	Operating Supply Voltage		1.8(1)	5.5	V
T_A	Operating temperature range		-40	125	°C

Note:

1. Operation is guaranteed down to 1.8V or VBOD with BODLEVEL0, whichever is lower.

Table 4-3. Operating Voltage and Frequency

Symbol	Description	Condition	Min.	Max.	Unit
f_{CLK_CPU}	Nominal operating system clock frequency	V_{DD}=[1.8, 5.5]V T_A=[-40, 105]°C(1)(4)	0	5	MHz
		V_{DD}=[2.7, 5.5]V T_A=[-40, 105]°C(2)(4)	0	10	
		V_{DD}=[4.5, 5.5]V T_A=[-40, 105]°C(3)(4)	0	20	
		V_{DD}=[2.7, 5.5]V T_A=[-40, 125]°C(2)	0	8	
		V_{DD}=[4.5, 5.5]V T_A=[-40, 125]°C(2)	0	16	

Note:

1. Operation is guaranteed down to BOD triggering level, V_{BOD} with BODLEVEL0.
2. Operation is guaranteed down to BOD triggering level, V_{BOD} with BODLEVEL2.
3. Operation is guaranteed down to BOD triggering level, V_{BOD} with BODLEVEL7.
4. These specifications do not apply to automotive range parts (-VAO).

The maximum CPU clock frequency depends on V_{DD}. As shown in the figure below, the Maximum Frequency vs. V_{DD} is linear between $1.8V < V_{DD} < 2.7V$ and $2.7V < V_{DD} < 4.5V$.

Figure 4-1. Maximum Frequency vs. V_{DD} for [-40, 105]°C



4.4 Power Considerations

The average die junction temperature, T_J (in °C) is given from the formula

$T_J = T_A + P_D * R_{\theta JA}$

where P_D is the total power dissipation.

The total thermal resistance of a package ($R_{\theta JA}$) can be separated into two components, $R_{\theta JC}$ and $R_{\theta CA}$, representing the barrier to heat flow from the semiconductor junction to the package (case) surface ($R_{\theta JC}$) and from the case to the outside ambient air ($R_{\theta CA}$). These terms are related by the equation:

$R_{\theta JA} = R_{\theta JC} + R_{\theta CA}$.

$R_{\theta JC}$ is device related and cannot be influenced by the user. However, $R_{\theta CA}$ is user dependent and can be minimized by thermal management techniques such as heat sinks, ambient air cooling, and thermal convection. Thus, good thermal management on the part of the user can significantly reduce $R_{\theta CA}$ so that $R_{\theta JA}$ approximately equals $R_{\theta JC}$.

The power dissipation curve is negatively sloped as ambient temperature increase. The maximum power dissipation is therefore at minimum ambient temperature while the highest junction temperature occurs at the maximum ambient temperature.

Table 4-4. Power Dissipation and Junction Temperature vs Temperature

Package	T_A Range	$R_{\theta JA}$ (°C/W)	P_D (W) Typical	$T_J - T_A$(°C) Typical
UQFN48	-40°C to 125°C		1.0	
TQFP48	-40°C to 125°C		1.0	

4.5 Power Consumption

The values are measured power consumption under the following conditions, except where noted:

- V_{DD}=3V
- T_A=25°C
- OSC20M used as system clock source, except where otherwise specified

- System power consumption measured with peripherals disabled and I/O ports driven low with inputs disabled

Table 4-5. Power Consumption in Active and Idle Mode

Mode	Description	Condition		Typ.	Max.	Unit
Active	Active power consumption	f_{CLK_CPU}=20 MHz (OSC20M)	V_{DD}=5V	8.5	-	mA
		f_{CLK_CPU}=10 MHz (OSC20M div2)	V_{DD}=5V	4.3	-	mA
			V_{DD}=3V	2.3	-	mA
		f_{CLK_CPU}=5 MHz (OSC20M div4)	V_{DD}=5V	2.2	-	mA
			V_{DD}=3V	1.2	-	mA
			V_{DD}=2V	0.75	-	mA
		f_{CLK_CPU}=32.768 kHz (OSCULP32K)	V_{DD}=5V	16.4	-	µA
			V_{DD}=3V	9.0	-	µA
			V_{DD}=2V	6.0	-	µA
Idle	Idle power consumption	f_{CLK_CPU}=20 MHz (OSC20M)	V_{DD}=5V	2.8	-	mA
		f_{CLK_CPU}=10 MHz (OSC20M div2)	V_{DD}=5V	1.4	-	mA
			V_{DD}=3V	0.8	-	mA
		f_{CLK_CPU}=5 MHz (OSC20M div4)	V_{DD}=5V	0.7	-	mA
			V_{DD}=3V	0.4	-	mA
			V_{DD}=2V	0.25	-	mA
		f_{CLK_CPU}=32.768 kHz (OSCULP32K)	V_{DD}=5V	5.6	-	µA
			V_{DD}=3V	2.8	-	µA
			V_{DD}=2V	1.8	-	µA

Table 4-6. Power Consumption in Power-Down, Standby and Reset Mode

Mode	Description	Condition		Typ. 25°C	Max. 85°C(1)	Max. 125°C	Unit
Standby	Standby power consumption	RTC running at 1.024 kHz from external XOSC32K (CL=7.5 pF)	V_{DD}=3V	0.7	-	-	µA
		RTC running at 1.024 kHz from internal OSCULP32K	V_{DD}=3V	0.7	6.0	16.0	µA

.....continued							
Mode	**Description**	**Condition**		**Typ. 25°C**	**Max. 85°C(1)**	**Max. 125°C**	**Unit**
Power Down/ Standby	Power down/ Standby power consumption are the same when all peripherals are stopped	All peripherals stopped	V_{DD}=3V	0.1	5.0	15.0	µA
Reset	Reset power consumption	RESET line pulled low	V_{DD}=3V	100	-	-	µA

Note:

1. These parameters are for design guidance only and are not tested.

4.6 Peripherals Power Consumption

The table below can be used to calculate the additional current consumption for the different I/O peripherals in the various operating modes.

Some peripherals will request the clock to be enabled when operating in STANDBY. See the peripheral chapter for further information.

Operating conditions:

- V_{DD}=3V
- T=25°C
- OSC20M at 1 MHz used as system clock source, except where otherwise specified
- In Idle Sleep mode, except where otherwise specified

Table 4-7. Peripherals Power Consumption

Peripheral	Conditions	Typ.(1)	Unit
BOD	Continuous	19	µA
	Sampling @ 1 kHz	1.2	
TCA	16-bit count @ 1 MHz	13.0	µA
TCB	16-bit count @ 1 MHz	7.4	µA
RTC	16-bit count @ OSCULP32K	1.2	µA
WDT (including OSCULP32K)		0.7	µA
OSC20M		130	µA
AC	Fast Mode(2)	92	µA
	Low-Power Mode(2)	45	µA
ADC(3)	50 ksps	330	µA
	100 ksps	340	µA

.....continued			
Peripheral	**Conditions**	**Typ.(1)**	**Unit**
XOSC32K	C_L=7.5 pF	0.5	µA
OSCULP32K		0.4	µA
USART	Enable @ 9600 Baud	13.0	µA
SPI (Master)	Enable @ 100 kHz	2.1	µA
TWI (Master)	Enable @ 100 kHz	24.0	µA
TWI (Slave)	Enable @ 100 kHz	17.0	µA
Flash programming	Erase Operation	1.5	mA
	Write Operation	3.0	

Note:

1. Current consumption of the module only. To calculate the total internal power consumption of the microcontroller, add this value to the base power consumption given in “Power Consumption” section in electrical characteristics.
2. CPU in Standby mode.
3. Average power consumption with ADC active in Free-Running mode.

4.7 BOD and POR Characteristics

Table 4-8. Power Supply Characteristics

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
SRON(1)	Power-on Slope		-	-	100(2)	V/ms

Note:

1. For design guidance only and not tested in production.
2. A slope faster than the maximum rating can trigger a reset of the device if changing the voltage level after an initial power-up.

Table 4-9. Power-on Reset (POR) Characteristics

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
V_{POR}	POR threshold voltage on V_{DD} falling	V_{DD} falls/rises at 0.5V/ms or slower	0.8(1)	-	1.6(1)	V
	POR threshold voltage on V_{DD} rising		1.4(1)	-	1.8	

Note:

1. For design guidance only and not tested in production.

Table 4-10. Brown-out Detector (BOD) Characteristics

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
V_{BOD}	BOD detection level (falling/ rising)	BODLEVEL0	1.7	1.8	2.0	V
		BODLEVEL2	2.4	2.6	2.9	
		BODLEVEL7	3.9	4.3	4.5	
V_{HYS}	Hysteresis	BODLEVEL0	-	25	-	mV
		BODLEVEL2	-	40	-	
		BODLEVEL7	-	80	-	
t_{BOD}	Detection time	Continuous	-	7	-	µs
		Sampled, 1 kHz	-	1	-	ms
		Sampled, 125 Hz	-	8	-	
$t_{startup}$	Start-up time	Time from enable to ready	-	40	-	µs
V_{INT}	Interrupt level 0	Percentage above the selected BOD level	-	4	-	%
	Interrupt level 1		-	13	-	
	Interrupt level 2		-	25	-	

4.8 External Reset Characteristics

Table 4-11. External Reset Characteristics

Mode	Description	Condition	Min.	Typ.	Max.	Unit
V_{VIH_RST}	Input Voltage for $\overline{\text{RESET}}$		0.7×V_{DD}	-	V_{DD}+0.2	V
V_{VIL_RST}	Input Low Voltage for $\overline{\text{RESET}}$		-0.2	-	0.3×V_{DD}	
t_{MIN_RST}	Minimum pulse width on $\overline{\text{RESET}}$ pin(1)		-	-	2.5	µs
R_{p_RST}	$\overline{\text{RESET}}$ pull-up resistor	V_{Reset}=0V	20	35	50	kΩ

Note:

1. These parameters are for design guidance only and are not production tested.

4.9 Oscillators and Clocks

Operating conditions:

- V_{DD}=3V, except where specified otherwise

Table 4-12. 20 MHz Internal Oscillator (OSC20M) Characteristics

Symbol	Description	Condition		Min.	Typ.	Max.	Unit
f_{OSC20M}	Factory calibration frequency	FREQSEL=0	T_A=25°C, 3.0V		16		MHz
		FREQSEL=1			20		

.....continued

Symbol	Description	Condition		Min.	Typ.	Max.	Unit
f_{CAL}	Frequency calibration range	OSC16M(2)		14.5		17.5	MHz
		OSC20M(2)		18.5		21.5	MHz
E_{TOTAL}	Total error with 16 MHz and 20 MHz frequency selection	From target frequency	T_A=25°C, 3.0V	-1.5		1.5	%
			T_A=[0, 70]°C, V_{DD}=[1.8, 3.6]V	-2.0		2.0	%
			Full operation range	-4.0		4.0	
E_{DRIFT}	Accuracy with 16 MHz and 20 MHz frequency selection relative to the factory-stored frequency value	Factory calibrated V_{DD}=3V(1)	T_A=[0, 70]°C, V_{DD}=[1.8, 5.5]V	-1.8		1.8	%
Δf_{OSC20M}	Calibration step size			-	0.75	-	%
D_{OSC20M}	Duty cycle			-	50	-	%
$t_{startup}$	Start-up time	Within 2% accuracy		-	12	-	µs

Note:

1. See also the description of OSC20M on calibration.
2. Oscillator Frequencies above speed specification must be divided so the CPU clock is always within specification.

Table 4-13. 32.768 kHz Internal Oscillator (OSCULP32K) Characteristics

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
$f_{OSCULP32K}$	Factory calibration frequency			32.768		kHz
	Factory calibration accuracy	T_A=25°C, 3.0V	-3		3	%
E_{TOTAL}	Total error from target frequency	T_A=[0, 70]°C, V_{DD}=[1.8, 3.6]V	-10		+10	%
		Full operation range	-20		+20	
$D_{OSCULP32K}$	Duty cycle			50		%
$t_{startup}$	Start-up time		-	250	-	µs

Table 4-14. 32.768 kHz External Crystal Oscillator (XOSC32K) Characteristics

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
f_{out}	Frequency		-	32.768	-	kHz
$t_{startup}$	Start-up time	C_L=7.5 pF	-	300	-	ms
C_L	Crystal load capacitance(1)		7.5	-	12.5	pF
$C_{TOSC1/TOSC2}$	Parasitic pin capacitance		-	5.5	-	pF

.....continued						
Symbol	**Description**	**Condition**	**Min.**	**Typ.**	**Max.**	**Unit**
ESR(1)	Equivalent Series Resistance - Safety Factor=3	C_L=7.5 pF	-	-	80	kΩ
		C_L=12.5 pF	-	-	40	

Note:

1. This parameter is for design guidance only and not production tested.

Figure 4-2. External Clock Waveform Characteristics



Table 4-15. External Clock Characteristics

Symbol	Description	Condition	V_{DD}=[1.8, 5.5]V		V_{DD}=[2.7, 5.5]V		V_{DD}=[4.5, 5.5]V		Unit
			Min.	Max.	Min.	Max.	Min.	Max.	
f_{CLCL}	Frequency		0	5.0	0.0	10.0	0.0	20.0	MHz
t_{CLCL}	Clock Period		200	-	100	-	50	-	ns
t_{CHCX}(1)	High Time		80	-	40	-	20	-	ns
t_{CLCX}(1)	Low Time		80	-	40	-	20	-	ns
t_{CLCH}(1)	Rise Time (for maximum frequency)		-	40	-	20	-	10	ns
t_{CHCL}(1)	Fall Time (for maximum frequency)		-	40	-	20	-	10	ns
Δt_{CLCL}(1)	Change in period from one clock cycle to the next		-	20	-	20	-	20	%

Note:

1. This parameter is for design guidance only and not production tested.

4.10 I/O Pin Characteristics

Table 4-16. I/O Pin Characteristics (T_A=[-40, 85]°C, V_{DD}=[1.8, 5.5]V unless otherwise noted)

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
V_{IL}	Input Low Voltage		-0.2	-	0.3×V_{DD}	V
V_{IH}	Input High Voltage		0.7×V_{DD}	-	V_{DD}+0.2V	V

.....continued

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
I_{IH} / I_{IL}	I/O pin Input Leakage Current	V_{DD}=5.5V, pin high	-	< 0.05	-	µA
		V_{DD}=5.5V, pin low	-	< 0.05	-	
V_{OL}	I/O pin drive strength	V_{DD}=1.8V, I_{OL}=1.5 mA	-	-	0.36	V
		V_{DD}=3.0V, I_{OL}=7.5 mA	-	-	0.6	
		V_{DD}=5.0V, I_{OL}=15 mA	-	-	1	
V_{OH}	I/O pin drive strength	V_{DD}=1.8V, I_{OH}=1.5 mA	1.44	-	-	V
		V_{DD}=3.0V, I_{OH}=7.5 mA	2.4	-	-	
		V_{DD}=5.0V, I_{OH}=15 mA	4	-	-	
I_{total}	Maximum combined I/O sink/ source current per pin group(1,2)	T_A=125°C	-	-	100	mA
	Maximum combined I/O sink/ source current per pin group(1,2)	T_A=25°C	-	-	200	
t_{RISE}	Rise time	V_{DD}=3.0V, load=20 pF	-	2.5	-	ns
		V_{DD}=5.0V, load=20 pF	-	1.5	-	
		V_{DD}=3.0V, load=20 pF, slew rate enabled	-	19	-	
		V_{DD}=5.0V, load=20 pF, slew rate enabled	-	9	-	
t_{FALL}	Fall time	V_{DD}=3.0V, load=20 pF	-	2.0	-	ns
		V_{DD}=5.0V, load=20 pF	-	1.3	-	
		V_{DD}=3.0V, load=20 pF, slew rate enabled	-	21	-	
		V_{DD}=5.0V, load=20 pF, slew rate enabled	-	11	-	
C_{pin}	I/O pin capacitance except for TOSC, VREFA, and TWI pins		-	3.5	-	pF
C_{pin}	I/O pin capacitance on TOSC pins		-	4	-	pF
C_{pin}	I/O pin capacitance on TWI pins		-	10	-	pF
C_{pin}	I/O pin capacitance on VREFA pin		-	14	-	pF
R_p	Pull-up resistor		20	35	50	kΩ

Note:

1. Pin group A (PA[7:0]), PF[6:2]), pin group B (PB[7:0], PC[7:0]), pin group C (PD:7:0, PE[3:0], PF[1:0]). For 28-pin and 32-pin devices pin group A and B should be seen as a single group. The combined continuous sink/source current for each individual group should not exceed the limits.
2. These parameters are for design guidance only and are not production tested.

4.11 USART

Figure 4-3. USART in SPI Mode - Timing Requirements in Master Mode



Table 4-17. USART in SPI Master Mode - Timing Characteristics

Symbol(1)	Description	Condition	Min.	Typ.	Max.	Unit
f_{SCK}	SCK clock frequency	Master	-	-	10	MHz
t_{SCK}	SCK period	Master	100	-	-	ns
t_{SCKW}	SCK high/low width	Master	-	$0.5 \times t_{SCK}$	-	ns
t_{SCKR}	SCK rise time	Master	-	2.7	-	ns
t_{SCKF}	SCK fall time	Master	-	2.7	-	ns
t_{MIS}	MISO setup to SCK	Master	-	10	-	ns
t_{MIH}	MISO hold after SCK	Master	-	10	-	ns
t_{MOS}	MOSI setup to SCK	Master	-	$0.5 \times t_{SCK}$	-	ns
t_{MOH}	MOSI hold after SCK	Master	-	1.0	-	ns

Note:

1. These parameters are for design guidance only and are not production tested.

4.12 SPI

Figure 4-4. SPI - Timing Requirements in Master Mode



Figure 4-5. SPI - Timing Requirements in Slave Mode



Table 4-18. SPI - Timing Characteristics

Symbol(1)	Description	Condition	Min.	Typ.	Max.	Unit
f_{SCK}	SCK clock frequency	Master	-	-	10	MHz
t_{SCK}	SCK period	Master	100	-	-	ns
t_{SCKW}	SCK high/low width	Master	-	0.5*SCK	-	ns
t_{SCKR}	SCK rise time	Master	-	2.7	-	ns
t_{SCKF}	SCK fall time	Master	-	2.7	-	ns
t_{MIS}	MISO setup to SCK	Master	-	10	-	ns
t_{MIH}	MISO hold after SCK	Master	-	10	-	ns
t_{MOS}	MOSI setup to SCK	Master	-	0.5*SCK	-	ns
t_{MOH}	MOSI hold after SCK	Master	-	1.0	-	ns

.....continued						
Symbol(1)	**Description**	**Condition**	**Min.**	**Typ.**	**Max.**	**Unit**
f_{SSCK}	Slave SCK clock frequency	Slave	-	-	5	MHz
t_{SSCK}	Slave SCK period	Slave	4*t Clkper	-	-	ns
t_{SSCKW}	SCK high/low width	Slave	2*t Clkper	-	-	ns
t_{SSCKR}	SCK rise time	Slave	-	-	1600	ns
t_{SSCKF}	SCK fall time	Slave	-	-	1600	ns
t_{SIS}	MOSI setup to SCK	Slave	3.0	-	-	ns
t_{SIH}	MOSI hold after SCK	Slave	t_{Clkper}	-	-	ns
t_{SSS}	SS setup to SCK	Slave	21	-	-	ns
t_{SSH}	SS hold after SCK	Slave	20	-	-	ns
t_{SOS}	MISO setup to SCK	Slave	-	8.0	-	ns
t_{SOH}	MISO hold after SCK	Slave	-	13	-	ns
t_{SOSS}	MISO setup after SS low	Slave	-	11	-	ns
t_{SOSH}	MISO hold after SS low	Slave	-	8.0	-	ns

Note:

1. These parameters are for design guidance only and are not production tested.

4.13 TWI

Figure 4-6. TWI - Timing Requirements



Table 4-19. TWI - Timing Characteristics

Symbol(1)	**Description**	**Condition**	**Min.**	**Typ.**	**Max.**	**Unit**
f_{SCL}	SCL clock frequency	Max. frequency requires system clock at 10 MHz, which, in turn, requires V_{DD}=[2.7, 5.5]V and T=[-40, 105]°C	0	-	1000	kHz
V_{IH}	Input high voltage		$0.7 \times V_{DD}$	-	-	V
V_{IL}	Input low voltage		-	-	$0.3 \times V_{DD}$	V

.....continued

Symbol[(1)]	Description	Condition		Min.	Typ.	Max.	Unit
V_{HYS}	Hysteresis of Schmitt trigger inputs			$0.1 \times V_{DD}$		$0.4 \times V_{DD}$	V
V_{OL}	Output low voltage	I_{load}=20 mA, Fast mode+		-	-	$0.2xV_{DD}$	V
		I_{load}=3 mA, Normal mode, V_{DD}>2V		-	-	0.4V	
		I_{load}=3 mA, Normal mode, V_{DD}≤2V		-	-	$0.2 \times V_{DD}$	
I_{OL}	Low-level output current	f_{SCL}≤400 kHz, V_{OL}=0.4V		3	-	-	mA
		f_{SCL}≤1 MHz, V_{OL}=0.4V		20	-	-	
C_B	Capacitive load for each bus line	f_{SCL}≤100 kHz		-	-	400	pF
		f_{SCL}≤400 kHz		-	-	400	
		f_{SCL}≤1 MHz		-	-	550	
t_R	Rise time for both SDA and SCL	f_{SCL}≤100 kHz		-	-	1000	ns
		f_{SCL}≤400 kHz		20	-	300	
		f_{SCL}≤1 MHz		-	-	120	
t_{OF}	Output fall time from V_{IHmin} to V_{ILmax}	10 pF < capacitance of bus line < 400 pF	f_{SCL}≤400 kHz	$20+0.1 \times C_B$	-	300	ns
			f_{SCL}≤1 MHz	$20+0.1 \times C_B$	-	120	
t_{SP}	Spikes suppressed by the input filter			0	-	50	ns
I_L	Input current for each I/O pin	$0.1 \times V_{DD} < V_I < 0.9 \times V_{DD}$		-	-	1	µA
C_I	Capacitance for each I/O pin			-	-	10	pF
R_P	Value of pull-up resistor	f_{SCL}≤100 kHz		$(V_{DD}-V_{OL}(max)) / I_{OL}$	-	1000 ns/ $(0.8473 \times C_B)$	Ω
		f_{SCL}≤400 kHz		-	-	300 ns/ $(0.8473 \times C_B)$	
		f_{SCL}≤1 MHz		-	-	120 ns/ $(0.8473 \times C_B)$	
$t_{HD;STA}$	Hold time (repeated) Start condition	f_{SCL}≤100 kHz		4.0	-	-	µs
		f_{SCL}≤400 kHz		0.6	-	-	
		f_{SCL}≤1 MHz		0.26	-	-	

.....continued

Symbol[1]	Description	Condition	Min.	Typ.	Max.	Unit
t_{LOW}	Low period of SCL Clock	f_{SCL}≤100 kHz	4.7	-	-	µs
		f_{SCL}≤400 kHz	1.3	-	-	
		f_{SCL}≤1 MHz	0.5	-	-	
t_{HIGH}	High period of SCL Clock	f_{SCL}≤100 kHz	4.0	-	-	µs
		f_{SCL}≤400 kHz	0.6	-	-	
		f_{SCL}≤1 MHz	0.26	-	-	
$t_{SU;STA}$	Setup time for a repeated Start condition	f_{SCL}≤100 kHz	4.7	-	-	µs
		f_{SCL}≤400 kHz	0.6	-	-	
		f_{SCL}≤1 MHz	0.26	-	-	
$t_{HD;DAT}$	Data hold time	f_{SCL}≤100 kHz	0	-	3.45	µs
		f_{SCL}≤400 kHz	0	-	0.9	
		f_{SCL}≤1 MHz	0	-	0.45	
$t_{SU;DAT}$	Data setup time	f_{SCL}≤100 kHz	250	-	-	ns
		f_{SCL}≤400 kHz	100	-	-	
		f_{SCL}≤1 MHz	50	-	-	
$t_{SU;STO}$	Setup time for Stop condition	f_{SCL}≤100 kHz	4	-	-	µs
		f_{SCL}≤400 kHz	0.6	-	-	
		f_{SCL}≤1 MHz	0.26	-	-	
t_{BUF}	Bus free time between a Stop and Start condition	f_{SCL}≤100 kHz	4.7	-	-	µs
		f_{SCL}≤400 kHz	1.3	-	-	
		f_{SCL}≤1 MHz	0.5	-	-	

Note:

1. These parameters are for design guidance only and are not production tested.

4.14 VREF

Table 4-20. Internal Voltage Reference Characteristics

Symbol[1]	Description	Min.	Typ.	Max.	Unit
t_{start}	Start-up time	-	25	-	µs

.....continued					
Symbol(1)	**Description**	**Min.**	**Typ.**	**Max.**	**Unit**
V_{DD}	Power supply voltage range for 0V55	1.8	-	5.5	V
	Power supply voltage range for 1V1	1.8	-	5.5	
	Power supply voltage range for 1V5	1.8	-	5.5	
	Power supply voltage range for 2V5	3.0	-	5.5	
	Power supply voltage range for 4V3	4.8	-	5.5	

Note:

1. These parameters are for design guidance only and are not production tested.

Table 4-21. ADC Internal Voltage Reference Characteristics(1)

Symbol(2)	Description	Condition	Min.	Typ.	Max.	Unit
1V1	Internal reference voltage	V_{DD}=[1.8V, 5.5V] T=[0 - 105]°C	-2.0		2.0	%
0V55 1V5 2V5 4V3	Internal reference voltage	V_{DD}=[1.8V, 5.5V] T=[0 - 105]°C	-3.0		3.0	
0V55 1V1 1V5 2V5 4V3	Internal reference voltage	V_{DD}=[1.8V, 5.5V] T=[-40 - 125]°C	-5.0		5.0	

Note:

1. These values are based on characterization and not covered by production test limits.
2. The symbols xxxx refer to the respective values of the ADC0REFSEL bit field in the VREF.CTRLA register.

Table 4-22. AC Internal Voltage Reference Characteristics(1)

Symbol(2)	Description	Condition	Min.	Typ.	Max.	Unit
0V55 1V1 1V5 2V5	Internal reference voltage	V_{DD}=[1.8V, 5.5V] T=[0 - 105]°C	-3.0		3.0	%
0V55 1V1 1V5 2V5 4V3	Internal reference voltage	V_{DD}=[1.8V, 5.5V] T=[-40 - 125]°C	-5.0		5.0	

Note:

1. These values are based on characterization and not covered by production test limits.
2. The symbols xxxx refer to the respective values of the AC0REFSEL bit field in the VREF.CTRLA register.

4.15 ADC

4.15.1 Internal Reference Characteristics

Operating conditions:

- V_{DD} = 1.8 to 5.5V
- Temperature = -40°C to 125°C
- DUTYCYC = 25%
- CLK_{ADC} = 13 * f_{ADC}
- SAMPCAP is 10 pF for 0.55V reference, while it is set to 5 pF for V_{REF}≥1.1V
- Applies for all allowed combinations of V_{REF} selections and Sample Rates unless otherwise noted

Table 4-23. Power Supply, Reference, and Input Range

Symbol	Description	Conditions	Min.	Typ.	Max.	Unit
V_{DD}	Supply voltage	CLK_{ADC} ≤1.5 MHz	1.8	-	5.5	V
		CLK_{ADC} >1.5 MHz	2.7	-	5.5	
V_{REF}	Reference voltage	REFSEL = Internal reference	0.55	-	V_{DD}-0.5	V
		REFSEL = External reference	1.1		V_{DD}	
		REFSEL = V_{DD}	1.8	-	5.5	
C_{IN}	Input capacitance	SAMPCAP=5 pF	-	5	-	pF
		SAMPCAP=10 pF	-	10	-	
V_{IN}	Input voltage range		0	-	V_{REF}	V
I_{BAND}	Input bandwidth	1.1V≤V_{REF}	-	-	57.5	kHz

Table 4-24. Clock and Timing Characteristics(1)

Symbol	Description	Conditions	Min.	Typ.	Max.	Unit
f_{ADC}	Sample rate	1.1V≤V_{REF}	15	-	115	ksps
		1.1V≤V_{REF} (8-bit resolution)	15	-	150	
		V_{REF}=0.55V (10 bits)	7.5	-	20	
CLK_{ADC}	Clock frequency	V_{REF}=0.55V (10 bits)	100	-	260	kHz
		1.1V≤V_{REF} (10 bits)	200	-	1500	
		1.1V≤V_{REF} (8-bit resolution)	200	-	2000	
Ts	Sampling time		2	2	33	CLK_{ADC} cycles
T_{CONV}	Conversion time (latency)	Sampling time = 2 CLK_{ADC}	8.7	-	50	µs

.....continued						
Symbol	**Description**	**Conditions**	**Min.**	**Typ.**	**Max.**	**Unit**
T_{START}	Start-up time	Internal V_{REF}	-	22	-	µs

Note:

1. These parameters are for design guidance only and are not production tested.

Table 4-25. Accuracy Characteristics Internal Reference(2)

Symbol	Description	Conditions		Min.	Typ.	Max.	Unit
Res	Resolution			-	10	-	bit
INL	Integral Non-linearity	REFSEL = INTERNAL V_{REF}=0.55V	f_{ADC}=7.7 ksps	-	1.0	-	LSB
		REFSEL = INTERNAL or VDD	f_{ADC}=15 ksps	-	1.0	-	
		REFSEL = INTERNAL or VDD 1.1V≤V_{REF}	f_{ADC}=77 ksps	-	1.0	-	
			f_{ADC}=115 ksps	-	1.2	-	
DNL(1)	Differential Non-linearity	REFSEL = INTERNAL V_{REF} = 0.55V	f_{ADC}=7.7 ksps	-	0.6	-	LSB
		REFSEL = INTERNAL V_{REF} = 1.1V	f_{ADC}=15 ksps	-	0.4	-	
		REFSEL = INTERNAL or VDD 1.5V≤V_{REF}	f_{ADC}=15 ksps	-	0.4	-	
		REFSEL = INTERNAL or VDD 1.1V≤V_{REF}	f_{ADC}=77 ksps	-	0.4	-	
		REFSEL = INTERNAL 1.1V≤V_{REF}	f_{ADC}=115 ksps	-	0.5	-	
		REFSEL = VDD 1.8V≤V_{REF}	f_{ADC}=115 ksps	-	0.9	-	

.....continued

Symbol	Description	Conditions		Min.	Typ.	Max.	Unit
EABS	Absolute accuracy	REFSEL = INTERNAL V_{REF} = 1.1V	T=[0-105]°C V_{DD} = [1.8V-3.6V]	-	<10	-	LSB
			V_{DD} = [1.8V-3.6V]	-	<15	-	
		REFSEL = V_{DD}		-	2.5	-	
		REFSEL = INTERNAL		-	<35	-	
EGAIN	Gain error	REFSEL = INTERNAL V_{REF} = 1.1V	T=[0-105]°C V_{DD} = [1.8V-3.6V]	-	±15	-	LSB
			V_{DD} = [1.8V-3.6V]	-	±20	-	
		REFSEL = V_{DD}		-	2	-	
		REFSEL = INTERNAL		-	±35	-	
EOFF	Offset error	REFSEL = INTERNAL V_{REF} = 0.55V		-	-1	-	LSB
		REFSEL = INTERNAL 1.1V ≤ V_{REF}		-	-0.5	-	LSB

Note:

1. A DNL error of less than or equal to 1 LSB ensures a monotonic transfer function with no missing codes.
2. These parameters are for design guidance only and are not production tested.
3. Reference setting and f_{ADC} must fulfill the specification in “Clock and Timing Characteristics” and “Power supply, Reference, and Input Range” tables.

4.15.2 External Reference Characteristics

Operating conditions:

- V_{DD} = 1.8 to 5.5V
- Temperature = -40°C to 125°C
- DUTYCYC = 25%
- CLK_{ADC} = 13 * f_{ADC}
- SAMPCAP is 5 pF

The accuracy characteristics numbers are based on the characterization of the following input reference levels and V_{DD} ranges:

- Vref = 1.8V, V_{DD} = 1.8 to 5.5V
- Vref = 2.6V, V_{DD} = 2.7 to 5.5V
- Vref = 4.096V, V_{DD} = 4.5 to 5.5V

- Vref = 4.3V, V_{DD} = 4.5 to 5.5V

Table 4-26. ADC Accuracy Characteristics External Reference(2)

Symbol	Description	Conditions		Min.	Typ.	Max.	Unit
Res	Resolution			-	10	-	bit
INL	Integral Non-linearity		f_{ADC}=15 ksps	-	0.9	-	LSB
			f_{ADC}=77 ksps	-	0.9	-	
			f_{ADC}=115 ksps	-	1.2	-	
DNL(1)	Differential Non-linearity		f_{ADC}=15 ksps	-	0.2	-	LSB
			f_{ADC}=77 ksps	-	0.4	-	
			f_{ADC}=115 ksps	-	0.8	-	
EABS	Absolute accuracy		f_{ADC}=15 ksps	-	2	-	LSB
			f_{ADC}=77 ksps	-	2	-	
			f_{ADC}=115 ksps	-	2	-	
EGAIN	Gain error		f_{ADC}=15 ksps	-	2	-	LSB
			f_{ADC}=77 ksps	-	2	-	
			f_{ADC}=115 ksps	-	2	-	
EOFF	Offset error			-	-0.5	-	LSB

Note:

1. A DNL error of less than or equal to 1 LSB ensures a monotonic transfer function with no missing codes.
2. These parameters are for design guidance only and are not production tested.

4.16 AC

Table 4-27. Analog Comparator Characteristics, Low-Power Mode Disabled

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
V_{IN}	Input voltage		-0.2	-	V_{DD}	V
C_{IN}	Input pin capacitance	PD1 to PD6	-	3.5	-	pF
		PD7	-	14	-	
V_{OFF}	Input offset voltage	$0.7V<V_{IN}<(V_{DD}-0.7V)$	-20	±5	+20	mV
		V_{IN}=[-0.2V, V_{DD}]	-40	±20	+40	
I_L	Input leakage current		-	5	-	nA
T_{START}	Start-up time		-	1.3	-	µs

.....continued						
Symbol	**Description**	**Condition**	**Min.**	**Typ.**	**Max.**	**Unit**
V_{HYS}	Hysteresis	HYSMODE=0x0	-	0	-	mV
		HYSMODE=0x1	-	10	-	
		HYSMODE=0x2	-	25	-	
		HYSMODE=0x3	-	50	-	
t_{PD}	Propagation delay	25 mV Overdrive, V_{DD}≥2.7V	-	50	-	ns

Table 4-28. Analog Comparator Characteristics, Low-Power Mode Enabled

Symbol	Description	Condition	Min.	Typ.	Max.	Unit
V_{IN}	Input voltage		-0.2	-	V_{DD}	V
C_{IN}	Input pin capacitance	PD1 to PD6	-	3.5	-	pF
		PD7	-	14	-	
V_{OFF}	Input offset voltage	0.7V<V_{IN}<(V_{DD}-0.7V)	-30	±10	+30	mV
		V_{IN}=[0V, V_{DD}]	-50	±30	+50	
I_L	Input leakage current		-	5	-	nA
T_{START}	Start-up time		-	1.3	-	µs
V_{HYS}	Hysteresis	HYSMODE=0x0	-	0	-	mV
		HYSMODE=0x1	-	10	-	
		HYSMODE=0x2	-	25	-	
		HYSMODE=0x3	-	50	-	
t_{PD}	Propagation delay	25 mV overdrive, V_{DD}≥2.7V	-	150	-	ns

4.17 UPDI Timing

UPDI Enable Sequence (1)

Symbol	Description	Min.	Max.	Unit
T_{RES}	Duration of Handshake/Break on RESET	10	200	µs
T_{UPDI}	Duration of UPDI.txd=0	10	200	µs
T_{Deb0}	Duration of Debugger.txd=0	0.2	1	µs
T_{DebZ}	Duration of Debugger.txd=z	200	14000	µs

Note:

1. These parameters are for design guidance only and are not production tested.

4.18 Programming Time

See the table below for typical programming times for Flash and EEPROM.

Table 4-29. Programming Times

Symbol	Typical Programming Time
Page Buffer Clear	7 CLK_CPU cycles
Page Write	2 ms
Page Erase	2 ms
Page Erase-Write	4 ms
Chip Erase	4 ms
EEPROM Erase	4 ms

5. Typical Characteristics

5.1 Power Consumption

5.1.1 Supply Currents in Active Mode

Figure 5-1. Active Supply Current vs. Frequency (1-20 MHz) at T=25°C



Figure 5-2. Active Supply Current vs. Frequency [0.1, 1.0] MHz at T=25°C



Figure 5-3. Active Supply Current vs. Temperature (f=20 MHz OSC20M)



Figure 5-4. Active Supply Current vs. V_{DD} (f=[1.25, 20] MHz OSC20M) at T=25°C



Figure 5-5. Active Supply Current vs. V_{DD} (f=32.768 kHz OSCULP32K)



5.1.2 Supply Currents in Idle Mode

Figure 5-6. Idle Supply Current vs. Frequency (1-20 MHz) at T=25°C



Figure 5-7. Idle Supply Current vs. Low Frequency (0.1-1.0 MHz) at T=25°C



Figure 5-8. Idle Supply Current vs. Temperature (f=20 MHz OSC20M)



Figure 5-9. Idle Supply Current vs. V_{DD} (f=32.768 kHz OSCULP32K)



5.1.3 Supply Currents in Power-Down Mode

Figure 5-10. Power-Down Mode Supply Current vs. Temperature (all functions disabled)



Figure 5-11. Power-Down Mode Supply Current vs. V_{DD} (all functions disabled)



Figure 5-12. Power-Down Mode Supply Current vs. V_{DD} (all functions disabled)



5.1.4 Supply Currents in Standby Mode

Figure 5-13. Standby Mode Supply Current vs. V_{DD} (RTC running with internal OSCULP32K)



Figure 5-14. Standby Mode Supply Current vs. V_{DD} (Sampled BOD running at 125 Hz)



Figure 5-15. Standby Mode Supply Current vs. V_{DD} (Sampled BOD running at 1 kHz)



5.1.5 Power-on Supply Currents

Figure 5-16. Power-on Supply Current vs. V_{DD} (BOD enabled at 4.3V level)



5.2 GPIO

GPIO Input Characteristics

Figure 5-17. I/O Pin Input Hysteresis vs. V_{DD}



Figure 5-18. I/O Pin Input Threshold Voltage vs. V_{DD} (T=25°C)



Figure 5-19. I/O Pin Input Threshold Voltage vs. V_{DD} (V_{IH})



Figure 5-20. I/O Pin Input Threshold Voltage vs. V_{DD} (V_{IL})



GPIO Output Characteristics

Figure 5-21. I/O Pin Output Voltage vs. Sink Current (V_{DD}=1.8V)



Figure 5-22. I/O Pin Output Voltage vs. Sink Current (V_{DD}=3.0V)



Figure 5-23. I/O Pin Output Voltage vs. Sink Current (V_{DD}=5.0V)



Figure 5-24. I/O Pin Output Voltage vs. Sink Current (T=25°C)



Figure 5-25. I/O Pin Output Voltage vs. Source Current (V_{DD}=1.8V)



Figure 5-26. I/O Pin Output Voltage vs. Source Current (V_{DD}=3.0V)



Figure 5-27. I/O Pin Output Voltage vs. Source Current (V_{DD}=5.0V)



Figure 5-28. I/O Pin Output Voltage vs. Source Current (T=25°C)



GPIO Pull-Up Characteristics

Figure 5-29. I/O Pin Pull-Up Resistor Current vs. Input Voltage (V_{DD}=1.8V)



Figure 5-30. I/O Pin Pull-Up Resistor Current vs. Input Voltage (V_{DD}=3.0V)



Figure 5-31. I/O Pin Pull-Up Resistor Current vs. Input Voltage (V_{DD}=5.0V)



5.3 VREF Characteristics

Figure 5-32. Internal 0.55V Reference vs. Temperature



Figure 5-33. Internal 1.1V Reference vs. Temperature



Figure 5-34. Internal 2.5V Reference vs. Temperature



Figure 5-35. Internal 4.3V Reference vs. Temperature



5.4 BOD Characteristics

BOD Current vs. V_{DD}

Figure 5-36. BOD Current vs. V_{DD} (Continuous Mode Enabled)



Figure 5-37. BOD Current vs. V_{DD} (Sampled BOD at 125 Hz)



Figure 5-38. BOD Current vs. V_{DD} (Sampled BOD at 1 kHz)



BOD Threshold vs. Temperature

Figure 5-39. BOD Threshold vs. Temperature (Level 1.8V)



Figure 5-40. BOD Threshold vs. Temperature (Level 2.6V)



Figure 5-41. BOD Threshold vs. Temperature (Level 4.3V)



5.5 ADC Characteristics

Figure 5-42. Absolute Accuracy vs. V_{DD} (f_{ADC}=115 ksps) at T=25°C, REFSEL = Internal Reference



Figure 5-43. Absolute Accuracy vs. V_{ref} (V_{DD}=5.0V, f_{ADC}=115 ksps), REFSEL = Internal Reference



Figure 5-44. DNL Error vs. V_{DD} (f_{ADC}=115 ksps) at T=25°C, REFSEL = Internal Reference



Figure 5-45. DNL vs. V_{ref} (V_{DD}=5.0V, f_{ADC}=115 ksps), REFSEL = Internal Reference



Figure 5-46. Gain Error vs. V_{DD} (f_{ADC}=115 ksps) at T=25°C, REFSEL = Internal Reference



Figure 5-47. Gain Error vs. V_{ref} (V_{DD}=5.0V, f_{ADC}=115 ksps), REFSEL = Internal Reference



Figure 5-48. INL vs. V_{DD} (f_{ADC}=115 ksps) at T=25°C, REFSEL = Internal Reference



Figure 5-49. INL vs. V_{ref} (V_{DD}=5.0V, f_{ADC}=115 ksps), REFSEL = Internal Reference



Figure 5-50. Offset Error vs. V_{DD} (f_{ADC}=115 ksps) at T=25°C, REFSEL = Internal Reference



Figure 5-51. Offset Error vs. V_{ref} (V_{DD}=5.0V, f_{ADC}=115 ksps), REFSEL = Internal Reference



Figure 5-52. Absolute Accuracy vs. V_{DD} (f_{ADC}=115 ksps, T=25°C), REFSEL = External Reference



Figure 5-53. Absolute Accuracy vs. V_{REF} (V_{DD}=5.0V, f_{ADC}=115 ksps, REFSEL = External Reference)



Figure 5-54. DNL vs. V_{DD} (f_{ADC}=115 ksps, T=25°C, REFSEL = External Reference)



Figure 5-55. DNL vs. V_{REF} (V_{DD}=5.0V, f_{ADC}=115 ksps, REFSEL = External Reference)



Figure 5-56. Gain vs. V_{DD} (f_{ADC}=115 ksps, T=25°C, REFSEL = External Reference)



Figure 5-57. Gain vs. V_{REF} (V_{DD}=5.0V, f_{ADC}=115 ksps, REFSEL = External Reference)



Figure 5-58. INL vs. V_{DD} (f_{ADC}=115 ksps, T=25°C, REFSEL = External Reference)



Figure 5-59. INL vs. V_{REF} (V_{DD}=5.0V, f_{ADC}=115 ksps, REFSEL = External Reference)



Figure 5-60. Offset vs. V_{DD} (f_{ADC}=115 ksps, T=25°C, REFSEL = External Reference)



Figure 5-61. Offset vs. V_{REF} (V_{DD}=5.0V, f_{ADC}=115 ksps, REFSEL = External Reference)



5.6 AC Characteristics

Figure 5-62. Hysteresis vs. V_{CM} - 10 mV (V_{DD}=5V)



Figure 5-63. Hysteresis vs. V_{CM} - 10 mV to 50 mV (V_{DD}=5V, T=25°C)



Figure 5-64. Offset vs. V_{CM} - 10 mV (V_{DD}=5V)



Figure 5-65. Offset vs. V_{CM} - 10 mV to 50 mV (V_{DD}=5V, T=25°C)



5.7 OSC20M Characteristics

Figure 5-66. OSC20M Internal Oscillator: Calibration Stepsize vs. Calibration Value (V_{DD}=3V)



Figure 5-67. OSC20M Internal Oscillator: Frequency vs. Calibration Value (V_{DD}=3V)



Figure 5-68. OSC20M Internal Oscillator: Frequency vs. Temperature



Figure 5-69. OSC20M Internal Oscillator: Frequency vs. V_{DD}



5.8 OSCULP32K Characteristics

Figure 5-70. OSCULP32K Internal Oscillator Frequency vs. Temperature



Figure 5-71. OSCULP32K Internal Oscillator Frequency vs. V_{DD}



6. Ordering Information

- Available ordering options can be found by:
  - Clicking on one of the following product page links:
    - ATmega809 Product Page
    - ATmega1609 Product Page
    - ATmega3209 Product Page
    - ATmega4809 Product Page
  - Searching by product name at microchipdirect.com
  - Contacting your local sales representative

Figure 6-1. Product Identification System

To order or obtain information, for example on pricing or delivery, refer to the factory or the listed sales office.



Note: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

7. Online Package Drawings

For the most recent package drawings:

1. Go to http://www.microchip.com/packaging.
2. Go to the package type specific page, for example VQFN.
3. Search for either Drawing Number or Style to find the most recent package drawings.

Table 7-1. Drawing Numbers

Package Type	Drawing Number	Style
UQFN48	C04-153	MV
TQFP48	C04-300	PT

8. Package Drawings

8.1 48-Pin TQFP

48-Lead Thin Quad Flatpack (PT) - 7x7x1.0 mm Body [TQFP]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



TOP VIEW



SIDE VIEW

Microchip Technology Drawing C04-300-PT Rev A Sheet 1 of 2

48-Lead Thin Quad Flatpack (PT) - 7x7x1.0 mm Body [TQFP]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



SECTION A-A

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Leads	N		48	
Lead Pitch	e		0.50 BSC	
Overall Height	A	-	-	1.20
Standoff	A1	0.05	-	0.15
Molded Package Thickness	A2	0.95	1.00	1.05
Foot Length	L	0.45	0.60	0.75
Footprint	L1		1.00 REF	
Foot Angle	ϕ	0°	3.5°	7°
Overall Width	E		9.00 BSC	
Overall Length	D		9.00 BSC	
Molded Package Width	E1		7.00 BSC	
Molded Package Length	D1		7.00 BSC	
Lead Thickness	c	0.09	-	0.16
Lead Width	b	0.17	0.22	0.27
Mold Draft Angle Top	α	11°	12°	13°
Mold Draft Angle Bottom	β	11°	12°	13°

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Chamfers at corners are optional; size may vary.
3. Dimensions D1 and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.25mm per side.
4. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

   REF: Reference Dimension, usually without tolerance, for information purposes only.
5. Datums A-B and D to be determined at center line between leads where leads exit plastic body at datum plane H

Microchip Technology Drawing C04-300-PT Rev A Sheet 2 of 2

48-Lead Thin Quad Flatpack (PT) - 7x7x1.0 mm Body [TQFP]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.50 BSC	
Contact Pad Spacing	C1		8.40	
Contact Pad Spacing	C2		8.40	
Contact Pad Width (X48)	X1			0.30
Contact Pad Length (X48)	Y1			1.50
Distance Between Pads	G	0.20		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2300-PT Rev A

Table 8-1. Device and Package Maximum Weight

140	mg

Table 8-2. Package Characteristics

Moisture Sensitivity Level	MSL3

Table 8-3. Package Reference

JEDEC Drawing Reference	MS-026
J-STD-609 Material Code	e3

Table 8-4. Package Code

Y8X

8.2 48-Pin UQFN

48-Lead Plastic Ultra Thin Quad Flat, No Lead Package (MV) – 6x6x0.5 mm Body [UQFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Microchip Technology Drawing C04-153A Sheet 1 of 2

48-Lead Plastic Ultra Thin Quad Flat, No Lead Package (MV) – 6x6x0.5 mm Body [UQFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Pins	N		48	
Pitch	e		0.40 BSC	
Overall Height	A	0.45	0.50	0.55
Standoff	A1	0.00	0.02	0.05
Contact Thickness	A3		0.127 REF	
Overall Width	E		6.00 BSC	
Exposed Pad Width	E2	4.45	4.60	4.75
Overall Length	D		6.00 BSC	
Exposed Pad Length	D2	4.45	4.60	4.75
Contact Width	b	0.15	0.20	0.25
Contact Length	L	0.30	0.40	0.50
Contact-to-Exposed Pad	K	0.20	-	-

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated.
3. Dimensioning and tolerancing per ASME Y14.5M.

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

   REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-153A Sheet 2 of 2

48-Lead Ultra Thin Plastic Quad Flat, No Lead Package (MV) - 6x6 mm Body [UQFN]
With 0.40 mm Contact Length

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.40 BSC	
Optional Center Pad Width	W2			4.45
Optional Center Pad Length	T2			4.45
Contact Pad Spacing	C1		6.00	
Contact Pad Spacing	C2		6.00	
Contact Pad Width (X28)	X1			0.20
Contact Pad Length (X28)	Y1			0.80
Distance Between Pads	G	0.20		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-2153A

Table 8-5. Device and Package Maximum Weight

TBD	mg

Table 8-6. Package Characteristics

Moisture Sensitivity Level	MSL1

Table 8-7. Package Reference

JEDEC Drawing Reference	MO-220
J-STD-609 Material Code	e3

Table 8-8. Package Code

R7X

9. Conventions

9.1 Memory Size and Type

Table 9-1. Memory Size and Bit Rate

Symbol	Description
KB	kilobyte (2^{10} = 1024)
MB	megabyte (2^{20} = 1024*1024)
GB	gigabyte (2^{30} = 1024*1024*1024)
b	bit (binary '0' or '1')
B	byte (8 bits)
1 kbit/s	1,000 bit/s rate (not 1,024 bit/s)
1 Mbit/s	1,000,000 bit/s rate
1 Gbit/s	1,000,000,000 bit/s rate
word	16-bit

9.2 Frequency and Time

Table 9-2. Frequency and Time

Symbol	Description
kHz	1 kHz = 10^3 Hz = 1,000 Hz
KHz	1 KHz = 1,024 Hz, 32 KHz = 32,768 Hz
MHz	1 MHz = 10^6 Hz = 1,000,000 Hz
GHz	1 GHz = 10^9 Hz = 1,000,000,000 Hz
ms	1 ms = 10^{-3}s = 0.001s
µs	1 µs = 10^{-6}s = 0.000001s
ns	1 ns = 10^{-9}s = 0.000000001s

10. Data Sheet Revision History

Note: The data sheet revision is independent of the die revision and the device variant (last letter of the ordering number).

10.1 Rev.B - 03/2019

Chapter	Changes
Entire Document	• Added ATmega809/ATmega1609 • Updated *Electrical Characteristics* section and *Typical Characteristics* section • Added package drawing for UQFN • Updated package drawing for TQFP

10.2 Rev. A - 02/2018

Initial release.

The Microchip Web Site

Microchip provides online support via our web site at http://www.microchip.com/. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Customer Change Notification Service

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at http://www.microchip.com/. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: http://www.microchip.com/support

Product Identification System

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.



Note: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Legal Notice

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting

from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, memBrain, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2019, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: 978-1-5224-4321-6

Quality Management System Certified by DNV

ISO/TS 16949

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: http://www.microchip.com/support Web Address: www.microchip.com **Atlanta** Duluth, GA Tel: 678-957-9614 Fax: 678-957-1455 **Austin, TX** Tel: 512-257-3370 **Boston** Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088 **Chicago** Itasca, IL Tel: 630-285-0071 Fax: 630-285-0075 **Dallas** Addison, TX Tel: 972-818-7423 Fax: 972-818-2924 **Detroit** Novi, MI Tel: 248-848-4000 **Houston, TX** Tel: 281-894-5983 **Indianapolis** Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380 **Los Angeles** Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800 **Raleigh, NC** Tel: 919-844-7510 **New York, NY** Tel: 631-435-6000 **San Jose, CA** Tel: 408-735-9110 Tel: 408-436-4270 **Canada - Toronto** Tel: 905-695-1980 Fax: 905-695-2078	**Australia - Sydney** Tel: 61-2-9868-6733 **China - Beijing** Tel: 86-10-8569-7000 **China - Chengdu** Tel: 86-28-8665-5511 **China - Chongqing** Tel: 86-23-8980-9588 **China - Dongguan** Tel: 86-769-8702-9880 **China - Guangzhou** Tel: 86-20-8755-8029 **China - Hangzhou** Tel: 86-571-8792-8115 **China - Hong Kong SAR** Tel: 852-2943-5100 **China - Nanjing** Tel: 86-25-8473-2460 **China - Qingdao** Tel: 86-532-8502-7355 **China - Shanghai** Tel: 86-21-3326-8000 **China - Shenyang** Tel: 86-24-2334-2829 **China - Shenzhen** Tel: 86-755-8864-2200 **China - Suzhou** Tel: 86-186-6233-1526 **China - Wuhan** Tel: 86-27-5980-5300 **China - Xian** Tel: 86-29-8833-7252 **China - Xiamen** Tel: 86-592-2388138 **China - Zhuhai** Tel: 86-756-3210040	**India - Bangalore** Tel: 91-80-3090-4444 **India - New Delhi** Tel: 91-11-4160-8631 **India - Pune** Tel: 91-20-4121-0141 **Japan - Osaka** Tel: 81-6-6152-7160 **Japan - Tokyo** Tel: 81-3-6880- 3770 **Korea - Daegu** Tel: 82-53-744-4301 **Korea - Seoul** Tel: 82-2-554-7200 **Malaysia - Kuala Lumpur** Tel: 60-3-7651-7906 **Malaysia - Penang** Tel: 60-4-227-8870 **Philippines - Manila** Tel: 63-2-634-9065 **Singapore** Tel: 65-6334-8870 **Taiwan - Hsin Chu** Tel: 886-3-577-8366 **Taiwan - Kaohsiung** Tel: 886-7-213-7830 **Taiwan - Taipei** Tel: 886-2-2508-8600 **Thailand - Bangkok** Tel: 66-2-694-1351 **Vietnam - Ho Chi Minh** Tel: 84-28-5448-2100	**Austria - Wels** Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 **Denmark - Copenhagen** Tel: 45-4450-2828 Fax: 45-4485-2829 **Finland - Espoo** Tel: 358-9-4520-820 **France - Paris** Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 **Germany - Garching** Tel: 49-8931-9700 **Germany - Haan** Tel: 49-2129-3766400 **Germany - Heilbronn** Tel: 49-7131-67-3636 **Germany - Karlsruhe** Tel: 49-721-625370 **Germany - Munich** Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 **Germany - Rosenheim** Tel: 49-8031-354-560 **Israel - Ra'anana** Tel: 972-9-744-7705 **Italy - Milan** Tel: 39-0331-742611 Fax: 39-0331-466781 **Italy - Padova** Tel: 39-049-7625286 **Netherlands - Drunen** Tel: 31-416-690399 Fax: 31-416-690340 **Norway - Trondheim** Tel: 47-72884388 **Poland - Warsaw** Tel: 48-22-3325737 **Romania - Bucharest** Tel: 40-21-407-87-50 **Spain - Madrid** Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 **Sweden - Gothenberg** Tel: 46-31-704-60-40 **Sweden - Stockholm** Tel: 46-8-5090-4654 **UK - Wokingham** Tel: 44-118-921-5800 Fax: 44-118-921-5820

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Microchip:

ATMEGA4809-AFR ATMEGA3209-MFR ATMEGA3209-AFR ATMEGA4809-MFR ATMEGA1609-AFR ATMEGA1609-MFR ATMEGA1609-AF ATMEGA1609-MF ATMEGA809-AFR ATMEGA809-MFR ATMEGA808-AF ATMEGA808-MF ATMEGA808-XF ATMEGA809-AF ATMEGA809-MF ATMEGA4809-MUR ATMEGA4809-AU ATMEGA4809-AUR ATMEGA4809-MF ATMEGA4809-AF ATMEGA4809-MU ATMEGA3209-AU ATMEGA3209-AUR ATMEGA809-AU ATMEGA1609-AU ATMEGA1609-MUR ATMEGA809-MUR ATMEGA1609-MU ATMEGA809-MU ATMEGA809-AUR ATMEGA3209-MF ATMEGA3209-MU ATMEGA3209-MUR ATMEGA3209-AF ATMEGA1609-AUR

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331