



RXJ Series

Features

- 105°C, 2,000 ~ 5,000 hours assured
- Low ESR, suitable for switching power supplies
- Smaller size with large permissible ripple current
- RoHS Compliance




Sleeve & Marking Color: Brown & White

Specifications

Items	Performance																																												
Category Temperature Range	6.3 ~ 63V					100V																																							
	-55°C ~ +105°C					-40°C ~ +105°C																																							
Capacitance Tolerance	±20% (at 120Hz, 20°C)																																												
Leakage Current (at 20°C)	I = 0.01CV or 3 (μA) whichever is greater (after 2 minutes) Where, C = rated capacitance in μF V = rated DC working voltage in V																																												
Tanδ (at 120Hz, 20°C)	<table><tr><td>Rated Voltage</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td></tr><tr><td>Tanδ (max)</td><td>0.22</td><td>0.19</td><td>0.16</td><td>0.14</td><td>0.12</td><td>0.10</td><td>0.09</td><td>0.08</td></tr></table>									Rated Voltage	6.3	10	16	25	35	50	63	100	Tanδ (max)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08																		
	Rated Voltage	6.3	10	16	25	35	50	63	100																																				
	Tanδ (max)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08																																				
When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.																																													
Low Temperature Characteristics (at 120Hz)	Impedance ratio shall not exceed the values given in the table below.																																												
	<table><tr><td>Rated Voltage</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>100</td></tr><tr><td>Impedance Ratio</td><td>Z(-55°C)/Z(+20°C)</td><td>4</td><td>4</td><td>3</td><td>3</td><td>3</td><td>3</td><td>3</td></tr></table>		Rated Voltage	6.3	10	16	25	35	50	63	100	Impedance Ratio	Z(-55°C)/Z(+20°C)	4	4	3	3	3	3	3																									
Rated Voltage	6.3	10	16	25	35	50	63	100																																					
Impedance Ratio	Z(-55°C)/Z(+20°C)	4	4	3	3	3	3	3																																					
Endurance	<table><tr><td>Test Time</td><td colspan="8">2,000 Hrs for ϕ D ≤ 8 mm; 5,000 Hrs for ϕ D ≥ 10 mm</td></tr><tr><td>Capacitance Change</td><td colspan="8">Within ±20% of initial value</td></tr><tr><td>Tanδ</td><td colspan="8">Less than 200% of specified value</td></tr><tr><td>Leakage Current</td><td colspan="8">Within specified value</td></tr></table>									Test Time	2,000 Hrs for ϕ D ≤ 8 mm; 5,000 Hrs for ϕ D ≥ 10 mm								Capacitance Change	Within ±20% of initial value								Tanδ	Less than 200% of specified value								Leakage Current	Within specified value							
	Test Time	2,000 Hrs for ϕ D ≤ 8 mm; 5,000 Hrs for ϕ D ≥ 10 mm																																											
	Capacitance Change	Within ±20% of initial value																																											
	Tanδ	Less than 200% of specified value																																											
Leakage Current	Within specified value																																												
* The above Specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied with rated ripple current for 2,000/5,000 hours at 105°C.																																													
Shelf Life Test	<table><tr><td>Test Time</td><td colspan="8">1,000 Hrs</td></tr><tr><td>Capacitance Change</td><td colspan="8">Within ±20% of initial value</td></tr><tr><td>Tanδ</td><td colspan="8">Less than 200% of specified value</td></tr><tr><td>Leakage Current</td><td colspan="8">Within specified value</td></tr></table>									Test Time	1,000 Hrs								Capacitance Change	Within ±20% of initial value								Tanδ	Less than 200% of specified value								Leakage Current	Within specified value							
	Test Time	1,000 Hrs																																											
	Capacitance Change	Within ±20% of initial value																																											
	Tanδ	Less than 200% of specified value																																											
Leakage Current	Within specified value																																												
* The above Specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied.																																													
Ripple Current & Frequency Multipliers	<table><tr><td rowspan="5">Cap.(μF) \ Freq.(Hz)</td><td>60 (50)</td><td>120</td><td>500</td><td>1k</td><td>10k</td><td>100k</td></tr><tr><td>Under 33</td><td>0.40</td><td>0.55</td><td>0.65</td><td>0.80</td><td>0.90</td><td>1.00</td></tr><tr><td>39 ~ 330</td><td>0.60</td><td>0.70</td><td>0.80</td><td>0.90</td><td>0.95</td><td>1.00</td></tr><tr><td>390 ~ 1,000</td><td>0.65</td><td>0.80</td><td>0.85</td><td>0.98</td><td>1.00</td><td>1.00</td></tr><tr><td>1,200 up above</td><td>0.80</td><td>0.90</td><td>0.95</td><td>0.98</td><td>1.00</td><td>1.00</td></tr></table>									Cap.(μF) \ Freq.(Hz)	60 (50)	120	500	1k	10k	100k	Under 33	0.40	0.55	0.65	0.80	0.90	1.00	39 ~ 330	0.60	0.70	0.80	0.90	0.95	1.00	390 ~ 1,000	0.65	0.80	0.85	0.98	1.00	1.00	1,200 up above	0.80	0.90	0.95	0.98	1.00	1.00	
	Cap.(μF) \ Freq.(Hz)	60 (50)	120	500	1k	10k	100k																																						
		Under 33	0.40	0.55	0.65	0.80	0.90	1.00																																					
		39 ~ 330	0.60	0.70	0.80	0.90	0.95	1.00																																					
		390 ~ 1,000	0.65	0.80	0.85	0.98	1.00	1.00																																					
1,200 up above		0.80	0.90	0.95	0.98	1.00	1.00																																						

Diagram of Dimensions



Lead Spacing and Diameter							Unit: mm
ϕD	5	6.3	8	10	12.5	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
ϕd	0.5		0.6			0.8	
α	L<20: 1.5, L $\geq$ 20: 2.0						
β	0.5						



Dimension: $\phi D \times L(mm)$

Ripple Current: mA/rms at 100k Hz, 105°C

Dimension & Permissible Ripple Current

V. DC Item μF	6.3V (0J)					10V (1A)					16V (1C)				
	$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)	
		20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz
33											5×11	1.30	3.90	108	154
39											5×11	1.30	3.90	108	154
47						5×11	2.10	5.50	78	111	6.3×11	0.60	1.80	182	260
56						5×11	1.90	4.80	85	121	6.3×11	0.60	1.80	182	260
68						5×11	1.30	3.90	108	154	6.3×11	0.60	1.80	182	260
100	5×11	1.30	3.90	108	154	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260
220	6.3×11	0.60	1.80	182	260	8×11.5	0.33	0.99	280	400	8×11.5	0.33	0.99	320	400
330	8×11.5	0.33	0.88	280	400	8×11.5	0.33	0.99	280	400	10×12.5	0.25	0.75	360	510
390	8×11.5	0.33	0.88	320	400	10×12.5	0.27	0.75	410	510	10×16	0.19	0.57	510	635
470	10×12.5	0.25	0.75	410	510	10×12.5	0.25	0.75	410	510	10×16	0.19	0.57	510	635
560	10×12.5	0.25	0.75	410	510	10×16	0.19	0.57	510	635	10×20	0.14	0.42	775	860
680	10×16	0.19	0.57	510	635	10×16	0.19	0.57	510	635	10×20	0.14	0.42	775	860
1,000	10×20	0.14	0.42	690	860	10×20	0.14	0.37	690	860	12.5×20	0.085	0.26	1,000	1,250
1,200	10×20	0.14	0.42	775	860	10×25	0.12	0.30	930	1,030	12.5×20	0.085	0.26	1,125	1,250
2,200	12.5×20	0.085	0.26	1,125	1,250	12.5×25	0.070	0.21	1,200	1,355	12.5×25	0.070	0.21	1,200	1,355
3,300	12.5×25	0.070	0.21	1,200	1,355	12.5×25	0.070	0.21	1,200	1,355	16×31.5	0.048	0.14	1,830	2,030
4,700	16×25	0.060	0.18	1,595	1,770	16×31.5	0.048	0.14	1,830	2,030	16×35.5	0.044	0.13	2,065	2,295

V. DC Item μF	25V (1E)					35V (1V)					50V (1H)				
	$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)	
		20°C	-10°C	120Hz	100KHz		20°C	-10°C	120Hz	100KHz		20°C	-10°C	120Hz	100KHz
2.2											5×11	4.0	12.0	48	88
3.3											5×11	3.50	11.0	52	94
4.7											5×11	3.00	9.00	55	100
6.8											5×11	3.00	9.00	55	100
10											5×11	2.00	6.00	68	124
22						5×11	1.30	3.90	108	154	6.3×11	0.60	1.80	143	260
33	5×11	1.30	3.90	108	154	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	143	260
39	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260
47	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260	8×11.5	0.33	0.99	320	400
56	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260	8×11.5	0.33	0.99	320	400
68	6.3×11	0.60	1.80	182	260	6.3×11	0.60	1.80	182	260	8×11.5	0.33	0.99	320	400
100	8×11.5	0.33	0.99	320	400	8×11.5	0.33	0.99	320	400	10×16	0.19	0.57	445	635
220	10×12.5	0.25	0.75	360	510	10×16	0.19	0.57	445	635	10×25	0.12	0.30	825	1,030
330	10×16	0.19	0.57	445	635	10×20	0.12	0.42	600	860	12.5×20	0.085	0.26	875	1,250
390	10×20	0.14	0.42	775	965	10×25	0.12	0.30	930	1,030	12.5×25	0.070	0.21	1,085	1,355
470	10×20	0.14	0.42	775	965	12.5×20	0.085	0.26	1,000	1,250	12.5×25	0.070	0.21	1,085	1,355
560	10×25	0.12	0.30	930	1,030	12.5×20	0.085	0.26	1,000	1,250	12.5×25	0.070	0.21	1,085	1,355
680	12.5×20	0.085	0.26	1,000	1,250	12.5×25	0.070	0.21	1,085	1,355	16×25	0.060	0.18	1,415	1,770
1,000	12.5×25	0.070	0.23	1,080	1,355	12.5×25	0.070	0.21	1,085	1,355	16×25	0.060	0.18	1,595	1,770
1,200	12.5×25	0.070	0.21	1,200	1,355	12.5×25	0.070	0.21	1,200	1,355	16×31.5	0.048	0.14	1,830	2,030
2,200	16×25	0.060	0.18	1,595	1,770	16×35.5	0.044	0.13	2,065	2,295	18×40	0.037	0.10	2,465	2,740
3,300	16×35.5	0.044	0.13	2,065	2,295	18×40	0.037	0.10	2,465	2,740					
4,700	18×40	0.037	0.10	2,465	2,740										



Dimension & Permissible Ripple Current Dimension: $\phi D \times L$ (mm)
Ripple Current: mA/rms at 100k Hz, 105°C

Dimension & Permissible Ripple Current						Ripple Current: mVrms at 100k Hz					
μ F	V. DC Item	63V (1J)				100V (2A)					
		ϕ D×L	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)		ϕ D×L	Impedance (Ω , Max/100k Hz)		Ripple Current (mA/rms, 105°C)	
			20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz
2.2							5×11	6.00	21.0	40	72
3.3							5×11	5.00	18.0	43	78
4.7							6.3×11	1.20	4.20	100	180
6.8							6.3×11	1.20	4.20	100	180
10		6.3×11	1.20	4.20	100	180	8×11.5	0.56	2.00	168	305
22		6.3×11	1.20	4.20	100	180	8×11.5	0.56	2.00	168	308
33		8×11.5	0.56	2.00	170	305	10×12.5	0.50	1.80	210	380
39		8×11.5	0.56	2.00	170	305	10×16	0.32	1.10	350	500
47		8×11.5	0.56	2.00	170	305	10×20	0.27	0.95	435	620
56		10×12.5	0.50	1.80	265	380	10×20	0.27	0.95	435	620
68		10×12.5	0.50	1.80	265	380	10×25	0.21	0.63	530	760
100		10×20	0.27	0.95	435	620	12.5×20	0.16	0.56	625	890
220		12.5×20	0.094	0.24	570	820	16×25	0.090	0.32	1,010	1,440
330		12.5×25	0.073	0.21	770	1,100	16×31.5	0.060	0.17	1,255	1,790
390		12.5×25	0.073	0.21	770	1,100	16×35.5	0.056	0.14	1,650	2,065
470		16×25	0.060	0.18	1,420	1,770					
560		16×31.5	0.048	0.14	1,625	2,030					
680		16×31.5	0.048	0.14	1,625	2,030					
1,000		18×35.5	0.041	0.11	1,790	2,240					

Part Numbering System

RXJ series	470 μF	±20%	6.3V	Bulk Package	Gas Type	10 ϕ ×12.5L	Pb-free and PET sleeve
<u>RXJ</u>	<u>471</u>	<u>M</u>	<u>0J</u>	<u>BK</u>	<u>-</u>	<u>1012</u>	
Series	Capacitance	Capacitance Tolerance	Rated Voltage	Lead Configuration & Package	Rubber Type	Case Size	Lead Wire and Sleeve type

Note: For more details, please refer to "Part Numbering System (Radial Type)" on page 10.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331