

1192A Non-Paired - Four-Conductor Star Quad, Low-Impedance Cable

| | | |
|---|--|---|
|  |  | <p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> |
|---|--|---|

Description:

24 AWG stranded (42x40) high-conductivity bare copper conductors, polyethylene insulation, tinned copper braid shield (95% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

| | |
|----------------------------|------------------------|
| Number of Conductors | 4 |
| Total Number of Conductors | 4 |
| AWG | 24 |
| Stranding | 42x40 |
| Conductor Diameter | .024 in. |
| Conductor Material | SBC - Soft Bare Copper |

INSULATION:

| | |
|--------------------------------|-------------------|
| Insulation Material | PE - Polyethylene |
| Nom. Insulation Wall Thickness | .016 in. |
| Insulation Diameter | .056 in. |

OVERALL CABLING:

Overall Cabling Color Code Chart :

| Number | Color | Number | Color |
|--------|-------|--------|---------------------|
| 1 | Blue | 3 | Blue w/White Stripe |
| 2 | White | 4 | White w/Blue Stripe |

OUTER SHIELD:

| | |
|-------------------------|--------------------|
| Outer Shield Type | Braid |
| Outer Shield Material | TC - Tinned Copper |
| Outer Shield % Coverage | 95 % |

OUTER JACKET:

| | |
|-------------------------------------|--------------------------|
| Outer Jacket Material | PVC - Polyvinyl Chloride |
| Outer Jacket Nominal Wall Thickness | .045 in. |

OVERALL NOMINAL DIAMETER:

| | |
|--------------------------|----------|
| Overall Nominal Diameter | .245 in. |
|--------------------------|----------|

MECHANICAL CHARACTERISTICS:

1192A Non-Paired - Four-Conductor Star Quad, Low-Impedance Cable

| | |
|----------------------------------|-----------------|
| Operating Temperature Range | -30°C To +75°C |
| Non-UL Temperature Rating | 75°C |
| Bulk Cable Weight | 33 lbs/1000 ft. |
| Max. Recommended Pulling Tension | 21 lbs. |
| Min. Bend Radius (Install) | 2.45 in. |

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

| | |
|---------------------------------------|------------|
| EU CE Mark (Y/N) | Yes |
| EU RoHS Compliant (Y/N) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |

PLENUM/NON-PLENUM:

| | |
|--------------|---|
| Plenum (Y/N) | N |
|--------------|---|

ELECTRICAL CHARACTERISTICS:

| | |
|---|-------------------|
| Nom. Characteristic Impedance | 40 Ohms |
| Nom. Inductance | .21 µH/ft |
| Nom. Capacitance Conductor to Conductor @ 1 KHz | 39.2 pF/ft |
| Nom. Cap. Between Cond. in a Quad Config. @ 1 KHz | 57.4 pF/ft |
| Nominal Velocity of Propagation | 66 % |
| Nom. Conductor DC Resistance @ 20 Deg. C | 26.6 Ohms/1000 ft |
| Nominal Outer Shield DC Resistance @ 20 Deg. C | 7.1 Ohms/1000 ft |
| Max. Operating Voltage - UL | 100 V RMS |

Max. Operating Voltage - Other :

| Other Voltage | Description |
|---------------|---|
| 18.0 kV | Nom. breakdown voltage between conductors |
| 16.9 kV | Nom. breakdown voltage conductors to shield |

| | |
|-----------------------------------|---|
| Max. Recommended Current | 2.9 Amps per conductor @ 25°C |
| Other Electrical Characteristic 1 | 2/c 21 AWG equivalent DCR when connected to a 3-pin XLR |

NOTES:

| | |
|-------|---|
| Notes | Quad connection scheme: The two blue wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the two white wires (or remaining wires) are connected together to form the second conductor. |
|-------|---|

PUT-UPS AND COLORS:

| Item | Description | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|---------------|----------------------------|--------------|--------------------|--------------|-------|
| 1192A B59100 | 4 #24 PE SH PVC BLK MTT | 100 | 3.3 | BLACK, MATTE | |
| 1192A B591000 | 4 #24 PE SH PVC BLK MTT | 1000 | 37 | BLACK, MATTE | C |
| 1192A B59500 | 4 #24 PE SH PVC BLK MTT | 500 | 16.5 | BLACK, MATTE | C |

1192A Non-Paired - Four-Conductor Star Quad, Low-Impedance Cable

| | | | | | |
|---------------|----------------------------|------|------|---------------|---|
| 1192A G7V1000 | 4 #24 PE SH PVC RED MTT | 1000 | 37 | RED, MATTE | C |
| 1192A G7W1000 | 4 #24 PE SH PVC GRN MTT | 1000 | 37 | GREEN, MATTE | C |
| 1192A G7X1000 | 4 #24 PE SH PVC BLU MTT | 1000 | 37 | BLUE, MATTE | C |
| 1192A G7X500 | 4 #24 PE SH PVC BLU MTT | 500 | 16.5 | BLUE, MATTE | |
| 1192A G8M1000 | 4 #24 PE SH PVC YEL MTT | 1000 | 37 | YELLOW, MATTE | |
| 1192A U901000 | 4 #24 PE SH PVC GRY MTT | 1000 | 37 | GRAY, MATTE | C |

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 07-27-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331