

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N3009
2N3013
2N3014

NPN SILICON HIGH SPEED
SWITCHING TRANSISTORS

JEDEC TO-18 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N3009, 2N3013, 2N3014 types are Silicon NPN switching Transistors designed for high speed, medium power saturated switching applications.

MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

	SYMBOL	2N3009	2N3013	2N3014	UNIT
Collector-Base Voltage	V _{CB0}	40	40	40	V
Collector-Emitter Voltage	V _{CES}	40	40	40	V
Collector-Emitter Voltage	V _{CEO}	15	15	20	V
Emitter-Base Voltage	V _{EBO}	4.0	5.0	5.0	V
Collector Current	I _C	200	200	200	mA
Collector Current Peak (10μs pulse)	I _C	500	500	500	mA
Power Dissipation	P _D	360	360	300	mW
Power Dissipation (T _C =25°C)	P _D	1.2	1.2	1.2	W
Oper. and Storage Junction Temp.	T _J , T _{stg}		-65 TO +200		°C

ELECTRICAL CHARACTERISTICS (T_A=25°C)

SYMBOL	TEST CONDITIONS	2N3009		2N3013		2N3014		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
I _{CES}	V _{CE} =20V		0.5		0.3		0.3	μA
I _B	V _{CE} =20V, V _{BE} =0		0.5		0.3		0.3	μA
BV _{CB0}	I _C =100μA	40		40		40		V
BV _{CES}	I _C =100μA	40		40		40		V
BV _{CEO}	I _C =10mA	15		15		20		V
BV _{EBO}	I _E =100μA	4.0		5.0		5.0		V
V _{CE} (SAT)	I _C =30mA, I _B =3.0mA		0.18		0.18		0.18	V
V _{CE} (SAT)	I _C =100mA, I _B =10mA		0.28		0.28		0.35	V
V _{CE} (SAT)	I _C =300mA, I _B =30mA		0.5		0.5		-	V
V _{CE} (SAT)	I _C =10mA, I _B =1.0mA		-		-		0.18	V
V _{BE} (SAT)	I _C =30mA, I _B =3.0mA	0.75	0.95	0.75	0.95	0.75	0.95	V
V _{BE} (SAT)	I _C =100mA, I _B =10mA		1.2		1.2		1.2	V
V _{BE} (SAT)	I _C =300mA, I _B =30mA		1.7		1.7		-	V
V _{BE} (SAT)	I _C =10mA, I _B =1.0mA	-	-	-	-	0.7	0.8	V
h _{FE}	V _{CE} =0.4V, I _C =30mA	30	120	30	120	30	120	
h _{FE}	V _{CE} =0.4V, I _C =10mA	-	-	-	-	25	-	
h _{FE}	V _{CE} =0.5V, I _C =100mA	25	-	25	-	-	-	
h _{FE}	V _{CE} =1.0V, I _C =100mA	-	-	-	-	25	-	
h _{FE}	V _{CE} =1.0V, I _C =300mA	15	-	15	-	-	-	
f _T	V _{CE} =10V, I _C =30mA, f=100MHz	350	-	350	-	350	-	MHz
C _{ob}	V _{CB} =5.0V, I _E =0, f=140kHz		5.0		5.0		5.0	pF
C _{ib}	V _{BE} =0.5, I _C =0, f=140kHz		8.0		8.0		8.0	pF
t _{on}	V _{CC} =15V, I _C =300mA, I _{B1} ≈30mA		15		15		-	ns
t _{on}	V _{CC} =2.0V, I _C =30mA, I _{B1} ≈3.0mA		-		-		16	ns
t _{off}	V _{CC} =15V, I _C =300mA, I _{B1} ≈I _{B2} ≈30mA		25		25		-	ns
t _{off}	V _{CC} =2.0V, I _C =30mA, I _{B1} ≈I _{B2} ≈3.0mA		-		-		25	ns
τ _s	I _C ≈I _{B1} ≈I _{B2} ≈10mA		18		18		18	ns

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331