


- Unmatched performance thanks to dual ARM Cortex-A9 @ 800MHz
- All memories you need: on-board NOR and NAND Flash
- Enabling smarter system thanks to Artix-7 FPGA integrated on chip
- FPGA banks wide range PSU input from 1.2V to 3.3V
- Highest security and reliability: internal voltage monitoring and power good enable
- Reduced carrier complexity: dual CAN, USB, Ethernet GB and native 3.3V I/O
- Easy to fit thanks to its small form factor
- Accurate timing application thanks to on-board 5ppm RTC



XILINX®

BORA is the new top-class Dual Cortex-A9 + FPGA CPU module by DAVE Embedded Systems, based on the recent Xilinx Zynq XC7Z010/XC7Z020 application processor. Thanks to BORA, customers are going to save time and resources by using a compact solution that includes both a CPU and an FPGA, avoiding complexities on the carrier PCB.

The use of this processor enables extensive system-level differentiation of new applications in many industry fields, where high-performance and extremely compact form factor (85mm x 50mm) are key factors. Smarter system designs are made possible, following the trends in functionalities and interfaces of the new, state-of-the-art embedded products.


BORA offers great computational power, thanks to the rich set of peripherals, the Dual Cortex-A9 and the Artix-7 FPGA together with a large set of high-speed I/Os (up to 5GHz).

BORA enables designers to create rugged products suitable for harsh mechanical and thermal environments, allowing for the development of the most advanced and robust products.

Thanks to the tight integration between the ARM-based processing system and the on-chip programmable logic, designers are free to add virtually any peripheral or create custom accelerators that extend system performance and better match specific application requirements.

BORA is designed and manufactured according to DAVE Embedded Systems ULTRA Line specifications, in order to guarantee premium quality and technical value for customers who require top performances and flexibility.

BORA is suitable for high-end applications such as medical instrumentation, advanced communication systems, critical real-time operations and safety applications.



**CPU** Xilinx Dual ARM Cortex-A9 Zynq XC7Z010/XC7Z020 @ 800MHz

**Supervisor** On-board power supply supervision and power sequencer  
Watchdog and RTC

## Memory

**Cache** 32Kbyte instruction, 32Kbyte data, 512Kbyte L2 for each core

**SDRAM** Up to 1GB DDR3 @ 533MHz

**NOR** Bootable SPI NOR 8, 16, 32 MB

**NAND** All sizes, on request

**SRAM** 256 Kbyte

## Interfaces (full-spec models) \*

**LAN** Ethernet 10/100/1000 Mbps  
Additional RMII interface

**UART** up to 2x UART ports

**USB** up to 2 x 2.0 OTG ports

**CAN** up to 2 x CAN

**Debug** JTAG IEEE 1149.1 Test Access Port  
CoreSight™ and Program Trace Macrocell (PTM)

**Other** PC Card: 2 x SD/SDIO 2.0/MMC 3.31 compliant controllers  
up to 6 x I²C channels  
up to 6 x SPI channels  
GPIOs available

## FPGA

**Model** Artix-7

**Logic Cells** 28K to 56K

**LUTs** 17K to 53K

**Flip Flops** 35K to 100K

**RAM** 240KB to 560KB

**DSP Slices** 80 to 220

**Differential Pairs** up to 34 differential pairs for high freq. interfaces

## Mechanical

**Connectors** 3 x 140 pin 0.6mm pitch

**Size** 85mm x 50mm

**Temperature** Commercial (0°C / +70°C)  
Industrial (-40°C / +85°C)

## PSU

**Input** 3.3V, on-board voltage regulation

## Software



**Bootloader** U-Boot

**Multitasking** Linux 3.x.x

## Evaluation Kit


The BORA evaluation kit is available in a development kit that includes a SOM, a carrier board and all accessories required for immediate start-up.

\*: interface availability depends on pin multiplexing.  
Please contact your local FAE.



## Product code configurator \*

Family	Processor	NOR flash	DDR RAM	NAND flash	BOOT	Temp. range
DBR	A: XC7Z010-1	0= 0MB	1= 1GB	0= 0MB	0 = Nor Boot	C: Commercial temp.
	B: XC7Z010-2	3= 8MB	9= 512MB	1= 1024MB		
	C: XC7Z010-3	5= 32MB		2= 2048MB		0 / +70°C
	D: XC7Z020-1	6= 64MB		7= 128MB		I: Industrial temp.
	E: XC7Z020-2			8= 256MB		-40 / +85°C
	F: XC7Z020-3			9= 512MB		



© 2014 DAVE S.r.l.

All trademarks and registered trademarks are the property of their respective owners.

All features and specifications subject to change without notice.



**DAVE S.r.l.**  
Via Talponedo, 29/A  
33080 Porcia (PN) - ITALY  
Ph +390434921215  
Fax +3904341994030

[www.dave.eu](http://www.dave.eu)  
[wiki.dave.eu](http://wiki.dave.eu)  
[sales@dave.eu](mailto:sales@dave.eu)  
[support-bora@dave.eu](mailto:support-bora@dave.eu)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331