

Silver Line Series – Single & Multi-Output Linear

The Silver Line series follows the industry accepted footprint for open frame, linear power supplies. Standard screw terminal connections and optional covers are offered for safety considerations.






Applications

- Industrial Control Circuits and Components
- Instrumentation
- Drives
- CNC Machinery
- Equipment for food industry
- Microprocessor Circuits
- Analog Circuits
- Noise sensitive Circuitry and Sensors

Features

- Easy-to-install screw terminal connections
- Cover options
- Industry standard footprint
- Universal input and approvals (115/230 Vac)
- Low noise, extremely quiet DC output. For noise sensitive or analog circuitry.
- Fast transient response. Ideal for test applications.
- Built-in OVP on 5 V models and optional on 12, 15 and 24 V models
- Automatic resetting overload protection
- Short circuit protected
- Two year limited warranty

Certifications and Compliances

-  Recognized Component, ITE
 - UL 60950-1
-  Certified, ITE
 - CSA C22.2 CSA 60950-1
- 
 - IEC60950-1

Specifications

| Parameter | Condition | Limit |
|--|--|---|
| Input | | |
| Input Voltage | | 100/120/220/230/240 Vac Selectable |
| Input Frequency | | 47-63 Hz |
| Output | | |
| Line Regulation | for 10% change | 0.05% |
| Load Regulation | for 50% change | 0.05% |
| Ripple | | 3.0 mV maximum Peak-to-Peak |
| DC Output Adjustment Range | | ±5% Minimum |
| Overvoltage Protection | | All 5-Volt outputs include build-in OVP as standard (setting is 6.2 V ±0.4 V) OVP is optionally available on other types |
| Transient Response Time | at 50% Load Changes | 50 msec. |
| Overload Protection | | Automatic current limit foldback |
| Remote Sensing | Available to compensate for output voltage drop on selected models. | 0.5 Vdc |
| General | | |
| Operating Temperature Range | Derate to 40% at +70°C | 0 to +50°C |
| Storage Temperature Range | | -25°C to +85°C |
| Temperature Coefficient (Typical) | | 0.01% 0°C |
| Stability | After warm-up | ±.5% |
| EMI/RFI | Linear power supplies have inherently low conducted and radiate noise levels | For most system applications they will meet requirements of FCC Class B and VDE 0871 for Class B |
| Cover Option | Derate power by an additional 15% | |
| Cooling | Forced air. 20 CFM required for full rating Derate 30% without cooling | |

Specifications are typical. Load Regulation on outputs without Remote Sense, .1% typical.

SL Series Selection Table

| Catalog Number | Output 1 | Output 2 | Output 3 | Case |
|-------------------------------|--|---|---|------|
| SLS-05-030-1T | 5 V @ 3 A *2 | - | - | A |
| SLS-05-060-1T | 5 V @ 6 A *2 | - | - | B1 |
| SLS-05-090-1T | 5 V @ 9 A *2 | - | - | C |
| SLS-05-120-1T | 5 V @ 12 A *2 | - | - | I2 |
| SLS-12-017T1 | 12 V @ 1.7 A ² or 15 V @ 1.5 A | - | - | A |
| SLS-12-034T | 12 V @ 3.4 A ² | - | - | B1 |
| SLS-12-051T | 12 V @ 5.1 A ² | - | - | C |
| SLS-12-068T | 12 V @ 6.8 A ² | - | - | I2 |
| SLS-15-045T | 15 V @ 4.5 A ² | - | - | C |
| SLS-15-060T | 15 V @ 6 A ² | - | - | I2 |
| SLS-24-012T | 24 V @ 1.2 A v | - | - | A |
| SLS-24-024T | 24 V @ 2.4 A ² | - | - | B2 |
| SLS-24-036T | 24 V @ 3.6 A ² | - | - | C |
| SLS-24-048T | 24 V @ 4.8 A ² | - | - | I2 |
| SLS-24-072T | 24 V @ 7.2 A ² | - | - | K |
| SLS-24-120T | 24 V @ 12.0 A ² | - | - | L |
| SLD-12-1010-12T ¹ | 12 V @ 1 A or 15 V @ .8 A | -12 V @ 1 A or -15 V @ .8 | - | H1 |
| SLD-12-1818-12T ¹ | 12 V @ 1.8 A or 15 V @ 1.5 A | -12 V @ 1.8 A or -15 V @ 1.5 A | - | D |
| SLD-12-3434-12T | 12 V @ 3.4 A ² | -12 V @ 3.4 A ² | - | I3 |
| SLD-15-3030-15T | 15 V @ 3 A ² | -15 V @ 3 A ² | - | I3 |
| SLD-12-6034-05T | 5 V @ 6 A *2 | 12 V @ 3.4 A ² | - | I1 |
| SLD-12-3015-05T | 5 V @ 3 A *2 | 12 V @ 1.5 A | - | C1 |
| SLT 12-20404-12T ¹ | 5 V @ 2 A *2 | 12 V @ .4 A or 15 V @ .4 A | -12 V @ .4 A or -15 V @ .4 A | H2 |
| SLT 12-31010-12T1 | 5 V @ 3 A *2 | 12 V @ 1 A ² or 15 V @ .8 A | -12 V @ 1 A ² or -15 V @ .8 A | F |
| SLT 12-61818-12T1 | 5V @ 6A *2 | 12 V @ 1.8 A or 15 V @ 1.5 A | -12 V @ 1.8 A or -15 V @ 1.5 A | G2 |
| Over Voltage Protector (OVP) | | | | |
| SLO-12-000-1 | 6.2 V to 34 V Adjustable @ 8 A | For Cases B through K | | J1 |
| SLO-12-000-TB | 6.2 V to 34 V Adjustable @ 8 A | For Case A or Cases B through K (when used with a cover) | | J2 |

Notes:

* With Built-In OVP

- 12/15 Volt models are factory set for 12 Volt operation. 15 Volt operation is field adjustable.
2. With Remote Sense (R.S.)

Dimensions - inches (mm)



Case A



Case B

Cover Options

| Catalog Number | Description | Catalog Number | Description |
|----------------|------------------|----------------|------------------------------|
| SLCASA-CVR | Cover for Case A | SLCASI-CVR | Cover for Cases I1, I2, & I3 |
| SLCASB-CVR | Cover for Case B | SLCASK-CVR | Cover for Case K |
| SLCASC-CVR | Cover for Case C | SLCASL-CVR | Cover for Case L |

Note:

Covers are sold separately. When used, derate the power supply by 15% of its rated value.

Silver Line Dimensions (inches/mm)



Cases C and C1



Case D



Case F



Case G2



Cases H1 and H2

AC Input Jumper Connections

| For use at: | 100 Vac | 120 Vac | 220 Vac | 230/240 Vac |
|-------------|----------|----------|---------|-------------|
| Connect: | 1-3, 2-4 | 1-3, 2-4 | 2-3 | 2-3 |
| Apply AC: | 1 & 5 | 1 & 4 | 1 & 5 | 1 & 4 |

Silver Line Dimensions (inches/mm)



Cases I1, I2 and I3



Notes:

All dimensions in inches (mm). Dimensions may change and should not be used for construction purposes.

Be sure to specify the complete part number when ordering. Orders may be placed with your local SolaHD distributor.





Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331