

## Vitreous Wirewound Power Resistors



### FEATURES

- High dissipation
- Applicable standard: NFC 93214
- 3 models:
  - VNF traction lug
  - VNB rings
  - VNN collars
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL | POWER RATING<br>W | RESISTANCE RANGE<br>$\Omega$ | TOLERANCE<br>$\pm$ % | $U_{LIM.}$<br>V |
|--------------|-------------------|------------------------------|----------------------|-----------------|
| VN 42 x 362  | 600               | 8.2 to 470K                  | 5                    | 4500            |
| VN 30 x 250  | 320               | 4.7 to 390K                  | 5                    | 3000            |
| VN 30 x 153  | 200               | 3.3 to 270K                  | 5                    | 1700            |
| VN 25 x 168  | 180               | 2.7 to 270K                  | 5                    | 1900            |
| VN 25 x 138  | 145               | 2.7 to 180K                  | 5                    | 1400            |
| VN 25 x 110  | 120               | 2.7 to 120K                  | 5                    | 1000            |
| VN 25 x 84   | 85                | 2.2 to 82K                   | 5                    | 650             |
| VN 20 x 117  | 90                | 2.2 to 120K                  | 5                    | 1100            |
| VN 16 x 94   | 55                | 2.2 to 68K                   | 5                    | 900             |
| VN 13 x 70   | 35                | 2.2 to 56K                   | 5                    | 650             |
| VN 10 x 52   | 22                | 1.0 to 33K                   | 5                    | 450             |

### NFC 93214 CHARACTERISTICS

| GLOBAL MODEL              | $P_n$<br>W | RESISTANCE RANGE<br>$\Omega$ |                        |
|---------------------------|------------|------------------------------|------------------------|
|                           |            | $\varnothing$ 63 $\mu$ (1)   | $\varnothing$ 38 $\mu$ |
| VN 30 x 250 (RB 30 x 250) | 240        | 4.7 to 56K                   | 4.7 to 180K            |
| VN 25 x 168 (RB 25 x 168) | 140        | 2.7 to 33K                   | 2.7 to 100K            |
| VN 20 x 117 (RB 20 x 117) | 72         | 2.7 to 15K                   | 2.7 to 47K             |
| VN 13 x 70 (RB 13 x 70)   | 28         | 2.2 to 4.7K                  | 2.2 to 15K             |

**Note**






(1) Wire diameter set by standard

### TECHNICAL SPECIFICATIONS

| PARAMETER                   | UNIT              | RESISTOR CHARACTERISTICS       |
|-----------------------------|-------------------|--------------------------------|
| Temperature coefficient     | ppm/ $^{\circ}$ C | 75 ppm/ $^{\circ}$ C (typical) |
| Operating temperature range | $^{\circ}$ C      | -55 to +450                    |

### GENERAL CHARACTERISTICS

|              |            |
|--------------|------------|
| Core         | Ceramic    |
| Winding      | NiCr alloy |
| Coating      | Vitreous   |
| Ohmic values | E12        |

**DIMENSIONS in millimeters AND WEIGHT in g**
**VNF**

 Terminal for  
 $\varnothing 10, \varnothing 13$ 
**VNB**

**VNN**


| TYPE        | 42 x 362      | 30 x 250        | 30 x 153        | 25 x 168        | 25 x 138        | 25 x 110        | 25 x 84         | 20 x 117        | 16 x 94            | 13 x 70            | 10 x 52            |
|-------------|---------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------------|--------------------|--------------------|
| A           | 362 ± 7       | 250 ± 2         | 152.5 ± 2       | 168 ± 2         | 138 ± 2         | 110 ± 2         | 84 ± 2          | 117 ± 2         | 94 ± 2             | 70 ± 2             | 52 ± 1             |
| B + 0.5/- 0 | 30            | 25              | 25              | 24              | 24              | 24              | 24              | -               | -                  | 13                 | 6                  |
| b           | 43 ± 1.5      | 33 ± 1          | 33 ± 1          | 28.5 ± 1        | 28.5 ± 1        | 28.5 ± 1        | 28.5 ± 1        | 26 ± 0.7        | 22 ± 0.5           | 20 ± 0.5           | 18 ± 0.5           |
| D max.      | 46            | 33              | 33              | 28              | 28              | 28              | 28              | 23              | 19                 | 16                 | 13                 |
| D1          | -             | 31 ± 1          | 31 ± 1          | 26 ± 0.9        | 26 ± 0.9        | 26 ± 0.9        | 26 ± 0.9        | 21 ± 0.7        | 17 ± 0.6           | 13 ± 0.5           | 11 ± 0.6           |
| d           | 26 ± 0.5      | 17 min.         | 17 min.         | 17 ± 0.35       | 17 ± 0.35       | 17 ± 0.35       | 17 ± 0.35       | 12 ± 0.5        | 10 ± 0.3           | 7 ± 0.21           | 6.2<br>+ 0/- 2     |
| E           | 9 ± 0.5       | 9 ± 0.5         | 9 ± 0.5         | 6.5 ± 0.2       | 6.5 ± 0.2       | 6.5 ± 0.2       | 6.5 ± 0.2       | -               | -                  | 4.2 ± 0.2          | 3 ± 0.2            |
| e ± 1       | 18            | 13              | 13              | 9               | 9               | 9               | 9               | 9               | 8                  | 7                  | 7                  |
| F           | -             | 18<br>+ 0.5/- 0 | 18<br>+ 0.5/- 0 | 15<br>+ 0.5/- 0 | 15<br>+ 0.5/- 0 | 15<br>+ 0.5/- 0 | 15<br>+ 0.5/- 0 | 14<br>+ 0.5/- 0 | 12<br>+ 0.5/- 0    | 10.5<br>+ 0.5/- 0  | 8 ± 0.5            |
| g max.      | 88            | 63              | 63              | 55              | 55              | 55              | 55              | 48.5            | 40                 | 37                 | 34                 |
| H max.      | 72            | 62              | 62              | 53              | 53              | 53              | 53              | -               | -                  | 20.5               | 18                 |
| h ± 2       | 45            | 30              | 30              | 27              | 27              | 27              | 27              | -               | -                  | 7                  | 6                  |
| J           | 52 ± 1.5      | 39 ± 1          | 39 ± 1          | 33.5 ± 1        | 33.5 ± 1        | 33.5 ± 1        | 33.5 ± 1        | 31 ± 0.7        | 26.5 ± 0.5         | 24 ± 0.5           | 22 ± 0.5           |
| L max.      | 440           | 320             | 222.5           | 230             | 200             | 171             | 145             | -               | -                  | 93                 | 70                 |
| M           | 10<br>+ 3/- 0 | 5 ± 1.5         | 5 ± 1.5         | 6 ± 1.5         | 6 ± 1.5         | 6 ± 1.5         | 6 ± 1.5         | 5 ± 1.5         | 4 ± 1.5            | 3.5 ± 1.5          | 2 ± 1.5            |
| Ø           | 6.2 ± 0.5     | 5.7 ± 0.5       | 5.7 ± 0.5       | 5 ± 0.8         | 5 ± 0.8         | 5 ± 0.8         | 5 ± 0.8         | 5 ± 0.8         | 4.2<br>+ 0.3/- 0.1 | 4.2<br>+ 0.3/- 0.1 | 4.2<br>+ 0.3/- 0.1 |
| X ± 2       | 398           | 285             | 187.5           | 198             | 168             | 141             | 115             | -               | -                  | 81                 | 62                 |
| Mass        | 1300          | 380             | 250             | 250             | 200             | 160             | 75              | 85              | 40                 | 25                 | 16                 |

**SPECIFIC NON-INDUCTIVE "A" VN MODEL CHARACTERISTICS**


| TYPE              | 42 x 362A | 30 x 250A | 30 x 153A | 28 x 168A | 25 x 138A | 25 x 110A | 25 x 84A | 20 x 117A | 16 x 94A | 13 x 70A | 10 x 52A |
|-------------------|-----------|-----------|-----------|-----------|-----------|-----------|----------|-----------|----------|----------|----------|
| R <sub>min.</sub> | 8.2 Ω     | 4.7 Ω     | 3.3 Ω     | 2.7 Ω     | 2.7 Ω     | 2.7 Ω     | 2.2 Ω    | 2.2 Ω     | 2.2 Ω    | 2.2 Ω    | 1.0 Ω    |
| R <sub>max.</sub> | 1.5 kΩ    | 820 Ω     | 560 Ω     | 680 Ω     | 470 Ω     | 330 Ω     | 180 Ω    | 390 Ω     | 270 Ω    | 220 Ω    | 150 Ω    |

| PERFORMANCES          |  |                                |   |
|-----------------------|--|--------------------------------|---|
| TESTS                 | CONDITIONS                                   | NFC 93214 REQUIREMENTS         | TYPICAL VALUES                          |
| Overloads             | 10 P <sub>n</sub> (temp. nom.), 5 s          | 2 % or 0.05 Ω <sup>(1)</sup>   | 0.5 %                                   |
| Climatic              | -55 °C, 5 cycles, +200 °C                    | 3 % or 0.05 Ω <sup>(1)</sup>   | Insulated mounting > 10 <sup>2</sup> MΩ |
| Damp heat             | 56 days 95 % HR                              |                                |   |
| Thermal shocks        | P <sub>n</sub> -55 °C                        | 2 % or 0.05 Ω <sup>(1)</sup>   | 0.2 %                                   |
| Shocks                | Severity 50 A                                | 0.5 % or 0.05 Ω <sup>(1)</sup> | 0.25 %                                  |
| Vibrations            | Severity 55/10                               | 0.5 % or 0.05 Ω <sup>(1)</sup> | 0.25 %                                  |
| Strength of terminals | 40 N collar 60 Ncm rings                     | 1 % or 0.05 Ω <sup>(1)</sup>   | 0.1 %                                   |
| Endurance             | 500 cycles P <sub>n</sub><br>90 min / 30 min | 5 %                            | 1.5 %                                   |


**Note**

(1) The higher of either value.

**DISSIPATION**




Power P<sub>w</sub> as a Function of Surface Temperature  
P(W) = f(Temperature Surface)




Derating in Power as a Function of Ambient Temperature

**OVERLOADS**



Intermittent Overloads  
Exceptional Operation  
Initial Temperature < 70 °C  
k × P<sub>n</sub> = f(t)

**PERMISSIBLE ENERGY**



Repetitive Operation  
Energy as a Function of R<sub>n</sub>  
Pulse Duration < 100 ms  
E = f(R)



**OPTIONS** (Consult us)

- Other values than E12 series
- Intermediate terminals

| <b>PART NUMBER INFORMATION</b> |                 |                       |                    |            |
|--------------------------------|-----------------|-----------------------|--------------------|------------|
| <b>VNF</b>                     | <b>30 x 153</b> | <b>A</b>              | <b>100 Ω</b>       | <b>5 %</b> |
| MODEL                          | TYPE            | "A" FOR NON-INDUCTIVE | VALUE (E12 SERIES) | TOLERANCE  |



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331