

## 5582UG Multi-Conductor - Residential, Light Commercial and Institutional Applications



For more Information  
please call

1-800-Belden1

**General Description:**

Security & Alarm Cable, Rated-CM, 4-22 AWG solid bare copper conductors with polyolefin insulation, PVC jacket

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 4            | 22  | Solid     | BC - Bare Copper   |

Total Number of Conductors:

4

**Insulation**

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|---------------------|----------------------|
| PP - Polypropylene  | .006                 |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .015                      |

**Overall Cable**

Overall Cabling Color Code Chart:

| Color  |
|--------|
| Black  |
| Red    |
| Yellow |
| Green  |

Overall Nominal Diameter:

0.122 in.

**Mechanical Characteristics (Overall)**

|                                   |                 |
|-----------------------------------|-----------------|
| Operating Temperature Range:      | -20°C To +75°C  |
| UL Temperature Rating:            | 75°C            |
| Bulk Cable Weight:                | 13 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 31.200 lbs.     |
| Min. Bend Radius/Minor Axis:      | 1.200 in.       |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |            |
|---------------------------------------|------------|
| NEC(UL) Specification:                | CM         |
| NEC Articles:                         | 800        |
| CEC/C(UL) Specification:              | CM         |
| EU Directive 2011/65/EU (ROHS II):    | Yes        |
| EU CE Mark:                           | Yes        |
| EU Directive 2000/53/EC (ELV):        | Yes        |
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |

## ENGLISH MEASUREMENT VERSION

## 5582UG Multi-Conductor - Residential, Light Commercial and Institutional Applications

|                                |     |
|--------------------------------|-----|
| EU Directive 2003/11/EC (BFR): | Yes |
|--------------------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| CA Prop 65 (CJ for Wire & Cable): | Yes |
|-----------------------------------|-----|

|                             |     |
|-----------------------------|-----|
| MII Order #39 (China RoHS): | Yes |
|-----------------------------|-----|

**Flame Test**

|                |                   |
|----------------|-------------------|
| UL Flame Test: | UL1685 UL Loading |
|----------------|-------------------|

|                 |     |
|-----------------|-----|
| CSA Flame Test: | FT1 |
|-----------------|-----|

**Plenum/Non-Plenum**

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

**Electrical Characteristics (Overall)**

Nom. Conductor DC Resistance:

**DCR @ 20°C (Ohm/1000 ft)**

15.7

Max. Operating Voltage - UL:

**Voltage**

300 V RMS

Max. Recommended Current:

**Current**

2.2 Amps per conductor @ 25°C

**Put Ups and Colors:**

| Item #          | Putup    | Ship Weight | Color     | Notes | Item Desc      |
|-----------------|----------|-------------|-----------|-------|----------------|
| 5582UG U4FC1000 | 1,000 FT | 12.000 LB   | BEIGE U4F |       | 4 #22 PP FRPVC |
| 5582UG U4FC500  | 500 FT   | 6.000 LB    | BEIGE U4F |       | 4 #22 PP FRPVC |
| 5582UG U4FU1000 | 1,000 FT | 13.000 LB   | BEIGE U4F |       | 4 #22 PP FRPVC |
| 5582UG 001C500  | 500 FT   | 6.000 LB    | BROWN     |       | 4 #22 PP FRPVC |
| 5582UG 008C1000 | 1,000 FT | 12.000 LB   | GRAY      |       | 4 #22 PP FRPVC |
| 5582UG 008C500  | 500 FT   | 6.000 LB    | GRAY      |       | 4 #22 PP FRPVC |
| 5582UG 009C1000 | 1,000 FT | 12.000 LB   | WHITE     |       | 4 #22 PP FRPVC |
| 5582UG 009C500  | 500 FT   | 6.000 LB    | WHITE     |       | 4 #22 PP FRPVC |
| 5582UG 009U1000 | 1,000 FT | 13.000 LB   | WHITE     |       | 4 #22 PP FRPVC |

Revision Number: 1    Revision Date: 03-11-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331