DUAL N-CHANNEL ENHANCEMENT MODE MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(ON)}$ max	I_D max $T_A = 25°C$
60V	7.5Ω @ V_{GS} = 5V	0.23A

Description

This MOSFET has been designed to minimize the on-state resistance ($R_{DS(on)}$) and yet maintain superior switching performance, making it ideal for high efficiency power management applications.

Applications

- Motor control
- Power Management Functions

Features

- Dual N-Channel MOSFET
- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Ultra-Small Surface Mount Package
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Notes 3 & 4)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT363
- Case Material: Molded Plastic. "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish annealed over Alloy 42 leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208 e3
- Terminal Connections: See Diagram
- Weight: 0.006 grams (approximate)

SOT363

Top View



Top View
Internal Schematic

Ordering Information (Note 5)

Part Number	Qualification	Case	Packaging
2N7002DW-7-F	Commercial	SOT363	3,000/Tape & Reel
2N7002DWQ-7-F	Automotive	SOT363	3,000/Tape & Reel
2N7002DW-13-F	Commercial	SOT363	10,000/Tape & Reel
2N7002DWQ-13-F	Automotive	SOT363	10,000/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb_2O_3 Fire Retardants.
5. For packaging details, go to our website at http://www.diodes.com.

Marking Information



K72 = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: N = 2002)
M = Month (ex: 9 = September)

Date Code Key

Year	1998	1999	2000	2001	2002	2003	2004	…	2011	2012	2013	2014	2015	2016	2017
Code	J	K	L	M	N	P	R	…	Y	Z	A	B	C	D	E

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Units
Drain-Source Voltage			V_{DSS}	60	V
Drain-Gate Voltage $R_{GS} \leq 1.0M\Omega$			V_{DGR}	60	V
Gate-Source Voltage	Continuous		V_{GSS}	±20	V
	Pulsed		V_{GSS}	±40	V
Continuous Drain Current (Note 7) V_{GS} = 5V	Steady State	T_A = +25°C T_A = +70°C T_A = +100°C	I_D	0.23 0.18 0.14	A
Maximum Continuous Body Diode Forward Current (Note 7)			I_S	0.53	A
Pulsed Drain Current (10µs pulse, duty cycle = 1%)			I_{DM}	0.8	A

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Units
Total Power Dissipation (Note 6)	T_A = +25°C	P_D	0.31	W
	T_A = +70°C		0.2	
	T_A = +100°C		0.12	
Thermal Resistance, Junction to Ambient (Note 6)	Steady state	$R_{\theta JA}$	410	°C/W
Total Power Dissipation (Note 7)	T_A = +25°C	P_D	0.4	W
	T_A = +70°C		0.25	
	T_A = +100°C		0.15	
Thermal Resistance, Junction to Ambient (Note 7)	Steady state	$R_{\theta JA}$	318	°C/W
Thermal Resistance, Junction to Case (Note 7)	Steady state	$R_{\theta JC}$	135	°C/W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 8)							
Drain-Source Breakdown Voltage		BV_{DSS}	60	70	—	V	V_{GS} = 0V, I_D = 10µA
Zero Gate Voltage Drain Current	@ T_C = +25°C @ T_C = +125°C	I_{DSS}	—	—	1.0 500	µA	V_{DS} = 60V, V_{GS} = 0V
Gate-Body Leakage		I_{GSS}	—	—	±10	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS (Note 8)							
Gate Threshold Voltage		$V_{GS(th)}$	1.0	—	2.0	V	V_{DS} = V_{GS}, I_D = 250µA
Static Drain-Source On-Resistance	@ T_J = +25°C	$R_{DS\ (ON)}$	—	3.2	7.5	Ω	V_{GS} = 5.0V, I_D = 0.05A
	@ T_J = +125°C			4.4	13.5		V_{GS} = 10V, I_D = 0.5A
On-State Drain Current		$I_{D(ON)}$	0.5	1.0	—	A	V_{GS} = 10V, V_{DS} = 7.5V
Forward Transconductance		g_{FS}	80	—	—	mS	V_{DS} =10V, I_D = 0.2A
Diode Forward Voltage		V_{SD}	—	0.78	1.5	V	V_{GS} = 0V, I_S = 115mA
DYNAMIC CHARACTERISTICS (Note 9)							
Input Capacitance		C_{iss}	—	22	50	pF	V_{DS} = 25V, V_{GS} = 0V f = 1.0MHz
Output Capacitance		C_{oss}	—	11	25	pF	
Reverse Transfer Capacitance		C_{rss}	—	2.0	5.0	pF	
SWITCHING CHARACTERISTICS (Note 9)							
Turn-On Delay Time		$t_{D(on)}$	—	7.0	20	ns	V_{DD} = 30V, I_D = 0.2A, R_L = 150Ω, V_{GEN} = 10V, R_{GEN} = 25Ω
Turn-Off Delay Time		$t_{D(off)}$	—	11.0	20		

Notes:
6. Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout
7. Device mounted on FR-4 substrate PC board, 2oz copper, with thermal vias to bottom layer 1inch square copper plate
8. Short duration pulse test used to minimize self-heating effect.
9. Guaranteed by design. Not subject to product testing.

© Diodes Incorporated



Fig. 1 On-Region Characteristics



Fig. 2 On-Resistance vs. Drain Current



Fig. 3 On-Resistance vs. Junction Temperature



Fig. 4 On-Resistance vs. Gate-Source Voltage

Package Outline Dimensions

Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for latest version.



SOT363		
Dim	**Min**	**Max**
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Typ	
F	0.40	0.45
H	1.80	2.20
J	0	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.22
α	0°	8°
All Dimensions in mm		

© Diodes Incorporated

Suggested Pad Layout

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
Z	2.5
G	1.3
X	0.42
Y	0.6
C1	1.9
C2	0.65

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

www.diodes.com

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331