


# HSMF-C16x

## Miniature Bi-Color Surface Mount ChipLEDs



### Data Sheet



#### Description

This series of bi-color ChipLEDs is designed with the smallest footprint to achieve high density of components on board. They have the industry standard footprint of 1.6 mm x 0.8 mm and a height of only 0.5 mm. This makes them very suitable for cellular phone and mobile equipment backlighting and indication. They are available in a wide range of color combinations. In order to facilitate automated pick and place operation, these ChipLEDs are shipped in tape and reel, with 4000 units per reel. These parts are compatible with reflow soldering.

#### Features

- Small size
- 0603 industry standard footprint
- Diffused optics
- Operating temperature range of  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$
- Compatible with reflow soldering
- Available in various color combination
- Available in 8 mm tape on 7" (178 mm) diameter reels

#### Applications


- Keypad backlighting
- Symbol indicator
- LCD backlighting
- Pushbutton backlighting
- Front panel indicator

#### Device Selection Guide

| Part Number | Color                           | Package Description |
|-------------|---------------------------------|---------------------|
| HSMF-C162   | AlInGaP Red / AlInGaP Amber     | Untinted, Diffused  |
| HSMF-C163   | AlInGaP Red / InGaN Green       | Untinted, Diffused  |
| HSMF-C164   | AlInGaP Red / InGaN Blue        | Untinted, Diffused  |
| HSMF-C165   | High Efficiency Red / GaP Green | Untinted, Diffused  |
| HSMF-C166   | GaP Yellow / GaP Green          | Untinted, Diffused  |
| HSMF-C167   | GaP Orange / GaP Green          | Untinted, Diffused  |
| HSMF-C168   | InGaN Green / InGaN Blue        | Untinted, Diffused  |
| HSMF-C169   | AlInGaP Amber / InGaN Blue      | Untinted, Diffused  |

**CAUTION:** HSMF-C16x LEDs are class 1A ESD sensitive per JESD22-A114C.01 standard. Please observe appropriate precautions during handling and processing. Refer to Avago Technologies Application Note AN-1142 for additional details.

## Package Dimensions



| POLARITY | HSMF-C162 | HSMF-C163 | HSMF-C164 | HSMF-C165 | HSMF-C166 | HSMF-C167 | HSMF-C168 | HSMF-C169 |
|----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| ① — — ③  | AMBER     | GREEN     | BLUE      | GREEN     | GREEN     | GREEN     | BLUE      | BLUE      |
| ② — — ④  | RED       | RED       | RED       | RED       | YELLOW    | ORANGE    | GREEN     | AMBER     |

### NOTES:

- ALL DIMENSIONS IN MILLIMETERS (INCHES).
- TOLERANCE IS  $\pm 0.1$  MM ( $\pm 0.004$  IN.) UNLESS OTHERWISE SPECIFIED.

### Absolute Maximum Ratings for Each Die at $T_A = 25^\circ\text{C}$

| Parameter                         | AlInGaP                                     | InGaN | GaP | Units            |
|-----------------------------------|---------------------------------------------|-------|-----|------------------|
| DC Forward Current <sup>[1]</sup> | 20                                          | 10    | 20  | mA               |
| Power Dissipation                 | 48                                          | 38    | 52  | mW               |
| Reverse Voltage                   | 5                                           | 5     | 5   | V                |
| LED Junction Temperature          | 95                                          | 95    | 95  | $^\circ\text{C}$ |
| Operating Temperature Range       | -40 to +85                                  |       |     | $^\circ\text{C}$ |
| Storage Temperature Range         | -40 to +85                                  |       |     | $^\circ\text{C}$ |
| Soldering Temperature             | See reflow soldering profile (Figure 6 & 7) |       |     |                  |

### Note:

- Derate linearly as shown in Figure 4.

### Electrical Characteristics at $T_A = 25^\circ\text{C}$

| Color                        |       | Forward Voltage<br>$V_F$ (Volts) @ $I_F$ <sup>[1]</sup> |      | Reverse<br>Breakdown<br>$V_R$ (Volts)<br>@ $I_R = 100\ \mu\text{A}$ | Capacitance<br>$C$ (pF), @ $V_F = 0$ ,<br>$f = 1\ \text{MHz}$ | Thermal<br>Resistance<br>$R\theta_{J-PIN}$ ( $^\circ\text{C/W}$ ) |
|------------------------------|-------|---------------------------------------------------------|------|---------------------------------------------------------------------|---------------------------------------------------------------|-------------------------------------------------------------------|
|                              |       | Typ.                                                    | Max. | Min.                                                                | Typ.                                                          | Typ.                                                              |
| AlInGaP Red                  | 20 mA | 1.9                                                     | 2.4  | 5                                                                   | 15                                                            | 300                                                               |
| AlInGaP Amber                | 20 mA | 1.9                                                     | 2.4  | 5                                                                   | 11                                                            | 300                                                               |
| AlInGaP Red <sup>[2]</sup>   | 10 mA | 1.8                                                     | 2.3  | 5                                                                   | 15                                                            | 300                                                               |
| AlInGaP Amber <sup>[2]</sup> | 10 mA | 1.8                                                     | 2.3  | 5                                                                   | 11                                                            | 300                                                               |
| InGaN Green                  | 10 mA | 3.4                                                     | 3.8  | 5                                                                   | 35                                                            | 500                                                               |
| InGaN Blue                   | 10 mA | 3.4                                                     | 3.8  | 5                                                                   | 35                                                            | 500                                                               |
| HER                          | 20 mA | 1.95                                                    | 2.6  | 5                                                                   | 5                                                             | 325                                                               |
| GaP Orange                   | 20 mA | 2.2                                                     | 2.6  | 5                                                                   | 7                                                             | 325                                                               |
| GaP Yellow                   | 20 mA | 2.1                                                     | 2.6  | 5                                                                   | 6                                                             | 325                                                               |
| GaP Green                    | 20 mA | 2.2                                                     | 2.6  | 5                                                                   | 9                                                             | 325                                                               |

**Notes:**

1.  $V_F$  Tolerance:  $\pm 0.1\ \text{V}$ .
2. The product testing is based on 20 mA. This is for reference only.

### Optical Characteristics at $T_A = 25^\circ\text{C}$

| Color                        |       | Luminous Intensity<br>$I_v$ (mcd) @ $I_F$ <sup>[1]</sup> |      | Peak<br>Wavelength<br>$\lambda_{\text{peak}}$ (nm) | Color<br>Dominant<br>Wavelength<br>$\lambda_d$ <sup>[2]</sup> (nm) | Viewing Angle<br>$2\ \theta_{1/2}$ Degrees <sup>[3]</sup> | Luminous<br>Efficacy<br>$\eta_v$ (lm/W) |
|------------------------------|-------|----------------------------------------------------------|------|----------------------------------------------------|--------------------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------|
|                              |       | Min.                                                     | Typ. | Typ.                                               | Typ.                                                               | Typ.                                                      | Typ.                                    |
| AlInGaP Red                  | 20 mA | 28.5                                                     | 90   | 637                                                | 626                                                                | 120                                                       | 155                                     |
| AlInGaP Amber                | 20 mA | 28.5                                                     | 90   | 595                                                | 592                                                                | 120                                                       | 480                                     |
| AlInGaP Red <sup>[4]</sup>   | 10 mA | 11.2                                                     | 35   | 637                                                | 626                                                                | 120                                                       | 155                                     |
| AlInGaP Amber <sup>[4]</sup> | 10 mA | 11.2                                                     | 35   | 595                                                | 592                                                                | 120                                                       | 480                                     |
| InGaN Green                  | 10 mA | 18                                                       | 45   | 523                                                | 525                                                                | 120                                                       | 500                                     |
| InGaN Blue                   | 10 mA | 2.8                                                      | 10   | 468                                                | 470                                                                | 120                                                       | 80                                      |
| HER                          | 20 mA | 2.8                                                      | 10   | 636                                                | 621                                                                | 120                                                       | 145                                     |
| GaP Orange                   | 20 mA | 2.8                                                      | 8    | 605                                                | 604                                                                | 120                                                       | 380                                     |
| GaP Yellow                   | 20 mA | 2.8                                                      | 8    | 589                                                | 586                                                                | 120                                                       | 500                                     |
| GaP Green                    | 20 mA | 4.5                                                      | 15   | 570                                                | 572                                                                | 120                                                       | 595                                     |

**Notes:**

1. The luminous intensity  $I_v$  is measured at the peak of the spatial radiation pattern which may not be aligned with the mechanical axis of the lamp package.
2. The dominant wavelength  $\lambda_d$  is derived from the CIE Chromaticity Diagram and represents the perceived color of the device.
3.  $\theta_{1/2}$  is the off-axis angle where the luminous intensity is 1/2 the peak intensity.
4. The product testing is based on 20 mA. This is for reference purpose.

## Color Bin Limits<sup>[1]</sup>

| Green Color Bins <sup>[1]</sup> |       |       |
|---------------------------------|-------|-------|
| Dom. Wavelength (nm)            |       |       |
| Bin ID                          | Min.  | Max.  |
| A                               | 561.5 | 564.5 |
| B                               | 564.5 | 567.5 |
| C                               | 567.5 | 570.5 |
| D                               | 570.5 | 573.5 |
| E                               | 573.5 | 576.5 |

Tolerance:  $\pm 0.5$  nm

| Blue Color Bins <sup>[1]</sup> |       |       |
|--------------------------------|-------|-------|
| Dom. Wavelength (nm)           |       |       |
| Bin ID                         | Min.  | Max.  |
| A                              | 460.0 | 465.0 |
| B                              | 465.0 | 470.0 |
| C                              | 470.0 | 475.0 |
| D                              | 475.0 | 480.0 |

Tolerance:  $\pm 1$  nm

| Orange Color Bins <sup>[1]</sup> |       |       |
|----------------------------------|-------|-------|
| Dom. Wavelength (nm)             |       |       |
| Bin ID                           | Min.  | Max.  |
| A                                | 597.0 | 600.0 |
| B                                | 600.0 | 603.0 |
| C                                | 603.0 | 606.0 |
| D                                | 606.0 | 609.0 |
| E                                | 609.0 | 612.0 |
| F                                | 612.0 | 615.0 |

Tolerance:  $\pm 1$  nm

### Note:

1. Bin categories are established for classification of products. Products may not be available in all categories. Please contact your Avago representative for information on currently available bins.

| Yellow/Amber Color Bins <sup>[1]</sup> |       |       |
|----------------------------------------|-------|-------|
| Dom. Wavelength (nm)                   |       |       |
| Bin ID                                 | Min.  | Max.  |
| A                                      | 582.0 | 584.5 |
| B                                      | 584.5 | 587.0 |
| C                                      | 587.0 | 589.5 |
| D                                      | 589.5 | 592.0 |
| E                                      | 592.0 | 594.5 |
| F                                      | 594.5 | 597.0 |

Tolerance:  $\pm 0.5$  nm

| InGaN Green Color Bins <sup>[1]</sup> |       |       |
|---------------------------------------|-------|-------|
| Dom. Wavelength (nm)                  |       |       |
| Bin ID                                | Min.  | Max.  |
| A                                     | 515.0 | 520.0 |
| B                                     | 520.0 | 525.0 |
| C                                     | 525.0 | 530.0 |
| D                                     | 530.0 | 535.0 |

Tolerance:  $\pm 1$  nm

## Intensity ( $I_v$ ) Bin Limits<sup>[1]</sup>

| Bin ID | Intensity @ 20 mA (mcd) |         |
|--------|-------------------------|---------|
|        | Min.                    | Max.    |
| A      | 0.11                    | 0.18    |
| B      | 0.18                    | 0.29    |
| C      | 0.29                    | 0.45    |
| D      | 0.45                    | 0.72    |
| E      | 0.72                    | 1.10    |
| F      | 1.10                    | 1.80    |
| G      | 1.80                    | 2.80    |
| H      | 2.80                    | 4.50    |
| J      | 4.50                    | 7.20    |
| K      | 7.20                    | 11.20   |
| L      | 11.20                   | 18.00   |
| M      | 18.00                   | 28.50   |
| N      | 28.50                   | 45.00   |
| P      | 45.00                   | 71.50   |
| Q      | 71.50                   | 112.50  |
| R      | 112.50                  | 180.00  |
| S      | 180.00                  | 285.00  |
| T      | 285.00                  | 450.00  |
| U      | 450.00                  | 715.00  |
| V      | 715.00                  | 1125.00 |
| W      | 1125.00                 | 1800.00 |
| X      | 1800.00                 | 2850.00 |
| Y      | 2850.00                 | 4500.00 |

Tolerance:  $\pm 15\%$ .

### Note:

1. Bin categories are established for classification of products. Products may not be available in all categories. Please contact your Avago representative for information on currently available bins.





Figure 1. Relative intensity vs. wavelength.





Figure 2. Forward current vs. forward voltage.






Figure 3. Luminous intensity vs. forward current.




Figure 4. Maximum forward current vs. ambient temperature.




Figure 5. Relative intensity vs. angle.




Figure 6. Recommended reflow soldering profile.




Figure 7. Recommended Pb-free reflow soldering profile.




Figure 8. Recommended soldering pad pattern.





Figure 9. Reeling orientation.



NOTE:

1. ALL DIMENSIONS IN MILLIMETERS (INCHES).

Figure 10. Reel dimensions.





TABLE 1  
DIMENSIONS IN MILLIMETERS (INCHES)

| PART NUMBER | DIM. A<br>$\pm 0.10 (\pm 0.004)$ | DIM. B<br>$\pm 0.10 (\pm 0.004)$ | DIM. C<br>$\pm 0.10 (\pm 0.004)$ |
|-------------|----------------------------------|----------------------------------|----------------------------------|
| HSMF-C16x   | 1.75 (0.069)                     | 0.95 (0.037)                     | 0.60 (0.024)                     |

Figure 11. Tape dimensions.



NOTES:

1. ALL DIMENSIONS IN MILLIMETERS (INCHES).
2. TOLERANCE IS  $\pm 0.1 \text{ mm} (\pm 0.004 \text{ IN.})$  UNLESS OTHERWISE SPECIFIED.

Figure 12. Tape leader and trailer dimensions.

**Reflow Soldering**

For more information on reflow soldering, refer to Application Note 1060, *Surface Mounting SMT LED Indicator Components*.

**Storage Condition:**

5 to 30° C @ 60% RH max.

Baking is required under the condition:

- a) the blue silica gel indicator becoming white/transparent color
- b) the pack has been opened for more than 672 hours.

Baking recommended condition:  $60 \pm 5^\circ \text{C}$  for 20 hours.

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331