

## Lower Voltage Ceramic DC Disc Capacitors 1000 V<sub>DC</sub> General Purpose


**RoHS**  
COMPLIANT

**FEATURES**

- Low losses
- High stability
- High capacitance in small size
- Complete range of capacitance values
- Radial leads
- Ceramic singlelayer capacitor
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

**APPLICATIONS**

- Bypassing
- Resonant circuit
- Coupling

**DESIGN**

The capacitors consist of a ceramic disc of which both sides are silver-plated. Connection leads are made of tinned copper or tinned copper clad steel having diameters of 0.020" (0.51 mm) or 0.025" (0.64 mm).

The capacitors may be supplied with radial kinked or straight leads having lead spacing of 0.250" (6.35 mm) or 0.375" (9.5 mm).

The standard tolerance is  $\pm 20\%$ .

Coating is made of resin coating or flammable resistant epoxy resin in accordance with "UL 94 V-0".

**CAPACITANCE RANGE**

10 pF to 0.1  $\mu$ F

**RATED VOLTAGE**

1000 V<sub>DC</sub>

**DIELECTRIC STRENGTH BETWEEN LEADS**

Component test:

2500 V<sub>DC</sub>, 2 s

**CERAMIC DIELECTRIC**

C0G, U2J (Class 1)

X5F, X7R, Y5U, Z5U (Class 2)

QUICK REFERENCE DATA						
DESCRIPTION	VALUE					
Ceramic Class	1			2		
Ceramic Dielectric	C0G	U2J	X5F	X7R	Y5U	Z5U
Voltage (V <sub>DC</sub> )	1000					
Min. Capacitance (pF)	10	33	100	1000	1000	1200
Max. Capacitance (pF)	10	33	500	1000	1000	100 000
Mounting	Radial					

**INSULATION RESISTANCE**

Min. 1000  $\Omega$ F or 20 000 M $\Omega$

**TOLERANCE ON CAPACITANCE**

$\pm 20\%$

**DISSIPATION FACTOR**

2.5 % max. at 1 kHz; 1 V

**CATEGORY TEMPERATURE RANGE**

(- 55 to + 125) °C      C0G, U2J, X7R

(- 25 to + 85) °C      X5F, Y5U, Z5U

**CLIMATIC CATEGORY ACC. TO EN 60068-1**

55/125/21      C0G, U2J, X7R

25/085/21      X5F, Y5U, Z5U

**OPERATING TEMPERATURE RANGE**

(- 55 to + 105) °C

DIMENSIONS in inches (millimeters)	
<b>LEAD OFFSET "LO" (nominal)</b>	
1000 V <sub>DC</sub>	0.050" (1.3 mm)

ORDERING INFORMATION, CERAMIC 1000 V <sub>DC</sub> GENERAL PURPOSE									
C (pF)	TOL. (%)	D DIAMETER INCH (mm)	T THICKNESS INCH (mm)	LS LEAD SPACE INCH (mm)	FIG.	WIRE SIZE		ORDERING CODE	
						AWG	INCH (mm)		
<b>C0G (NPO)</b>									
10	± 20	0.250 (6.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	561R5GAQ10	
<b>U2J (N750)</b>									
33	± 20	0.290 (7.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	561R5GAQ33	
<b>X5F</b>									
100	± 20	0.250 (6.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	562R5GAT10	
150								562R5GAT15	
200								562R5GAT20	
220								562R5GAT22	
330								562R5GAT33	
470								562R5GAT47	
500	562R5GAT50								
<b>X7R</b>									
1000	± 20	0.290 (7.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	562R5GAD10	
<b>Y5U</b>									
1000	+ 100 - 0	0.290 (7.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	562R5HKD10	
<b>Z5U</b>									
1200	± 20	0.290 (7.4)	0.156 (4.0)	0.250 (6.4)	2	24	0.020 (0.51)	562R5GAD12	
1500								562R5GAD15	
2000								562R5GAD20	
2200								562R5GAD22	
2500								562R5GAD25	
2700								562R5GAD27	
3000								562R5GAD30	
3300								562R5GAD33	
4700								562R5GAD47	
5000								562R5GAD50	
6800								562R5GAD68	
8200								562R5GAD82	
0.010 μF								562R5GAS10	
0.010 μF								562R5HKMS10	
0.010 μF	562R5HKS10								
0.015 μF	562R5GAS15								
0.020 μF	562R5GAS20								
0.050 μF	565R10HKS50								
0.10 μF	565R10GAP10								

**TAPE AND REEL OPTIONS**

- Tape and reel available on diameter sizes 0.250" to 0.680"
- Part number codes and specifications for tape and reel packaging are found in the general information document - find web-link below

RELATED DOCUMENTS	
General Information	<a href="http://www.vishay.com/doc?23140">www.vishay.com/doc?23140</a>



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331