

## 3A, 50V - 1000V Glass Passivated Rectifier

### FEATURES

- Glass passivated chip junction
- High current capability, Low  $V_F$
- High reliability
- High surge current capability
- Low power loss, high efficiency
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

### APPLICATIONS

- High frequency rectification
- Freewheeling application
- Switching mode converters and inverters in computer and telecommunication.

### MECHANICAL DATA

- Case: DO-201AD
- Molding compound meets UL 94V-0 flammability rating
- Packing code with suffix "G" means green compound (halogen-free)
- Terminal: Pure tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Polarity: As marked
- Weight: 1.2 g (approximately)

| KEY PARAMETERS |            |      |
|----------------|------------|------|
| PARAMETER      | VALUE      | UNIT |
| $I_{F(AV)}$    | 3          | A    |
| $V_{RRM}$      | 50 - 1000  | V    |
| $I_{FSM}$      | 125        | A    |
| $T_{J\ MAX}$   | 150        | °C   |
| Package        | DO-201AD   |      |
| Configuration  | Single Die |      |



DO-201AD

| ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)                   |              |               |               |               |               |               |               |               |      |
|---|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|------|
| PARAMETER   | SYMBOL       | 1N5400<br>G-K | 1N5401<br>G-K | 1N5402<br>G-K | 1N5404<br>G-K | 1N5406<br>G-K | 1N5407<br>G-K | 1N5408<br>G-K | UNIT |
| Marking code on the device  |              | 1N5400G       | 1N5401G       | 1N5402G       | 1N5404G       | 1N5406G       | 1N5407G       | 1N5408G       |      |
| Repetitive peak reverse voltage   | $V_{RRM}$    | 50            | 100           | 200           | 400           | 600           | 800           | 1000          | V    |
| Reverse voltage, total rms value  | $V_{R(RMS)}$ | 35            | 70            | 140           | 280           | 420           | 560           | 700           | V    |
| Maximum DC blocking voltage   | $V_{DC}$     | 50            | 100           | 200           | 400           | 600           | 800           | 1000          | V    |
| Forward current   | $I_{F(AV)}$  | 3             |               |               |               |               |               |               | A    |
| Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load per diode | $I_{FSM}$    | 125           |               |               |               |               |               |               | A    |
| Junction temperature  | $T_J$        | - 55 to +150  |               |               |               |               |               |               | °C   |
| Storage temperature   | $T_{STG}$    | - 55 to +150  |               |               |               |               |               |               | °C   |

**THERMAL PERFORMANCE**

| PARAMETER                              | SYMBOL          | LIMIT | UNIT |
|--|-----------------|-------|------|
| Junction-to-ambient thermal resistance | $R_{\theta JA}$ | 45    | °C/W |
| Junction-to-case thermal resistance    | $R_{\theta JC}$ | 15    | °C/W |

**ELECTRICAL SPECIFICATIONS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| PARAMETER  | CONDITIONS                         | SYMBOL | TYP | MAX | UNIT          |
|--|------------------------------------|--------|-----|-----|---------------|
| Forward voltage per diode <sup>(1)</sup>               | $I_F = 3A, T_J = 25^\circ\text{C}$ | $V_F$  | -   | 1.1 | V             |
|  |                                    |        | -   | 1.0 | V             |
|  |                                    |        | -   | -   | -             |
|  |                                    |        | -   | -   | -             |
|  |                                    |        | -   | -   | -             |
|  |                                    |        | -   | -   | -             |
| Reverse current @ rated $V_R$ per diode <sup>(2)</sup> | $T_J = 25^\circ\text{C}$           | $I_R$  | -   | 5   | $\mu\text{A}$ |
|  | $T_J = 125^\circ\text{C}$          |        | -   | 100 | $\mu\text{A}$ |
| Junction capacitance                                   | 1 MHz, $V_R = 4.0V$                | $C_J$  | 25  | -   | pF            |

**Notes:**

1. Pulse test with  $PW = 0.3$  ms
2. Pulse test with  $PW = 30$  ms

**ORDERING INFORMATION**

| PART NO.                 | PACKING CODE | PACKING CODE SUFFIX | PACKAGE  | PACKING                |
|--------------------------|--------------|---------------------|----------|------------------------|
| 1N540xG-K<br>(Note 1, 2) | A0           | G                   | DO-201AD | 500 / Ammo box         |
|                          | R0           |                     | DO-201AD | 1,250 / 13" Paper reel |
|                          | B0           |                     | DO-201AD | 500 / Bulk packing     |

**Notes:**

1. "x" defines voltage from 50V (1N5400G-K) to 1000V (1N5408G-K)
2. Whole series with green compound (halogen-free)


**EXAMPLE P/N**

| EXAMPLE P/N   | PART NO.  | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION    |
|---------------|-----------|--------------|---------------------|----------------|
| 1N5400G-K A0G | 1N5400G-K | A0           | G                   | Green compound |


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Junction Capacitance**



**Fig.3 Typical Reverse Characteristics**




**Fig.4 Typical Forward Characteristics**



**CHARACTERISTICS CURVES**


( $T_A = 25^\circ\text{C}$  unless otherwise noted)

**Fig.5 Maximum Non-repetitive Forward Surge Current**



**PACKAGE OUTLINE DIMENSIONS**

DO-201AD



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 5.00      | 5.60 | 0.197       | 0.220 |
| B    | 1.20      | 1.30 | 0.048       | 0.052 |
| C    | 25.40     | -    | 1.000       | -     |
| D    | 8.50      | 9.50 | 0.335       | 0.375 |
| E    | 25.40     | -    | 1.000       | -     |

**MARKING DIAGRAM**



- P/N = Marking Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331