

# DATA SHEET

**CURRENT SENSOR - LOW TCR  
AUTOMOTIVE GRADE**

PA\_E series

5%, 1%, 0.5%

sizes 2512

RoHS compliant & Halogen free



**SCOPE**

This specification describes PA series current sensor - low TCR with lead-free terminations made by metal substrate.

**APPLICATIONS**

- Consumer goods
- Computer
- Telecom / Datacom
- Industrial / Power supply
- Alternative Energy
- Car electronics

**FEATURES**

- AEC-Q200 qualified
- Halogen-free Epoxy
- RoHS compliant
- Reduce environmentally hazardous wastes
- High component and equipment reliability
- Non-forbidden materials used in products/production
- Low resistances applied to current sensing
- Anti-sulfur

**ORDERING INFORMATION - GLOBAL PART NUMBER**

Global part numbers are identified by the series, size, tolerance, packing type, temperature coefficient, taping reel and resistance value.

**GLOBAL PART NUMBER**

PA XXXX X X X XX XXXX E  
 (1) (2) (3) (4) (5) (6) (7)

**(1) SIZE**

2512

**(2) TOLERANCE**

D =  $\pm 0.5\%$

F =  $\pm 1\%$

J =  $\pm 5\%$

**(3) PACKAGING TYPE**

K = Embossed taping reel

**(4) TEMPERATURE COEFFICIENT OF RESISTANCE**

F =  $\pm 100 \text{ ppm}/^\circ\text{C}$

M =  $\pm 75 \text{ ppm}/^\circ\text{C}$

E =  $\pm 50 \text{ ppm}/^\circ\text{C}$

**(5) TAPING REEL**

07 = 7 inch dia. Reel & standard power (1W)

7W = 7 inch dia. Reel & 2 x standard power (2W)

7T = 7 inch dia. Reel & 3 x standard power (3W)

**(6) RESISTANCE VALUE**

0.5 m $\Omega$  to 100 m $\Omega$

**(7) DEFAULT CODE**

Letter E is the system default code for ordering only. (Note)


| Resistance rule of global part number |                      |
|---------------------------------------|----------------------|
| Resistance code rule                  | Example              |
| XUXX                                  | 0U5 = 0.5m $\Omega$  |
| 0RXXX                                 | 0R001 = 1 m $\Omega$ |
| (1 to 100 m $\Omega$ )                | 0R05 = 50 m $\Omega$ |

**ORDERING EXAMPLE**

The ordering code of a PA2512 1W chip resistor, TC100, value 0.003 $\Omega$  with  $\pm 1\%$  tolerance, supplied in 7-inch tape reel is: PA2512FKF070R003E

**NOTE**


1. All our RChip products are RoHS compliant. "LFP" of the internal 2D reel label mentions "Lead-Free Process"

**MARKING****PA2512**

4 digits

The "m" is used as decimal point; the other 3 digits are significant and the unit is milliohm


PA2512: 0.5mΩ and 0.75mΩ



4 digits

The "R" is used as a decimal point; the other 3 digits are significant

PA2512: 1mΩ to 4 mΩ



4 digits

The "R" is used as a decimal point; the other 3 digits are significant

PA2512: 5 mΩ to 100 mΩ

**CONSTRUCTION**

The resistors are constructed using outstanding TCR level material, which makes Yageo PA resistors excellent for current sensing application in battery charger circuit & DC-DC converter.

The composition of the resistive material is adjusted to give the approximate required resistance and is covered with a protective coating. Marking is printed on the top side of the resistor.

Finally, the three external terminations (Cu / Ni / matte Tin) are added, as shown in Fig. 4.


**Outlines**

Fig. 4 Chip resistor outlines

**DIMENSION**

Table 1 For outlines, please refer to Fig. 4

| TYPE   | RESISTANCE RANGE                                   | L (mm)          | W (mm)          | H (mm)          | L <sub>1</sub> (mm) | L <sub>2</sub> (mm) |
|--------|----------------------------------------------------|-----------------|-----------------|-----------------|---------------------|---------------------|
| PA2512 | $0.5\text{m}\Omega \leq R \leq 0.75\text{m}\Omega$ | $6.35 \pm 0.25$ | $3.18 \pm 0.25$ | $0.63 \pm 0.25$ | $2.72 \pm 0.25$     | $2.72 \pm 0.25$     |
|        | $1\text{m}\Omega \leq R \leq 4\text{m}\Omega$      | $6.35 \pm 0.25$ | $3.18 \pm 0.25$ | $0.63 \pm 0.25$ | $2.21 \pm 0.25$     | $2.21 \pm 0.25$     |
|        | $5\text{m}\Omega \leq R \leq 6\text{m}\Omega$      | $6.35 \pm 0.25$ | $3.18 \pm 0.25$ | $0.63 \pm 0.25$ | $1.19 \pm 0.25$     | $1.19 \pm 0.25$     |
|        | $7\text{m}\Omega \leq R \leq 100\text{m}\Omega$    | $6.35 \pm 0.25$ | $3.18 \pm 0.25$ | $0.63 \pm 0.25$ | $0.76 \pm 0.25$     | $0.76 \pm 0.25$     |

Note:

1. For relevant physical dimensions, please refer to construction outlines.
2. Please contact with sales offices, distributors and representatives in your region before ordering.

**ELECTRICAL CHARACTERISTICS**

Table 2

| TYPE | SIZE | POWER RATING | TOLERANCE   | RESISTANCE RANGE                                  | TEMPERATURE COEFFICIENT OF RESISTANCE |
|------|------|--------------|-------------|---------------------------------------------------|---------------------------------------|
| PA   | 2512 | 1W           | $\pm 0.5\%$ | $0.5\text{m}\Omega \leq R \leq 100\text{m}\Omega$ | $\pm 50\text{ppm}/^\circ\text{C}$     |
|      |      | 2W           | $\pm 1\%$   |                                                   | $\pm 75\text{ppm}/^\circ\text{C}$     |
|      |      | 3W           | $\pm 5\%$   |                                                   | $\pm 100\text{ppm}/^\circ\text{C}$    |

Note: Please contact with sales offices, distributors and representatives in your region before ordering.

**FUNCTIONAL DESCRIPTION****OPERATING TEMPERATURE RANGE**

PA2512 Range:  $-55^\circ\text{C}$  to  $+170^\circ\text{C}$

**POWER RATING**

Standard rated power at  $70^\circ\text{C}$ :

For detail power value, please refer to Table 2.

**RATED VOLTAGE**

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V = \sqrt{P \times R}$$

Where

V = Continuous rated DC or AC (rms) working voltage (V)

P = Rated power (W)

R = Resistance value ( $\Omega$ )





Fig. 5 Maximum dissipation ( $P_{\max}$ ) in percentage of rated power as a function of the operating ambient temperature ( $T_{\text{amb}}$ )

## PACKING STYLE AND PACKAGING QUANTITY

**Table 3** Packing style and packaging quantity

| PACKING STYLE            | REEL DIMENSION | PA2512 |
|--------------------------|----------------|--------|
| Embossed taping reel (K) | 7" (178 mm)    | 4,000  |

## EMBOSSED TAPE




**Fig. 6** Embossed Tape

**Table 4** Dimensions of embossed tape for relevant chip resistors size

| SIZE   | SYMBOL          |                 |                  |                 |                 |                 |                 |                 |                   |                   | Unit: mm        |
|--------|-----------------|-----------------|------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-------------------|-------------------|-----------------|
|        | $A_0$           | $B_0$           | $W$              | $E$             | $F$             | $P_0$           | $P_1$           | $P_2$           | $\varnothing D_0$ | $\varnothing D_1$ | $T$             |
| PA2512 | $3.40 \pm 0.15$ | $6.70 \pm 0.15$ | $12.00 \pm 0.30$ | $1.75 \pm 0.10$ | $5.50 \pm 0.10$ | $4.00 \pm 0.10$ | $4.00 \pm 0.10$ | $2.00 \pm 0.10$ | $1.55 \pm 0.05$   | $1.50 \pm 0.10$   | $0.80 \pm 0.15$ |


## REEL SPECIFICATION



**Table 5** Dimensions of reel specification for relevant chip resistors size

| SIZE   | QUANTITY<br>PER REEL | REEL SIZE         |                    | SYMBOL    |           |           |          | Unit: mm       |                     |
|--------|----------------------|-------------------|--------------------|-----------|-----------|-----------|----------|----------------|---------------------|
|        |                      | 8 mm<br>TAPE WIDE | 12 mm<br>TAPE WIDE | A         | N         | C         | D        | W <sub>1</sub> | W <sub>2</sub> MAX. |
| PA2512 | 4000                 | --                | 7" (Ø178 mm)       | 178.0±1.0 | 60.0+1/-0 | 13.50±0.5 | 21.0±0.8 | 13.6±0.5       | 16.5±0.5            |

## LEADER/TRAILER TAPE SPECIFICATION



## FOOTPRINT AND SOLDERING PROFILES

For recommended soldering profiles, please refer to data sheet “Chip resistors mounting”.

### FOOTPRINT




Table 6 Footprint dimensions

|        |                                                 |      |      |      | Unit: mm |
|--------|-------------------------------------------------|------|------|------|----------|
| SIZE   | RESISTANCE RANGE                                | A    | B    | C    | D        |
| PA2512 | $0.5\text{m}\Omega \leq R < 1\text{m}\Omega$    | 7.36 | 0.50 | 3.43 | 3.68     |
|        | $1\text{m}\Omega \leq R \leq 4\text{m}\Omega$   | 7.37 | 1.27 | 3.05 | 3.68     |
|        | $5\text{m}\Omega \leq R \leq 6\text{m}\Omega$   | 7.40 | 3.18 | 2.11 | 3.68     |
|        | $7\text{m}\Omega \leq R \leq 100\text{m}\Omega$ | 7.36 | 4.06 | 1.65 | 3.68     |

## TESTS AND REQUIREMENTS

Table 8 Test condition, procedure and requirements

| TEST                         | TEST METHOD            | PROCEDURE                                                                                                                                                                                                                       | REQUIREMENT                                    |
|------------------------------|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Short time overload          | IEC60115-1 4.13        | 5 times of rated power for 5 seconds at room temperature                                                                                                                                                                        | $\pm(0.5\%+0.0005\Omega)$<br>No visible damage |
| High Temperature Exposure    | MIL-STD-202-Method 108 | 1,000 hours at maximum operating temperature depending on specification, unpowered<br><br>No direct impingement of forced air to the parts Tolerances: $170\pm3^{\circ}\text{C}$                                                | $\pm(1.0\%+0.0005\Omega)$                      |
| Temperature Cycling          | JESD22-A104C           | 1,000 cycles, $-55/+125^{\circ}\text{C}$ for 1 cycle per hour                                                                                                                                                                   | $\pm(0.5\%+0.0005\Omega)$                      |
| Moisture Resistance          | MIL-STD-202-Method 106 | Each temperature / humidity cycle is defined at 8 hours (method 106F), 3 cycles / 24 hours for 10d with $25^{\circ}\text{C}$ / $65^{\circ}\text{C}$ 95% R.H, without steps 7a & 7b, unpowered                                   | $\pm(0.5\%+0.0005\Omega)$                      |
| Biased Humidity              | MIL-STD-202 Method 103 | 1,000 hours; $85^{\circ}\text{C}$ / 85% RH<br><br>10% of operating power                                                                                                                                                        | $\pm(0.5\%+0.0005\Omega)$                      |
| Operational Life/ Endurance  | MIL-STD-202-Method 108 | 1,000 hours at $125\pm3^{\circ}\text{C}$ , de-rated voltage applied for 1.5 hours on, 0.5 hour off, still-air required                                                                                                          | $\pm(1.0\%+0.0005\Omega)$                      |
|                              |                        | 1,000 hours at $70\pm2^{\circ}\text{C}$ applied RCWV<br>1.5 hours on, 0.5 hour off, still air required                                                                                                                          | $\pm(1.0\%+0.0005\Omega)$                      |
| Resistance to Solvents       | MIL-STD-202 Method 215 | Immerse in isopropyl alcohol for 5 min with ultrasonic at room temperature                                                                                                                                                      | No Visible damage                              |
| Mechanical Shock             | MIL-STD-202 Method 213 | Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen.<br><br>Peak value: 100 g's<br><br>Duration: 6 ms<br><br>Velocity change: 12.3 ft/s<br><br>Waveform: Half sine | $\pm(0.5\%+0.0005\Omega)$                      |
| Vibration                    | MIL-STD-202 Method 204 | 5 g's for 20 min., 12 cycles each of 3 orientations<br><br>Test from 10-2000 Hz.                                                                                                                                                | $\pm(0.5\%+0.0005\Omega)$                      |
| Resistance to Soldering Heat | MIL-STD-202-method 210 | Condition B, no pre-heat of samples<br>Leadfree solder, $260^{\circ}\text{C}$ , 10 seconds immersion time<br><br>Procedure 2 for SMD: devices fluxed and cleaned with isopropanol                                               | $\pm(0.5\%+0.0005\Omega)$<br>No visible damage |
| Thermal Shock                | MIL-STD-202 Method 107 | $-55/+125^{\circ}\text{C}$ , Number of cycles is 300.<br><br>Devices mounted.<br><br>Maximum transfer time is 20 seconds.<br><br>Dwell time is 15 minutes. Air -Air                                                             | $\pm(0.5\%+0.0005\Omega)$<br>No visible damage |

| TEST                                           | TEST METHOD            | PROCEDURE                                                                                                                                                                                                                                                                                       | REQUIREMENT                                        |
|------------------------------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Electrostatic Discharge                        | AEC-Q200-002           | Human Body Model, 1 pos + 1 neg.<br>Discharges 2512=2KV                                                                                                                                                                                                                                         | $\pm(1.0\%+0.0005\Omega)$<br>No visible damage     |
| Solderability<br>- Wetting                     | J-STD-002B test B      | (a) Method B, aging 4 hours at 155°C dry heat, dipping at 235±3°C for 5±0.5 seconds.<br><br>(b) Method B, steam aging 8 hours, dipping at 215±3°C for 5±0.5 seconds.<br><br>(c) Method D, steam aging 8 hours, dipping at 260±3 °C for 7±0.5 seconds.                                           | Well tinned<br>(>95% covered)<br>No visible damage |
| Flammability                                   | UL94                   | Try to inflame a specimen by a needle flame                                                                                                                                                                                                                                                     | No ignition of specimen;<br>V-0                    |
| Board Flex / Bending                           | AEC-Q200-005           | Chips mounted on a 90mm glass epoxy resin PCB (FR4), Bending for 2512=2 mm<br>Holding time: Min.60 seconds                                                                                                                                                                                      | $\pm(1.0\%+0.0005\Omega)$                          |
| Terminal Strength (SMD)                        | AEC-Q200-006           | Applied a 17.7N (1.8Kg) for 60±1 seconds.                                                                                                                                                                                                                                                       | $\pm(1.0\%+0.0005\Omega)$<br>No visible damage     |
| Flame Retardance                               | AEC-Q200-001           | Apply voltage from 9V to 32V to increase the surface temp to 350°C                                                                                                                                                                                                                              | No flame,<br>no explosion                          |
| Temperature Coefficient of Resistance (T.C.R.) | MIL-STD-202 Method 304 | At +25/+150°C<br>Formula:<br>$T.C.R = \frac{R_2 - R_1}{R_1(t_2 - t_1)} \times 10^6 (\text{ppm}/^\circ\text{C})$<br>Where<br>t1=+25°C or specified room temperature<br>t2=+150°C test temperature<br>R1=resistance at reference temperature in ohms<br>R2=resistance at test temperature in ohms | Refer to table 2                                   |
| Flower-of-Sulfur (FOS)                         | Modified ASTM B809-95  | Sulfur 105°C, 750 hours, unpowered.                                                                                                                                                                                                                                                             | $\pm(1.0\%+0.0005\Omega)$                          |

**REVISION HISTORY**

| REVISION   | DATE          | CHANGE NOTIFICATION | DESCRIPTION                                                                               |
|------------|---------------|---------------------|-------------------------------------------------------------------------------------------|
| Version 10 | Jan. 31, 2018 | -                   | - Extend 0.5% Tolerance                                                                   |
| Version 9  | Nov. 21, 2017 | -                   | - Extend resistor value for 3W                                                            |
| Version 8  | Oct. 23, 2017 | -                   | - Update footprint dimensions                                                             |
| Version 7  | Jul. 24, 2017 | -                   | - Add part number coding details for the relationship between taping reel and rated power |
| Version 6  | Apr. 19, 2017 | -                   | - Extend resistor value                                                                   |
| Version 5  | Nov. 30, 2016 | -                   | - Extend resistor value                                                                   |
| Version 4  | Oct. 27, 2016 | -                   | - Modify the error of test procedure                                                      |
| Version 3  | Mar. 31, 2016 | -                   | - Update TCR                                                                              |
| Version 2  | Dec. 31, 2015 | -                   | - Extend resistor value                                                                   |
| Version 1  | Dec. 18, 2015 | -                   | - Update tests and requirements                                                           |

*“Yageo reserves all the rights for revising the content of this datasheet without further notification, as long as the products itself are unchanged. Any product change will be announced by PCN.”*

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yageo:

[PA2512JKF7W0R005E](#) [PA2512JKF7W0R001E](#) [PA2512JKF7W0R003E](#) [PA2512JKF7W0R002E](#)  
[PA2512JKF7W0R004E](#) [PA2512JKF7T0R004E](#) [PA2512JKF070R003E](#) [PA2512JKF7T0R002E](#) [PA2512JKF7T0R005E](#)  
[PA2512JKF070R004E](#) [PA2512JKF7T0R001E](#) [PA2512JKF7T0R003E](#) [PA2512FKF7W0R004E](#)  
[PA2512FKF7T0R001E](#) [PA2512FKF7T0R002E](#) [PA2512FKF7T0R003E](#) [PA2512FKF7T0R004E](#) [PA2512FKF7T0R005E](#)  
[PA2512JKF070R002E](#) [PA2512FKF070R001E](#) [PA2512FKF070R002E](#) [PA2512FKF070R003E](#)  
[PA2512FKF070R004E](#) [PA2512FKF070R005E](#) [PA2512FKF7W0R001E](#) [PA2512FKF7W0R002E](#)  
[PA2512FKF7W0R003E](#) [PA2512FKF7W0R005E](#) [PA2512JKF070R001E](#) [PA2512JKF070R005E](#)  
[PA2512FKF7W0R007E](#) [PA2512FKF070R007E](#) [PA2512FKF7W0R006E](#) [PA2512FKF7W0R01E](#) [PA2512FKF7W0R05E](#)  
[PA2512FKF070R01E](#) [PA2512FKF7T0R01E](#) [PA2512FKE7W0R005E](#) [PA2512FKF7T0U5E](#) [PA2512FKE7W0R01E](#)  
[PA2512FKF7W0R01L](#) [PA2512FKM7W0R001E](#) [PA2512FKM7W0R002E](#) [PA2512FKM7W0R005E](#)  
[PA2512FKM070R1E](#) [PA2512FKM070R01E](#) [PA2512FKE7T0R015E](#) [PA2512FKE7W0R007E](#) [PA2512FKM7W0R02E](#)  
[PA2512FKE7W0R002E](#) [PA2512FKE7W0R001E](#) [PA2512FKE7T0R004E](#) [PS0306FRF7T0R01L](#) [PE1206FRM7W0R1L](#)  
[PE1206FRM7W0R07L](#) [PA2512FKF7W0R008E](#) [PA2512FKF7W0R02E](#) [PA2512FKF7W0U5E](#) [PA2512FKF7T0R02E](#)  
[PA2512FKF070U5E](#) [PA2512FKF7W0R015E](#) [PA2512FKM7W0R003E](#) [PA2512FKF7W0U75E](#) [PA2512FKF070R006E](#)  
[PA2512FKF7T0R05E](#) [PA2512FKF070R015E](#) [PA2512FKM7W1U5E](#) [PA2512FKF070R025E](#) [PA2512FKF7W0R07E](#)  
[PA2512FKM7W0R01E](#) [PA2512FKF070R04E](#) [PA2512FKF070R008E](#) [PA2512FKE7T0R025E](#) [PA2512FKF7W0R04E](#)  
[PA2512FKF070R05E](#) [PA2512FKF7W0R018E](#) [PA2512FKF7W0R03E](#) [PA2512FKF070R08E](#) [PA2512FKE7W0R05E](#)  
[PA2512FKM7W0R004E](#) [PA2512FKM070R007E](#) [PA2512FKM070R02E](#) [PA2512FKF7W1U5E](#) [PA2512FKM7W0R007E](#)  
[PA2512FKF7T0R012E](#) [PA2512FKF7W0R009E](#) [PA2512FKM7W0R015E](#) [PA2512FKF071U5E](#)  
[PA2512FKF7T0R015E](#) [PA2512FKM070R003E](#) [PA2512FKE7W0R004E](#) [PA2512FKE7W0U5E](#) [PA2512FKF070R02E](#)  
[PA2512FKF7W0R047E](#) [PA2512FKE7W0R03E](#) [PA2512FKF7T0R007E](#) [PA2512FKF7W0R033E](#)  
[PA2512FKM070R004E](#) [PA2512FKM070R005E](#) [PA2512JKF7T0R007E](#)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331