

Features and Benefits

- ☐ Built-in Reverse Voltage Protection
- ☐ Built-in RFI Filter
- ☐ Power Efficient CMOS and Power MOSFET Drivers allow 400mA without overheating
- ☐ Built-in Zener Diodes Protect Outputs Eliminate all Fan Components Eliminate PC Board
- ☐ 5V and 12V Operation
- ☐ High Sensitivity for switching symmetry
- ☐ Locked Rotor Shutdown

Applications

- ☐ Fan sizes up to 90mm
- ☐ Current range up to 400mA

Ordering Code


Product Code	Temperature Code	Package Code	Option Code	Packing Form Code
US79	K	UA	AAA-000	BU

Legend:

Temperature Code:	K for Temperature Range -40°C to 125°C
Package Code:	UA for TO-92(flat)
Option Code:	xxx-000: Standard version
Packing Form:	BU for Bulk

Ordering example: US79KUA-AAA-000-BU

1. Functional Diagram



2. Description

The US79KUA is the most advanced Smart Fan Control Hall IC. It is designed for 5V and 12V cooling commutation. The chip contains many features to allow survival in a harsh environment. The IC was designed to eliminate all discrete components such as capacitors, resistors, transistors, diodes, PC board and associated labor, replacing US\$0.25 to US\$0.35 in direct cost.

The K rating guarantees proper operation up to an ambient temperature of 125°C. Hall IC circuitry and power FET output provide a low power dissipation cool chip.

Locked Rotor conditions are detected by the IC when there is no motion for one second and will shut off the motor drive for five seconds. Then, the IC will turn on the drive current for one second. This sequence continues indefinitely until the locked rotor condition is fixed. This feature prevents overheating.

TABLE OF CONTENTS

FEATURES AND BENEFITS	1
APPLICATIONS.....	1
ORDERING INFORMATION.....	1
1. FUNCTIONAL DIAGRAM.....	1
2. DESCRIPTION.....	1
3. GLOSSARY OF TERMS	3
4. ABSOLUTE MAXIMUM RATINGS	3
5. US79 ELECTRICAL SPECIFICATIONS.....	3
6. US79 MAGNETIC SPECIFICATIONS.....	3
7. UNIQUE FEATURES.....	4
8. PERFORMANCE GRAPHS.....	4
9. APPLICATION INFORMATION	6
10. STANDARD INFORMATION REGARDING MANUFACTURABILITY OF MELEXIS PRODUCTS WITH DIFFERENT SOLDERING PROCESSES.....	7
11. ESD PRECAUTIONS.....	7
12. PACKAGE INFORMATION.....	8
13. DISCLAIMER.....	9

3. Glossary of Terms

MilliTesla (mT), Gauss: Units of magnetic flux density; 1 milliTesla = 10 Gauss.

Two-Coil Fan: a fan with two coil windings, current alternates from 1 coil to the other depending on the polarity of the magnetic field.

Two-wire Fan: A fan that has only two connections for the power supply plus and minus.

Locked rotor: The condition of a fan that has stopped spinning due to mechanical blockage .

4. Absolute Maximum Ratings

Supply Voltage, V_{DD}	(-0.3 to 18)V
Output Current (Fault), I_{OUT}	500mA
Operating Temperature Range, T_A	-40 to 125 °C
Storage Temperature Range, T_s	-55 to 165 °C
Maximum Junction Temp, T_J	150 °C

Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

5. US79 Electrical Specifications

DC operating parameters: $T_A = 25\text{ °C}$, $V_{DD} = 12V$ unless otherwise specified

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Supply Voltage	V_{DD}	Operating	3.5	-	18	V
Supply Current	I_{DD}	Operating		2.0	4	mA
Output Saturation voltage	V_{DSS}	$I_{OUT} = 150mA$		300	600	mV
Output Saturation voltage	V_{DSS}	$I_{OUT} = 350mA$		650	1100	mV
Thermal resistance	R_{th}	Operating		190		°C/W
Locked-Rotor Period	t_{on}			0.8		S
Locked-Rotor period	t_{off}			5		S

6. US79 Magnetic Specifications

DC operating parameters: $T_A = 25\text{ °C}$, $V_{DD} = 12V$ unless otherwise specified.

Parameter	Symbol	Test Conditions	Min	Typ	Max	Units
Operate Point	B_{OP}	Operating		2.5	6.0	mT
Release Point	B_{RP}	Operating	-6.0	-2.5		mT
Hysteresis	B_{HYS}	Operating	2.0	5.0	-	mT

7. Unique Features

Reverse voltage protection eliminates the need for a diode. Reverse current flows through the coils and the chip. Power dissipation is $(2 * I_{\text{stall}}/I_{\text{start}} * 0.7V)$.


Table 1 presents max temperature for each current.


$I_{\text{stall}}/I_{\text{start}}$	T_A Maximum Rev V Test
100mA	125°C
200mA	100°C
300mA	70°C
400mA	40°C

Reverse Voltage protection is provided by the motor windings.



The 35V Zener diodes clamp the output drivers for overstress protection.

8. Performance Graphs





9. Applications Information



10. Standard information regarding manufacturability of Melexis products with different soldering processes

Our products are classified and qualified regarding soldering technology, solderability and moisture sensitivity level according to following test methods:

Reflow Soldering SMD's (Surface Mount Device)s

- IPC/JEDEC J-STD-020
Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices (classification reflow profiles according to table 5-2)
- EIA/JEDEC JESD22-A113
Preconditioning of Nonhermetic Surface Mount Devices Prior to Reliability Testing (reflow profiles according to table 2)

Wave Soldering SMD's (Surface Mount Device)s and THD's (Through Hole Device)s

- EN60749-20
Resistance of plastic- encapsulated SMD's to combined effect of moisture and soldering heat
- EIA/JEDEC JESD22-B106 and EN60749-15
Resistance to soldering temperature for through-hole mounted devices

Iron Soldering THD's (Through Hole Device)s

- EN60749-15
Resistance to soldering temperature for through-hole mounted devices

Solderability SMD's (Surface Mount Device)s and THD's (Through Hole Device)s

- EIA/JEDEC JESD22-B102 and EN60749-21
Solderability

For all soldering technologies deviating from above mentioned standard conditions (regarding peak temperature, temperature gradient, temperature profile etc) additional classification and qualification tests have to be agreed upon with Melexis.


The application of Wave Soldering for SMD's is allowed only after consulting Melexis regarding assurance of adhesive strength between device and board.

Melexis is contributing to global environmental conservation by promoting **lead free** solutions. For more information on qualifications of **RoHS** compliant products (RoHS = European directive on the Restriction Of the use of certain Hazardous Substances) please visit the quality page on our website: <http://www.melexis.com/quality.aspx>

11. ESD Precautions

Electronic semiconductor products are sensitive to Electro Static Discharge (ESD).
Always observe Electro Static Discharge control procedures whenever handling semiconductor products.

12. Package Information



SYMBOL	DIMENSIONS [MM/INCH]		
	MIN	NOM	MAX
A	2.80	3.00	3.20
	.110	.118	.126
a1	0.35	—	0.41
	.014	—	.016
a	0.35	—	0.44
	.014	—	.017
b1	0.43	—	0.49
	.017	—	.019
b	0.43	—	0.52
	.017	—	.020
c1	0.35	—	0.41
	.014	—	.016
c	0.35	—	0.44
	.014	—	.017
F1	0.45	—	0.66
	.018	—	.026
K	0.00	—	0.15
	.000	—	.006
D	3.90	4.10	4.30
	0.153	.161	.169

SYMBOL	DIMENSIONS [MM/INCH]		
	MIN	NOM	MAX
e1	1.24	1.27	1.30
	.049	.050	.051
E	1.40	1.50	1.60
	.055	.059	.063
J	2.51	2.62	2.72
	.099	0.103	.107
L	14.00	14.50	15.00
	.551	.5709	.5906
	10.00	10.5	11.00
	.3937	.4134	.4331
L1	0.90	1.0	1.10
	.035	.039	0.43
S	0.63	0.74	0.84
	.025	.029	.033
e	2.51	2.54	2.57
	.099	.100	.101
M	—	—	0.0152
	—	—	.0006


NOTES :

1. DIMENSIONS A AND D DO NOT INCLUDE MOLD GATE AND SIDE FLASH (PROTUSION) ALLOWABLE IS 0.127 [.005] PER SIDE. A AND D ARE MAXIMUM PLASTIC BODY SIZE DIMENSIONS INCLUDING MOLD MISMATCH.

2. CONTROLLING DIMENSION IN MM.

3. a1, b1, c1 ARE DIM FOR BARE LEAD FRAMES

4. a, b, c ARE DIM FOR PLATED LEAD FRAMES.



13. Disclaimer

Devices sold by Melexis are covered by the warranty and patent indemnification provisions appearing in its Term of Sale. Melexis makes no warranty, express, statutory, implied, or by description regarding the information set forth herein or regarding the freedom of the described devices from patent infringement. Melexis reserves the right to change specifications and prices at any time and without notice. Therefore, prior to designing this product into a system, it is necessary to check with Melexis for current information. This product is intended for use in normal commercial applications. Applications requiring extended temperature range, unusual environmental requirements, or high reliability applications, such as military, medical life-support or life-sustaining equipment are specifically not recommended without additional processing by Melexis for each application.

The information furnished by Melexis is believed to be correct and accurate. However, Melexis shall not be liable to recipient or any third party for any damages, including but not limited to personal injury, property damage, loss of profits, loss of use, interrupt of business or indirect, special incidental or consequential damages, of any kind, in connection with or arising out of the furnishing, performance or use of the technical data herein. No obligation or liability to recipient or any third party shall arise or flow out of Melexis' rendering of technical or other services.

© 2012 Melexis NV. All rights reserved.

For the latest version of this document, go to our website at
www.melexis.com

Or for additional information contact Melexis Direct:

Europe, Africa, Asia:	America:
Phone: +32 1367 0495	Phone: +1 248 306 5400
E-mail: sales_europe@melexis.com	E-mail: sales_usa@melexis.com

ISO/TS 16949 and ISO14001 Certified



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331