

55505 Hall Effect Flange Mount Geartooth Sensor



Features

- Ferrous target sensing
- Internal circuit protection
- Protection against severe and automotive environments
- Self adjusting magnetic range
- Automotive grade circuit protection
- High speed operation
- Short circuit and reverse voltage protection
- On board 10 bit A/D convertor


Benefits

- No chopper delay
- Rotational alignment to target not critical
- Immune to target run out

Benefits

- Wheel, transmission and camshaft speed sensing
- Geartooth sensor
- Rotary encoders
- Industrial
- Commercial
- Automotive


DIMENSIONS (in) mm



SPECIFICATIONS

Hall Type		Digital Switch 3 Wire (Voltage Output)	
Supply Voltage	Operate	Vdc	4.75 to 24
Supply Voltage	Overvoltage Protection	Vdc - max.	27
Supply Voltage	Reverse Voltage Protection	Vdc - max.	-25
Output High Voltage		Vdc	VDD -2 (-2 sinking output with internal pull-up)
Output Low Voltage		Vdc - max.	0.6 @ 20mA
Output Current (continuously on)		mA - max.	20
Current Consumption		mA - max.	1
Current Consumption		mA - max.	10.5
Switching Speed		kHz - max.	15
Temperature	Operate	°C	-40 to +125
Temperature	Storage	°C	-65 to +125

APPLICATION EXAMPLE - Geartooth Sensor



CUSTOMER OPTIONS - Cable Length and Termination

TABLE 1	
Cable Length:- (Cable Type 20AWG Type TXL per SAE J-1128)	
Standard Lengths	
SELECT OPTION	CABLE LENGTH (in) mm
01	(3.94) 100
02	(11.81) 300
03	(19.69) 500
04	(29.53) 750
05	(39.37) 1000

TABLE 2	
Termination Options:-	
SELECT OPTION	DESCRIPTION
A	Tinned Leads
B	Deutsch DTM04-3P
C	Molex MX 150

ORDERING INFORMATION

55505	-	00	-	XX	-	X
Series 55505						
Cable Length	Table 1					
Termination	Table 2					



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331