



SILEGO

SLG59M1466V

Ultra-small 40 mΩ, 1.0 A Integrated Power Switch with Discharge

General Description


The SLG59M1466V is designed for load switching applications. The part comes with one 40 mΩ 1.0 A rated MOSFET controlled by a single ON control pin. The MOSFET's ramp rate is fixed at 3 V/ms.

The product is packaged in an ultra-small 1.0 x 1.0 mm package.

Features


- One 40 mΩ 1.0 A MOSFET
- One integrated VGS Charge Pump
- Integrated Discharge Resistor
- Fixed Slew rate: 3 V/ms
- Pb-Free / Halogen-Free / RoHS compliant
- STDFN 4L, 1.0 x 1.0 x 0.55 mm

Pin Configuration



4-pin STDFN
(Top View)

Block Diagram






Pin Description

Pin #	Pin Name	Type	Pin Description
1	ON	Input	Turns on MOSFET
2	D	MOSFET	Drain of Power MOSFET
3	S	MOSFET	Source of Power MOSFET
4	GND	GND	Ground

Ordering Information

Part Number	Type	Production Flow
SLG59M1466V	STDFN 4L	Extended Commercial, -20 °C to 70 °C
SLG59M1466VTR	STDFN 4L (Tape and Reel)	Extended Commercial, -20 °C to 70 °C

Application Diagram





Absolute Maximum Ratings

Parameter	Description	Conditions	Min.	Typ.	Max.	Unit
V_{DD}	Power Supply		--	--	6	V
T_S	Storage Temperature		-65	--	150	°C
ESD_{HBM}	ESD Protection	Human Body Model	2000	--	--	V
W_{DIS}	Package Power Dissipation		--	--	1.5	W
MOSFET IDS_{PK}	Peak Current from Drain to Source	For no more than 1 ms with 1% duty cycle	--	--	2	A

Note: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.


Electrical Characteristics

$T_A = -20$ to 70 °C (unless otherwise stated)


Parameter	Description	Conditions	Min.	Typ.	Max.	Unit
V_D	Power Supply Voltage	-20 to 70 °C	2.5	--	5.5	V
I_{DD}	Power Supply Current (PIN 2)	when OFF	--	0.1	1	μ A
		when ON, No load	--	18	25	μ A
$R_{DS_{ON}}$	Static Drain to Source ON Resistance	T_A 25 °C MOSFET	--	40	50	m Ω
		T_A 70 °C MOSFET	--	50	55	m Ω
IDS	Operating Current	$V_D = 2.5$ V to 5.5 V	--	--	1.0	A
T_{ON_Delay}	ON pin Delay Time	50% ON to Ramp Begin, $V_D = 5$ V, $C_L = 10$ μ F	--	0.5	1	ms
T_{Total_ON}	Total Turn On Time	50% ON to 90% V_S , $V_D = 5$ V, $C_L = 10$ μ F	1.6	2.0	2.4	ms
$T_{SLEWRATE}$	Slew Rate	10% V_S to 90% V_S , $V_D = 5$ V, $C_L = 10$ μ F	2.5	3.0	3.75	V/ms
R_{DIS}	Discharge Resistance		100	150	300	Ω
ON_ V_{IH_INI}	Initial Turn On Voltage	Internal Charge Pump ON	0.9	--	V_{DD}	V
ON_ V_{IL}	Low Input Voltage on ON pin	Internal Charge Pump OFF	-0.3	0	0.3	V
ON_ R	Input Impedance on ON pin		100	--	--	M Ω
T_{OFF_Delay}	OFF Delay Time	50% ON to V_S Fall, $V_D = 5$ V	--	--	5	μ s
T_{FALL}	V_S Fall Time	90% V_S to 10% V_S , $V_D = 5$ V	--	35	--	μ s



T_{Total_ON} , T_{ON_Delay} and Slew Rate Measurement




SLG59M1466V Layout Suggestion






Package Top Marking System Definition





Package Drawing and Dimensions

4 Lead STDFN Package 1.0 x 1.0 mm



Unit: mm

Symbol	Min	Nom.	Max	Symbol	Min	Nom.	Max
A	0.50	0.55	0.60	D	0.95	1.00	1.05
A1	0.005	-	0.060	E	0.95	1.00	1.05
A2	0.10	0.15	0.20	L	0.35	0.40	0.45
b	0.15	0.20	0.25	S	0.2 REF		
e	0.40 BSC						




Tape and Reel Specifications

Package Type	# of Pins	Nominal Package Size [mm]	Max Units		Reel & Hub Size [mm]	Leader (min)		Trailer (min)		Tape Width [mm]	Part Pitch [mm]
			per Reel	per Box		Pockets	Length [mm]	Pockets	Length [mm]		
STDFN 4L Green	4	1.0 x 1.0 x 0.55	8000	8000	178 / 60	200	400	200	400	8	2

Carrier Tape Drawing and Dimensions

Package Type	Pocket BTM Length	Pocket BTM Width	Pocket Depth	Index Hole Pitch	Pocket Pitch	Index Hole Diameter	Index Hole to Tape Edge	Index Hole to Pocket Center	Tape Width
	A0	B0	K0	P0	P1	D0	E	F	W
STDFN 4L Green	1.16	1.16	0.63	4	2	1.5	1.75	3.5	8



Refer to EIA-481 specification

Recommended Reflow Soldering Profile

Please see IPC/JEDEC J-STD-020: latest revision for reflow profile based on package volume of 0.55 mm³ (nominal). More information can be found at www.jedec.org.



SILEGO

SLG59M1466V

Revision History

Date	Version	Change
9/14/2015	1.00	Production Release



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331