

## Insulated Precision Wirewound Resistors Axial Leads




In wirewound precision resistors, the RLP series holds a leading position in professional applications whenever an excellent stability of the ohmic value and a correspondingly low temperature coefficient are required at the same time.

The RLP model resistors comply with the most stringent requirements of the EN 140-100 specification. The series consists of 5 models covering the power range from 1 W to 10 W.

Non-inductive versions can be supplied on request by specifying RLP-NI. For higher power dissipations, the use of RH series resistors is recommended.

### DIMENSIONS in millimeters



### FEATURES

- 1 W to 10 W at 25 °C
- CECC 40201-006
- Conforms to EN 140-100
- Excellent stability  $< \pm 0.3 \%$  after 1000 h
- High power up to 10 W at 25 °C
- Low ohmic values 10 mΩ available
- Low temperature coefficient  $\leq \pm 50$  ppm/°C
- Electrical insulation
- Climatic protection
- Termination = Pure matte tin or Sn/Ag/Cu according to the ohmic value



**RoHS**  
COMPLIANT

### DIMENSIONS in millimeters

|                  | MOLDED     |       | INSULATED |       |        |
|------------------|------------|-------|-----------|-------|--------|
| SERIES AND STYLE | RLP 1      | RLP 2 | RLP 3     | RLP 6 | RLP 10 |
| A max.           | 7          | 10.2  | 14        | 23.82 | 46.78  |
| Ø B max.         | R > 0.15 Ω | 2.5   | 4.0       | 5.54  | 8.71   |
|                  | R ≤ 0.15 Ω | -     | 6         | 9     | 11     |
| E ± 0.1          | 0.6        | 0.6   | 0.8       | 0.8   | 0.8    |
| Weight in g      | 0.27       | 0.48  | 1.3       | 3.4   | 8.6    |

### TECHNICAL SPECIFICATIONS

| VISHAY SFERNICE SERIES AND STYLE     |                        | RLP1  | RLP2  | RLP3  | RLP6             | RLP10            |
|--------------------------------------|------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|------------------|------------------|
| NF C 83-210                          |                        | RP8                                                                                      | RP7                                                                                      | RP4                                                                                        | -                | -                |
| CECC 40201-006                       |                        | A                                                                                        | B                                                                                        | C                                                                                          | -                | -                |
| Power Rating at + 25 °C              | VISHAY SFERNICE Limits | 1 W                                                                                      | 2 W                                                                                      | 3 W                                                                                        | 6 W              | 10 W             |
| Ohmic Range in Relation to Tolerance | ± 5 % E24              | 0.05 Ω<br>2 kΩ                                                                           | 0.025 Ω<br>6.8 kΩ                                                                        | 0.01 Ω<br>15 kΩ                                                                            | 0.02 Ω<br>59 kΩ  | 0.06 Ω<br>150 kΩ |
|                                      | ± 2 % E48              | 0.05 Ω<br>2 kΩ                                                                           | 0.025 Ω<br>6.8 kΩ                                                                        | 0.03 Ω<br>15 kΩ                                                                            | 0.02 Ω<br>59 kΩ  | 0.06 Ω<br>150 kΩ |
|                                      | ± 1 % E96              | 0.05 Ω<br>2 kΩ                                                                           | 0.025 Ω<br>6.8 kΩ                                                                        | 0.03 Ω<br>15 kΩ                                                                            | 0.02 Ω<br>59 kΩ  | 0.06 Ω<br>150 kΩ |
|                                      | ± 0.5 % E96            | 0.4 Ω<br>2 kΩ                                                                            | 0.4 Ω<br>6.8 kΩ                                                                          | 0.0499 Ω<br>15 kΩ                                                                          | 0.3 Ω<br>59 kΩ   | 0.3 Ω<br>150 kΩ  |
|                                      | ± 0.1 % E96            | Please consult VISHAY SFERNICE                                                           |                                                                                          |                                                                                            |                  |                  |
| Qualified Ohmic Range NF C 83-210    |                        | 1 Ω<br>470 Ω                                                                             | 0.2 Ω<br>1.78 kΩ                                                                         | 0.1 Ω<br>3.57 kΩ                                                                           | 0.1 Ω<br>12.1 kΩ | 0.1 Ω<br>40.2 kΩ |
| Limiting Element Voltage             |                        | 50 V                                                                                     | 120 V                                                                                    | 200 V                                                                                      | 300 V            | 720 V            |
| Critical Resistance                  |                        | out of nominal ohmic range                                                               |                                                                                          |                                                                                            | 17 800 Ω         | 51 100 Ω         |

 Undergoes European Quality Insurance System (CECC)

Insulated Precision Wirewound Resistors  
Axial Leads

Vishay Sfernice

| PERFORMANCE             |                                                        |                                                                           |                                                                |                                                                               |
|-------------------------|--------------------------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------|-------------------------------------------------------------------------------|
| TESTS                   | CONDITIONS                                             | REQUIREMENTS                                                              |                                                                | TYPICAL VALUES<br>AND DRIFTS                                                  |
|                         |                                                        | MIL-R-26 E                                                                | CECC40201-06                                                   |                                                                               |
| Dielectric w/s Voltage  | 500 VRMS for RLP 1-2-3<br>1000 VRMS for RLP 6-10       | $\pm (0.1 \% + 0.05 \Omega)$                                              | -                                                              | $\pm (0.05 \% + 0.05 \Omega)$                                                 |
| Short Time Overload     | 5 Pn/5 s for Pn < 5 W<br>10 Pn/5 s for Pn $\geq$ 5 W   | $\pm (0.2 \% + 0.05 \Omega)$                                              | $\pm 0.25 \% + 0.05 \Omega$                                    | $\pm (0.1 \% + 0.05 \Omega)$                                                  |
| Climatic Sequence       | EN 140-201<br>fasc. 19A - 55 °C/+ 200 °C<br>5 cycles   | -                                                                         | $\pm 0.5 \% + 0.05 \Omega$<br>Insulation R > 100 M $\Omega$    | $\pm (0.2 \% + 0.05 \Omega)$<br>Ins. resistance > 10 <sup>3</sup> M $\Omega$  |
| Humidity (Steady State) | EN 140-201<br>fasc. 3A 56 days 95 % R.H.               | -                                                                         | $\pm 0.5 \% + 0.05 \Omega$<br>Insulation R > 100 M $\Omega$    | $\pm (0.25 \% + 0.05 \Omega)$<br>Ins. resistance > 10 <sup>3</sup> M $\Omega$ |
| Vibration               | MIL-STD-202<br>Method 204 - Test D: 20 g<br>10/2000 Hz | $\pm (0.1 \% + 0.05 \Omega)$                                              | $\pm 0.25 \% + 0.05 \Omega$                                    | $\pm (0.05 \% + 0.05 \Omega)$                                                 |
| Load Life               | MIL-STD-202<br>Method 108 Pn 1000 h                    | $\pm (0.5 \% + 0.05 \Omega)$                                              | $\pm 0.5 \% + 0.05 \Omega$<br>Insulation R $\geq$ 1 G $\Omega$ | $\pm (0.3 \% + 0.05 \Omega)$                                                  |
| Moisture Resistance     | MIL-STD-202<br>Method 106                              | $\pm (0.2 \% + 0.05 \Omega)$<br>Insulation resistance<br>> 100 M $\Omega$ | -                                                              | $\pm (1 \% + 0.05 \Omega)$<br>Ins. resistance > 10 <sup>3</sup> M $\Omega$    |
| High Temperature        | 250 h at + 275 °C                                      | $\pm (0.5 \% + 0.05 \Omega)$                                              | $\pm 0.5 \% + 0.05 \Omega$<br>Insulation R $\geq$ 1 G $\Omega$ | $\pm (0.25 \% + 0.05 \Omega)$                                                 |
| Shock                   | MIL-STD-202<br>100 g Method 205 - Test C               | $\pm (0.1 \% + 0.05 \Omega)$                                              | $\pm 0.25 \% + 0.05 \Omega$                                    | $\pm (0.05 \% + 0.05 \Omega)$                                                 |


| TEMPERATURE COEFFICIENT IN THE RANGE - 55 °C TO + 200 °C |                                      |                                     |                                     |
|----------------------------------------------------------|--------------------------------------|-------------------------------------|-------------------------------------|
| OHMIC RANGE                                              | LIMITS                               |                                     | TYPICAL VALUE                       |
|                                                          | NF C                                 | MIL                                 |                                     |
| < 1 $\Omega$                                             | $\pm 100 \text{ ppm}/^\circ\text{C}$ | $\pm 90 \text{ ppm}/^\circ\text{C}$ | $\pm 50 \text{ ppm}/^\circ\text{C}$ |
| 1 $\Omega$ to < 10 $\Omega$                              | $\pm 50 \text{ ppm}/^\circ\text{C}$  | $\pm 50 \text{ ppm}/^\circ\text{C}$ |                                     |
| $\geq 10 \Omega$                                         | $\pm 25 \text{ ppm}/^\circ\text{C}$  | $\pm 30 \text{ ppm}/^\circ\text{C}$ | + 0 to - 20 ppm/°C                  |

## STABILITY AND POWER RATING


Stability changes slightly according to power rating and ambient temperature. This fact is especially important for users needing a life drift lower than the initial resistance tolerance. Typical drifts, after 2000 hours life test made under the 90°/30° conditions and at an ambient temperature of 25 °C, are:

| OHMIC RANGE | RLP1  | RLP2 | RLP3  | RLP6  | RLP10 | $\frac{\Delta R \%}{R \%}$ |
|-------------|-------|------|-------|-------|-------|----------------------------|
| Pn          | 1 W   | 2 W  | 3 W   | 5 W   | 10 W  | 0.3                        |
| 0.5 Pn      | 0.5 W | 1 W  | 1.5 W | 2.5 W | 5 W   | 0.15                       |


## INDUCTANCE (Example)



## POWER RATING CHART



## TEMPERATURE RISE



## MARKING

SFERNICE trademark, series, style, CECC style (if applicable) nominal resistance (in  $\Omega$ , k $\Omega$ ), tolerance (in %), manufacturing date.

### ORDERING INFORMATION

|       |       |                          |                       |                                                                                                |           |           |                                   |
|-------|-------|--------------------------|-----------------------|------------------------------------------------------------------------------------------------|-----------|-----------|-----------------------------------|
| RLP   | 1     |                          | XXX                   | 5U5                                                                                            | $\pm 5\%$ | TR100     | e1 (e3: RLP1 < 1R<br>RLP2 < 3R52) |
| MODEL | STYLE | NON INDUCTIVE<br>WINDING | SPECIAL<br>DESIGN     | OHMIC VALUE                                                                                    | TOLERANCE | PACKAGING | LEAD (Pb)-FREE                    |
|       |       | Optional<br>(NI)         | Method N°<br>Optional | Custom items<br>are subject to<br>extra-charge<br>and min. order.<br>Please see price<br>list. |           | Optional  |                                   |

### SAP PART NUMBERING GUIDELINES

|       |       |             |           |           |
|-------|-------|-------------|-----------|-----------|
| RLP   | 01    | 5R500       | J         | R15       |
| MODEL | STYLE | OHMIC VALUE | TOLERANCE | PACKAGING |



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331