



**COMPONENTS FOR A  
CONNECTED  
PLANET**

# Stewart Connector

modular interconnect products



## Modular Jacks

### Features / Benefits

- Minimum of 750 insertion cycles
- UL 94-V0 plastic
- Preloaded, formed wire contacts offer superior mechanical and electrical performance
- 45 degree, 90 degree, 180 degree, multi-port, and cable-ready versions available


## ARJ45™ Category 7a

**SS-77100-004** - Single port, horizontal, shielded jack

**CA77-XXXM0-8** - Cable assemblies, up to 10 meters

### Features / Benefits

- Meets IEC 60603-7-7 standard for Category 7 performance up to 600 MHz
- Meets proposed Category 7a standard for increased frequency up to 1000 MHz
- Meets IEC 60603-7-7 Category 7 interface standards and is compatible with Nexans GG45 connectors
- Includes built-in strain relief boot and anti-s snag feature for plug tab protection



Part Number	Orientation	Shield Type
SS-60300-014	180 Degree	Panel Grounds
SS-60300-016	180 Degree	No Panel Grounds
SS-60300-017	180 Degree	Unshielded
SS-60300-002	90 Degree	Panel Grounds
SS-60300-004	90 Degree	No Panel Grounds
SS-60300-021	90 Degree	Unshielded
SS-60300-023	45 Degree	Panel Grounds
SS-60300-024	45 Degree	No Panel Grounds

## Category 6a

**SS-60300 Series** - Shielded and unshielded

### Features / Benefits

- Integrated, flexible PCB design (patent pending) helps cancel Near End Cross Talk (NEXT)
- 45 degree, 90 degree, and 180 degree shielded and unshielded versions available
- Designed to meet Category 6a 500 MHz requirements
- Designed for use in 10Gigabit Ethernet applications

## Category 6 Jacks

**SS-60000 Series** - Shielded and unshielded

### Features / Benefits

- Through hole jacks for PCB soldering
- Designed for Category 6 patch panel and wall jack applications
- Patented design of contacts creates consistent performance for use in Category 6 applications
- 45 degree, 90 degree, and 180 degree shielded and unshielded versions available

Part Number	Orientation	Shield Type
SS-60000-008	180 Degree	No Panel Grounds
SS-60000-007	180 Degree	Unshielded
SS-60000-009	90 Degree	No Panel Grounds
SS-60000-010	90 Degree	Unshielded
SS-60000-011	45 Degree	No Panel Grounds
SS-60000-014	45 Degree	Unshielded



**COMPONENTS FOR A  
CONNECTED  
PLANET®**

# Stewart Connector

modular interconnect products

## Modular Jacks

### Features / Benefits

- Minimum of 750 insertion cycles
- UL 94-V0 plastic
- Preloaded, formed wire contacts offer superior mechanical and electrical performance
- 45 degree, 90 degree, 180 degree, multi-port, and cable-ready versions available





## Category 5E Jacks

### SS-71 Series - Unshielded

#### Features / Benefits

- Through hole jacks for PCB soldering
- Designed for Category 5E patch panel and wall jack applications
- 45 degree, 90 degree, and 180 degree shielded and unshielded versions available

Part Number	Orientation	Shield Type
SS-7188VS-A-NF	180 Degree	No Panel Grounds
SS-7188V-A-NF	180 Degree	Unshielded
SS-7188S-A-NF	90 Degree	No Panel Grounds
SS-7188-A-NF	90 Degree	Unshielded
SS-71100-001	45 Degree	No Panel Grounds
SS-71100-003	45 Degree	Unshielded



## Category 5E Cable Ready

### SS-82000-002 - Unshielded

### SS-82100-001 - Shielded

#### Features / Benefits


- Meets EIA/TIA Category 5E standard when terminated to Category 5E compliant cable
- Double IDC termination for reliable connections
- Load and lace wire management system reduces termination errors
- Can be panel or face plate mounted
- Shielded version provides 360° coverage
- Great for dongle or extension applications
- Requires Bel Stewart Connector termination tools



**COMPONENTS FOR A  
CONNECTED  
PLANET®**

# Stewart Connector

modular interconnect products



## Category 6

**SS-39100-021** - Unshielded

**450-034** - Optional snagless boot for SS-39100-021

**SS-39100-008** - Unshielded with integral boot

### Features / Benefits

- Meets EIA/TIA Category 6 component standard when terminated to Category 6 compliant cable
- Patented wire locking load bar for easy assembly
- Field installable with Category 6 termination tool

**SS-39200-011** - Shielded

### Features / Benefits

- Meets EIA/TIA Category 6 standard when terminated to Category 6 compliant cable
- Load bar for ease of assembly
- Reliable crimped shield grounding system
- One step termination process
- Field installable with shielded termination tool

## Category 5 and T1

**940-SP-3088R-A133** - Unshielded

### Features / Benefits

- Meets EIA/TIA Category 5 standard when terminated to Category 5 compliant cable
- Handles conductor OD of .040"
- Field installable with standard termination tool

**940-SP-360808-A108** - Shielded

### Features / Benefits

- Meets EIA/TIA Category 5 standard when terminated to Category 5 compliant cable
- Conductor management bar for easy assembly
- Reliable crimped ferrule grounding system
- Field installable with shielded termination tool and ferrule crimp tool

## Modular Plugs

### Features / Benefits

- Designed for solid and stranded conductors
- Electro-polished contacts for minimum of 750 insertion cycles
- UL 94-V0 plastic
- Keying options available

## Category 5E

**SS-37000-007** - Unshielded

**450-034** - Optional snagless boot for SS-37000-007

### Features / Benefits

- Meets EIA/TIA Category 5E standard when terminated to Category 5E compliant cable
- Single piece plug with staggered contact design reduces crosstalk
- Field installable with standard termination tool

**943-SP-370808SM2-A264** - Shielded


### Features / Benefits

- Meets EIA/TIA Category 5E standard when terminated to Category 5E compliant cable
- Staggered contact design reduces crosstalk
- Conductor management bar for easy assembly
- Reliable crimped ferrule grounding system

**SS-37200-028** - Shielded

### Features / Benefits

- Meets EIA/TIA Category 5E standard when terminated to Category 5E compliant cable
- Single piece design
- Staggered contact design reduces crosstalk
- Field installable with unshielded termination tool



## RJ11 and RJ12 Applications

**940-SP-3046** - Unshielded (4 contact, 6 position)

**940-SP-3066** - Unshielded (6 contact, 6 position)



**COMPONENTS FOR A  
CONNECTED  
PLANET®**

# Stewart Connector

modular interconnect products



## EPP-918A Environmental Protectant


### Features / Benefits

- Improves durability and reliability for RJ11 and RJ45 jacks
- Prevents corrosion from harsh environmental conditions
- Withstands high temperature soldering (in excess of 260° C for 10 seconds)
- Superior resistance to wear-and-tear during insertion testing
- Low Level Contact Resistance (LLCR) testing to 2500 cycles with no measurable change to gold-plated contacts
- Contains UV tracer for visible inspection of EPP-918A coating on contacts
- Can be used with any Bel Stewart Connector product to increase durability and reliability
- RoHS6 compliant

## SS-51 Series Punch Down Blocks

### Features / Benefits

- Designed for Category 6a applications
- Facilitates field cable termination
- Notched-head design secures cable prior to termination
- Compatible with industry standard termination tools
- Designed for AWG 22-26 solid copper wire
- Pre-printed with TIA 568A/B color coding
- Block design provides excellent pair-to-pair crosstalk performance
- Design allows staggered pair-to-pair spacing to reduce alien crosstalk in multi-port configurations
- RoHS6 compliant



Part Number	Description
SS-51000-003	8 Way Punch Down Block, no printing
SS-51000-004	8 Way Punch Down Block, with printed color code

### Bel Stewart Connector

11118 Susquehanna Trail South  
Glen Rock, PA 17327 USA  
Tel 717-235-7512  
Fax 717-235-4675  
[www.belstewart.com](http://www.belstewart.com)

### Bel Fuse Europe Ltd.

Preston Technology Mgmt Centre  
Marsh Lane, Suite G7  
Preston PR1 8UQ  
Lancashire, U.K.  
Tel 44-1772-556601  
Fax 44-1772-888366  
[www.belfuse.com](http://www.belfuse.com)

### Bel Stewart GmbH

Industriestrasse 20, D-61381  
Friedrichsdorf  
Germany  
Tel 49-6172-9552-0  
Fax 49-6172-9552-40  
[www.belstewart.com](http://www.belstewart.com)

### Bel Fuse Ltd.

8F/8 Luk Hop Street  
San Po Kong  
Kowloon, Hong Kong  
Tel 852-2328-5515  
Fax 852-2352-3706  
[www.belfuse.com](http://www.belfuse.com)



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331