

Ethernet PICtail™ Daughter Board

Overview

The Ethernet PICtail™ Daughter Board is an Ethernet demonstration board for evaluating Microchip Technology's ENC28J60 stand-alone 10 Base-T Ethernet controller. It is an expansion board compatible with a number of PICDEM™ demonstration boards. A complete list of compatible PICDEM demonstration boards is available on Microchip's web site.

Getting Started

To get started, a compatible PICDEM demonstration board is required. In general, a board is compatible if it has a PICtail™ board interface expansion port, which is a 14x2 connector. Most PICDEM demonstration boards do not have the female header installed. Thus, a 14x2 female connector is included with this kit for the user to install onto the PICDEM demonstration board if necessary. When connecting the two boards together, pay close attention to the orientation of the connector and pin alignment. The AC/DC power adapter should be plugged into the PICtail board's power socket. Only one AC/DC power adapter is required because the Ethernet PICtail board is capable of supplying power to the PICDEM demonstration board.

Features

- ENC28J60 Ethernet Controller with 25 MHz oscillator and integrated magnetic RJ-45 connector (see device data sheet DS39662 for additional information)
- 256 Kbits SPI EEPROM (25LC256) for storing web pages and configurations
- Dedicated power supply
- PICtail™ Daughter Board connection interface

Board Configurations

As shipped from the factory, some of the jumper locations are bridged by circuit traces forming a default setup. To change this, the user will need to cut the traces and install pins and a block jumper. Afterward, the features can be enabled or disabled easily by installing or removing the jumper.

| Jumper | Position | Function |
|--------|--------------------|---|
| J4 | Pin 1-2 (Default) | Clock out path from ENC28J60 to PICDEM™ board is disabled |
| | Pin 2-3 | Clock out path from ENC28J60 to PICDEM board is enabled |
| J5 | Pin 1-2 (Default) | RC5 is connected to ENC28J60/25LC256's SI pin |
| | Pin 2-3 | RC7 is connected to ENC28J60/25LC256's SI pin (1) |
| J6 | Pin 1-2 (Default) | RC4 is connected to ENC28J60/25LC256's SO pin |
| | Pin 2-3 | RB0 is connected to ENC28J60/25LC256's SO pin (1) |
| J7 | Pin 1-2 (Default) | RC3 is connected to ENC28J60/25LC256's SCK pin |
| | Pin 2-3 | RB1 is connected to ENC28J60/25LC256's SCK pin (1) |
| J8 | Disabled (Default) | Reserved – Do Not Use |
| J9 | Pin 1-2 | 3.3V power supply to PICDEM demonstration board |
| | Pin 2-3 (Default) | 5V power supply to PICDEM demonstration board |
| | Not connected | No power supply to PICDEM demonstration board |

Note 1: This option is available to support the PICDEM™ FS USB Demo Board.

Firmware

Firmware examples can be downloaded from <http://www.microchip.com/Ethernet>. Make sure to download the firmware version that has been designated for the particular PICDEM demonstration board that you have.

Signal Interface

| Function | I/O | Pin | Description |
|------------------------------|-----|------------|------------------------------------|
| \overline{CS} for ENC28J60 | I | RB3 | SPI Chip Select for ENC28J60 |
| \overline{CS} for 25LC256 | I | RB4 | SPI Chip Select for 25LC256 |
| SCK | I | RC3 or RB1 | SPI Clock |
| SO | O | RC4 or RB0 | SPI Data Out from ENC28J60/25LC256 |
| SI | I | RC5 or RC7 | SPI Data In to ENC28J60/25LC256 |
| \overline{RESET} | I | RB5 | Reset Signal |
| \overline{INT} | O | RB2 | \overline{INT} Interrupt Signal |
| CLKOUT | O | OSC1 | Programmable Clock Output |

Media Access Control (MAC) Address

For evaluation purposes, each Ethernet PICtail board comes with a board number which can be used to form a unique MAC address. This number can be found on the sticker label on the back of each board. To form a MAC address, replace the last 3 bytes of the following MAC address, 00-04-A3-XX-XX-XX, with the number from the sticker. The number on the sticker is in decimal format and conversion to a hex number is required. For example, if the sticker has the value of "12345", then the MAC address would be 00-04-A3-00-30-39.

Other Information

To obtain the most recent and complete documentation for this demonstration board, including:

- User's Guide
- Board Description
- Board Schematics
- Source Code
- Application Examples
- Links to Web Seminars

please refer to the web site: <http://www.microchip.com/Ethernet>

Americas

Atlanta (770) 640-0034
 Boston (774) 760-0087
 Chicago (630) 285-0071
 Dallas (972) 818-7423
 Detroit (248) 538-2250
 Kokomo (765) 864-8360
 Los Angeles (949) 462-9523
 Phoenix (480) 792-7200
 San Jose (650) 215-1444
 Toronto (905) 673-0699

Asia/Pacific

Australia - Sydney 61-2-9868-6733
 China - Beijing 86-10-8528-2100
 China - Chengdu 86-28-8676-6200
 China - Fuzhou 86-591-8750-3506
 China - Hong Kong SAR 852-2401-1200
 China - Qingdao 86-532-8502-7355
 China - Shanghai 86-21-5407-5533
 China - Shenyang 86-24-2334-2829
 China - Shenzhen 86-755-8203-2660
 China - Shunde 86-757-2839-5507
 China - Wuhan 86-27-5980-5300
 China - Xian 86-29-8833-7250
 India - Bangalore 91-80-2229-0061
 India - New Delhi 91-11-5160-8631
 India - Pune 91-20-2566-1512
 Japan - Yokohama 81-45-471-6166
 Korea - Gumi 82-54-473-4301
 Korea - Seoul 82-2-554-7200

Asia/Pacific

Malaysia - Penang 60-4-646-8870
 Philippines - Manila 63-2-634-9065
 Singapore 65-6334-8870
 Taiwan - Hsin Chu 886-3-572-9526
 Taiwan - Kaohsiung 886-7-536-4818
 Taiwan - Taipei 886-2-2500-6610
 Thailand - Bangkok 66-2-694-1351

Europe

Austria - Wels 43-7242-2244-399
 Denmark - Copenhagen 45-4450-2828
 France - Paris 33-1-69-53-63-20
 Germany - Munich 49-89-627-144-0
 Italy - Milan 39-0331-742611
 Netherlands - Drunen 31-416-690399
 Spain - Madrid 34-91-708-08-90
 UK - Wokingham 44-118-921-5869

As of 10/31/05



Microchip Technology Inc. • 2355 West Chandler Blvd. • Chandler, AZ 85224-6199
www.microchip.com

The Microchip name and logo, the Microchip logo, PIC and PICmicro are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. In-Circuit Serial Programming, ICSP, PICDEM and PICtail are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks mentioned herein are property of their respective companies. © 2006, Microchip Technology Incorporated, Printed in the U.S.A. All Rights Reserved. 1/06



DS51569B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[AC164121](#)



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331